

# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version            Revision Date:            SDS Number:            Date of last issue: 06/02/2020  
6.8                10/11/2020                1347323-00042            Date of first issue: 02/27/2017

---

### SECTION 1. IDENTIFICATION

Product name                : 858G-210 TOPCOAT CLEAR

SDS-Identcode              : 130000127955

#### Manufacturer or supplier's details

Company name of supplier   : The Chemours Company FC, LLC

Address                      : 1007 Market Street  
Wilmington, DE 19801 United States of America (USA)

Telephone                    : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone        : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

#### Recommended use of the chemical and restrictions on use

Recommended use            : Coatings

Restrictions on use           : For professional users only.  
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage           : Category 1

#### GHS label elements

Hazard pictograms            :



Signal Word                   : Danger

Hazard Statements            : H318 Causes serious eye damage.

Precautionary Statements   : **Prevention:**  
P280 Wear eye protection and face protection.

**Response:**

# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version 6.8      Revision Date: 10/11/2020      SDS Number: 1347323-00042      Date of last issue: 06/02/2020  
Date of first issue: 02/27/2017

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER.

### Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Paint

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol	60828-78-6	$\geq 5 - < 10$
2,2',2''-Nitrilotriethanol	102-71-6	$\geq 1 - < 5$
2-(2-Butoxyethoxy)ethanol	112-34-5	$\geq 1 - < 5$
Solvent naphtha (petroleum), light arom.	64742-95-6	$\geq 1 - < 5$
1,2,4-Trimethylbenzene	95-63-6	$\geq 1 - < 5$

Actual concentration is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention immediately.

If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.

Most important symptoms : Causes serious eye damage.

# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 06/02/2020
6.8	10/11/2020	1347323-00042	Date of first issue: 02/27/2017

---

and effects, both acute and delayed

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

---

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Hydrogen fluoride  
carbonyl fluoride  
potentially toxic fluorinated compounds  
aerosolized particulates  
Carbon oxides  
Nitrogen oxides (NO<sub>x</sub>)

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version 6.8      Revision Date: 10/11/2020      SDS Number: 1347323-00042      Date of last issue: 06/02/2020  
Date of first issue: 02/27/2017

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.  
Do not breathe vapors or spray mist.  
Do not swallow.  
Do not get in eyes.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep container tightly closed.  
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.  
Keep tightly closed.  
Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

Recommended storage temperature : 41 - 77 °F / 5 - 25 °C

Further information on storage stability : Do not freeze.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2,2',2''-Nitrilotriethanol	102-71-6	TWA	5 mg/m <sup>3</sup>	ACGIH
2-(2-Butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction)	10 ppm	ACGIH

# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version 6.8      Revision Date: 10/11/2020      SDS Number: 1347323-00042      Date of last issue: 06/02/2020  
 Date of first issue: 02/27/2017

		and vapor)		
Solvent naphtha (petroleum), light arom.	64742-95-6	TWA	500 ppm 2,000 mg/m <sup>3</sup>	OSHA Z-1
1,2,4-Trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m <sup>3</sup>	NIOSH REL
		TWA	25 ppm	ACGIH

### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrofluoric acid	7664-39-3	TWA	3 ppm 2.5 mg/m <sup>3</sup>	NIOSH REL
		C	6 ppm 5 mg/m <sup>3</sup>	NIOSH REL
		TWA	3 ppm	OSHA Z-2
		TWA	0.5 ppm (Fluorine)	ACGIH
Carbonyl difluoride	353-50-4	C	2 ppm (Fluorine)	ACGIH
		TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		ST	5 ppm 15 mg/m <sup>3</sup>	NIOSH REL
Carbon dioxide	124-38-9	TWA	2 ppm 5 mg/m <sup>3</sup>	NIOSH REL
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	OSHA Z-1
Carbon monoxide	630-08-0	TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	NIOSH REL
		ST	30,000 ppm 54,000 mg/m <sup>3</sup>	NIOSH REL
		TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m <sup>3</sup>	NIOSH REL
		C	200 ppm 229 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm 55 mg/m <sup>3</sup>	OSHA Z-1

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
 Ensure adequate ventilation, especially in confined areas.  
 Minimize workplace exposure concentrations.

### Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where

# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version 6.8      Revision Date: 10/11/2020      SDS Number: 1347323-00042      Date of last issue: 06/02/2020  
Date of first issue: 02/27/2017

---

concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

### Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Chemical resistant goggles must be worn.  
If splashes are likely to occur, wear:  
Face-shield

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : clear

Odor : No data available

Odor Threshold : No data available

pH : 8.5 - 11

# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version            Revision Date:            SDS Number:            Date of last issue: 06/02/2020  
6.8                10/11/2020              1347323-00042        Date of first issue: 02/27/2017

---

Melting point/freezing point    :    No data available

Initial boiling point and boiling range    :    > 212 °F / > 100 °C

Flash point                                        :    does not flash

Evaporation rate                                :    No data available

Flammability (solid, gas)                    :    Not applicable

Flammability (liquids)                      :    No data available

Upper explosion limit / Upper flammability limit    :    No data available

Lower explosion limit / Lower flammability limit    :    No data available

Vapor pressure                                 :    No data available

Relative vapor density                        :    No data available

Density    :    1.2730 g/cm<sup>3</sup>

Solubility(ies)  
    Water solubility                            :    No data available

Partition coefficient: n-octanol/water        :    Not applicable

Autoignition temperature                    :    No data available

Decomposition temperature                  :    No data available

Viscosity  
    Viscosity, dynamic                        :    682 mPa.s

    Viscosity, kinematic                      :    No data available

Explosive properties                         :    Not explosive

Oxidizing properties                         :    The substance or mixture is not classified as oxidizing.

Particle size                                    :    Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity                                     :    Not classified as a reactivity hazard.

Chemical stability                            :    Stable under normal conditions.

# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version 6.8      Revision Date: 10/11/2020      SDS Number: 1347323-00042      Date of last issue: 06/02/2020  
Date of first issue: 02/27/2017

---

Possibility of hazardous reactions : Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : None known.

Incompatible materials : None.

### Hazardous decomposition products

Thermal decomposition : Hydrofluoric acid  
Carbonyl difluoride  
Carbon dioxide  
Carbon monoxide

---

## SECTION 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

### Acute toxicity

Not classified based on available information.

### Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

### Components:

#### **2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:**

Acute oral toxicity : LD50 (Rat): 3,300 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

#### **2,2',2''-Nitrilotriethanol:**

Acute oral toxicity : LD50 (Rat): 6,400 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

#### **2-(2-Butoxyethoxy)ethanol:**

Acute oral toxicity : LD50 (Mouse): 2,410 mg/kg



# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version 6.8      Revision Date: 10/11/2020      SDS Number: 1347323-00042      Date of last issue: 06/02/2020  
Date of first issue: 02/27/2017

---

Acute dermal toxicity : LD50 (Rabbit): 2,764 mg/kg

**Solvent naphtha (petroleum), light arom.:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.6 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

**1,2,4-Trimethylbenzene:**

Acute oral toxicity : LD50 (Rat): 3,280 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 10.2 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 3,160 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Components:**

**2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:**

Result : Skin irritation

**2,2',2''-Nitrilotriethanol:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

**2-(2-Butoxyethoxy)ethanol:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Mild skin irritation

**Solvent naphtha (petroleum), light arom.:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation

**1,2,4-Trimethylbenzene:**

# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version 6.8      Revision Date: 10/11/2020      SDS Number: 1347323-00042      Date of last issue: 06/02/2020  
Date of first issue: 02/27/2017

---

Species : Rabbit  
Result : Skin irritation  
Remarks : Based on data from similar materials

### Serious eye damage/eye irritation

Causes serious eye damage.

#### Components:

##### **2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:**

Result : Irreversible effects on the eye

##### **2,2',2''-Nitrilotriethanol:**

Species : Rabbit  
Result : No eye irritation

##### **2-(2-Butoxyethoxy)ethanol:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

##### **Solvent naphtha (petroleum), light arom.:**

Species : Rabbit  
Result : No eye irritation

##### **1,2,4-Trimethylbenzene:**

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

### Respiratory or skin sensitization

#### **Skin sensitization**

Not classified based on available information.

#### **Respiratory sensitization**

Not classified based on available information.

#### Components:

##### **2,2',2''-Nitrilotriethanol:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

##### **2-(2-Butoxyethoxy)ethanol:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version 6.8      Revision Date: 10/11/2020      SDS Number: 1347323-00042      Date of last issue: 06/02/2020  
Date of first issue: 02/27/2017

---

### **Solvent naphtha (petroleum), light arom.:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

### **1,2,4-Trimethylbenzene:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

### **Germ cell mutagenicity**

Not classified based on available information.

### **Components:**

#### **2,2',2''-Nitrilotriethanol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

#### **2-(2-Butoxyethoxy)ethanol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

### **Solvent naphtha (petroleum), light arom.:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: Intraperitoneal injection  
Result: negative

### **1,2,4-Trimethylbenzene:**

# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version 6.8      Revision Date: 10/11/2020      SDS Number: 1347323-00042      Date of last issue: 06/02/2020  
Date of first issue: 02/27/2017

---

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Remarks: Based on data from similar materials
- Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative
- Test Type: Mutagenicity (in vitro mammalian cytogenetic test)  
Result: negative  
Remarks: Based on data from similar materials
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative  
Remarks: Based on data from similar materials

### Carcinogenicity

Not classified based on available information.

### Components:

#### **2,2',2''-Nitrilotriethanol:**

Species : Rat  
Application Route : Skin contact  
Exposure time : 103 weeks  
Result : negative

#### **Solvent naphtha (petroleum), light arom.:**

Species : Mouse  
Application Route : Skin contact  
Exposure time : 102 weeks  
Result : negative

**IARC** No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

Not classified based on available information.

### Components:

#### **2,2',2''-Nitrilotriethanol:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat

# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version 6.8      Revision Date: 10/11/2020      SDS Number: 1347323-00042      Date of last issue: 06/02/2020  
Date of first issue: 02/27/2017

---

Application Route: Ingestion  
Method: OECD Test Guideline 416  
Result: negative

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 421  
Result: negative

### **2-(2-Butoxyethoxy)ethanol:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 415  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

### **Solvent naphtha (petroleum), light arom.:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### **1,2,4-Trimethylbenzene:**

Effects on fertility : Test Type: Three-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 414  
Result: negative

### **STOT-single exposure**

Not classified based on available information.

# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version 6.8      Revision Date: 10/11/2020      SDS Number: 1347323-00042      Date of last issue: 06/02/2020  
Date of first issue: 02/27/2017

---

### Components:

#### **Solvent naphtha (petroleum), light arom.:**

Assessment : May cause drowsiness or dizziness.

#### **1,2,4-Trimethylbenzene:**

Assessment : May cause respiratory irritation.

#### **STOT-repeated exposure**

Not classified based on available information.

### Components:

#### **2,2',2''-Nitrilotriethanol:**

Assessment : No significant health effects observed in animals at concentrations of 200 mg/kg bw or less., No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

#### **Repeated dose toxicity**

### Components:

#### **2,2',2''-Nitrilotriethanol:**

Species : Rat  
NOAEL :  $\geq 1,000$  mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

Species : Rat  
NOAEL :  $\geq 0.5$  mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 28 Days  
Method : OECD Test Guideline 412

Species : Rat  
NOAEL : 125 mg/kg  
Application Route : Skin contact  
Exposure time : 90 Days

#### **2-(2-Butoxyethoxy)ethanol:**

Species : Rat  
NOAEL : 250 mg/kg  
LOAEL : 1,000 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Method : OECD Test Guideline 408

Species : Rat  
NOAEL :  $\geq 0.094$  mg/l  
Application Route : inhalation (vapor)  
Exposure time : 90 Days  
Method : OECD Test Guideline 413

# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version 6.8      Revision Date: 10/11/2020      SDS Number: 1347323-00042      Date of last issue: 06/02/2020  
Date of first issue: 02/27/2017

---

Species : Rat  
NOAEL :  $\geq 2,000$  mg/kg  
Application Route : Skin contact  
Exposure time : 90 Days

### **Solvent naphtha (petroleum), light arom.:**

Species : Rat  
NOAEL : 1.4 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 107 Weeks

### **1,2,4-Trimethylbenzene:**

Species : Rat  
NOAEL : 600 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Method : OECD Test Guideline 408  
Remarks : Based on data from similar materials

Species : Rat  
NOAEL : 1230 mg/m<sup>3</sup>  
Application Route : inhalation (vapor)  
Exposure time : 90 Days

### **Aspiration toxicity**

Not classified based on available information.

### **Components:**

#### **Solvent naphtha (petroleum), light arom.:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### **1,2,4-Trimethylbenzene:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

---

## SECTION 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

#### **Components:**

##### **2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 39 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 81.2 mg/l  
Exposure time: 48 h

##### **2,2',2''-Nitrilotriethanol:**

# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version 6.8      Revision Date: 10/11/2020      SDS Number: 1347323-00042      Date of last issue: 06/02/2020  
Date of first issue: 02/27/2017

---

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 11,800 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 609.88 mg/l  
Exposure time: 48 h
- Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 512 mg/l  
Exposure time: 72 h  
Test substance: Neutralized product
- EC10 (Desmodesmus subspicatus (green algae)): 26 mg/l  
Exposure time: 72 h  
Test substance: Neutralized product
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 16 mg/l  
Exposure time: 21 d
- Toxicity to microorganisms : IC50: > 1,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

### **2-(2-Butoxyethoxy)ethanol:**

- Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 1,300 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201
- NOEC (Desmodesmus subspicatus (green algae)): >= 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC10: > 1,995 mg/l  
Exposure time: 30 min

### **Solvent naphtha (petroleum), light arom.:**

- Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): 8.2 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 4.5 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 880 mg/l



# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version 6.8      Revision Date: 10/11/2020      SDS Number: 1347323-00042      Date of last issue: 06/02/2020  
Date of first issue: 02/27/2017

---

Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): 0.1 mg/l

Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Pimephales promelas (fathead minnow)): 2.6 mg/l  
Exposure time: 14 d  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 204

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 2.6 mg/l  
Exposure time: 21 d  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 211

### **1,2,4-Trimethylbenzene:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 7.72 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3.6 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 2.356 mg/l  
Exposure time: 96 h

### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

### **Persistence and degradability**

#### **Components:**

#### **2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:**

Biodegradability : Result: Not readily biodegradable.

#### **2,2',2"-Nitrilotriethanol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 96 %  
Exposure time: 19 d

#### **2-(2-Butoxyethoxy)ethanol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 85 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301C

# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version 6.8      Revision Date: 10/11/2020      SDS Number: 1347323-00042      Date of last issue: 06/02/2020  
Date of first issue: 02/27/2017

---

### **Solvent naphtha (petroleum), light arom.:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 77 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

### **1,2,4-Trimethylbenzene:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 60 %  
Exposure time: 28 d

### **Bioaccumulative potential**

#### **Components:**

#### **2,2',2''-Nitrilotriethanol:**

Bioaccumulation : Species: Cyprinus carpio (Carp)  
Bioconcentration factor (BCF): < 3.9

Partition coefficient: n-octanol/water : log Pow: -1.9

#### **2-(2-Butoxyethoxy)ethanol:**

Partition coefficient: n-octanol/water : log Pow: 1

### **Solvent naphtha (petroleum), light arom.:**

Partition coefficient: n-octanol/water : log Pow: > 4

### **Mobility in soil**

No data available

### **Other adverse effects**

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

## SECTION 14. TRANSPORT INFORMATION

### **International Regulations**

UNRTDG

---

# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version 6.8      Revision Date: 10/11/2020      SDS Number: 1347323-00042      Date of last issue: 06/02/2020  
Date of first issue: 02/27/2017

Not regulated as a dangerous good

### IATA-DGR

Not regulated as a dangerous good

### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

Not regulated as a dangerous good

## SECTION 15. REGULATORY INFORMATION

### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	172413
2,2'-Iminodiethanol	111-42-2	100	*
Benzene	71-43-2	10	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Serious eye damage or eye irritation

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

2-(2-Butoxyethoxy)ethanol	112-34-5	>= 1 - < 5 %
1,2,4-Trimethylbenzene	95-63-6	>= 1 - < 5 %
2-Butoxyethanol	111-76-2	< 0.1 %

### Volatile organic compounds (VOC) content

VOC content: 234.63 g/l  
Remarks: less exempt

VOC content: 118.15 g/l  
Remarks: as packaged

# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version 6.8      Revision Date: 10/11/2020      SDS Number: 1347323-00042      Date of last issue: 06/02/2020  
Date of first issue: 02/27/2017

### US State Regulations

#### Pennsylvania Right To Know

Water	7732-18-5
Fluoropolymer	Trade secret
2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol	60828-78-6
2,2',2''-Nitrilotriethanol	102-71-6
2-(2-Butoxyethoxy)ethanol	112-34-5
Solvent naphtha (petroleum), light arom.	64742-95-6
Oleic acid	112-80-1
1,2,4-Trimethylbenzene	95-63-6
Cumene	98-82-8
Xylene	1330-20-7
Ammonium hydroxide	1336-21-6
2,2'-Iminodiethanol	111-42-2

#### California Prop. 65

WARNING: This product can expose you to chemicals including Cumene, which is/are known to the State of California to cause cancer, and Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### California List of Hazardous Substances

1,2,4-Trimethylbenzene	95-63-6
------------------------	---------


#### California Permissible Exposure Limits for Chemical Contaminants

2,2',2''-Nitrilotriethanol	102-71-6
1,2,4-Trimethylbenzene	95-63-6

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA 704:



#### HMIS® IV:

HEALTH	/	3
FLAMMABILITY		0
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information.

# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version            Revision Date:            SDS Number:            Date of last issue: 06/02/2020  
6.8                10/11/2020                1347323-00042            Date of first issue: 02/27/2017

---

For further information contact the local Chemours office or nominated distributors.

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	:	USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to : Internal technical data, data from raw material SDSs, OECD

# SAFETY DATA SHEET



## 858G-210 TOPCOAT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 06/02/2020
6.8	10/11/2020	1347323-00042	Date of first issue: 02/27/2017

---

compile the Material Safety  
Data Sheet

eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/11/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8