

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 858G-917 HIGH BUILD LIQUID RUBY RED

Version 7.13      Revision Date: 05/09/2024      SDS Number: 1347349-00047      Date of last issue: 01/30/2024  
Date of first issue: 02/27/2017

---

### SECTION 1. IDENTIFICATION

Product name : 858G-917 HIGH BUILD LIQUID RUBY RED  
Product code : D14891979  
SDS-Identcode : 130000127957

#### Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC  
Address : 1007 Market Street  
Wilmington, DE 19801 United States of America (USA)  
Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)  
Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

#### Recommended use of the chemical and restrictions on use

Recommended use : Coatings  
Restrictions on use : For industrial use only.  
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

#### GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

#### Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.

---

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture  
Chemical nature : Paint

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 858G-917 HIGH BUILD LIQUID RUBY RED

Version 7.13      Revision Date: 05/09/2024      SDS Number: 1347349-00047      Date of last issue: 01/30/2024  
Date of first issue: 02/27/2017

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Glycerine	56-81-5	$\geq 5 - < 10$
Mica	12001-26-2	$\geq 1 - < 5$
Diiron trioxide	1309-37-1	$\geq 1 - < 5$
2-Dimethylaminoethanol	108-01-0	$\geq 0.1 - < 1$

Actual concentration is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.  
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : No special precautions are necessary for first aid responders.
- Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Hydrogen fluoride  
carbonyl fluoride  
potentially toxic fluorinated compounds  
aerosolized particulates  
Carbon oxides  
Metal oxides

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 858G-917 HIGH BUILD LIQUID RUBY RED

Version	Revision Date:	SDS Number:	Date of last issue: 01/30/2024
7.13	05/09/2024	1347349-00047	Date of first issue: 02/27/2017

---

Silicon oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Use personal protective equipment.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Take care to prevent spills, waste and minimize release to the

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 858G-917 HIGH BUILD LIQUID RUBY RED

Version 7.13      Revision Date: 05/09/2024      SDS Number: 1347349-00047      Date of last issue: 01/30/2024  
Date of first issue: 02/27/2017

environment.

Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labeled containers.  
Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

Recommended storage temperature : 41 - 77 °F / 5 - 25 °C

Further information on storage stability : Do not freeze.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Mica	12001-26-2	TWA (Respirable particulate matter)	0.1 mg/m <sup>3</sup>	ACGIH
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	3 mg/m <sup>3</sup>	NIOSH REL
Diiron trioxide	1309-37-1	TWA (Respirable particulate matter)	5 mg/m <sup>3</sup>	ACGIH
		TWA (dust and fume)	5 mg/m <sup>3</sup> (Iron)	NIOSH REL
		TWA (Fumes)	10 mg/m <sup>3</sup>	OSHA Z-1
		TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable fraction)	5 mg/m <sup>3</sup>	OSHA Z-1

#### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 858G-917 HIGH BUILD LIQUID RUBY RED

Version 7.13      Revision Date: 05/09/2024      SDS Number: 1347349-00047      Date of last issue: 01/30/2024  
Date of first issue: 02/27/2017

		C	6 ppm 5 mg/m <sup>3</sup>	NIOSH REL
		TWA	3 ppm 2.5 mg/m <sup>3</sup>	NIOSH REL
		TWA	3 ppm	OSHA Z-2
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m <sup>3</sup>	NIOSH REL
		ST	5 ppm 15 mg/m <sup>3</sup>	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	NIOSH REL
		ST	30,000 ppm 54,000 mg/m <sup>3</sup>	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	OSHA Z-1
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m <sup>3</sup>	NIOSH REL
		C	200 ppm 229 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm 55 mg/m <sup>3</sup>	OSHA Z-1

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

### Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Remarks : Wash hands before breaks and at the end of workday.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 858G-917 HIGH BUILD LIQUID RUBY RED

Version	Revision Date:	SDS Number:	Date of last issue: 01/30/2024
7.13	05/09/2024	1347349-00047	Date of first issue: 02/27/2017

---

Eye protection : Wear the following personal protective equipment:  
Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : red

Odor : No data available

Odor Threshold : No data available

pH : 8.5 - 11

Melting point/freezing point : No data available

Initial boiling point and boiling range : > 212 °F / > 100 °C

Flash point : does not flash

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Not applicable

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : 1.4620 g/cm<sup>3</sup>

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 858G-917 HIGH BUILD LIQUID RUBY RED

Version	Revision Date:	SDS Number:	Date of last issue: 01/30/2024
7.13	05/09/2024	1347349-00047	Date of first issue: 02/27/2017

---

Solubility(ies)  
Water solubility : No data available

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : 684 mPa.s  
Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics  
Particle size : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : None known.

Incompatible materials : None.

#### Hazardous decomposition products

Thermal decomposition : Hydrogen fluoride  
Carbonyl difluoride  
Carbon dioxide  
Carbon monoxide

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 858G-917 HIGH BUILD LIQUID RUBY RED

Version 7.13      Revision Date: 05/09/2024      SDS Number: 1347349-00047      Date of last issue: 01/30/2024  
Date of first issue: 02/27/2017

---

### Acute toxicity

Not classified based on available information.

### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

### Components:

#### **Glycerine:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Acute dermal toxicity : LD50 (Guinea pig): > 5,000 mg/kg

#### **Diiron trioxide:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

#### **2-Dimethylaminoethanol:**

Acute oral toxicity : LD50 (Rat): 1,182 mg/kg  
Method: OECD Test Guideline 401  
Acute inhalation toxicity : LC50 (Rat): 5.97 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403  
Acute dermal toxicity : LD50 (Rabbit): 1,214 mg/kg

### **Skin corrosion/irritation**

Not classified based on available information.

### Components:

#### **Glycerine:**

Species : Rabbit  
Result : No skin irritation

#### **Diiron trioxide:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

#### **2-Dimethylaminoethanol:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Corrosive after 3 minutes to 1 hour of exposure



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 858G-917 HIGH BUILD LIQUID RUBY RED

Version 7.13      Revision Date: 05/09/2024      SDS Number: 1347349-00047      Date of last issue: 01/30/2024  
Date of first issue: 02/27/2017

---

### Serious eye damage/eye irritation

Not classified based on available information.

#### Components:

##### Glycerine:

Species : Rabbit  
Result : No eye irritation

##### Diiron trioxide:

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

##### 2-Dimethylaminoethanol:

Species : Rabbit  
Result : Irreversible effects on the eye

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

#### Components:

##### Diiron trioxide:

Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

##### 2-Dimethylaminoethanol:

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

### Germ cell mutagenicity

Not classified based on available information.

#### Components:

##### Glycerine:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: Chromosome aberration test in vitro

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 858G-917 HIGH BUILD LIQUID RUBY RED

Version 7.13      Revision Date: 05/09/2024      SDS Number: 1347349-00047      Date of last issue: 01/30/2024  
Date of first issue: 02/27/2017

---

Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: negative

### **Diiron trioxide:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

### **2-Dimethylaminoethanol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

### **Carcinogenicity**

Not classified based on available information.

### **Components:**

#### **Glycerine:**

Species : Rat  
Application Route : Ingestion  
Exposure time : 2 Years  
Result : negative

#### **Diiron trioxide:**

Species : Rat  
Application Route : Intraperitoneal injection  
Exposure time : 790 - 914 days  
Result : negative

#### **2-Dimethylaminoethanol:**

Species : Mouse  
Application Route : Ingestion  
Exposure time : 105 weeks  
Result : negative

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 858G-917 HIGH BUILD LIQUID RUBY RED

Version	Revision Date:	SDS Number:	Date of last issue: 01/30/2024
7.13	05/09/2024	1347349-00047	Date of first issue: 02/27/2017

---

**IARC** No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

Not classified based on available information.

#### Components:

##### **Glycerine:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

##### **2-Dimethylaminoethanol:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 421  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 414  
Result: negative

Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Method: OPPTS 870.3700  
Result: negative

### STOT-single exposure

Not classified based on available information.

#### Components:

##### **2-Dimethylaminoethanol:**

Assessment : May cause respiratory irritation.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 858G-917 HIGH BUILD LIQUID RUBY RED

Version 7.13      Revision Date: 05/09/2024      SDS Number: 1347349-00047      Date of last issue: 01/30/2024  
Date of first issue: 02/27/2017

---

### STOT-repeated exposure

Not classified based on available information.

### Repeated dose toxicity

#### Components:

##### Glycerine:

Species : Rat  
NOAEL : 0.167 mg/l  
LOAEL : 0.622 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 13 Weeks

Species : Rat  
NOAEL : 8,000 - 10,000 mg/kg  
Application Route : Ingestion  
Exposure time : 2 y

Species : Rabbit  
NOAEL : 5,040 mg/kg  
Application Route : Skin contact  
Exposure time : 45 Weeks

### Aspiration toxicity

Not classified based on available information.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### Glycerine:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 54,000 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,955 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to microorganisms : NOEC (Pseudomonas putida): > 10,000 mg/l  
Exposure time: 16 h  
Method: DIN 38 412 Part 8

##### Diiron trioxide:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 50,000 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
aquatic invertebrates Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to microorganisms : EC50: > 10,000 mg/l

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 858G-917 HIGH BUILD LIQUID RUBY RED

Version 7.13      Revision Date: 05/09/2024      SDS Number: 1347349-00047      Date of last issue: 01/30/2024  
Date of first issue: 02/27/2017

---

Exposure time: 3 h

### 2-Dimethylaminoethanol:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 146.63 mg/l  
Exposure time: 96 h  
Test substance: Neutralized product  
Method: DIN 38412

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 98.37 mg/l  
Exposure time: 48 h  
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 66.08 mg/l  
Exposure time: 72 h

EC10 (Desmodesmus subspicatus (green algae)): 24.49 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : EC10 (Pseudomonas putida): 273.8 mg/l  
Exposure time: 17 h  
Method: DIN 38 412 Part 8

### Persistence and degradability

#### Components:

##### Glycerine:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 92 %  
Exposure time: 30 d  
Method: OECD Test Guideline 301D

##### 2-Dimethylaminoethanol:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 60.5 %  
Exposure time: 14 d  
Method: OECD Test Guideline 301C

### Bioaccumulative potential

#### Components:

##### Glycerine:

Partition coefficient: n-octanol/water : log Pow: -1.75

##### 2-Dimethylaminoethanol:

Partition coefficient: n-octanol/water : log Pow: -0.55

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 858G-917 HIGH BUILD LIQUID RUBY RED

Version	Revision Date:	SDS Number:	Date of last issue: 01/30/2024
7.13	05/09/2024	1347349-00047	Date of first issue: 02/27/2017

---

### Mobility in soil

No data available

### Other adverse effects

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.  
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

Not regulated as a dangerous good

### Special precautions for user

Not applicable

---

## SECTION 15. REGULATORY INFORMATION

### CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : No SARA Hazards

---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 858G-917 HIGH BUILD LIQUID RUBY RED

Version	Revision Date:	SDS Number:	Date of last issue: 01/30/2024
7.13	05/09/2024	1347349-00047	Date of first issue: 02/27/2017

---

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Volatile organic compounds (VOC) content**

VOC content: 18.69 g/l  
Remarks: less exempt

VOC content: 9.23 g/l  
Remarks: as packaged

### US State Regulations

#### Pennsylvania Right To Know

Fluoropolymer	Trade secret
Water	7732-18-5
Glycerine	56-81-5
Mica	12001-26-2
Diiron trioxide	1309-37-1

#### California Prop. 65

WARNING: This product can expose you to chemicals including Ethyl acrylate, which is/are known to the State of California to cause cancer, and Carbon monoxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### California List of Hazardous Substances

Mica	12001-26-2
Diiron trioxide	1309-37-1

#### California Permissible Exposure Limits for Chemical Contaminants

Glycerine	56-81-5
Mica	12001-26-2
Diiron trioxide	1309-37-1

---

### SECTION 16. OTHER INFORMATION

#### Further information

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 858G-917 HIGH BUILD LIQUID RUBY RED


Version  
7.13

Revision Date:  
05/09/2024

SDS Number:  
1347349-00047

Date of last issue: 01/30/2024  
Date of first issue: 02/27/2017

### NFPA 704:



### HMIS® IV:

HEALTH	/	0
FLAMMABILITY		0
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or nominated distributors.

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	:	USA. Occupational Exposure Limits (OSHA) - Table Z-2
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 858G-917 HIGH BUILD LIQUID RUBY RED

Version	Revision Date:	SDS Number:	Date of last issue: 01/30/2024
7.13	05/09/2024	1347349-00047	Date of first issue: 02/27/2017

---

International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 05/09/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8