

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

---

### SECTION 1. IDENTIFICATION

Product name : 959G-205 ONE COAT DARK BROWN  
Product code : D14568523  
SDS-Identcode : 130000127987

#### Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC  
Address : 1007 Market Street  
Wilmington, DE 19899 United States of America (USA)  
Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)  
Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

#### Recommended use of the chemical and restrictions on use

Recommended use : Coatings  
Restrictions on use : For professional users only.  
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 3  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Carcinogenicity : Category 2  
Reproductive toxicity : Category 1B  
Specific target organ systemic toxicity - single exposure : Category 3




#### GHS label elements

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

Hazard pictograms	:	  
Signal Word	:	Danger
Hazard Statements	:	H226 Flammable liquid and vapor. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H360D May damage the unborn child.
Precautionary Statements	:	<b>Prevention:</b> P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P233 Keep container tightly closed. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing mist or vapors. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. <b>Response:</b> P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P332 + P313 If skin irritation occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it before reuse. <b>Storage:</b> P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. <b>Disposal:</b> P501 Dispose of contents/ container to an approved waste dis-

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

posal plant.

### Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.  
Vapors may form explosive mixture with air.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
N-Methyl-2-pyrrolidone	872-50-4	>= 30 - < 50
Isobutyl methyl ketone	108-10-1	>= 20 - < 30
Solvent naphtha (petroleum), light arom.	64742-95-6	>= 1 - < 5
1,2,4-Trimethylbenzene	95-63-6	>= 1 - < 5
Diiron trioxide	1309-37-1	>= 1 - < 5
2-(2-Butoxyethoxy)ethanol	112-34-5	>= 1 - < 5
Carbon black	1333-86-4	>= 0.1 - < 1
Cumene	98-82-8	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and : Causes skin irritation.  
Causes serious eye irritation.

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

---

delayed      May cause respiratory irritation.  
Suspected of causing cancer.  
May damage the unborn child.

Protection of first-aiders      :    First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.

Notes to physician      :    Treat symptomatically and supportively.

---

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media      :    Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media      :    High volume water jet

Specific hazards during fire fighting      :    Do not use a solid water stream as it may scatter and spread fire.  
Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.

Hazardous combustion products      :    Nitrogen oxides (NO<sub>x</sub>)  
Carbon oxides  
Hydrogen fluoride  
carbonyl fluoride  
potentially toxic fluorinated compounds  
aerosolized particulates  
Formaldehyde  
Metal oxides

Specific extinguishing methods      :    Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters      :    In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures      :    Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions      :    Discharge into the environment must be avoided.

---

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

---

Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use with local exhaust ventilation.  
Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential

Advice on safe handling : Do not get on skin or clothing.  
Do not breathe vapors or spray mist.  
Do not swallow.  
Do not get in eyes.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Non-sparking tools should be used.  
Keep container tightly closed.  
Already sensitized individuals should consult their physician regarding working with respiratory irritants or sensitizers.  
Keep away from heat and sources of ignition.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.  
Store locked up.  
Keep tightly closed.  
Keep in a cool, well-ventilated place.

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
 Date of first issue: 02/27/2017

Store in accordance with the particular national regulations.  
 Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:  
 Strong oxidizing agents  
 Organic peroxides  
 Flammable solids  
 Pyrophoric liquids  
 Pyrophoric solids  
 Self-heating substances and mixtures  
 Substances and mixtures which in contact with water emit flammable gases  
 Explosives  
 Gases

Recommended storage temperature : 41 - 77 °F / 5 - 25 °C

Further information on storage stability : Do not freeze.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
N-Methyl-2-pyrrolidone	872-50-4	TWA	10 ppm	US WEEL
Isobutyl methyl ketone	108-10-1	TWA	20 ppm	ACGIH
		STEL	75 ppm	ACGIH
		TWA	50 ppm 205 mg/m <sup>3</sup>	NIOSH REL
		ST	75 ppm 300 mg/m <sup>3</sup>	NIOSH REL
		TWA	100 ppm 410 mg/m <sup>3</sup>	OSHA Z-1
Solvent naphtha (petroleum), light arom.	64742-95-6	TWA	500 ppm 2,000 mg/m <sup>3</sup>	OSHA Z-1
1,2,4-Trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m <sup>3</sup>	NIOSH REL
Diiron trioxide	1309-37-1	TWA	25 ppm	ACGIH
		TWA (Respirable fraction)	5 mg/m <sup>3</sup>	ACGIH
		TWA (Fumes)	10 mg/m <sup>3</sup>	OSHA Z-1
		TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable fraction)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (dust and fume)	5 mg/m <sup>3</sup> (Iron)	NIOSH REL

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
 Date of first issue: 02/27/2017

2-(2-Butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH
Carbon black	1333-86-4	TWA	3.5 mg/m <sup>3</sup>	NIOSH REL
		TWA	3.5 mg/m <sup>3</sup>	OSHA Z-1
Cumene	98-82-8	TWA (Inhalable fraction)	3 mg/m <sup>3</sup>	ACGIH
		TWA	50 ppm	ACGIH
		TWA	50 ppm 245 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm 245 mg/m <sup>3</sup>	OSHA Z-1

### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrofluoric acid	7664-39-3	TWA	3 ppm 2.5 mg/m <sup>3</sup>	NIOSH REL
		C	6 ppm 5 mg/m <sup>3</sup>	NIOSH REL
		TWA	3 ppm	OSHA Z-2
		TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		ST	5 ppm 15 mg/m <sup>3</sup>	NIOSH REL
		TWA	2 ppm 5 mg/m <sup>3</sup>	NIOSH REL
		TWA	5,000 ppm	ACGIH
Carbon dioxide	124-38-9	STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	OSHA Z-1
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	NIOSH REL
		ST	30,000 ppm 54,000 mg/m <sup>3</sup>	NIOSH REL
		TWA	25 ppm	ACGIH
Carbon monoxide	630-08-0	TWA	35 ppm 40 mg/m <sup>3</sup>	NIOSH REL
		C	200 ppm 229 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm 55 mg/m <sup>3</sup>	OSHA Z-1
		C	0.01 ppm	ACGIH
Formaldehyde	50-00-0	TWA	0.016 ppm	NIOSH REL

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
 Date of first issue: 02/27/2017

		C	0.1 ppm	NIOSH REL
		PEL	0.75 ppm	OSHA CARC
		STEL	2 ppm	OSHA CARC
		TWA	0.016 ppm (Formaldehyde)	NIOSH REL
		C	0.1 ppm (Formaldehyde)	NIOSH REL
Butan-1-ol	71-36-3	TWA	20 ppm	ACGIH
		C	50 ppm 150 mg/m <sup>3</sup>	NIOSH REL
		TWA	100 ppm 300 mg/m <sup>3</sup>	OSHA Z-1
2-Methyl-1-propanol	78-83-1	TWA	50 ppm	ACGIH
		TWA	50 ppm 150 mg/m <sup>3</sup>	NIOSH REL
		TWA	100 ppm 300 mg/m <sup>3</sup>	OSHA Z-1

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
N-Methyl-2-pyrrolidone	872-50-4	5-Hydroxy-N-methyl-2-pyrrolidone	Urine	End of shift (As soon as possible after exposure ceases)	100 mg/l	ACGIH BEI
Isobutyl methyl ketone	108-10-1	methyl isobutyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	1 mg/l	ACGIH BEI

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
 Minimize workplace exposure concentrations.  
 Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential  
 Use with local exhaust ventilation.

### Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and



# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

---

use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

### Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
Flame retardant antistatic protective clothing, unless assessment demonstrates that the risk of explosive atmospheres or flash fires is low  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid  
Color : brown  
Odor : No data available  
Odor Threshold : No data available  
pH : No data available  
Melting point/freezing point : No data available

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

---

Initial boiling point and boiling range : > 212 °F / > 100 °C

Flash point : 96.01 °F / 35.56 °C  
Method: ISO 2719

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Sustains combustion

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : 1.0720 g/cm<sup>3</sup>

Solubility(ies)  
Water solubility : No data available

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Flammable liquid and vapor.  
Vapors may form explosive mixture with air.  
Can react with strong oxidizing agents.

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

---

Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

### Hazardous decomposition products

Thermal decomposition : Hydrofluoric acid  
Carbonyl difluoride  
Carbon dioxide  
Carbon monoxide  
1-Propene, 1,1,3,3,3-pentafluoro-2-(trifluoromethyl)-  
Formaldehyde  
Butan-1-ol  
2-Methyl-1-propanol

---

## SECTION 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

### Acute toxicity

Not classified based on available information.

### Product:

Acute oral toxicity : Acute toxicity estimate: 4,817 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 48.25 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

### Components:

#### **N-Methyl-2-pyrrolidone:**

Acute oral toxicity : LD50 (Rat): 4,150 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.1 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

---

**Isobutyl methyl ketone:**

Acute oral toxicity : LD50 (Rat): 2,080 mg/kg

Acute inhalation toxicity : LC50 (Rat): 11.6 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

**Solvent naphtha (petroleum), light arom.:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.6 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

**1,2,4-Trimethylbenzene:**

Acute oral toxicity : LD50 (Rat): 3,280 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 10.2 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 3,160 mg/kg

**Diiron trioxide:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

**2-(2-Butoxyethoxy)ethanol:**

Acute oral toxicity : LD50 (Mouse): 2,410 mg/kg  
Method: OECD Test Guideline 401

LD50 (Rat): 3,306 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 2,764 mg/kg  
Method: OECD Test Guideline 402

**Carbon black:**

Acute oral toxicity : LD50 (Rat): > 10,000 mg/kg

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

---

### Cumene:

Acute oral toxicity : LD50 (Rat): 2,700 mg/kg  
Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

### Skin corrosion/irritation

Causes skin irritation.

### Components:

#### N-Methyl-2-pyrrolidone:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation

#### Isobutyl methyl ketone:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

#### Solvent naphtha (petroleum), light arom.:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation

#### 1,2,4-Trimethylbenzene:

Species : Rabbit  
Result : Skin irritation  
Remarks : Based on data from similar materials

#### Diiron trioxide:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

#### 2-(2-Butoxyethoxy)ethanol:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Mild skin irritation

#### Carbon black:

Species : Rabbit  
Result : No skin irritation

### Cumene:

Species : Rabbit

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

---

Result : No skin irritation

### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Components:

##### **N-Methyl-2-pyrrolidone:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

##### **Isobutyl methyl ketone:**

Result : Irritation to eyes, reversing within 21 days  
Remarks : Based on harmonised classification in EU regulation 1272/2008, Annex VI

##### **Solvent naphtha (petroleum), light arom.:**

Species : Rabbit  
Result : No eye irritation

##### **1,2,4-Trimethylbenzene:**

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

##### **Diiron trioxide:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

##### **2-(2-Butoxyethoxy)ethanol:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days  
Method : OECD Test Guideline 405

##### **Carbon black:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

##### **Cumene:**

Species : Rabbit  
Result : No eye irritation

### Respiratory or skin sensitization

#### **Skin sensitization**

Not classified based on available information.

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

---

### Respiratory sensitization

Not classified based on available information.

### Components:

#### **N-Methyl-2-pyrrolidone:**

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : negative  
Remarks : Based on data from similar materials

#### **Isobutyl methyl ketone:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

#### **Solvent naphtha (petroleum), light arom.:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

#### **1,2,4-Trimethylbenzene:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

#### **Diiron trioxide:**

Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

#### **2-(2-Butoxyethoxy)ethanol:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

#### **Carbon black:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

---

### **Cumene:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

### **Germ cell mutagenicity**

Not classified based on available information.

### **Components:**

#### **N-Methyl-2-pyrrolidone:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Method: OECD Test Guideline 474  
Result: negative

#### **Isobutyl methyl ketone:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

#### **Solvent naphtha (petroleum), light arom.:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow  
cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: Intraperitoneal injection  
Result: negative

#### **1,2,4-Trimethylbenzene:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative



# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

	Remarks: Based on data from similar materials
	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
	Test Type: Mutagenicity (in vitro mammalian cytogenetic test) Result: negative Remarks: Based on data from similar materials
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative Remarks: Based on data from similar materials
<b>Diiron trioxide:</b>	
Genotoxicity in vitro	: Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
<b>2-(2-Butoxyethoxy)ethanol:</b>	
Genotoxicity in vitro	: Test Type: Chromosome aberration test in vitro Result: negative
	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Mouse Application Route: Ingestion Method: OECD Test Guideline 475 Result: negative
<b>Carbon black:</b>	
Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
	Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
	Test Type: In vitro sister chromatid exchange assay in mammalian cells Method: OECD Test Guideline 479 Result: negative
	Test Type: in vitro micronucleus test Method: OECD Test Guideline 487 Result: negative

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in *Drosophila melanogaster* (in vivo)  
Species: *Drosophila melanogaster* (vinegar fly)  
Application Route: Ingestion  
Method: OECD Test Guideline 477  
Result: negative

### **Cumene:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative

### **Carcinogenicity**

Suspected of causing cancer.

### **Components:**

#### **N-Methyl-2-pyrrolidone:**

Species : Mouse  
Application Route : Ingestion  
Method : OECD Test Guideline 451  
Result : positive  
Remarks : The mechanism or mode of action may not be relevant in humans.

Species : Rat  
Application Route : Inhalation  
Result : negative

#### **Isobutyl methyl ketone:**

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Method : OECD Test Guideline 451  
Result : positive  
Remarks : The mechanism or mode of action may not be relevant in humans.

Species : Mouse  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Method : OECD Test Guideline 451  
Result : positive  
Remarks : The mechanism or mode of action may not be relevant in humans.

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

**Solvent naphtha (petroleum), light arom.:**

Species : Mouse  
Application Route : Skin contact  
Exposure time : 102 weeks  
Result : negative

**Diiron trioxide:**

Species : Rat  
Application Route : Intraperitoneal injection  
Exposure time : 790 - 914 days  
Result : negative

**Carbon black:**

Species : Rat  
Application Route : Inhalation  
Exposure time : 24 Months  
Result : positive

Species : Rat  
Application Route : Ingestion  
Exposure time : 2 Years  
Result : negative

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

**Cumene:**

Species : Rat  
Application Route : inhalation (gas)  
Exposure time : 105 weeks  
Result : negative

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

<b>IARC</b>	Group 2B: Possibly carcinogenic to humans	
	Isobutyl methyl ketone	108-10-1
	Group 2B: Possibly carcinogenic to humans	
	Carbon black	1333-86-4
	Group 2B: Possibly carcinogenic to humans	
	Cumene	98-82-8

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

<b>NTP</b>	Reasonably anticipated to be a human carcinogen	
	Cumene	98-82-8

## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
 Date of first issue: 02/27/2017

**Reproductive toxicity**

May damage the unborn child.

**Components:****N-Methyl-2-pyrrolidone:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 416  
 Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 414  
 Result: positive

Test Type: Two-generation reproduction toxicity study  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 416  
 Result: positive

Reproductive toxicity - Assessment : Clear evidence of adverse effects on development, based on animal experiments.

**Isobutyl methyl ketone:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
 Species: Rat  
 Application Route: inhalation (vapor)  
 Method: OECD Test Guideline 416  
 Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
 Species: Mouse  
 Application Route: inhalation (vapor)  
 Result: negative

**Solvent naphtha (petroleum), light arom.:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
 Species: Rat  
 Application Route: inhalation (vapor)  
 Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
 Species: Rat  
 Application Route: inhalation (vapor)  
 Result: negative

**1,2,4-Trimethylbenzene:**

Effects on fertility : Test Type: Three-generation reproduction toxicity study  
 Species: Rat

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

		Application Route: inhalation (vapor) Result: negative Remarks: Based on data from similar materials
Effects on fetal development	:	Test Type: Embryo-fetal development Species: Rat Application Route: inhalation (vapor) Method: OECD Test Guideline 414 Result: negative
<b>2-(2-Butoxyethoxy)ethanol:</b>		
Effects on fertility	:	Test Type: One-generation reproduction toxicity study Species: Rat Application Route: Skin contact Method: OECD Test Guideline 415 Result: negative
<b>Carbon black:</b>		
Effects on fetal development	:	Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Method: OECD Test Guideline 414 Result: negative
		Test Type: Embryo-fetal development Species: Mouse Application Route: inhalation (dust/mist/fume) Result: negative
<b>Cumene:</b>		
Effects on fertility	:	Species: Rat, male Application Route: inhalation (vapor) Result: negative
Effects on fetal development	:	Test Type: Embryo-fetal development Species: Rat Application Route: inhalation (vapor) Method: OECD Test Guideline 414 Result: negative

### STOT-single exposure

May cause respiratory irritation.

### Components:

#### **N-Methyl-2-pyrrolidone:**

Assessment : May cause respiratory irritation.

#### **Isobutyl methyl ketone:**

Assessment : May cause respiratory irritation.

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

---

**Solvent naphtha (petroleum), light arom.:**  
Assessment : May cause drowsiness or dizziness.

**1,2,4-Trimethylbenzene:**  
Assessment : May cause respiratory irritation.

**Cumene:**  
Assessment : May cause respiratory irritation.

### STOT-repeated exposure

Not classified based on available information.

### Components:

**N-Methyl-2-pyrrolidone:**  
Routes of exposure : inhalation (vapor)  
Assessment : No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

**2-(2-Butoxyethoxy)ethanol:**  
Routes of exposure : inhalation (vapor)  
Assessment : No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

### Repeated dose toxicity

#### Components:

**N-Methyl-2-pyrrolidone:**  
Species : Rat  
NOAEL : 0.5 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 90 Days  
Method : OECD Test Guideline 413

Species : Rat  
NOAEL : 169 - 217 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Method : OECD Test Guideline 408

Species : Rabbit  
NOAEL : 826 mg/kg  
Application Route : Skin contact  
Exposure time : 20 Days

**Isobutyl methyl ketone:**  
Species : Rat  
NOAEL : 1,840 mg/m<sup>3</sup>  
Application Route : inhalation (vapor)  
Exposure time : 13 Weeks

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

---

### **Solvent naphtha (petroleum), light arom.:**

Species : Rat  
NOAEL : 1.4 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 107 Weeks

### **1,2,4-Trimethylbenzene:**

Species : Rat  
NOAEL : 600 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Method : OECD Test Guideline 408  
Remarks : Based on data from similar materials

Species : Rat  
NOAEL : 1230 mg/m<sup>3</sup>  
Application Route : inhalation (vapor)  
Exposure time : 90 Days

### **2-(2-Butoxyethoxy)ethanol:**

Species : Rat  
NOAEL : 250 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Method : OECD Test Guideline 408

Species : Rat  
NOAEL :  $\geq 0.094$  mg/l  
Application Route : inhalation (vapor)  
Exposure time : 90 Days  
Method : OECD Test Guideline 413

Species : Rat  
NOAEL :  $> 2,000$  mg/kg  
Application Route : Skin contact  
Exposure time : 90 Days  
Method : OECD Test Guideline 411

### **Cumene:**

Species : Rat  
NOAEL : 125 ppm  
LOAEL : 250 ppm  
Application Route : inhalation (vapor)  
Exposure time : 90 Days

### **Aspiration toxicity**

Not classified based on available information.

## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
 Date of first issue: 02/27/2017

**Components:****Solvent naphtha (petroleum), light arom.:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**1,2,4-Trimethylbenzene:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Cumene:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****N-Methyl-2-pyrrolidone:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 500 mg/l  
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l  
 Exposure time: 24 h  
 Method: DIN 38412

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 600.5 mg/l  
 Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 12.5 mg/l  
 Exposure time: 21 d  
 Method: OECD Test Guideline 211

**Isobutyl methyl ketone:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 179 mg/l  
 Exposure time: 96 h  
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 200 mg/l  
 Exposure time: 48 h  
 Method: OECD Test Guideline 202

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 30 mg/l  
 Exposure time: 21 d

Toxicity to microorganisms : EC10 (Pseudomonas putida): 275 mg/l  
 Exposure time: 16 h



# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

### **Solvent naphtha (petroleum), light arom.:**

- Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): 8.2 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 4.5 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202
- Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): 880 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201
- NOELR (Pseudokirchneriella subcapitata (green algae)): 0.1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOELR (Pimephales promelas (fathead minnow)): 2.6 mg/l  
Exposure time: 14 d  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 204
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 2.6 mg/l  
Exposure time: 21 d  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 211

### **1,2,4-Trimethylbenzene:**

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 7.72 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3.6 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 2.356 mg/l  
Exposure time: 96 h

### **Ecotoxicology Assessment**

- Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

### **Diiron trioxide:**

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 50,000 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

Toxicity to microorganisms : EC50: > 10,000 mg/l  
Exposure time: 3 h

### 2-(2-Butoxyethoxy)ethanol:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 1,300 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae : NOEC (Desmodesmus subspicatus (green algae)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10: > 1,995 mg/l  
Exposure time: 30 min  
Method: OECD Test Guideline 209

### Carbon black:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 5,600 mg/l  
Exposure time: 24 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

Toxicity to algae : EL10 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

EL50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

### Cumene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.8 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.14 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae : ErC50 (Desmodesmus subspicatus (green algae)): 2.01 mg/l  
Exposure time: 72 h

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

Method: OECD Test Guideline 201  
EC10 (Desmodesmus subspicatus (green algae)): 1.35 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.35 mg/l  
Exposure time: 21 d

### Persistence and degradability

#### Components:

##### **N-Methyl-2-pyrrolidone:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 73 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301C

##### **Isobutyl methyl ketone:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

##### **Solvent naphtha (petroleum), light arom.:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 77 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

##### **1,2,4-Trimethylbenzene:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 60 %  
Exposure time: 28 d

##### **2-(2-Butoxyethoxy)ethanol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 85 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301C

##### **Cumene:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 70 %  
Exposure time: 20 d

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

---

### Bioaccumulative potential

#### Components:

##### **N-Methyl-2-pyrrolidone:**

Partition coefficient: n-octanol/water : log Pow: -0.46

##### **Isobutyl methyl ketone:**

Partition coefficient: n-octanol/water : log Pow: 1.9

##### **Solvent naphtha (petroleum), light arom.:**

Partition coefficient: n-octanol/water : log Pow: > 4

##### **2-(2-Butoxyethoxy)ethanol:**

Partition coefficient: n-octanol/water : log Pow: 1

##### **Cumene:**

Partition coefficient: n-octanol/water : log Pow: 3.55

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Results of PBT and vPvB assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

UN number : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : 3

##### IATA-DGR

UN/ID No. : UN 1263  
Proper shipping name : Paint  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

##### IMDG-Code

UN number : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

##### 49 CFR

UN/ID/NA number : UN 1263  
Proper shipping name : Paint  
Class : 3  
Packing group : III  
Labels : FLAMMABLE LIQUID  
ERG Code : 128  
Marine pollutant : no

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version: 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

### SECTION 15. REGULATORY INFORMATION

#### EPCRA - Emergency Planning and Community Right-to-Know

##### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Isobutyl methyl ketone	108-10-1	5000	23159
Xylene	1330-20-7	100	81037
Formaldehyde	50-00-0	100	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

##### SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Formaldehyde	50-00-0	100	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

##### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Carcinogenicity  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

N-Methyl-2-pyrrolidone	872-50-4	>= 30 - < 50 %
Isobutyl methyl ketone	108-10-1	>= 20 - < 30 %
1,2,4-Trimethylbenzene	95-63-6	>= 1 - < 5 %
2-(2-Butoxyethoxy)ethanol	112-34-5	>= 1 - < 5 %
2-Butoxyethanol	111-76-2	< 0.1 %

##### Volatile organic compounds (VOC) content

VOC content: 738.27 g/l  
Remarks: less exempt

VOC content: 738.15 g/l  
Remarks: as packaged

# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

---

### US State Regulations

#### Pennsylvania Right To Know

N-Methyl-2-pyrrolidone	872-50-4
Isobutyl methyl ketone	108-10-1
Fluoropolymer	Trade secret
Polyamide-imide	Trade secret
Solvent naphtha (petroleum), light arom.	64742-95-6
1,3,5-Triazine-2,4,6-triamine, polymer with formaldehyde, butylated isobutylated	68002-24-4
1,2,4-Trimethylbenzene	95-63-6
Diiron trioxide	1309-37-1
2-(2-Butoxyethoxy)ethanol	112-34-5
Butan-1-ol	71-36-3
Butan-2-ol	78-92-2
Cumene	98-82-8
Xylene	1330-20-7
2-Methyl-1-propanol	78-83-1
Formaldehyde	50-00-0
Toluene	108-88-3
Ammonium sulfate	7783-20-2

#### California Prop. 65

WARNING: This product can expose you to chemicals including Isobutyl methyl ketone, Benzene, Carbon black, Cumene, Formaldehyde, which is/are known to the State of California to cause cancer, and N-Methyl-2-pyrrolidone, Isobutyl methyl ketone, Benzene, Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### California List of Hazardous Substances

Isobutyl methyl ketone	108-10-1
1,2,4-Trimethylbenzene	95-63-6
Diiron trioxide	1309-37-1

#### California Permissible Exposure Limits for Chemical Contaminants

N-Methyl-2-pyrrolidone	872-50-4
Isobutyl methyl ketone	108-10-1
1,2,4-Trimethylbenzene	95-63-6
Diiron trioxide	1309-37-1

# SAFETY DATA SHEET




## 959G-205 ONE COAT DARK BROWN

Version 8.0      Revision Date: 09/11/2018      SDS Number: 1347724-00035      Date of last issue: 04/05/2018  
Date of first issue: 02/27/2017

### SECTION 16. OTHER INFORMATION

#### Further information

##### NFPA 704:



##### HMIS® IV:

HEALTH	*	2
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or nominated distributors. All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

#### Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA CARC	: OSHA Specifically Regulated Chemicals/Carcinogens
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	: USA. Occupational Exposure Limits (OSHA) - Table Z-2
US WEEL	: USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
ACGIH / C	: Ceiling limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	: Ceiling value not be exceeded at any time.
OSHA CARC / PEL	: Permissible exposure limit (PEL)
OSHA CARC / STEL	: Excursion limit
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-2 / TWA	: 8-hour time weighted average
US WEEL / TWA	: 8-hr TWA

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Sub-



# SAFETY DATA SHEET



## 959G-205 ONE COAT DARK BROWN

Version	Revision Date:	SDS Number:	Date of last issue: 04/05/2018
8.0	09/11/2018	1347724-00035	Date of first issue: 02/27/2017

stances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/11/2018

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8