Tedlar® 68080 Flexible Product Adhesive

Version 2.1

Issue Date Revision Date : 05/20/2021 08/13/2019 :

Ref. 13000000851

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name Product Use	 Tedlar® 68080 Flexible Product Adhesive Adhesives
Restrictions on use	: Do not use in medical applications involving permanent implantation in the human body.
Manufacturer/Supplier	: DuPont 974 Centre Road Wilmington, DE 19805, USA
Product Information Medical Emergency Transport Emergency	 +1-833-338-7668 (outside the U.S. +1-302-996-8439) 1-800-441-3637 (outside the U.S. 1-302-774-1139) +1-800-424-9300 (outside the U.S. & Canada +1-703-527-3887)

SECTION 2. HAZARDS IDENTIFICATION

Product hazard category


Flammable liquids	Category 2
Skin irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Reproductive toxicity	Category 2
Specific target organ toxicity -	Category 3
single exposure	
Specific target organ toxicity -	Category 2
repeated exposure	
Aspiration hazard	Category 1

Safety Data Sheet

OUPONT

Tedlar® 68080 Flexible Product Adhesive

Version 2.1





Tedlar® 68080 Flexible Product Adhesive

Version 2.1

Issue Date Revision Date	:	05/20/2021 Ref. 13000000851 08/13/2019
Hazardous prevention measures		 Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection. IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. Store in a well-ventilated place. Keep cool. Store in a well-ventilated place. Keep cool. Store is a well-ventilated place. Keep cool. Store ocntents/ container to an approved waste disposal plant.
Other hazards The following percentage	je of t	the mixture consists of ingredient(s) with unknown acute toxicity: 30 - 40 %

Tedlar® 68080 Flexible Product Adhesive

Version 2.1

 Issue Date
 :
 05/20/2021

 Revision Date
 :
 08/13/2019

Ref. 13000000851

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
Acrylic Polymer		25 - 35 %
Propan-2-ol	67-63-0	25 - 35 %
Toluene	108-88-3	33 - 35 %

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4. FIRST AID MEASURES

 No applicable data available. Move to fresh air. Artificial respiration and/or oxygen may be necessary. Consult a physician.
: Wash off immediately with soap and plenty of water. Wash clothing before reuse.
: Hold eye open and rinse slowly and gently with water for 15-20 minutes. If eye irritation persists, consult a specialist.
: Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Consult a physician.
: No applicable data available.
No applicable data available.No applicable data available.

SECTION 5. FIREFIGHTING MEASURES

Tedlar® 68080 Flexible Product Adhesive

Version 2.1

	05/20/2021 08/13/2019	Ref. 13000000851
Suitable extinguishing media	: Dry chemical, Carbor	n dioxide (CO2), Alcohol-resistant foam
Unsuitable extinguishing media	: High volume water je	t, (contamination risk)
Specific hazards	flammable at tempera	xplosive mixtures with air. Fine mists or sprays may be atures below the flashpoint. Fire will produce dense black zardous combustion products (see section 10). on products: Carbon monoxide Nitrogen oxides (NOx)
Special protective equipment for firefighters	: Wear self-contained	breathing apparatus and protective suit.
Further information	: Cool containers/tanks upwind of fire.	s with water spray. Evacuate personnel and keep

SECTION 6. ACCIDENTAL RELEASE MEASURES

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Safeguards (Personnel)	:	Wear personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.
Environmental precautions	:	Prevent material from entering sewers, waterways, or low areas. Do not let product enter drains.
Spill Cleanup	:	Soak up with inert absorbent material. Clean with detergents. Avoid solvents.
Accidental Release Measures	:	No applicable data available.

SECTION 7. HANDLING AND STORAGE

Handling (Personnel)	:	Avoid contact with skin, eyes and clothing. Avoid breathing vapours or mist. Keep away from flames and sparks. Do not store or consume food, drink or tobacco in areas where they may become contaminated with this material. Do not breathe vapours or spray mist. Wash hands before breaks and immediately after handling the product.
		5 / 15

Tedlar® 68080 Flexible Product Adhesive

Version 2.1

	05/20/2021 Ref. 13000000851 08/13/2019
Handling (Physical Aspects)	: When transferring from one container to another apply earthing measures and use conductive hose material. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Vapours may form explosive mixtures with air. Vapours are heavier than air and may spread along floors.
Dust explosion class Storage	 No applicable data available. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Storage period	: No applicable data available.
Storage temperature	: No applicable data available.
SECTION 8. EXPOSURE CONTR Personal protective equipment Respiratory protection	
Hand protection	 Material: butyl-rubber Glove thickness: > 0.4 mm Wearing time: 8 h Additional protection: Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Eye protection	: Safety glasses
Exposure Guidelines Exposure Limit Values	
Acrylic Polymer No applicable data ava	ailable
	6/15
	6 / 15

Tedlar® 68080 Flexible Product Adhesive

Version 2.1

Issue Date Revision Date

: 05/20/2021 : 08/13/2019 Ref. 13000000851

Propan-2-ol			
TLV	(ACGIH)	200 ppm	TWA
TLV	(ACGIH)	400 ppm	STEL
REL	(NIOSH)	400 ppm 980 mg/m3	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
REL	(NIOSH)	500 ppm 1,225 mg/m3	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
PEL (Permissible Exposure Limit)	(OSHA)	400 ppm 980 mg/m3	8 hr. TWA
PEL (Permissible Exposure Limit)	(OSHA)	400 ppm 980 mg/m3	TWA
PEL (Permissible Exposure Limit)	(OSHA)	500 ppm 1,225 mg/m3	STEL
AEL *	(DuPont)	200 ppm	8 & 12 hr. TWA

Toluene			
TLV	(ACGIH)	20 ppm	TWA
REL	(NIOSH)	100 ppm 375 mg/m3	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
REL	(NIOSH)	150 ppm 560 mg/m3	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
PEL (Permissible Exposure Limit)	(OSHA)	200 ppm	TWA
PEL (Permissible Exposure Limit)	(OSHA)	300 ppm	CEIL
PEL (Permissible Exposure Limit)	(OSHA)	500 ppm	Peak
PEL (Permissible Exposure Limit)	(OSHA)	100 ppm 375 mg/m3	TWA
PEL (Permissible Exposure Limit)	(OSHA)	150 ppm 560 mg/m3	STEL
AEL *	(DuPont)	20 ppm	8 & 12 hr. TWA

Biological Exposure Indices

Propan-2-ol
BEI

(ACGIH)

40 mg/l

7/15

Acetone/Urine

Tedlar® 68080 Flexible Product Adhesive

Version 2.1

Issue Date Revision Date

: 05/20/2021 : 08/13/2019 Ref. 13000000851

			End of shift at end of workweek		
Toluene					
BEI	(ACGIH)	0.02 mg/l	Toluene/In blood Prior to last shift of workweek		
BEI	(ACGIH)	0.03 mg/l	Toluene/Urine End of shift (As soon as possible after exposure ceases)		
BEI	(ACGIH)	0.3	o-Cresol/Urine End of shift (As soon as possible after exposure ceases)		

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Physical state Form Color	: liquid : liquid : clear
Odor	: aromatic
Odor threshold	: No applicable data available.
рН	: No applicable data available.
Melting point/range	: No applicable data available.
Boiling point/boiling range	: Boiling point/boiling range 82 - 111 °C (180 - 232 °F)
Flash point	: 5 °C Method: closed cup
Evaporation rate	: No applicable data available.
Flammability (solid, gas)	: No applicable data available.

8/15

Tedlar® 68080 Flexible Product Adhesive

Version 2.1

Issue Date : Revision Date :	05/20/2021 08/13/2019	Ref. 13000000851
Upper explosion limit	: 12 vol%	
Lower explosion limit	: 1 vol%	
Vapor pressure	: ca. 22.5 hPa at 25	°C (77 °F)
Vapour density	: No applicable data	available.
Density	: ca. 0.91 g/cm3	
Specific gravity (Relative density)	: No applicable data	available.
Water solubility	: No applicable data	available.
Solubility(ies)	: No applicable data	available.
Partition coefficient: n- octanol/water	: No applicable data	available.
Auto-ignition temperature	: No applicable data	available.
Decomposition temperature	: No applicable data	available.
Viscosity, kinematic	: No applicable data	available.
Viscosity, dynamic	: No applicable data	available.
% Volatile	: 65 - 70 %	

SECTION 10. STABILITY AND REACTIVITY

Reactivity Chemical stability	No applicable data available. No decomposition if stored and applied as directed.	
Possibility of hazardous reactions Conditions to avoid	polymerisation Polymerization will not occur. Heat, flames and sparks.	
Incompatible materials	Oxidizing agents	
Hazardous decomposition	Hazardous decomposition products formed under fire conditions.: Carbon	
	9 / 15	

Safety	Data	Sheet
--------	------	-------

Tedlar® 68080 Flexible Product Adhesive

Version 2.1

 Issue Date
 :
 05/20/2021

 Revision Date
 :
 08/13/2019

Ref. 13000000851

products

monoxide, Carbon dioxide (CO2), Nitrogen oxides (NOx), Smoke

SECTION 11. TOXICOLOGICAL INFORMATION

Propan-2-ol

			10 / 15
	Teratogenicity	:	Animal testing showed effects on embryo-fetal development at levels equal to or above those causing maternal toxicity.
	Reproductive toxicity	:	No toxicity to reproduction Animal testing showed effects on reproduction at levels equal to or above those causing parental toxicity.
	Mutagenicity	:	Animal testing did not show any mutagenic effects. Tests on bacterial or mammalian cell cultures did not show mutagenic effects.
	Carcinogenicity	:	Not classifiable as a human carcinogen. Overall weight of evidence indicates that the substance is not carcinogenic.
			- No toxicologically significant effects were found.
	Repeated dose toxicity	:	Inhalation multiple species
			Does not cause respiratory sensitisation., Mouse
	Skin sensitization	:	Does not cause skin sensitisation., Guinea pig
	Eye irritation	:	Irritation to eyes, reversing after 7 to 21 days, Rabbit
	Skin irritation	:	No skin irritation, Rabbit
	Oral LD50	:	5,840 mg/kg , Rat
	Dermal LD50	:	12,870 mg/kg , Rabbit
	Inhalation 4 h LC50	:	> 24.5 mg/l , Rat Target Organs: Central nervous system Central nervous system depression
Jpan-2-0	1		

Tedlar® 68080 Flexible Product Adhesive

Version 2.1

Issue Dat Revision)5/20/2021)8/13/2019	Ref. 13000000851
Foluene	Inhalation 4 h LC	50	:	28.1 mg/l , Rat Target Organs: Central nervous system
	Dermal LD50		:	> 5,000 mg/kg , Rabbit
	Oral LD50		:	5,580 mg/kg , Rat
	Skin irritation		:	Severe skin irritation, Rat
	Eye irritation		:	Irritation to eyes, reversing within 7 days, Rabbit
	Skin sensitization		:	Does not cause skin sensitisation., Guinea pig
				Does not cause respiratory sensitisation., Not tested on animals
	Repeated dose to	oxicit	y :	Inhalation Rat - 28 d vapour LOAEL: 0.3 mg/l Target Organs: Central nervous system Central nervous system effects
	Carcinogenicity		:	Animal testing did not show any carcinogenic effects.
	Mutagenicity		:	Animal testing did not show any mutagenic effects. Tests on bacterial or mammalian cell cultures did not show mutagenic effects.
	Reproductive toxi	city	:	Some evidence of adverse effects on sexual function and fertility, based on animal experiments. Animal testing showed effects on reproduction at levels below those causing parental toxicity that included: Reduced sperm count
	Teratogenicity		:	Animal testing showed effects on embryo-fetal development at levels equal to or above those causing maternal toxicity.

The carcinogenicity classifications for this product and/or its ingredients have been determined according to HazCom 2012, Appendix A.6. The classifications may differ from those listed in the National Toxicology



Tedlar® 68080 Flexible Product Adhesive

Version 2.1

Issue Date Revision Date : 05/20/2021 : 08/13/2019 Ref. 13000000851

Program (NTP) Report on Carcinogens (latest edition) or those found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition).

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen.

Aquatic To			
Propan-2-o	96 h LC50	:	Pimephales promelas (fathead minnow) 9,640 mg/I OECD Test Guideline 203
	72 h ErC50	:	Scenedesmus quadricauda (Green algae) > 1,000 mg/l
	24 h EC50	:	Daphnia (water flea) > 10,000 mg/I OECD Test Guideline 202
	48 h EC50	:	Crangon crangon (shrimp) 1,400 mg/l
	21 d	:	NOEC Daphnia magna (Water flea) 30 mg/l
Toluene	96 h LC50	:	Fish (unspecified species) 5.5 mg/l
	72 h EC50	:	Algae 207 mg/l
	48 h EC50	:	Ceriodaphnia dubia (water flea) 3.78 mg/l
	40 d	:	NOEC Fish (unspecified species) 1.39 mg/l
	7 d	:	NOEC Ceriodaphnia dubia (water flea) 0.74 mg/l
Enviro	onmental Fate		
Propan-2-o	bl Bioaccumulation	:	Bioaccumulation is unlikely.
Toluene	Bioaccumulation	:	Bioaccumulation is unlikely.
			12 / 15
			12713

Tedlar® 68080 Flexible Product Adhesive

.

Version 2.1

Issue Date Revision Date : 05/20/2021 08/13/2019 Ref. 13000000851

SECTION 13. DISPOSAL CONSIDERATIONS

Waste disposal methods -: In accordance with local and national regulations. Must be incinerated in a Product suitable incineration plant holding a permit delivered by the competent authorities. Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

DOT	UN number	: 1133
	Proper shipping name	: Adhesives
	Class	: 3
	Packing group	: 11
	Labelling No.	: 3
IATA_C	UN number	: 1133
	Proper shipping name	: Adhesives
	Class	: 3
	Packing group	: 11
	Labelling No.	: 3
IMDG	UN number	: 1133
	Proper shipping name	: ADHESIVES
	Class	: 3
	Packing group	: 11
	Labelling No.	: 3

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazard

TSCA

: Flammable (gases, aerosols, liquids, or solids) 13/15

: On the inventory, or in compliance with the inventory

Tedlar® 68080 Flexible Product Adhesive

Version 2.1

Issue Date Revision Date	: :	05/20/2021 08/13/2019	Ref. 13000000851
classification		Skin corrosion or irrita Serious eye damage Reproductive toxicity Specific target organ Aspiration hazard	
SARA 313 Regulate Chemical(s)	d	a 1	ents are subject to reporting levels established by a 313: Toluene, Propan-2-ol
California Prop. 65		California to cause ca	ose you to Benzene, which is/are known to the State of ncer and birth defects or other reproductive harm. For o www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Restrictions for use : Do not use DuPont materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless the material has been provided from DuPont under a written contract that is consistent with DuPont policy regarding medical applications and expressly acknowledges the contemplated use. For further information, please contact your DuPont representative. You may also request a copy of the DuPont POLICY Regarding Medical Applications and DuPont CAUTION Regarding Medical Applications.

The DuPont Oval Logo, DuPont[™] and all products denoted with ® or [™] are trademarks or registered trademarks of affiliates of DuPont de Nemours, Inc.

Issue Date	:	05/20/2021
Revision Date	:	08/13/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

14 / 15



Tedlar® 68080 Flexible Product Adhesive

Version 2.1

 Issue Date
 :
 05/20/2021

 Revision Date
 :
 08/13/2019

Ref. 13000000851

15/15