according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Dispersion PFAD 335D

Versi 8.2	on	Revision Date: 01/08/2024		0S Number: 35563-00045	Date of last issue: 04/25/2023 Date of first issue: 02/27/2017			
SECI	SECTION 1. IDENTIFICATION							
F	Product	name	:	PFA Fluoroplastic Dispersion PFAD 335D				
F	Product	code	:	D14717121				
Ş	SDS-Id	entcode	:	13000043046				
г	Manufa	cturer or supplier's	deta	nils				
(Compa	ny name of supplier	:	The Chemours C	ompany FC, LLC			
Address		:	1007 Market Street Wilmington, DE 19801 United States of America (USA)					
7	Telepho	one	:	1-844-773-CHEM	(outside the U.S. 1-302-773-1000)			
E	Emerge	ency telephone	:		cy: 1-866-595-1473 (outside the U.S. 1-302- nsport emergency: +1-800-424-9300 (outside 527-3887)			
F	Recom	mended use of the c	hen	nical and restriction	ons on use			
F	Recom	mended use	:	Coatings				
F	Restrict	ions on use	:	tions involving im internal body fluid written agreemen	only. ell Chemours™ materials in medical applica- plantation in the human body or contact with s or tissues unless agreed to by Seller in a t covering such use. For further information, ur Chemours representative.			

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)				
Eye irritation	Category 2A			
GHS label elements Hazard pictograms				
Signal Word	Warning			
Hazard Statements	H319 Causes serious eye irritation.			

according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Dispersion PFAD 335D

Version 8.2	Revision Date: 01/08/2024	SDS Number: 1335563-00045	Date of last issue: 04/25/2023 Date of first issue: 02/27/2017
Preca	uutionary Statements	P280 Wear eye	n thoroughly after handling. e protection and face protection.
		for several minute to do. Continue	P338 IF IN EYES: Rinse cautiously with water utes. Remove contact lenses, if present and easy rinsing. eye irritation persists: Get medical attention.

Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flulike symptoms in humans, especially when smoking contaminated tobacco.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
2,6,8-Trimethyl-4-	60828-78-6	>= 1 - < 5
nonyloxypolyethyleneoxyethanol		

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	:	In the case of accident or if you feel unwell, seek medical ad- vice immediately. When symptoms persist or in all cases of doubt seek medical advice.
If inhaled	:	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
In case of eye contact	:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention.
If swallowed	:	If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and	:	Local irritation Symptoms may be delayed.

Chemours⁻

according to the OSHA Hazard Communication Standard

PFA Fluoroplastic Dispersion PFAD 335D

Version 8.2	Revision Date: 01/08/2024	SDS Number: 1335563-00045	Date of last issue: 04/25/2023 Date of first issue: 02/27/2017
delay	ed	respiratory tr Lung edema Impairment o Causes serio	
Protection of first-aiders		and use the	oonders should pay attention to self-protection, recommended personal protective equipment ential for exposure exists (see section 8).
Notes	s to physician	: Treat sympto	matically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	None known.
Specific hazards during fire fighting	:	Exposure to combustion products may be a hazard to health.
Hazardous combustion prod- ucts	:	Hydrogen fluoride carbonyl fluoride potentially toxic fluorinated compounds aerosolized particulates Carbon oxides
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Follow safe handling advice (see section 7) and personal pro- tective equipment recommendations (see section 8).
Environmental precautions	:	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g., by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages



PFA Fluoroplastic Dispersion PFAD 335D

Version	Revision Date:	SDS Number:	Date of last issue: 04/25/2023
8.2	01/08/2024	1335563-00045	Date of first issue: 02/27/2017
	ds and materials for nment and cleaning up	For large spi ment to keep pumped, sto Clean up rer bent. Local or nati sal of this ma ployed in the which regula Sections 13	ontained. Ils, provide diking or other appropriate contain- o material from spreading. If diked material can be re recovered material in appropriate container. naining materials from spill with suitable absor- onal regulations may apply to releases and dispo- aterial, as well as those materials and items em- e cleanup of releases. You will need to determine tions are applicable. and 15 of this SDS provide information regarding or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures	:	See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation	:	Use only with adequate ventilation.
Advice on safe handling	:	Do not get on skin or clothing. Avoid inhalation of vapor or mist. Do not swallow. Do not get in eyes. Wash skin thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as- sessment Take care to prevent spills, waste and minimize release to the environment. Do not breathe decomposition products.
Conditions for safe storage	:	Keep in properly labeled containers. Store in accordance with the particular national regulations.
Materials to avoid	:	No special restrictions on storage with other products.
Recommended storage tem- perature	:	45 - 75 °F / 7 - 24 °C
Further information on stor- age stability	:	Do not freeze.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Dispersion PFAD 335D

Version	Revision Date:	SDS Number:	Date of last issue: 04/25/2023
8.2	01/08/2024	1335563-00045	Date of first issue: 02/27/2017

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		С	2 ppm (Fluorine)	ACGIH
		С	6 ppm 5 mg/m³	NIOSH REL
		TWA	3 ppm 2.5 mg/m ³	NIOSH REL
		TWA	3 ppm	OSHA Z-2
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m ³	NIOSH REL
		ST	5 ppm 15 mg/m³	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m ³	NIOSH REL
		ST	30,000 ppm 54,000 mg/m ³	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m ³	OSHA Z-1
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m ³	NIOSH REL
		С	200 ppm 229 mg/m ³	NIOSH REL
		TWA	50 ppm 55 mg/m³	OSHA Z-1

Engineering measures

Processing may form hazardous compounds (see section 10).

Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied

according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Dispersion PFAD 335D

Version 8.2	Revision Date: 01/08/2024	SDS Numbe 1335563-00		
		exposur	r if there is any potential for uncontrolled release, e levels are unknown, or any other circumstance r purifying respirators may not provide adequate n.	
Hand protection Material Glove thickness Wearing time			PVC > 0.6 mm 480 min	
R	emarks	on the c applicati micals o manufac workday	gloves to protect hands against chemicals depending oncentration specific to place of work. For special ons, we recommend clarifying the resistance to che- f the aforementioned protective gloves with the glove turer. Wash hands before breaks and at the end of . Breakthrough time is not determined for the pro- ange gloves often!	
Eye	protection	: Wear the Safety g	e following personal protective equipment: oggles	
Skin	and body protection	resistano potentia Skin cor	opropriate protective clothing based on chemical ce data and an assessment of the local exposure tact must be avoided by using impervious protective (gloves, aprons, boots, etc).	
Hygi	ene measures	eye flush king plac When us	ure to chemical is likely during typical use, provide ning systems and safety showers close to the wor- ce. sing do not eat, drink or smoke. Intaminated clothing before re-use.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid, dispersion
Color	:	milky, white
Odor	:	slight, ammoniacal
Odor Threshold	:	No data available
рН	:	9 - 11
Melting point/freezing point	:	No data available
Initial boiling point and boiling	:	212 °F / 100 °C

according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Dispersion PFAD 335D

Ver 8.2	sion	Revision Date: 01/08/2024		S Number: 35563-00045	Date of last issue: 04/25/2023 Date of first issue: 02/27/2017
	range				
	Flash p	point	:	does not flash	
	Evapor	ration rate	:	No data available	e
	Flamm	ability (solid, gas)	:	Not applicable	
	Flamm	ability (liquids)	:	Not applicable	
		explosion limit / Upper ability limit	:	No data available	9
	Lower explosion limit / Lower flammability limit		:	No data available	2
	Vapor pressure		:	No data available	9
	Relative vapor density		:	No data available	9
	Density		:	1.48 g/cm ³	
	Solubility(ies) Water solubility		:	dispersible	
	Partitio octano	n coefficient: n- I/water	:	Not applicable	
	Autoig	nition temperature	:	No data available	9
	Decom	position temperature	:	No data available	9
	Viscos Visc	ity cosity, kinematic	:	No data available	9
	Explos	ive properties	:	Not explosive	
	Oxidizi	ng properties	:	The substance o	r mixture is not classified as oxidizing.
	Particle size		:	Not applicable	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reac- tions	:	Hazardous decomposition products will be formed at elevated temperatures.

according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Dispersion PFAD 335D

sion	Revision Date: 01/08/2024		Date of last issue: 04/25/2023 Date of first issue: 02/27/2017
Cond	itions to avoid	: None known.	
Incon	npatible materials	: None.	
	rdous decompositio	products	
Therr	nal decomposition	: Hydrogen fluoride Carbonyl difluoride Carbon dioxide Carbon monoxide	
CTION	11. TOXICOLOGICA	INFORMATION	
Infor	mation on likely rou	s of exposure	
Inges	contact		
	e toxicity lassified based on av	able information.	
Prod	uct:		
Acute	e oral toxicity	: Acute toxicity estimated Method: Calculation	
<u>Com</u>	oonents:		
2,6,8	Trimethyl-4-nonylo	polyethyleneoxyethanol	1:
Acute	oral toxicity	: LD50 (Rat): 3,300 n	ng/kg
Acute	e dermal toxicity	: LD50 (Rabbit): > 5,0	000 mg/kg
	corrosion/irritation		
Skin		able information	
-	lassified based on av		
Not c	lassified based on av ponents:		
Not c <u>Com</u>	ponents:	polyethyleneoxyethanol	1:

Causes serious eye irritation.

Product:

Species	:	In Vitro - Bovine
Result	:	Irritation to eyes, reversing within 21 days
Remarks	:	Based on data from similar materials

according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Dispersion PFAD 335D

Version	Revision Date:	SDS Number:	Date of last issue: 04/25/2023
8.2	01/08/2024	1335563-00045	Date of first issue: 02/27/2017

Components:

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Result

: Irreversible effects on the eye

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Germ cell mutagenicity

Not classified based on available information.

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC	No ingredient of this product present at levels greater than or equal to 0.1% is
	identified as probable, possible or confirmed human carcinogen by IARC.

- **OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
- **NTP** No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 39 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 81.2 mg/l Exposure time: 48 h

according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Dispersion PFAD 335D

Version 8.2	Revision Date: 01/08/2024	SDS Number: 1335563-00045	Date of last issue: 04/25/2023 Date of first issue: 02/27/2017
Persi	stence and degradal	bility	
<u>Comp</u>	oonents:		
2,6,8-	Trimethyl-4-nonylox	ypolyethyleneoxyetha	anol:
Biode	gradability	: Result: Not read	dily biodegradable.
No da	cumulative potentia ata available lity in soil	I	
No da	ita available		
Other	adverse effects		
No da	ita available		
SECTION	13. DISPOSAL CON	SIDERATIONS	
Dispo	osal methods		

Disposal methods		
Waste from residues	:	Dispose of in accordance with local regulations. Do not dispose of waste into sewer.
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR Not regulated as a dangerous good

Special precautions for user

Not applicable

according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Dispersion PFAD 335D

Version	Revision Date:	SDS Number:	Date of last issue: 04/25/2023
8.2	01/08/2024	1335563-00045	Date of first issue: 02/27/2017

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	Serious eye damage or eye irritation
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Poly(Heptafluoropropyl Trifluorovinyl Ether/Tetrafluoroethylene)	26655-00-5
Water	7732-18-5
Ammonium hydroxide	1336-21-6

California Prop. 65

WARNING: This product can expose you to chemicals including Pentadecafluorooctanoic acid, which is/are known to the State of California to cause cancer, and Carbon monoxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. Note to User: This product is not made with PFOA nor is PFOA intentionally present in the product; however, it is possible that PFOA may be present as an impurity at background (environmental) levels.


SECTION 16. OTHER INFORMATION

Further information

according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Dispersion PFAD 335D



Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

Full text of other abbreviations

ACGIH NIOSH REL OSHA Z-1		USA. ACGIH Threshold Limit Values (TLV) USA. NIOSH Recommended Exposure Limits USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
OSHA Z-2	:	USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organiza-

SAFETY DATA SHEET according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Dispersion PFAD 335D

Version	Revision Date:	SDS Number:	Date of last issue: 04/25/2023
8.2	01/08/2024	1335563-00045	Date of first issue: 02/27/2017

tion; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-
Data Sheet		cy, http://echa.europa.eu/

Revision Date

: 01/08/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8