according to the OSHA Hazard Communication Standard



# PFA Fluoroplastic Resin 450HP X

Version 5.2	Revision Date: 11/02/2023	SDS Number: 1854290-00017	Date of last issue: 04/11/2023 Date of first issue: 08/12/2017		
SECTIO	N 1. IDENTIFICATION				
Proc	duct name	: PFA Fluorop	lastic Resin 450HP X		
SDS	S-Identcode	: 130000051	460		
Mar	ufacturer or supplier's	details			
Con	npany name of supplier	: The Chemo	urs Company FC, LLC		
Add	ress		1007 Market Street Wilmington, DE 19801 United States of America (USA)		
Tele	phone	: 1-844-773-0	1-844-773-CHEM (outside the U.S. 1-302-773-1000)		
Eme	ergency telephone	773-2000) ;	ergency: 1-866-595-1473 (outside the U.S. 1-302- Transport emergency: +1-800-424-9300 (outside 703-527-3887)		
Rec	ommended use of the	chemical and res	rictions on use		
Rec	ommended use	: Resin for mo	oulding and/or extrusion		
Res	trictions on use	tions involvir internal body written agree	I use only. or resell Chemours™ materials in medical applica- ng implantation in the human body or contact with / fluids or tissues unless agreed to by Seller in a ement covering such use. For further information, act your Chemours representative.		

### **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

### **GHS** label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

#### Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flulike symptoms in humans, especially when smoking contaminated tobacco.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Substance
Substance name	:	Poly(Heptafluoropropyl Trifluorovinyl Ether/Tetrafluoroethylene)

according to the OSHA Hazard Communication Standard



# PFA Fluoroplastic Resin 450HP X

Version 5.2	Revision Date: 11/02/2023		OS Number: 54290-00017	Date of last issue: 04/11/2023 Date of first issue: 08/12/2017
CAS-	CAS-No.		26655-00-5	
-	oonents azardous ingredients			
SECTION	4. FIRST AID MEASU	RES		
lf inha	aled	:	If inhaled, remo Get medical att	ove to fresh air. ention if symptoms occur.
In cas	In case of skin contact			er and soap as a precaution. Tention if symptoms occur.
In cas	In case of eye contact			n water as a precaution. Tention if irritation develops and persists.
lf swa	If swallowed		Get medical att	O NOT induce vomiting. ention if symptoms occur. oroughly with water.
	important symptoms ffects, both acute and ed	:	: Polymer fume fever	
Prote	ction of first-aiders	:	: No special precautions are necessary for first aid respon	
Notes	Notes to physician		Treat symptom	atically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	None known.
Specific hazards during fire fighting	:	Exposure to combustion products may be a hazard to health.
Hazardous combustion prod- ucts	:	Hydrogen fluoride carbonyl fluoride potentially toxic fluorinated compounds aerosolized particulates Carbon oxides
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do

according to the OSHA Hazard Communication Standard



# PFA Fluoroplastic Resin 450HP X

Vers 5.2	sion	Revision Date: 11/02/2023		S Number: 54290-00017	Date of last issue: 04/11/2023 Date of first issue: 08/12/2017				
				so. Evacuate area.					
	Special protective equipment for fire-fighters		:	<ul> <li>Wear self-contained breathing apparatus for firefighting if necessary.</li> <li>Use personal protective equipment.</li> </ul>					
SEC	TION 6	ACCIDENTAL RELE	ASE	E MEASURES					
	tive equ	al precautions, protec- lipment and emer- procedures	:		ing advice (see section 7) and personal pro- recommendations (see section 8).				
	Environ	mental precautions	:	Retain and dispos	akage or spillage if safe to do so. e of contaminated wash water. should be advised if significant spillages				
		s and materials for ment and cleaning up	:	tainer for disposal Local or national r sal of this materia ployed in the clear which regulations Sections 13 and 1	egulations may apply to releases and dispo- l, as well as those materials and items em- nup of releases. You will need to determine				

### SECTION 7. HANDLING AND STORAGE

Technical measures	:	See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation	:	Use only with adequate ventilation.
Advice on safe handling	:	Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as- sessment Take care to prevent spills, waste and minimize release to the environment.
		Do not breathe decomposition products.
Conditions for safe storage	:	Keep in properly labeled containers. Store in accordance with the particular national regulations.
Materials to avoid	:	Do not store with the following product types: Strong oxidizing agents
Further information on stor- age stability	:	Stable under recommended storage conditions.

according to the OSHA Hazard Communication Standard



# PFA Fluoroplastic Resin 450HP X

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
5.2	11/02/2023	1854290-00017	Date of first issue: 08/12/2017

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

#### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		С	2 ppm (Fluorine)	ACGIH
		С	6 ppm 5 mg/m³	NIOSH REL
		TWA	3 ppm 2.5 mg/m <sup>3</sup>	NIOSH REL
		TWA	3 ppm	OSHA Z-2
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m <sup>3</sup>	NIOSH REL
		ST	5 ppm 15 mg/m³	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	NIOSH REL
		ST	30,000 ppm 54,000 mg/m <sup>3</sup>	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	OSHA Z-1
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m <sup>3</sup>	NIOSH REL
		С	200 ppm 229 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm 55 mg/m³	OSHA Z-1

Engineering measures

Processing may form hazardous compounds (see section 10).
 Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

#### Personal protective equipment

Respiratory protection

: General and local exhaust ventilation is recommended to

according to the OSHA Hazard Communication Standard



# PFA Fluoroplastic Resin 450HP X

Version 5.2	Revision Date: 11/02/2023		DS Number: 54290-00017	Date of last issue: 04/11/2023 Date of first issue: 08/12/2017
			concentrations ar unknown, approp Follow OSHA res use NIOSH/MSH by air purifying re dous chemical is respirator if there exposure levels a	cposures below recommended limits. Where e above recommended limits or are riate respiratory protection should be worn. pirator regulations (29 CFR 1910.134) and A approved respirators. Protection provided spirators against exposure to any hazar- limited. Use a positive pressure air supplied is any potential for uncontrolled release, are unknown, or any other circumstance g respirators may not provide adequate
	Hand protection Material		Heat resistant glo	ives
Re	Remarks		on the concentrat applications, we r micals of the afor manufacturer. Wa	protect hands against chemicals depending ion specific to place of work. For special recommend clarifying the resistance to che- ementioned protective gloves with the glove ash hands before breaks and at the end of rough time is not determined for the pro- ves often!
Eye p	Eye protection		Wear the following personal protective equipment: Safety glasses	
Skin	Skin and body protection		Skin should be washed after contact.	
Hygie	ene measures	:	eye flushing syste king place. When using do n	emical is likely during typical use, provide ems and safety showers close to the wor- ot eat, drink or smoke. red clothing before re-use.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	granules
Color	:	translucent
Odor	:	odorless
Odor Threshold	:	No data available
рН	:	No data available
Melting point/freezing point	:	> 572 °F / > 300 °C

according to the OSHA Hazard Communication Standard



# PFA Fluoroplastic Resin 450HP X

Vers 5.2	sion	Revision Date: 11/02/2023		S Number: 4290-00017	Date of last issue: 04/11/2023 Date of first issue: 08/12/2017
	Initial be range	oiling point and boiling	:	No data available	
	Flash p	oint	:	Not applicable	
	Evapora	ation rate	:	Not applicable	
	Flamma	ability (solid, gas)	:	Not classified as explosive dust-ai	a flammability hazard, Not expected to form r mixtures.
		explosion limit / Upper bility limit	:	No data available	
		explosion limit / Lower bility limit	:	No data available	
	Vapor p	pressure	:	Not applicable	
	Relative	e vapor density	:	Not applicable	
	Density		:	2.1 - 2.2 g/cm <sup>3</sup>	
	Solubili Wate	ty(ies) er solubility	:	insoluble	
	Partition octanol	n coefficient: n- /water	:	No data available	
	Autoign	ition temperature	:	No data available	)
	Decom	position temperature	:	No data available	)
	Viscosit Visc	ty osity, kinematic	:	Not applicable	
	Explosi	ve properties	:	Not explosive	
	Oxidizir	ng properties	:	The substance or	mixture is not classified as oxidizing.
	Particle	size	:	No data available	9

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reac- tions	:	Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevated temperatures.

according to the OSHA Hazard Communication Standard



# PFA Fluoroplastic Resin 450HP X

Version 5.2	Revision Date: 11/02/2023	SDS Number: 1854290-00017	Date of last issue: 04/11/2023 Date of first issue: 08/12/2017		
Condi	tions to avoid	: None known.			
Incom	patible materials	: Oxidizing ager	nts		
Hazardous decomposition products					
	nal decomposition	: Hydrogen fluor Carbonyl difluo Carbon dioxide Carbon mono	oride e		

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Skin contact Ingestion Eye contact

#### Acute toxicity

Not classified based on available information.

#### Skin corrosion/irritation

Not classified based on available information.

#### Serious eye damage/eye irritation

Not classified based on available information.

### Respiratory or skin sensitization

### Skin sensitization

Not classified based on available information.

#### **Respiratory sensitization**

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

- **IARC** No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- **OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
- **NTP** No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

Not classified based on available information.

according to the OSHA Hazard Communication Standard



# PFA Fluoroplastic Resin 450HP X

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
5.2	11/02/2023	1854290-00017	Date of first issue: 08/12/2017

### STOT-single exposure

Not classified based on available information.

#### STOT-repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

#### **SECTION 12. ECOLOGICAL INFORMATION**

Ecotoxicity No data available Persistence and degradability No data available Bioaccumulative potential No data available Mobility in soil No data available Other adverse effects No data available

### **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods		
Waste from residues	:	Dispose of in accordance with local regulations. Do not dispose of waste into sewer.
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.

#### **SECTION 14. TRANSPORT INFORMATION**

#### **International Regulations**

UNRTDG

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **Domestic regulation**

according to the OSHA Hazard Communication Standard



# PFA Fluoroplastic Resin 450HP X

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
5.2	11/02/2023	1854290-00017	Date of first issue: 08/12/2017

### 49 CFR

Not regulated as a dangerous good

#### Special precautions for user

Not applicable

### **SECTION 15. REGULATORY INFORMATION**

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	: No SARA Hazards	
SARA 313	: This material does not contain any chemical component known CAS numbers that exceed the threshold (De Mir reporting levels established by SARA Title III, Section 3	nimis)

### **US State Regulations**

#### Pennsylvania Right To Know

Poly(Heptafluoropropyl Trifluorovinyl Ether/Tetrafluoroethylene)

26655-00-5

### California Prop. 65

WARNING: This product can expose you to chemicals including Pentadecafluorooctanoic acid, which is/are known to the State of California to cause cancer, and Carbon monoxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. Note to User: This product is not made with PFOA nor is PFOA intentionally present in the product; however, it is possible that PFOA may be present as an impurity at background (environmental) levels.


### SECTION 16. OTHER INFORMATION

**Further information** 

according to the OSHA Hazard Communication Standard



### PFA Fluoroplastic Resin 450HP X



Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

#### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
OSHA Z-2	:	USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organiza-

according to the OSHA Hazard Communication Standard



# PFA Fluoroplastic Resin 450HP X

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
5.2	11/02/2023	1854290-00017	Date of first issue: 08/12/2017

tion; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to	:	Internal technical data, data from raw material SDSs, OECD
compile the Material Safety		eChem Portal search results and European Chemicals Agen-
Data Sheet		cy, http://echa.europa.eu/

Revision Date

: 11/02/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8