according to the OSHA Hazard Communication Standard



Zonyl™ MP 1300 PTFE Fluoroplastic Resin Additive

Version Revision Date: SDS Number: Date of last issue: 04/11/2023 8.1 09/08/2023 1541860-00016 Date of first issue: 04/26/2017

SECTION 1. IDENTIFICATION

Product name : Zonyl™ MP 1300 PTFE Fluoroplastic Resin Additive

SDS-Identcode : 130000024250

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street

Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-

773-2000); Transport emergency: +1-800-424-9300 (outside

the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Additive

Restrictions on use : For industrial use only.

Do not use or resell Chemours[™] materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information,

please contact your Chemours representative.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flulike symptoms in humans, especially when smoking contaminated tobacco.

Dust contact with the eyes can lead to mechanical irritation.

Contact with dust can cause mechanical irritation or drying of the skin.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

according to the OSHA Hazard Communication Standard



Zonyl™ MP 1300 PTFE Fluoroplastic Resin Additive

Version Revision Date: SDS Number: Date of last issue: 04/11/2023 8.1 09/08/2023 1541860-00016 Date of first issue: 04/26/2017

Substance name : Polytetrafluoroethylene

CAS-No. : 9002-84-0

Components

No hazardous ingredients

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap.

Get medical attention if symptoms occur.

In case of eye contact : If in eyes, rinse well with water.

Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms

and effects, both acute and

delayed

Polymer fume fever

Contact with dust can cause mechanical irritation or drying of

the skin.

Dust contact with the eyes can lead to mechanical irritation.

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

according to the OSHA Hazard Communication Standard



Zonyl™ MP 1300 PTFE Fluoroplastic Resin Additive

Version Revision Date: SDS Number: Date of last issue: 04/11/2023 8.1 09/08/2023 1541860-00016 Date of first issue: 04/26/2017

Hazardous combustion prod-

ucts

Hydrogen fluoride carbonyl fluoride

potentially toxic fluorinated compounds

aerosolized particulates

Carbon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.
Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

so.

Evacuate area.

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec-:

tive equipment and emer-

gency procedures

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Sweep up or vacuum up spillage and collect in suitable con-

tainer for disposal.

Avoid dispersal of dust in the air (i.e., clearing dust surfaces

with compressed air).

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not breathe dust.

Handle in accordance with good industrial hygiene and safety

practice, based on the results of the workplace exposure as-

sessment

according to the OSHA Hazard Communication Standard



Zonyl™ MP 1300 PTFE Fluoroplastic Resin Additive

Version Revision Date: SDS Number: Date of last issue: 04/11/2023 8.1 09/08/2023 1541860-00016 Date of first issue: 04/26/2017

Minimize dust generation and accumulation. Keep container closed when not in use.

Take care to prevent spills, waste and minimize release to the

environment.

Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

Further information on stor-

age stability

Stable under recommended storage conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

inert or nuisance dust 50 Million particles per cubic foot

Value type (Form of exposure): TWA (total dust)

Basis: OSHA Z-3

15 mg/m³

Value type (Form of exposure): TWA (total dust)

Basis: OSHA Z-3

5 mg/m³

Value type (Form of exposure): TWA (respirable fraction)

Basis: OSHA Z-3

15 Million particles per cubic foot

Value type (Form of exposure): TWA (respirable fraction)

Basis: OSHA Z-3

Dust, nuisance dust and par-

ticulates

10 mg/m³

Value type (Form of exposure): PEL (Total dust)

Basis: CAL PEL

5 mg/m³

Value type (Form of exposure): PEL (respirable dust fraction)

Basis: CAL PEL

Contains no substances with occupational exposure limit values.

according to the OSHA Hazard Communication Standard



Zonyl™ MP 1300 PTFE Fluoroplastic Resin Additive

Version Revision Date: SDS Number: Date of last issue: 04/11/2023 8.1 09/08/2023 1541860-00016 Date of first issue: 04/26/2017

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		С	2 ppm (Fluorine)	ACGIH
		С	6 ppm 5 mg/m³	NIOSH REL
		TWA	3 ppm 2.5 mg/m ³	NIOSH REL
		TWA	3 ppm	OSHA Z-2
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m³	NIOSH REL
		ST	5 ppm 15 mg/m³	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m³	NIOSH REL
		ST	30,000 ppm 54,000 mg/m ³	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m ³	OSHA Z-1
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m³	NIOSH REL
		С	200 ppm 229 mg/m³	NIOSH REL
		TWA	50 ppm 55 mg/m³	OSHA Z-1

Engineering measures

Processing may form hazardous compounds (see section 10)

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where

concentrations are above recommended limits or are

according to the OSHA Hazard Communication Standard



Zonyl™ MP 1300 PTFE Fluoroplastic Resin Additive

Version Revision Date: SDS Number: Date of last issue: 04/11/2023 8.1 09/08/2023 1541860-00016 Date of first issue: 04/26/2017

unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Heat resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the pro-

duct. Change gloves often!

Eye protection : Wear the following personal protective equipment:

Safety goggles

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the wor-

king place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Color : white

Odor : odorless

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : $> 608 \, ^{\circ}\text{F} / > 320 \, ^{\circ}\text{C}$

Initial boiling point and boiling : No data available

according to the OSHA Hazard Communication Standard



Zonyl™ MP 1300 PTFE Fluoroplastic Resin Additive

Version Revision Date: SDS Number: Date of last issue: 04/11/2023 8.1 09/08/2023 1541860-00016 Date of first issue: 04/26/2017

range

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard, Not expected to form

explosive dust-air mixtures.

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Density : 2.1 - 2.3 g/cm³

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Can react with strong oxidizing agents.

Hazardous decomposition products will be formed at elevated

temperatures.

according to the OSHA Hazard Communication Standard



Zonyl™ MP 1300 PTFE Fluoroplastic Resin Additive

Version Revision Date: SDS Number: Date of last issue: 04/11/2023 8.1 09/08/2023 1541860-00016 Date of first issue: 04/26/2017

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products

Thermal decomposition : Hydrogen fluoride

Carbonyl difluoride Carbon dioxide Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

according to the OSHA Hazard Communication Standard



Zonyl™ MP 1300 PTFE Fluoroplastic Resin Additive

Version Revision Date: SDS Number: Date of last issue: 04/11/2023 8.1 09/08/2023 1541860-00016 Date of first issue: 04/26/2017

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

according to the OSHA Hazard Communication Standard



Zonyl™ MP 1300 PTFE Fluoroplastic Resin Additive

Version Revision Date: SDS Number: Date of last issue: 04/11/2023 8.1 09/08/2023 1541860-00016 Date of first issue: 04/26/2017

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Polytetrafluoroethylene 9002-84-0

California Prop. 65

WARNING: This product can expose you to chemicals including Pentadecafluorooctanoic acid, which is/are known to the State of California to cause cancer, and Carbon monoxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. Note to User: This product is not made with PFOA nor is PFOA intentionally present in the product; however, it is possible that PFOA may be present as an impurity at background (environmental) levels.

SECTION 16. OTHER INFORMATION

Further information


according to the OSHA Hazard Communication Standard



Zonyl™ MP 1300 PTFE Fluoroplastic Resin Additive

Version **Revision Date:** SDS Number: Date of last issue: 04/11/2023 1541860-00016 8.1 09/08/2023 Date of first issue: 04/26/2017

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

Full text of other abbreviations

ACGIH USA, ACGIH Threshold Limit Values (TLV)

California permissible exposure limits for chemical contami-**CAL PEL**

nants (Title 8, Article 107)

USA. NIOSH Recommended Exposure Limits NIOSH REL

OSHA Z-1 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-2 USA. Occupational Exposure Limits (OSHA) - Table Z-2 OSHA Z-3

USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

ACGIH / TWA 8-hour, time-weighted average ACGIH / STEL Short-term exposure limit

ACGIH / C Ceiling limit

CAL PEL / PEL Permissible exposure limit

NIOSH REL / TWA Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

Ceiling value not be exceeded at any time. NIOSH REL / C

OSHA Z-1 / TWA 8-hour time weighted average OSHA Z-2 / TWA 8-hour time weighted average OSHA Z-3 / TWA 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Haz-

according to the OSHA Hazard Communication Standard



Zonyl™ MP 1300 PTFE Fluoroplastic Resin Additive

Version Date of last issue: 04/11/2023 Revision Date: SDS Number: 8.1 09/08/2023 1541860-00016 Date of first issue: 04/26/2017

ardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods: vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date 09/08/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8