

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1347029-00046 Date of last issue: 11/02/2023
Date of first issue: 02/27/2017

SECTION 1. IDENTIFICATION

Product name : 857G-135 MIDCOAT BLACK
Product code : D15444802
SDS-Identcode : 130000127894

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC
Address : 1007 Market Street
Wilmington, DE 19801 United States of America (USA)
Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)
Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Coatings
Restrictions on use : For industrial use only.
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage : Category 1
Reproductive toxicity : Category 1B

GHS label elements

Hazard pictograms :

Signal Word : Danger

Hazard Statements : H318 Causes serious eye damage.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1347029-00046 Date of last issue: 11/02/2023
Date of first issue: 02/27/2017

H360D May damage the unborn child.

Precautionary Statements

:

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER.

P308 + P313 IF exposed or concerned: Get medical attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Paint

Components

Chemical name	CAS-No.	Concentration (% w/w)
2,2',2''-Nitrilotriethanol	102-71-6	>= 5 - < 10
2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol	60828-78-6	>= 1 - < 5
2-(2-Butoxyethoxy)ethanol	112-34-5	>= 1 - < 5
Carbon black	1333-86-4	>= 0.1 - < 1
Cerium 2-ethylhexanoate	56797-01-4	>= 0.1 - < 1
Rutile (TiO ₂)	1317-80-2	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/02/2023
11.0	05/24/2024	1347029-00046	Date of first issue: 02/27/2017

- Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention immediately.
- If swallowed : If swallowed, DO NOT induce vomiting. Get medical attention. Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes serious eye damage. May damage the unborn child.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Hydrogen fluoride
carbonyl fluoride
potentially toxic fluorinated compounds
aerosolized particulates
Carbon oxides
Nitrogen oxides (NO_x)
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/02/2023
11.0	05/24/2024	1347029-00046	Date of first issue: 02/27/2017

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g., by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing. Do not breathe vapors or spray mist. Do not swallow. Do not get in eyes. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment. Keep container tightly closed. Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1347029-00046 Date of last issue: 11/02/2023
Date of first issue: 02/27/2017

- Conditions for safe storage : Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Explosives
Gases
- Recommended storage temperature : 41 - 77 °F / 5 - 25 °C
- Further information on storage stability : Do not freeze.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2,2',2''-Nitrilotriethanol	102-71-6	TWA	5 mg/m ³	ACGIH
2-(2-Butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH
Carbon black	1333-86-4	TWA (Inhalable particulate matter)	3 mg/m ³	ACGIH
		TWA	3.5 mg/m ³	NIOSH REL
		TWA	3.5 mg/m ³	OSHA Z-1
Rutile (TiO ₂)	1317-80-2	TWA (Respirable particulate matter)	2.5 mg/m ³ (Titanium dioxide)	ACGIH

This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Carbon black

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
		C	6 ppm	NIOSH REL

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1347029-00046 Date of last issue: 11/02/2023
Date of first issue: 02/27/2017

			5 mg/m ³	
		TWA	3 ppm 2.5 mg/m ³	NIOSH REL
		TWA	3 ppm	OSHA Z-2
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m ³	NIOSH REL
		ST	5 ppm 15 mg/m ³	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m ³	NIOSH REL
		ST	30,000 ppm 54,000 mg/m ³	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m ³	OSHA Z-1
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m ³	NIOSH REL
		C	200 ppm 229 mg/m ³	NIOSH REL
		TWA	50 ppm 55 mg/m ³	OSHA Z-1

Engineering measures : Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1347029-00046 Date of last issue: 11/02/2023
Date of first issue: 02/27/2017

- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment: Chemical resistant goggles must be worn. If splashes are likely to occur, wear: Face-shield
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : black
- Odor : No data available
- Odor Threshold : No data available
- pH : 8.5 - 11
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : > 212 °F / > 100 °C
- Flash point : does not flash
- Evaporation rate : No data available
- Flammability (solid, gas) : Not applicable

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/02/2023
11.0	05/24/2024	1347029-00046	Date of first issue: 02/27/2017

Flammability (liquids)	:	Not applicable
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Density	:	1.3170 g/cm ³
Solubility(ies)	:	
Water solubility	:	soluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, dynamic	:	682 mPa.s
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics	:	
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid	:	None known.
Incompatible materials	:	None.

Hazardous decomposition products

Thermal decomposition	:	Hydrogen fluoride
-----------------------	---	-------------------

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1347029-00046 Date of last issue: 11/02/2023
Date of first issue: 02/27/2017

Carbonyl difluoride
Carbon dioxide
Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

2,2',2''-Nitrilotriethanol:

Acute oral toxicity : LD50 (Rat): 6,400 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Acute oral toxicity : LD50 (Rat): 3,300 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

2-(2-Butoxyethoxy)ethanol:

Acute oral toxicity : LD50 (Mouse): 2,410 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 2,764 mg/kg

Carbon black:

Acute oral toxicity : LD50 (Rat): > 10,000 mg/kg

Cerium 2-ethylhexanoate:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg
Remarks: Based on data from similar materials

Rutile (TiO₂):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1347029-00046 Date of last issue: 11/02/2023
Date of first issue: 02/27/2017

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

2,2',2''-Nitrilotriethanol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Result : Skin irritation

2-(2-Butoxyethoxy)ethanol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Mild skin irritation

Carbon black:

Species : Rabbit
Result : No skin irritation

Cerium 2-ethylhexanoate:

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439

Result : No skin irritation

Rutile (TiO₂):

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,2',2''-Nitrilotriethanol:

Species : Rabbit
Result : No eye irritation

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1347029-00046 Date of last issue: 11/02/2023
Date of first issue: 02/27/2017

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Result : Irreversible effects on the eye

2-(2-Butoxyethoxy)ethanol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Carbon black:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Cerium 2-ethylhexanoate:

Species : Bovine cornea
Method : OECD Test Guideline 437

Result : No eye irritation

Rutile (TiO₂):

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

2,2',2''-Nitrilotriethanol:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

2-(2-Butoxyethoxy)ethanol:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Carbon black:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1347029-00046 Date of last issue: 11/02/2023
Date of first issue: 02/27/2017

Method : OECD Test Guideline 406
Result : negative

Cerium 2-ethylhexanoate:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : Based on data from similar materials

Rutile (TiO₂):

Test Type : Local lymph node assay (LLNA)
Species : Mouse
Result : negative

Test Type : Buehler Test
Species : Guinea pig
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

2,2',2"-Nitrilotriethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

2-(2-Butoxyethoxy)ethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Mouse
Application Route: Ingestion
Result: negative

Carbon black:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1347029-00046 Date of last issue: 11/02/2023
Date of first issue: 02/27/2017

Genotoxicity in vivo : Method: OECD Test Guideline 476
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Method: OECD Test Guideline 479
Result: negative

Test Type: in vitro micronucleus test
Method: OECD Test Guideline 487
Result: negative

: Test Type: Sex-linked recessive lethal test in *Drosophila melanogaster* (in vivo)
Species: *Drosophila melanogaster* (vinegar fly)
Application Route: Ingestion
Method: OECD Test Guideline 477
Result: negative

Cerium 2-ethylhexanoate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Rutile (TiO₂):

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity

Not classified based on available information.

Components:

2,2',2''-Nitrilotriethanol:

Species : Rat
Application Route : Skin contact
Exposure time : 103 weeks
Result : negative

Carbon black:

Species : Rat
Application Route : Inhalation
Exposure time : 24 Months
Result : positive

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1347029-00046 Date of last issue: 11/02/2023
Date of first issue: 02/27/2017

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

Rutile (TiO₂):

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

IARC Group 2B: Possibly carcinogenic to humans
Carbon black 1333-86-4
Group 2B: Possibly carcinogenic to humans
Rutile (TiO₂) 1317-80-2

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

May damage the unborn child.

Components:

2,2',2''-Nitrilotriethanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative

2-(2-Butoxyethoxy)ethanol:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 415
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Carbon black:

Effects on fetal development : Test Type: Embryo-fetal development

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1347029-00046 Date of last issue: 11/02/2023
Date of first issue: 02/27/2017

Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Test Type: Embryo-fetal development
Species: Mouse
Application Route: inhalation (dust/mist/fume)
Result: negative

Cerium 2-ethylhexanoate:

Effects on fertility : Test Type: Fertility/early embryonic development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 443
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Clear evidence of adverse effects on development, based on animal experiments.
Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Components:

2,2',2''-Nitrilotriethanol:

Assessment : No significant health effects observed in animals at concentrations of 200 mg/kg bw or less., No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

Rutile (TiO₂):

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

2,2',2''-Nitrilotriethanol:

Species : Rat
NOAEL : >= 1,000 mg/kg

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1347029-00046 Date of last issue: 11/02/2023
Date of first issue: 02/27/2017

Application Route : Ingestion
Exposure time : 90 Days

Species : Rat
NOAEL : ≥ 0.5 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 28 Days
Method : OECD Test Guideline 412

Species : Rat
NOAEL : 125 mg/kg
Application Route : Skin contact
Exposure time : 90 Days

2-(2-Butoxyethoxy)ethanol:

Species : Rat
NOAEL : 250 mg/kg
LOAEL : 1,000 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408

Species : Rat
NOAEL : ≥ 0.094 mg/l
Application Route : inhalation (vapor)
Exposure time : 90 Days
Method : OECD Test Guideline 413

Species : Rat
NOAEL : $\geq 2,000$ mg/kg
Application Route : Skin contact
Exposure time : 90 Days

Cerium 2-ethylhexanoate:

Species : Rat
NOAEL : > 215 mg/kg
Application Route : Ingestion
Exposure time : 42 - 47 Days
Method : OECD Test Guideline 422
Remarks : Based on data from similar materials

Rutile (TiO₂):

Species : Rat
NOAEL : 24,000 mg/kg
LOAEL : $> 24,000$ mg/kg
Application Route : Ingestion
Exposure time : 28 d
Remarks : No significant adverse effects were reported
Based on data from similar materials

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1347029-00046 Date of last issue: 11/02/2023
Date of first issue: 02/27/2017

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

2,2',2''-Nitrilotriethanol:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 11,800 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Ceriodaphnia dubia (water flea)): 609.88 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	ErC50 (Desmodesmus subspicatus (green algae)): 512 mg/l Exposure time: 72 h Test substance: Neutralized product
		EC10 (Desmodesmus subspicatus (green algae)): 26 mg/l Exposure time: 72 h Test substance: Neutralized product
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 16 mg/l Exposure time: 21 d
Toxicity to microorganisms	:	IC50: > 1,000 mg/l Exposure time: 3 h Method: OECD Test Guideline 209

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 39 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 81.2 mg/l Exposure time: 48 h

2-(2-Butoxyethoxy)ethanol:

Toxicity to fish	:	LC50 (Lepomis macrochirus (Bluegill sunfish)): 1,300 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 201
		NOEC (Desmodesmus subspicatus (green algae)): >= 100

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1347029-00046 Date of last issue: 11/02/2023
Date of first issue: 02/27/2017

mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10: > 1,995 mg/l
Exposure time: 30 min

Carbon black:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 1,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 5,600 mg/l
Exposure time: 24 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL10 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

EL50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Cerium 2-ethylhexanoate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.1 - 1 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 1 - 10 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Rutile (TiO₂):

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l
Exposure time: 96 h

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1347029-00046 Date of last issue: 11/02/2023
Date of first issue: 02/27/2017

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

NOEC (algae): 5,600 mg/l
Exposure time: 72 h

Persistence and degradability

Components:

2,2',2''-Nitrilotriethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 96 %
Exposure time: 19 d

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Biodegradability : Result: Not readily biodegradable.

2-(2-Butoxyethoxy)ethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 85 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Bioaccumulative potential

Components:

2,2',2''-Nitrilotriethanol:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): < 3.9

Partition coefficient: n-octanol/water : log Pow: -1.9

2-(2-Butoxyethoxy)ethanol:

Partition coefficient: n-octanol/water : log Pow: 1

Mobility in soil

No data available

Other adverse effects

No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/02/2023
11.0	05/24/2024	1347029-00046	Date of first issue: 02/27/2017

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.
-

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

- SARA 311/312 Hazards** : Reproductive toxicity
Serious eye damage or eye irritation

- SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1347029-00046 Date of last issue: 11/02/2023
Date of first issue: 02/27/2017

	2-(2-Butoxyethoxy)ethanol	112-34-5	>= 1 - < 5 %
	2-Butoxyethanol	111-76-2	< 0.1 %
	Lead	7439-92-1	< 0.1 %
Volatile organic compounds (VOC) content		VOC content: 201.43 g/l Remarks: less exempt	
		VOC content: 96.7 g/l Remarks: as packaged	

US State Regulations

Pennsylvania Right To Know

Water	7732-18-5
Fluoropolymer	Trade secret
Fluoropolymer	Trade secret
2,2',2''-Nitrilotriethanol	102-71-6
Acrylic Copolymer	Trade secret
2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol	60828-78-6
2-(2-Butoxyethoxy)ethanol	112-34-5
2,2'-Iminodiethanol	111-42-2
Ammonium hydroxide	1336-21-6

California Prop. 65

WARNING: This product can expose you to chemicals including Carbon black, which is/are known to the State of California to cause cancer, and Lead, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Permissible Exposure Limits for Chemical Contaminants

2,2',2''-Nitrilotriethanol	102-71-6
----------------------------	----------

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK


Version
11.0

Revision Date:
05/24/2024

SDS Number:
1347029-00046

Date of last issue: 11/02/2023
Date of first issue: 02/27/2017

NFPA 704:



HMIS® IV:

HEALTH	*	3
FLAMMABILITY		0
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or nominated distributors.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	:	USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organiza-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-135 MIDCOAT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/02/2023
11.0	05/24/2024	1347029-00046	Date of first issue: 02/27/2017

tion; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 05/24/2024

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8