

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

SECTION 1. IDENTIFICATION

Product name : 857G-508 ONE COAT RED

SDS-Identcode : 130000127908

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Coatings

Restrictions on use : For industrial use only.
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin irritation : Category 2

Serious eye damage : Category 1

Skin sensitization : Category 1

Carcinogenicity : Category 1B

Reproductive toxicity : Category 1B

Specific target organ toxicity : Category 3
- single exposure

GHS label elements

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H350 May cause cancer.
H360F May damage fertility.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER.
P308 + P313 IF exposed or concerned: Get medical attention.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:
P405 Store locked up.

Disposal:
P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Substance / Mixture : Mixture

Chemical nature : Paint

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|---|------------|-----------------------|
| Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200) | 25068-38-6 | >= 10 - < 20 |
| C.I. Pigment Red 101 | 1309-37-1 | >= 5 - < 10 |
| 2-Butoxyethanol | 111-76-2 | >= 1 - < 5 |
| 2-(2-Butoxyethoxy)ethanol | 112-34-5 | >= 1 - < 5 |
| 2-Dimethylaminoethanol | 108-01-0 | >= 1 - < 5 |
| Methacrylic acid | 79-41-4 | >= 1 - < 5 |
| Phenol | 108-95-2 | >= 0.1 - < 1 |
| Formaldehyde | 50-00-0 | >= 0.1 - < 0.2 |
| Bisphenol A | 80-05-7 | >= 0.1 - < 1 |

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention immediately.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.
May cause cancer.
May damage fertility.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/24/2024 |
| 10.1 | 07/29/2024 | 1347132-00049 | Date of first issue: 02/27/2017 |

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Chlorine compounds
Carbon oxides
Hydrogen fluoride
carbonyl fluoride
potentially toxic fluorinated compounds
aerosolized particulates
Nitrogen oxides (NO_x)

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/24/2024 |
| 10.1 | 07/29/2024 | 1347132-00049 | Date of first issue: 02/27/2017 |

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.
Avoid breathing mist or vapors.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Already sensitized individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitizers.
Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Explosives
Gases

Recommended storage temperature : 41 - 77 °F / 5 - 25 °C

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Further information on storage stability : Do not freeze.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|---------------------------|------------------------|-------------------------------------|--|-----------|
| C.I. Pigment Red 101 | 1309-37-1 | TWA (Respirable particulate matter) | 5 mg/m ³ | ACGIH |
| | | TWA (dust and fume) | 5 mg/m ³ (Iron) | NIOSH REL |
| | | TWA (Fumes) | 10 mg/m ³ | OSHA Z-1 |
| | | TWA (total dust) | 15 mg/m ³ | OSHA Z-1 |
| | | TWA (respirable fraction) | 5 mg/m ³ | OSHA Z-1 |
| 2-Butoxyethanol | 111-76-2 | TWA | 20 ppm | ACGIH |
| | | TWA | 5 ppm 24 mg/m ³ | NIOSH REL |
| | | TWA | 50 ppm 240 mg/m ³ | OSHA Z-1 |
| 2-(2-Butoxyethoxy)ethanol | 112-34-5 | TWA (Inhalable fraction and vapor) | 10 ppm | ACGIH |
| Methacrylic acid | 79-41-4 | TWA | 20 ppm | ACGIH |
| | | TWA | 20 ppm 70 mg/m ³ | NIOSH REL |
| Phenol | 108-95-2 | TWA | 5 ppm | ACGIH |
| | | TWA | 5 ppm 19 mg/m ³ | NIOSH REL |
| | | C | 15.6 ppm 60 mg/m ³ | NIOSH REL |
| | | TWA | 5 ppm 19 mg/m ³ | OSHA Z-1 |
| Formaldehyde | 50-00-0 | TWA | 0.1 ppm | ACGIH |
| | | STEL | 0.3 ppm | ACGIH |
| | | TWA | 0.016 ppm | NIOSH REL |
| | | C | 0.1 ppm | NIOSH REL |
| | | PEL | 0.75 ppm | OSHA CARC |
| | | STEL | 2 ppm | OSHA CARC |
| | | TWA | 0.016 ppm (Formaldehyde) | NIOSH REL |
| C | 0.1 ppm (Formaldehyde) | NIOSH REL | | |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version
10.1

Revision Date:
07/29/2024

SDS Number:
1347132-00049

Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Occupational exposure limits of decomposition products

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|---------------------|-----------|----------------------------------|--|-----------|
| Hydrogen fluoride | 7664-39-3 | TWA | 0.5 ppm (Fluorine) | ACGIH |
| | | C | 2 ppm (Fluorine) | ACGIH |
| | | C | 6 ppm 5 mg/m ³ | NIOSH REL |
| | | TWA | 3 ppm 2.5 mg/m ³ | NIOSH REL |
| | | TWA | 3 ppm | OSHA Z-2 |
| Carbonyl difluoride | 353-50-4 | TWA | 2 ppm | ACGIH |
| | | STEL | 5 ppm | ACGIH |
| | | TWA | 2 ppm 5 mg/m ³ | NIOSH REL |
| | | ST | 5 ppm 15 mg/m ³ | NIOSH REL |
| | | TWA | 5,000 ppm | OSHA Z-1 |
| Carbon dioxide | 124-38-9 | TWA | 5,000 ppm | ACGIH |
| | | STEL | 30,000 ppm | ACGIH |
| | | TWA | 5,000 ppm 9,000 mg/m ³ | NIOSH REL |
| | | ST | 30,000 ppm 54,000 mg/m ³ | NIOSH REL |
| | | TWA | 5,000 ppm 9,000 mg/m ³ | OSHA Z-1 |
| Carbon monoxide | 630-08-0 | TWA | 25 ppm | ACGIH |
| | | TWA | 35 ppm 40 mg/m ³ | NIOSH REL |
| | | C | 200 ppm 229 mg/m ³ | NIOSH REL |
| | | TWA | 50 ppm 55 mg/m ³ | OSHA Z-1 |
| | | TWA | 200 ppm | ACGIH |
| Methanol | 67-56-1 | STEL | 250 ppm | ACGIH |
| | | ST | 250 ppm 325 mg/m ³ | NIOSH REL |
| | | TWA | 200 ppm 260 mg/m ³ | NIOSH REL |
| | | TWA | 200 ppm 260 mg/m ³ | OSHA Z-1 |
| | | TWA | 0.1 ppm | ACGIH |
| Formaldehyde | 50-00-0 | STEL | 0.3 ppm | ACGIH |
| | | TWA | 0.016 ppm | NIOSH REL |
| | | C | 0.1 ppm | NIOSH REL |
| | | PEL | 0.75 ppm | OSHA CARC |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

| | | | | |
|--|--|------|-----------------------------|-----------|
| | | STEL | 2 ppm | OSHA CARC |
| | | TWA | 0.016 ppm (Formaldehyde) | NIOSH REL |
| | | C | 0.1 ppm (Formaldehyde) | NIOSH REL |

Biological occupational exposure limits

| Components | CAS-No. | Control parameters | Biological specimen | Sampling time | Permissible concentration | Basis |
|-----------------|----------|-------------------------|---------------------|--|---------------------------|-----------|
| 2-Butoxyethanol | 111-76-2 | Butoxyacetic acid (BAA) | Urine | End of shift (As soon as possible after exposure ceases) | 200 mg/g creatinine | ACGIH BEI |
| Phenol | 108-95-2 | Phenol | Urine | End of shift (As soon as possible after exposure ceases) | 250 mg/g creatinine | ACGIH BEI |

Engineering measures : Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the re-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/24/2024 |
| 10.1 | 07/29/2024 | 1347132-00049 | Date of first issue: 02/27/2017 |

- istance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment: Chemical resistant goggles must be worn. If splashes are likely to occur, wear: Face-shield
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : red
- Odor : No data available
- Odor Threshold : No data available
- pH : 8.5 - 11
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : > 203 °F / > 95 °C
- Flash point : does not flash
- Evaporation rate : No data available
- Flammability (solid, gas) : Not applicable
- Flammability (liquids) : No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/24/2024 |
| 10.1 | 07/29/2024 | 1347132-00049 | Date of first issue: 02/27/2017 |

| | | |
|--|---|--|
| Upper explosion limit / Upper flammability limit | : | No data available |
| Lower explosion limit / Lower flammability limit | : | No data available |
| Vapor pressure | : | No data available |
| Relative vapor density | : | No data available |
| Density | : | 1.1620 g/cm ³ |
| Solubility(ies) Water solubility | : | No data available |
| Partition coefficient: n-octanol/water | : | Not applicable |
| Autoignition temperature | : | No data available |
| Decomposition temperature | : | No data available |
| Viscosity Viscosity, kinematic | : | No data available |
| Explosive properties | : | Not explosive |
| Oxidizing properties | : | The substance or mixture is not classified as oxidizing. |
| Particle characteristics Particle size | : | Not applicable |

SECTION 10. STABILITY AND REACTIVITY

| | | |
|------------------------------------|---|---|
| Reactivity | : | Not classified as a reactivity hazard. |
| Chemical stability | : | Stable under normal conditions. |
| Possibility of hazardous reactions | : | Hazardous decomposition products will be formed at elevated temperatures. |
| Conditions to avoid | : | None known. |
| Incompatible materials | : | None. |

Hazardous decomposition products

| | | |
|-----------------------|---|---|
| Thermal decomposition | : | Hydrogen fluoride Carbonyl difluoride Carbon dioxide Carbon monoxide Methanol |
|-----------------------|---|---|

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

C.I. Pigment Red 101:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

2-Butoxyethanol:

Acute oral toxicity : LD50 (Guinea pig): 1,200 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Expert judgment

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Acute dermal toxicity : LD50 (Guinea pig): > 2,000 mg/kg

2-(2-Butoxyethoxy)ethanol:

Acute oral toxicity : LD50 (Mouse): 2,410 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 2,764 mg/kg

2-Dimethylaminoethanol:

Acute oral toxicity : LD50 (Rat): 1,182 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 5.97 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 1,214 mg/kg

Methacrylic acid:

Acute oral toxicity : LD50 (Rat): 1,320 mg/kg

Acute inhalation toxicity : LC50 (Rat): 3.6 - 4.7 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): 500 - 1,000 mg/kg

Phenol:

Acute oral toxicity : LD50 (Rat): 650 mg/kg
Method: OECD Test Guideline 401

Acute toxicity estimate (Humans): 140 - 290 mg/kg
Method: Expert judgment

Acute inhalation toxicity : LC0 (Rat): 0.9 mg/l
Exposure time: 8 h
Test atmosphere: dust/mist
Assessment: Corrosive to the respiratory tract.

Acute toxicity estimate (Humans): > 0.9 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgment

Acute dermal toxicity : LD50 (Rabbit): 660 mg/kg
Method: OECD Test Guideline 402

Acute toxicity estimate (Humans): 300 mg/kg
Method: Expert judgment

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Formaldehyde:

Acute oral toxicity : Acute toxicity estimate: 100 mg/kg
Method: Expert judgment
Remarks: Based on national or regional regulation.

Acute inhalation toxicity : Acute toxicity estimate (Rat): 100 ppm
Exposure time: 4 h
Test atmosphere: gas
Method: Expert judgment

Acute dermal toxicity : LD50 (Rabbit): 270 mg/kg

Bisphenol A:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 0.17 mg/l
Exposure time: 6 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): 2,230 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):

Result : Skin irritation

C.I. Pigment Red 101:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

2-Butoxyethanol:

Species : Rabbit
Method : Directive 67/548/EEC, Annex V, B.4.
Result : Skin irritation

2-(2-Butoxyethoxy)ethanol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Mild skin irritation

2-Dimethylaminoethanol:

Species : Rabbit
Method : OECD Test Guideline 404

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Result : Corrosive after 3 minutes to 1 hour of exposure

Methacrylic acid:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 3 minutes or less of exposure

Phenol:

Species : Rabbit
Result : Corrosive after 3 minutes to 1 hour of exposure

Formaldehyde:

Result : Corrosive after 3 minutes to 1 hour of exposure
Remarks : Based on national or regional regulation.

Bisphenol A:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):

Result : Irritation to eyes, reversing within 21 days

C.I. Pigment Red 101:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

2-Butoxyethanol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405

2-(2-Butoxyethoxy)ethanol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

2-Dimethylaminoethanol:

Species : Rabbit
Result : Irreversible effects on the eye

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Methacrylic acid:

Species : Rabbit
Result : Irreversible effects on the eye
Method : Draize Test

Phenol:

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405

Formaldehyde:

Result : Irreversible effects on the eye
Remarks : Based on skin corrosivity.

Bisphenol A:

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : positive
Remarks : Based on data from similar materials

Assessment : Probability or evidence of skin sensitization in humans

C.I. Pigment Red 101:

Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

2-Butoxyethanol:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Result : negative

2-(2-Butoxyethoxy)ethanol:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

2-Dimethylaminoethanol:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Methacrylic acid:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Phenol:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Formaldehyde:

Test Type : Human repeat insult patch test (HRIPT)
Routes of exposure : Skin contact
Species : Humans
Result : positive

Assessment : Probability or evidence of high skin sensitization rate in humans

Bisphenol A:

Assessment : Probability or evidence of skin sensitization in humans
Remarks : Based on national or regional regulation.

Germ cell mutagenicity

Not classified based on available information.

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

C.I. Pigment Red 101:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

2-Butoxyethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-
malian cells
Result: equivocal

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: Intraperitoneal injection
Result: negative

Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

2-(2-Butoxyethoxy)ethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow
cytogenetic test, chromosomal analysis)
Species: Mouse

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Application Route: Ingestion
Result: negative

2-Dimethylaminoethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-
malian cells
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Methacrylic acid:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow
cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Inhalation
Result: negative

Phenol:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: positive
Remarks: Annex VI From 1272/2008

Germ cell mutagenicity -
Assessment : Positive result(s) from in vivo mammalian somatic cell muta-
genicity tests.

Formaldehyde:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: positive

Test Type: In vitro mammalian cell gene mutation test

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Result: positive

Test Type: Chromosome aberration test in vitro
Result: positive

Genotoxicity in vivo : Test Type: In vivo mammalian alkaline comet assay
Species: Mouse
Application Route: Inhalation
Result: positive

Germ cell mutagenicity - Assessment : Positive result(s) from in vivo mammalian somatic cell mutagenicity tests.

Bisphenol A:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro
Species: Mouse
Application Route: Ingestion
Result: negative

Carcinogenicity

May cause cancer.

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):

Species : Rat
Application Route : Ingestion
Exposure time : 24 month(s)
Method : OECD Test Guideline 453
Result : negative
Remarks : Based on data from similar materials

C.I. Pigment Red 101:

Species : Rat
Application Route : Intraperitoneal injection
Exposure time : 790 - 914 days
Result : negative

2-Butoxyethanol:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 2 Years
Result : negative

2-Dimethylaminoethanol:

Species : Mouse
Application Route : Ingestion

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Exposure time : 105 weeks
Result : negative

Methacrylic acid:

Species : Rat
Application Route : Inhalation
Exposure time : 2 Years
Result : negative

Phenol:

Species : Mouse
Application Route : Ingestion
Exposure time : 103 weeks
Method : OECD Test Guideline 451
Result : negative

Formaldehyde:

Species : Rat
Application Route : inhalation (gas)
Exposure time : 28 Months
Result : positive

Carcinogenicity - Assessment : Sufficient evidence of carcinogenicity in animal experiments

Bisphenol A:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

IARC Group 1: Carcinogenic to humans
Formaldehyde 50-00-0

OSHA OSHA specifically regulated carcinogen
Formaldehyde 50-00-0

NTP Known to be human carcinogen
Formaldehyde 50-00-0

Reproductive toxicity

May damage fertility.

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

2-Butoxyethanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Mouse
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

2-(2-Butoxyethoxy)ethanol:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 415
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

2-Dimethylaminoethanol:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 414
Result: negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OPPTS 870.3700
Result: negative

Methacrylic acid:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Phenol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Formaldehyde:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (gas)
Result: negative

Bisphenol A:

Effects on fertility : Test Type: Three-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: positive

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, based on animal experiments.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

STOT-single exposure

May cause respiratory irritation.

Components:

2-Dimethylaminoethanol:

Assessment : May cause respiratory irritation.

Methacrylic acid:

Assessment : May cause respiratory irritation.

Formaldehyde:

Assessment : May cause respiratory irritation.

Bisphenol A:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Components:

Phenol:

Target Organs : Central nervous system, Kidney, Liver, Skin
Assessment : May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):

Species : Rat
NOAEL : 50 mg/kg
LOAEL : 250 mg/kg
Application Route : Ingestion
Exposure time : 14 Weeks
Method : OECD Test Guideline 408
Remarks : Based on data from similar materials

2-(2-Butoxyethoxy)ethanol:

Species : Rat
NOAEL : 250 mg/kg
LOAEL : 1,000 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Species : Rat
NOAEL : ≥ 0.094 mg/l
Application Route : inhalation (vapor)
Exposure time : 90 Days
Method : OECD Test Guideline 413

Species : Rat
NOAEL : $\geq 2,000$ mg/kg
Application Route : Skin contact
Exposure time : 90 Days

Methacrylic acid:

Species : Mouse
NOAEL : 600 mg/kg
Application Route : Skin contact
Exposure time : 3 Weeks

Phenol:

Species : Rat
LOAEL : 300 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408

Species : Rat
NOAEL : ≥ 0.1 mg/l
Application Route : inhalation (vapor)
Exposure time : 74 Days

Species : Rabbit
LOAEL : 260 mg/kg
Application Route : Skin contact
Exposure time : 18 Days

Bisphenol A:

Species : Rat
LOAEL : 120 mg/kg
Application Route : Ingestion
Exposure time : 2 y

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

C.I. Pigment Red 101:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): $> 50,000$ mg/l

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to microorganisms : EC50: > 10,000 mg/l
Exposure time: 3 h

2-Butoxyethanol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1,464 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,800 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 1,840 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC10 (Pseudokirchneriella subcapitata (green algae)): 679 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 21 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10 (Daphnia magna (Water flea)): 134 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

2-(2-Butoxyethoxy)ethanol:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 1,300 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): >= 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Toxicity to microorganisms : EC10: > 1,995 mg/l
Exposure time: 30 min

2-Dimethylaminoethanol:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 146.63 mg/l
Exposure time: 96 h
Test substance: Neutralized product
Method: DIN 38412

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 98.37 mg/l
Exposure time: 48 h
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 66.08 mg/l
Exposure time: 72 h

EC10 (Desmodesmus subspicatus (green algae)): 24.49 mg/l
Exposure time: 72 h

Toxicity to microorganisms : EC10 (Pseudomonas putida): 273.8 mg/l
Exposure time: 17 h
Method: DIN 38 412 Part 8

Methacrylic acid:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 85 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 130 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 45 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 8.2 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): 10 mg/l
Exposure time: 35 d
Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): > 53 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50 (Pseudomonas putida): 270 mg/l
Exposure time: 17 h
Method: DIN 38 412 Part 8

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Phenol:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 24.9 mg/l
Exposure time: 96 h

- Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 3.1 mg/l
Exposure time: 48 h

- Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 61.1 mg/l
Exposure time: 96 h

- Toxicity to fish (Chronic toxicity) : NOEC: 0.077 mg/l
Exposure time: 60 d

- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 16 d

- Toxicity to microorganisms : IC50 (Nitrosomonas sp.): 21 mg/l
Exposure time: 24 h

Formaldehyde:

- Toxicity to fish : LC50 (Morone saxatilis (striped bass)): 6.7 mg/l
Exposure time: 96 h

- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 5.8 mg/l
Exposure time: 48 h

- Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 4.89 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1.04 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

- Toxicity to microorganisms : EC50 (activated sludge): 19 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Bisphenol A:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 4.6 mg/l
Exposure time: 96 h

- Toxicity to daphnia and other aquatic invertebrates : EC50: 0.885 mg/l
Exposure time: 48 h
Method: ISO 14669 and PARCOM method

- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 2.73 mg/l
Exposure time: 96 h

- EC10 (Pseudokirchneriella subcapitata (green algae)): 1.36

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

mg/l
Exposure time: 96 h

Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): 0.000174 mg/l
Exposure time: 150 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.0194 mg/l
Exposure time: 28 d

Toxicity to microorganisms : EC10 (Pseudomonas putida): > 320 mg/l
Exposure time: 18 h

Persistence and degradability

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

2-Butoxyethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90.4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

2-(2-Butoxyethoxy)ethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 85 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

2-Dimethylaminoethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 60.5 %
Exposure time: 14 d
Method: OECD Test Guideline 301C

Methacrylic acid:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 86 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Phenol:

Biodegradability : Result: Readily biodegradable.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Biodegradation: 62 %
Exposure time: 10 d
Method: OECD Test Guideline 301C

Formaldehyde:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 99 %
Exposure time: 28 d
Method: OECD Test Guideline 301A

Bisphenol A:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 89 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Bioaccumulative potential

Components:

2-Butoxyethanol:

Partition coefficient: n-octanol/water : log Pow: 0.81

2-(2-Butoxyethoxy)ethanol:

Partition coefficient: n-octanol/water : log Pow: 1

2-Dimethylaminoethanol:

Partition coefficient: n-octanol/water : log Pow: -0.55

Methacrylic acid:

Partition coefficient: n-octanol/water : log Pow: 0.93

Phenol:

Bioaccumulation : Species: Fish
Bioconcentration factor (BCF): 17.5
Method: OECD Test Guideline 305

Partition coefficient: n-octanol/water : log Pow: 1.47

Formaldehyde:

Partition coefficient: n-octanol/water : log Pow: 0.35
Remarks: Calculation

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

Bisphenol A:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 5.1 - 67

Partition coefficient: n-octanol/water : log Pow: 3.4

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|--------------|---------|--------------------|-----------------------------|
| Formaldehyde | 50-00-0 | 100 | 93808 |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

SARA 304 Extremely Hazardous Substances Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|--------------|---------|--------------------|-----------------------------|
| Formaldehyde | 50-00-0 | 100 | 93808 |

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization
Carcinogenicity
Reproductive toxicity
Skin corrosion or irritation
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

| | | |
|---------------------------|-----------|----------------|
| 2-Butoxyethanol | 111-76-2 | >= 1 - < 5 % |
| 2-(2-Butoxyethoxy)ethanol | 112-34-5 | >= 1 - < 5 % |
| Formaldehyde | 50-00-0 | >= 0.1 - < 1 % |
| Lead | 7439-92-1 | < 0.1 % |
| Mercury | 7439-97-6 | < 0.1 % |

Volatile organic compounds (VOC) content

VOC content: 270.34 g/l
Remarks: less exempt

VOC content: 120.07 g/l
Remarks: as packaged

US State Regulations

Pennsylvania Right To Know

| | |
|---|--------------|
| Water | 7732-18-5 |
| Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200) | 25068-38-6 |
| C.I. Pigment Red 101 | 1309-37-1 |
| Fluoropolymer | Trade secret |
| 2-Butoxyethanol | 111-76-2 |
| 2-(2-Butoxyethoxy)ethanol | 112-34-5 |
| 2-Dimethylaminoethanol | 108-01-0 |
| Methacrylic acid | 79-41-4 |
| Butan-1-ol | 71-36-3 |
| Phenol | 108-95-2 |
| Benzoic acid | 65-85-0 |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

Version 10.1 Revision Date: 07/29/2024 SDS Number: 1347132-00049 Date of last issue: 05/24/2024
Date of first issue: 02/27/2017

| | |
|--------------------|-----------|
| Formaldehyde | 50-00-0 |
| Bisphenol A | 80-05-7 |
| Methanol | 67-56-1 |
| Ammonium hydroxide | 1336-21-6 |
| Phosphoric acid | 7664-38-2 |

California Prop. 65

WARNING: This product can expose you to chemicals including Formaldehyde, which is/are known to the State of California to cause cancer, and Bisphenol A, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

| | |
|----------------------|-----------|
| C.I. Pigment Red 101 | 1309-37-1 |
| 2-Butoxyethanol | 111-76-2 |
| Methacrylic acid | 79-41-4 |

California Permissible Exposure Limits for Chemical Contaminants

| | |
|----------------------|-----------|
| C.I. Pigment Red 101 | 1309-37-1 |
| 2-Butoxyethanol | 111-76-2 |
| Methacrylic acid | 79-41-4 |


California Regulated Carcinogens

| | |
|--------------|---------|
| Formaldehyde | 50-00-0 |
|--------------|---------|

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

| | | |
|-----------------|---|---|
| HEALTH | * | 3 |
| FLAMMABILITY | | 0 |
| PHYSICAL HAZARD | | 0 |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or nominated distributors.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/24/2024 |
| 10.1 | 07/29/2024 | 1347132-00049 | Date of first issue: 02/27/2017 |

Full text of other abbreviations

| | | |
|------------------|---|---|
| ACGIH | : | USA. ACGIH Threshold Limit Values (TLV) |
| ACGIH BEI | : | ACGIH - Biological Exposure Indices (BEI) |
| NIOSH REL | : | USA. NIOSH Recommended Exposure Limits |
| OSHA CARC | : | OSHA Specifically Regulated Chemicals/Carcinogens |
| OSHA Z-1 | : | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| OSHA Z-2 | : | USA. Occupational Exposure Limits (OSHA) - Table Z-2 |
| ACGIH / TWA | : | 8-hour, time-weighted average |
| ACGIH / STEL | : | Short-term exposure limit |
| ACGIH / C | : | Ceiling limit |
| NIOSH REL / TWA | : | Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek |
| NIOSH REL / ST | : | STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday |
| NIOSH REL / C | : | Ceiling value not be exceeded at any time. |
| OSHA CARC / PEL | : | Permissible exposure limit (PEL) |
| OSHA CARC / STEL | : | Excursion limit |
| OSHA Z-1 / TWA | : | 8-hour time weighted average |
| OSHA Z-2 / TWA | : | 8-hour time weighted average |

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-508 ONE COAT RED

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05/24/2024 |
| 10.1 | 07/29/2024 | 1347132-00049 | Date of first issue: 02/27/2017 |

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 07/29/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8