

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

SECTION 1. IDENTIFICATION

Product name : 857G-575 ONE COAT YELLOW

SDS-Identcode : 130000133187

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Coatings

Restrictions on use : For industrial use only.
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin irritation : Category 2

Serious eye damage : Category 1

Skin sensitization : Category 1

Specific target organ toxicity : Category 3
- single exposure

Specific target organ toxicity : Category 2 (Lungs)
- repeated exposure

GHS label elements

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H373 May cause damage to organs (Lungs) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves, eye protection and face protection.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER.
P314 Get medical attention if you feel unwell.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
Storage:
P405 Store locked up.
Disposal:
P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

Chemical nature : Paint

Components

Chemical name	CAS-No.	Concentration (% w/w)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200)	25068-38-6	>= 10 - < 20
2-Butoxyethanol	111-76-2	>= 5 - < 10
Bismuth vanadium tetraoxide	14059-33-7	>= 5 - < 10
2-Dimethylaminoethanol	108-01-0	>= 1 - < 5
2-(2-Butoxyethoxy)ethanol	112-34-5	>= 1 - < 5
Titanium dioxide	13463-67-7	>= 1 - < 5
Methacrylic acid	79-41-4	>= 1 - < 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention immediately.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version	Revision Date:	SDS Number:	Date of last issue: 01/24/2024
11.0	05/24/2024	1349283-00046	Date of first issue: 02/27/2017

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Chlorine compounds
Carbon oxides
Hydrogen fluoride
carbonyl fluoride
potentially toxic fluorinated compounds
aerosolized particulates
Nitrogen oxides (NO_x)
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version	Revision Date:	SDS Number:	Date of last issue: 01/24/2024
11.0	05/24/2024	1349283-00046	Date of first issue: 02/27/2017

Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Do not breathe mist or vapors.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Already sensitized individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitizers.
Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products.
- Conditions for safe storage : Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
- Materials to avoid : No special restrictions on storage with other products.
- Recommended storage temperature : 41 - 77 °F / 5 - 25 °C
- Further information on storage stability : Do not freeze.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-Butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m ³	NIOSH REL
		TWA	50 ppm 240 mg/m ³	OSHA Z-1
Bismuth vanadium tetraoxide	14059-33-7	C (Dust)	0.05 mg/m ³ (Vanadium)	NIOSH REL
		C (Fumes)	0.05 mg/m ³ (Vanadium)	NIOSH REL
2-(2-Butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (Respirable particulate matter)	2.5 mg/m ³ (Titanium dioxide)	ACGIH
Methacrylic acid	79-41-4	TWA	20 ppm	ACGIH
		TWA	20 ppm 70 mg/m ³	NIOSH REL

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
		C	6 ppm 5 mg/m ³	NIOSH REL
		TWA	3 ppm 2.5 mg/m ³	NIOSH REL
		TWA	3 ppm	OSHA Z-2
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m ³	NIOSH REL
		ST	5 ppm 15 mg/m ³	NIOSH REL
		TWA	5,000 ppm	ACGIH
Carbon dioxide	124-38-9	STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m ³	NIOSH REL
		ST	30,000 ppm	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m ³	NIOSH REL

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
 Date of first issue: 02/27/2017

			54,000 mg/m ³	
		TWA	5,000 ppm 9,000 mg/m ³	OSHA Z-1
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m ³	NIOSH REL
		C	200 ppm 229 mg/m ³	NIOSH REL
		TWA	50 ppm 55 mg/m ³	OSHA Z-1
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		ST	250 ppm 325 mg/m ³	NIOSH REL
		TWA	200 ppm 260 mg/m ³	NIOSH REL
		TWA	200 ppm 260 mg/m ³	OSHA Z-1
Formaldehyde	50-00-0	TWA	0.1 ppm	ACGIH
		STEL	0.3 ppm	ACGIH
		TWA	0.016 ppm	NIOSH REL
		C	0.1 ppm	NIOSH REL
		PEL	0.75 ppm	OSHA CARC
		STEL	2 ppm	OSHA CARC
		TWA	0.016 ppm (Formaldehyde)	NIOSH REL
		C	0.1 ppm (Formaldehyde)	NIOSH REL

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
2-Butoxyethanol	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g creatinine	ACGIH BEI

Engineering measures : Processing may form hazardous compounds (see section 10).
 Minimize workplace exposure concentrations.
 If sufficient ventilation is unavailable, use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version	Revision Date:	SDS Number:	Date of last issue: 01/24/2024
11.0	05/24/2024	1349283-00046	Date of first issue: 02/27/2017

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
If splashes are likely to occur, wear:
Face-shield

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : yellow

Odor : No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version	Revision Date:	SDS Number:	Date of last issue: 01/24/2024
11.0	05/24/2024	1349283-00046	Date of first issue: 02/27/2017

Odor Threshold	:	No data available
pH	:	7 - 10
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	does not flash
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Density	:	1.153 g/cm ³
Solubility(ies)		
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics		
Particle size	:	Not applicable

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : None known.

Incompatible materials : None.

Hazardous decomposition products

Thermal decomposition : Hydrogen fluoride
Carbonyl difluoride
Carbon dioxide
Carbon monoxide
Methanol
Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral tox-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

icity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

2-Butoxyethanol:

Acute oral toxicity : LD50 (Guinea pig): 1,200 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Expert judgment

Acute dermal toxicity : LD50 (Guinea pig): > 2,000 mg/kg

Bismuth vanadium tetraoxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.15 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

2-Dimethylaminoethanol:

Acute oral toxicity : LD50 (Rat): 1,182 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 5.97 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 1,214 mg/kg

2-(2-Butoxyethoxy)ethanol:

Acute oral toxicity : LD50 (Mouse): 2,410 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 2,764 mg/kg

Titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 425

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l
Exposure time: 4 h

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : Acute toxicity estimate (Rat): > 2,000 mg/kg
Method: Expert judgment
Assessment: The substance or mixture has no acute dermal toxicity

Methacrylic acid:

Acute oral toxicity : LD50 (Rat): 1,320 mg/kg

Acute inhalation toxicity : LC50 (Rat): 3.6 - 4.7 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): 500 - 1,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):

Result : Skin irritation

2-Butoxyethanol:

Species : Rabbit
Method : Directive 67/548/EEC, Annex V, B.4.
Result : Skin irritation

Bismuth vanadium tetraoxide:

Species : Rabbit
Result : No skin irritation

2-Dimethylaminoethanol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 3 minutes to 1 hour of exposure

2-(2-Butoxyethoxy)ethanol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Mild skin irritation

Titanium dioxide:

Species : Rabbit
Method : OECD Test Guideline 404

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

||Result : No skin irritation

Methacrylic acid:

||Species : Rabbit
||Method : OECD Test Guideline 404
||Result : Corrosive after 3 minutes or less of exposure

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):

||Result : Irritation to eyes, reversing within 21 days

2-Butoxyethanol:

||Species : Rabbit
||Result : Irritation to eyes, reversing within 21 days
||Method : OECD Test Guideline 405

Bismuth vanadium tetraoxide:

||Species : Rabbit
||Result : No eye irritation

2-Dimethylaminoethanol:

||Species : Rabbit
||Result : Irreversible effects on the eye

2-(2-Butoxyethoxy)ethanol:

||Species : Rabbit
||Result : Irritation to eyes, reversing within 21 days

Titanium dioxide:

||Species : Rabbit
||Result : No eye irritation
||Method : OECD Test Guideline 405

Methacrylic acid:

||Species : Rabbit
||Result : Irreversible effects on the eye
||Method : Draize Test

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

Respiratory sensitization

Not classified based on available information.

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	positive
Remarks	:	Based on data from similar materials

Assessment : Probability or evidence of skin sensitization in humans

2-Butoxyethanol:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

Bismuth vanadium tetraoxide:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

2-Dimethylaminoethanol:

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative

2-(2-Butoxyethoxy)ethanol:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative

Titanium dioxide:

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

Test Type : Local lymph node assay (LLNA)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

Routes of exposure : Inhalation
Species : Mouse
Result : negative

Routes of exposure : Inhalation
Species : Humans
Result : negative

Methacrylic acid:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

2-Butoxyethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: equivocal

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

Species: Rat
Application Route: Intraperitoneal injection
Result: negative

Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Bismuth vanadium tetraoxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

2-Dimethylaminoethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

2-(2-Butoxyethoxy)ethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro
Result: negative
: Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Mouse
Application Route: Ingestion
Result: negative

Titanium dioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: comet assay
Method: OPPTS 870.5140
Result: positive

Genotoxicity in vivo : Test Type: In vivo mammalian alkaline comet assay
Species: Rat
Application Route: intratracheal
Method: OECD Test Guideline 489
Result: negative

Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 475
Result: negative

Test Type: Transgenic rodent germ cell gene mutation assay
Species: Mouse
Application Route: Intravenous injection
Method: OECD Test Guideline 488
Result: negative

Germ cell mutagenicity - : Weight of evidence does not support classification as a germ

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

Assessment cell mutagen.

Methacrylic acid:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow
cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Inhalation
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):

Species : Rat
Application Route : Ingestion
Exposure time : 24 month(s)
Method : OECD Test Guideline 453
Result : negative
Remarks : Based on data from similar materials

2-Butoxyethanol:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 2 Years
Result : negative

2-Dimethylaminoethanol:

Species : Mouse
Application Route : Ingestion
Exposure time : 105 weeks
Result : negative

Titanium dioxide:

Species : Rat
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 Years
Result : negative

Species : Rat
Application Route : Ingestion
Exposure time : 105 weeks
Result : negative

Species : Mouse
Application Route : Ingestion

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

Exposure time : 103 weeks
Result : negative

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

Methacrylic acid:

Species : Rat
Application Route : Inhalation
Exposure time : 2 Years
Result : negative

IARC Group 2B: Possibly carcinogenic to humans
Titanium dioxide 13463-67-7

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

2-Butoxyethanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Mouse
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

2-Dimethylaminoethanol:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 414
Result: negative

Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OPPTS 870.3700
Result: negative

2-(2-Butoxyethoxy)ethanol:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 415
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Titanium dioxide:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 443
Result: negative

Effects on fetal development : Test Type: Prenatal development toxicity study (teratogenicity)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Reproductive toxicity - As- : Weight of evidence does not support classification for repro-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

Assessment : ductive toxicity

Methacrylic acid:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

STOT-single exposure

May cause respiratory irritation.

Components:

2-Dimethylaminoethanol:

Assessment : May cause respiratory irritation.

Titanium dioxide:

Routes of exposure : Skin contact
Assessment : No significant health effects observed in animals at concentrations of 2000 mg/kg bw or less

Routes of exposure : Ingestion
Assessment : No significant health effects observed in animals at concentrations of 2000 mg/kg bw or less

Routes of exposure : inhalation (dust/mist/fume)
Assessment : No significant health effects observed in animals at concentrations of 5.0 mg/l/4h or less

Methacrylic acid:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs (Lungs) through prolonged or repeated exposure.

Components:

Bismuth vanadium tetraoxide:

Routes of exposure : inhalation (dust/mist/fume)
Target Organs : Lungs
Assessment : Shown to produce significant health effects in animals at concentrations of >0.02 to 0.2 mg/l/6h/d.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

Titanium dioxide:

Routes of exposure : Ingestion
Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Routes of exposure : inhalation (dust/mist/fume)
Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

Routes of exposure : Ingestion
Assessment : No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

Repeated dose toxicity

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):

Species : Rat
NOAEL : 50 mg/kg
LOAEL : 250 mg/kg
Application Route : Ingestion
Exposure time : 14 Weeks
Method : OECD Test Guideline 408
Remarks : Based on data from similar materials

Bismuth vanadium tetraoxide:

Species : Rat
NOAEL : 200 mg/kg
Application Route : Ingestion
Exposure time : 28 Days

Species : Rat
NOAEL : 0.1 mg/l
LOAEL : 0.7 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 90 Days
Method : OECD Test Guideline 413

2-(2-Butoxyethoxy)ethanol:

Species : Rat
NOAEL : 250 mg/kg
LOAEL : 1,000 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408

Species : Rat
NOAEL : >= 0.094 mg/l
Application Route : inhalation (vapor)
Exposure time : 90 Days

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

|| Method : OECD Test Guideline 413

|| Species : Rat
|| NOAEL : $\geq 2,000$ mg/kg
|| Application Route : Skin contact
|| Exposure time : 90 Days

Titanium dioxide:

|| Species : Rat, male and female
|| NOAEL : 24,000 mg/kg
|| LOAEL : $> 24,000$ mg/kg
|| Application Route : Ingestion
|| Exposure time : 28 Days
|| Method : OECD Test Guideline 407
|| Remarks : No significant adverse effects were reported

|| Species : Rat, male and female
|| NOAEL : 0.01 mg/l
|| LOAEL : 0.5 mg/l
|| Application Route : inhalation (dust/mist/fume)
|| Exposure time : 24 Months
|| Method : OECD Test Guideline 453
|| Remarks : No significant adverse effects were reported

|| Species : Rat, male and female
|| NOAEL : 962 mg/kg
|| LOAEL : > 962 mg/kg
|| Application Route : Ingestion
|| Exposure time : 90 Days
|| Method : OECD Test Guideline 408
|| Remarks : No significant adverse effects were reported

Methacrylic acid:

|| Species : Mouse
|| NOAEL : 600 mg/kg
|| Application Route : Skin contact
|| Exposure time : 3 Weeks

Aspiration toxicity

Not classified based on available information.

Components:

Titanium dioxide:

|| No aspiration toxicity classification

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

2-Butoxyethanol:

- | | | |
|--|---|---|
| Toxicity to fish | : | LC50 (Oncorhynchus mykiss (rainbow trout)): 1,464 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): 1,800 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202 |
| Toxicity to algae/aquatic plants | : | ErC50 (Pseudokirchneriella subcapitata (green algae)): 1,840 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC10 (Pseudokirchneriella subcapitata (green algae)): 679 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201 |
| Toxicity to fish (Chronic toxicity) | : | NOEC (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 21 d |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | EC10 (Daphnia magna (Water flea)): 134 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211 |

Bismuth vanadium tetraoxide:

- | | | |
|---|---|--|
| Toxicity to fish | : | LL50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Remarks: Based on transformation/dissolution testing and data from soluble metal compounds |
| Toxicity to daphnia and other aquatic invertebrates | : | EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on transformation/dissolution testing and data from soluble metal compounds |
| Toxicity to algae/aquatic plants | : | EL50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on transformation/dissolution testing and data from soluble metal compounds

NOELR (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

Method: OECD Test Guideline 201

Remarks: Based on transformation/dissolution testing and data from soluble metal compounds

Toxicity to microorganisms : EC50 (*Pseudomonas putida*): > 10,000 mg/l
Exposure time: 16 h

2-Dimethylaminoethanol:

Toxicity to fish : LC50 (*Leuciscus idus* (Golden orfe)): 146.63 mg/l
Exposure time: 96 h
Test substance: Neutralized product
Method: DIN 38412

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 98.37 mg/l
Exposure time: 48 h
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic plants : ErC50 (*Desmodesmus subspicatus* (green algae)): 66.08 mg/l
Exposure time: 72 h

EC10 (*Desmodesmus subspicatus* (green algae)): 24.49 mg/l
Exposure time: 72 h

Toxicity to microorganisms : EC10 (*Pseudomonas putida*): 273.8 mg/l
Exposure time: 17 h
Method: DIN 38 412 Part 8

2-(2-Butoxyethoxy)ethanol:

Toxicity to fish : LC50 (*Lepomis macrochirus* (Bluegill sunfish)): 1,300 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (*Desmodesmus subspicatus* (green algae)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

NOEC (*Desmodesmus subspicatus* (green algae)): >= 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10: > 1,995 mg/l
Exposure time: 30 min

Titanium dioxide:

Toxicity to fish : LC50 (Fish): > 1,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

		LC50 (Marine species): > 10,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia sp. (Water flea)): > 1,000 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
		EC50 (No species specified): > 1,000 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
		EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l Exposure time: 72 h Method: ISO 10253
		NOEC (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 3 d Method: OECD Test Guideline 201
		NOEC (Skeletonema costatum (marine diatom)): 5,600 mg/l Exposure time: 3 d Method: ISO 10253

Methacrylic acid:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 85 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 130 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): 45 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
		NOEC (Pseudokirchneriella subcapitata (green algae)): 8.2 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	:	NOEC (Danio rerio (zebra fish)): 10 mg/l Exposure time: 35 d Method: OECD Test Guideline 210
Toxicity to daphnia and other aquatic invertebrates (Chronic)	:	NOEC (Daphnia magna (Water flea)): > 53 mg/l Exposure time: 21 d

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

Acute toxicity) Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50 (Pseudomonas putida): 270 mg/l
Exposure time: 17 h
Method: DIN 38 412 Part 8

Persistence and degradability

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

2-Butoxyethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90.4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

2-Dimethylaminoethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 60.5 %
Exposure time: 14 d
Method: OECD Test Guideline 301C

2-(2-Butoxyethoxy)ethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 85 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Methacrylic acid:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 86 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Bioaccumulative potential

Components:

2-Butoxyethanol:

Partition coefficient: n-octanol/water : log Pow: 0.81

Bismuth vanadium tetraoxide:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

Bioaccumulation : Species: *Oryzias latipes* (Orange-red killifish)
Bioconcentration factor (BCF): < 14
Method: OECD Test Guideline 305

2-Dimethylaminoethanol:

Partition coefficient: n-octanol/water : log Pow: -0.55

2-(2-Butoxyethoxy)ethanol:

Partition coefficient: n-octanol/water : log Pow: 1

Titanium dioxide:

Bioaccumulation : Species: *Oncorhynchus mykiss* (rainbow trout)
Bioconcentration factor (BCF): 352

Methacrylic acid:

Partition coefficient: n-octanol/water : log Pow: 0.93

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization
Specific target organ toxicity (single or repeated exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

2-Butoxyethanol	111-76-2	>= 5 - < 10 %
Bismuth vanadium tetraoxide	14059-33-7	>= 5 - < 10 %
2-(2-Butoxyethoxy)ethanol	112-34-5	>= 1 - < 5 %
Lead	7439-92-1	< 0.1 %

Volatile organic compounds (VOC) content

VOC content: 292 g/l
Remarks: less exempt

VOC content: 117 g/l
Remarks: as packaged

US State Regulations

Pennsylvania Right To Know

Water 7732-18-5
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin 25068-38-6

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version 11.0 Revision Date: 05/24/2024 SDS Number: 1349283-00046 Date of last issue: 01/24/2024
Date of first issue: 02/27/2017

(number average molecular weight >700 - 1200)	
Fluoropolymer	Trade secret
2-Butoxyethanol	111-76-2
Bismuth vanadium tetraoxide	14059-33-7
2-Dimethylaminoethanol	108-01-0
2-(2-Butoxyethoxy)ethanol	112-34-5
Titanium dioxide	13463-67-7
Methacrylic acid	79-41-4
Benzoic acid	65-85-0
Trizinc bis(orthophosphate)	7779-90-0
Aluminium	7429-90-5
Formaldehyde	50-00-0
Aluminum oxide	1344-28-1

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and Lead, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

2-Butoxyethanol	111-76-2
Methacrylic acid	79-41-4


California Permissible Exposure Limits for Chemical Contaminants

2-Butoxyethanol	111-76-2
Titanium dioxide	13463-67-7
Methacrylic acid	79-41-4

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	*	3
FLAMMABILITY		0
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version	Revision Date:	SDS Number:	Date of last issue: 01/24/2024
11.0	05/24/2024	1349283-00046	Date of first issue: 02/27/2017

Before use read Chemours safety information.
For further information contact the local Chemours office or nominated distributors.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA CARC	:	OSHA Specifically Regulated Chemicals/Carcinogens
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	:	USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA CARC / PEL	:	Permissible exposure limit (PEL)
OSHA CARC / STEL	:	Excursion limit
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EC_x - Concentration associated with x% response; EHS - Extremely Hazardous Substance; EL_x - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErC_x - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC₅₀ - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC₅₀ - Lethal Concentration to 50 % of a test population; LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



857G-575 ONE COAT YELLOW

Version	Revision Date:	SDS Number:	Date of last issue: 01/24/2024
11.0	05/24/2024	1349283-00046	Date of first issue: 02/27/2017

Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 05/24/2024

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8