

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

---

### SECTION 1. IDENTIFICATION

Product name : 953G-401 TOPCOAT PEWTER  
Product code : D14629264  
SDS-Identcode : 130000127967

#### Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC  
Address : 1007 Market Street  
Wilmington, DE 19801 United States of America (USA)  
Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)  
Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

#### Recommended use of the chemical and restrictions on use

Recommended use : Coatings  
Restrictions on use : For industrial use only.  
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.


---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 4  
Eye irritation : Category 2A

#### GHS label elements

Hazard pictograms : 

Signal Word : Warning  
Hazard Statements : H227 Combustible liquid.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

H319 Causes serious eye irritation.

Precautionary Statements

- Prevention:**  
P210 Keep away from heat, sparks, open flame and hot surfaces. No smoking.  
P264 Wash skin thoroughly after handling.  
P280 Wear protective gloves, eye protection and face protection.
- Response:**  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical attention.
- Storage:**  
P403 + P235 Store in a well-ventilated place. Keep cool.
- Disposal:**  
P501 Dispose of contents and container to an approved waste disposal plant.

### Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.  
Vapors may form explosive mixture with air.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Paint

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Mica	12001-26-2	>= 1 - < 5
2,2',2''-Nitrilotriethanol	102-71-6	>= 1 - < 5
Hydrocarbons, C9, aromatics	64742-95-6	>= 1 - < 5
2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol	60828-78-6	>= 1 - < 5
Titanium dioxide	13463-67-7	>= 1 - < 5
2-(2-Butoxyethoxy)ethanol	112-34-5	>= 1 - < 5
Carbon black	1333-86-4	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version	Revision Date:	SDS Number:	Date of last issue: 01/24/2024
12.0	05/03/2024	1347358-00051	Date of first issue: 02/27/2017

---

- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water  
for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes serious eye irritation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection,  
and use the recommended personal protective equipment  
when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread  
fire.  
Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Hydrogen fluoride  
carbonyl fluoride  
potentially toxic fluorinated compounds  
aerosolized particulates  
Carbon oxides  
Metal oxides  
Silicon oxides  
Nitrogen oxides (NO<sub>x</sub>)

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version	Revision Date:	SDS Number:	Date of last issue: 01/24/2024
12.0	05/03/2024	1347358-00051	Date of first issue: 02/27/2017

---

- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
- 

### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
Avoid inhalation of vapor or mist.
-

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep container tightly closed.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labeled containers.  
Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Explosives  
Gases

Recommended storage temperature : 41 - 77 °F / 5 - 25 °C

Further information on storage stability : Do not freeze.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Mica	12001-26-2	TWA (Respirable particulate matter)	0.1 mg/m <sup>3</sup>	ACGIH
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	3 mg/m <sup>3</sup>	NIOSH REL
2,2',2"-Nitrilotriethanol	102-71-6	TWA	5 mg/m <sup>3</sup>	ACGIH
Hydrocarbons, C9, aromatics	64742-95-6	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

		TWA (Mist)	5 mg/m <sup>3</sup>	NIOSH REL
		ST (Mist)	10 mg/m <sup>3</sup>	NIOSH REL
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Respirable particulate matter)	2.5 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH
2-(2-Butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH
Carbon black	1333-86-4	TWA (Inhalable particulate matter)	3 mg/m <sup>3</sup>	ACGIH
		TWA	3.5 mg/m <sup>3</sup>	NIOSH REL
		TWA	3.5 mg/m <sup>3</sup>	OSHA Z-1

**This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.**

Carbon black

### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
		C	6 ppm 5 mg/m <sup>3</sup>	NIOSH REL
		TWA	3 ppm 2.5 mg/m <sup>3</sup>	NIOSH REL
		TWA	3 ppm	OSHA Z-2
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m <sup>3</sup>	NIOSH REL
		ST	5 ppm 15 mg/m <sup>3</sup>	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	NIOSH REL
		ST	30,000 ppm 54,000 mg/m <sup>3</sup>	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	OSHA Z-1
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

		TWA	35 ppm 40 mg/m <sup>3</sup>	NIOSH REL
		C	200 ppm 229 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm 55 mg/m <sup>3</sup>	OSHA Z-1
1-Propene, 1,1,3,3,3-pentafluoro-2-(trifluoromethyl)-	382-21-8	C	0.01 ppm	ACGIH

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

### Personal protective equipment

**Respiratory protection** : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

### Hand protection

**Material** : Chemical-resistant gloves

**Remarks** : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

**Eye protection** : Wear the following personal protective equipment:  
Safety goggles

**Skin and body protection** : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version	Revision Date:	SDS Number:	Date of last issue: 01/24/2024
12.0	05/03/2024	1347358-00051	Date of first issue: 02/27/2017

---

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: gray
Odor	: No data available
Odor Threshold	: No data available
pH	: 8 - 11
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: 212 °F / 100 °C
Flash point	: 150.01 °F / 65.56 °C Method: ISO 2719
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Flammability (liquids)	: Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: No data available
Relative vapor density	: No data available
Density	: 1.3600 g/cm <sup>3</sup>
Solubility(ies) Water solubility	: soluble



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version	Revision Date:	SDS Number:	Date of last issue: 01/24/2024
12.0	05/03/2024	1347358-00051	Date of first issue: 02/27/2017

---

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

    Viscosity, dynamic : 2 mPa.s

    Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics

Particle size : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Combustible liquid.  
Vapors may form explosive mixture with air.  
Can react with strong oxidizing agents.  
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

#### Hazardous decomposition products

Thermal decomposition : Hydrogen fluoride  
Carbonyl difluoride  
Carbon dioxide  
Carbon monoxide  
1-Propene, 1,1,3,3,3-pentafluoro-2-(trifluoromethyl)-

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

---

Ingestion  
Eye contact

### Acute toxicity

Not classified based on available information.

### Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

### Components:

#### 2,2',2''-Nitrilotriethanol:

Acute oral toxicity : LD50 (Rat): 6,400 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

#### Hydrocarbons, C9, aromatics:

Acute oral toxicity : LD50 (Rat, female): 3,492 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.193 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

#### 2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Acute oral toxicity : LD50 (Rat): 3,300 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

#### Titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 425

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : Acute toxicity estimate (Rat): > 2,000 mg/kg  
Method: Expert judgment  
Assessment: The substance or mixture has no acute dermal toxicity

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

---

||

### 2-(2-Butoxyethoxy)ethanol:

|| Acute oral toxicity : LD50 (Mouse): 2,410 mg/kg

|| Acute dermal toxicity : LD50 (Rabbit): 2,764 mg/kg

### Carbon black:

|| Acute oral toxicity : LD50 (Rat): > 10,000 mg/kg

### Skin corrosion/irritation

Not classified based on available information.

### Components:

#### 2,2',2''-Nitrilotriethanol:

|| Species : Rabbit  
|| Method : OECD Test Guideline 404  
|| Result : No skin irritation

### Hydrocarbons, C9, aromatics:

|| Assessment : Repeated exposure may cause skin dryness or cracking.

### 2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

|| Result : Skin irritation

### Titanium dioxide:

|| Species : Rabbit  
|| Method : OECD Test Guideline 404  
|| Result : No skin irritation

### 2-(2-Butoxyethoxy)ethanol:

|| Species : Rabbit  
|| Method : OECD Test Guideline 404  
|| Result : Mild skin irritation

### Carbon black:

|| Species : Rabbit  
|| Result : No skin irritation

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Components:

#### 2,2',2''-Nitrilotriethanol:

|| Species : Rabbit  
|| Result : No eye irritation

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

---

### Hydrocarbons, C9, aromatics:

Species : Rabbit  
Result : No eye irritation

### 2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Result : Irreversible effects on the eye

### Titanium dioxide:

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

### 2-(2-Butoxyethoxy)ethanol:

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

### Carbon black:

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

### Components:

#### 2,2',2''-Nitrilotriethanol:

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

### Hydrocarbons, C9, aromatics:

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

### Titanium dioxide:

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

---

Method : OECD Test Guideline 406  
Result : negative

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : negative

Routes of exposure : Inhalation  
Species : Mouse  
Result : negative

Routes of exposure : Inhalation  
Species : Humans  
Result : negative

### **2-(2-Butoxyethoxy)ethanol:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

### **Carbon black:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

### **Germ cell mutagenicity**

Not classified based on available information.

### **Components:**

#### **2,2',2''-Nitrilotriethanol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

#### **Hydrocarbons, C9, aromatics:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Result: negative  
  
Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow  
cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

#### **Titanium dioxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

		Method: OECD Test Guideline 471 Result: negative
		Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
		Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
		Test Type: comet assay Method: OPPTS 870.5140 Result: positive
Genotoxicity in vivo	:	Test Type: In vivo mammalian alkaline comet assay Species: Rat Application Route: intratracheal Method: OECD Test Guideline 489 Result: negative
		Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: Ingestion Method: OECD Test Guideline 474 Result: negative
		Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 475 Result: negative
		Test Type: Transgenic rodent germ cell gene mutation assay Species: Mouse Application Route: Intravenous injection Method: OECD Test Guideline 488 Result: negative
Germ cell mutagenicity - Assessment	:	Weight of evidence does not support classification as a germ cell mutagen.

### 2-(2-Butoxyethoxy)ethanol:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
		Test Type: In vitro mammalian cell gene mutation test Result: negative
		Test Type: Chromosome aberration test in vitro Result: negative

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

### Carbon black:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells  
Method: OECD Test Guideline 479  
Result: negative

Test Type: in vitro micronucleus test  
Method: OECD Test Guideline 487  
Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in *Drosophila melanogaster* (in vivo)  
Species: *Drosophila melanogaster* (vinegar fly)  
Application Route: Ingestion  
Method: OECD Test Guideline 477  
Result: negative

### Carcinogenicity

Not classified based on available information.

### Components:

#### 2,2',2''-Nitrilotriethanol:

Species : Rat  
Application Route : Skin contact  
Exposure time : 103 weeks  
Result : negative

#### Titanium dioxide:

Species : Rat  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 Years  
Result : negative

Species : Rat  
Application Route : Ingestion  
Exposure time : 105 weeks

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

Result : negative

Species : Mouse  
Application Route : Ingestion  
Exposure time : 103 weeks  
Result : negative

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

### Carbon black:

Species : Rat  
Application Route : Inhalation  
Exposure time : 24 Months  
Result : positive

Species : Rat  
Application Route : Ingestion  
Exposure time : 2 Years  
Result : negative

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

**IARC**      Group 2B: Possibly carcinogenic to humans  
Titanium dioxide      13463-67-7  
Group 2B: Possibly carcinogenic to humans  
Carbon black      1333-86-4

**OSHA**      No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**      No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

Not classified based on available information.

### Components:

#### 2,2',2''-Nitrilotriethanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 416  
Result: negative

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 421  
Result: negative



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

---

||

### Hydrocarbons, C9, aromatics:

Effects on fertility : Test Type: Three-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Mouse  
Application Route: inhalation (vapor)  
Result: negative

### Titanium dioxide:

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 443  
Result: negative

Effects on fetal development : Test Type: Prenatal development toxicity study (teratogenicity)  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

### 2-(2-Butoxyethoxy)ethanol:

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 415  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

### Carbon black:

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

Test Type: Embryo-fetal development  
Species: Mouse  
Application Route: inhalation (dust/mist/fume)  
Result: negative

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

---

||

### STOT-single exposure

Not classified based on available information.

#### Components:

##### Hydrocarbons, C9, aromatics:

|| Assessment : May cause drowsiness or dizziness.

|| Assessment : May cause respiratory irritation.

##### Titanium dioxide:

|| Routes of exposure : Skin contact  
|| Assessment : No significant health effects observed in animals at concentrations of 2000 mg/kg bw or less

|| Routes of exposure : Ingestion  
|| Assessment : No significant health effects observed in animals at concentrations of 2000 mg/kg bw or less

|| Routes of exposure : inhalation (dust/mist/fume)  
|| Assessment : No significant health effects observed in animals at concentrations of 5.0 mg/l/4h or less

### STOT-repeated exposure

Not classified based on available information.

#### Components:

##### 2,2',2"-Nitrilotriethanol:

|| Assessment : No significant health effects observed in animals at concentrations of 200 mg/kg bw or less., No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

##### Titanium dioxide:

|| Routes of exposure : Ingestion  
|| Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

|| Routes of exposure : inhalation (dust/mist/fume)  
|| Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

|| Routes of exposure : Ingestion  
|| Assessment : No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

---

### Repeated dose toxicity

#### Components:

##### **2,2',2''-Nitrilotriethanol:**

Species	: Rat
NOAEL	: >= 1,000 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days
Species	: Rat
NOAEL	: >= 0.5 mg/l
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 28 Days
Method	: OECD Test Guideline 412
Species	: Rat
NOAEL	: 125 mg/kg
Application Route	: Skin contact
Exposure time	: 90 Days

##### **Hydrocarbons, C9, aromatics:**

Species	: Rat, female
NOAEL	: 900 mg/m <sup>3</sup>
Application Route	: inhalation (vapor)
Exposure time	: 12 Months
Remarks	: Based on data from similar materials

##### **Titanium dioxide:**

Species	: Rat, male and female
NOAEL	: 24,000 mg/kg
LOAEL	: > 24,000 mg/kg
Application Route	: Ingestion
Exposure time	: 28 Days
Method	: OECD Test Guideline 407
Remarks	: No significant adverse effects were reported
Species	: Rat, male and female
NOAEL	: 0.01 mg/l
LOAEL	: 0.5 mg/l
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 24 Months
Method	: OECD Test Guideline 453
Remarks	: No significant adverse effects were reported
Species	: Rat, male and female
NOAEL	: 962 mg/kg
LOAEL	: > 962 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days
Method	: OECD Test Guideline 408
Remarks	: No significant adverse effects were reported

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

### 2-(2-Butoxyethoxy)ethanol:

Species : Rat  
NOAEL : 250 mg/kg  
LOAEL : 1,000 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Method : OECD Test Guideline 408

Species : Rat  
NOAEL :  $\geq 0.094$  mg/l  
Application Route : inhalation (vapor)  
Exposure time : 90 Days  
Method : OECD Test Guideline 413

Species : Rat  
NOAEL :  $\geq 2,000$  mg/kg  
Application Route : Skin contact  
Exposure time : 90 Days

### Aspiration toxicity

Not classified based on available information.

### Components:

#### Hydrocarbons, C9, aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### Titanium dioxide:

No aspiration toxicity classification

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### 2,2',2''-Nitrilotriethanol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 11,800 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 609.88 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 512 mg/l  
Exposure time: 72 h  
Test substance: Neutralized product

EC10 (Desmodesmus subspicatus (green algae)): 26 mg/l  
Exposure time: 72 h  
Test substance: Neutralized product

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 16 mg/l  
Exposure time: 21 d

Toxicity to microorganisms : IC50: > 1,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

### Hydrocarbons, C9, aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 9.2 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3.2 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 7.9 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): 0.22 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 99 mg/l  
Exposure time: 10 min

### 2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 39 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 81.2 mg/l  
Exposure time: 48 h

### Titanium dioxide:

Toxicity to fish : LC50 (Fish): > 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

LC50 (Marine species): > 10,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia sp. (Water flea)): > 1,000 mg/l

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

aquatic invertebrates      Exposure time: 48 h  
Method: OECD Test Guideline 202  
  
EC50 (No species specified): > 1,000 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l  
Exposure time: 72 h  
Method: ISO 10253

NOEC (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 3 d  
Method: OECD Test Guideline 201

NOEC (Skeletonema costatum (marine diatom)): 5,600 mg/l  
Exposure time: 3 d  
Method: ISO 10253

### 2-(2-Butoxyethoxy)ethanol:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 1,300 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): >= 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10: > 1,995 mg/l  
Exposure time: 30 min

### Carbon black:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 5,600 mg/l  
Exposure time: 24 h

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL10 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

EL50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

### Persistence and degradability

#### Components:

##### **2,2',2''-Nitrilotriethanol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 96 %  
Exposure time: 19 d

##### **Hydrocarbons, C9, aromatics:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 78 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

##### **2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:**

Biodegradability : Result: Not readily biodegradable.

##### **2-(2-Butoxyethoxy)ethanol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 85 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301C

### Bioaccumulative potential

#### Components:

##### **2,2',2''-Nitrilotriethanol:**

Bioaccumulation : Species: Cyprinus carpio (Carp)  
Bioconcentration factor (BCF): < 3.9

Partition coefficient: n-octanol/water : log Pow: -1.9

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

---

### Hydrocarbons, C9, aromatics:

Partition coefficient: n-octanol/water : log Pow: 3.7 - 4.5

### Titanium dioxide:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)  
Bioconcentration factor (BCF): 352

### 2-(2-Butoxyethoxy)ethanol:

Partition coefficient: n-octanol/water : log Pow: 1

### Mobility in soil

No data available

### Other adverse effects

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.  
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

UN/ID/NA number : UN 1263

---



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

Proper shipping name : Paint

Class : CBL  
Packing group : III  
Labels : NONE  
ERG Code : 128  
Marine pollutant : no  
Remarks : Above applies only to containers over 119 gallons or 450 liters. Not regulated if shipped in packages less than or equal to 119 gallons (450 liters).

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Serious eye damage or eye irritation

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

2-(2-Butoxyethoxy)ethanol	112-34-5	>= 1 - < 5 %
2-Butoxyethanol	111-76-2	< 0.1 %
Lead	7439-92-1	< 0.1 %

### Volatile organic compounds (VOC) content

VOC content: 240.62 g/l  
Remarks: less exempt

VOC content: 106.29 g/l  
Remarks: as packaged

### US State Regulations

#### Pennsylvania Right To Know

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347358-00051      Date of last issue: 01/24/2024  
Date of first issue: 02/27/2017

Fluoropolymer	Trade secret
Water	7732-18-5
Mica	12001-26-2
2,2',2''-Nitrilotriethanol	102-71-6
Hydrocarbons, C9, aromatics	64742-95-6
Titanium dioxide	13463-67-7
2-(2-Butoxyethoxy)ethanol	112-34-5
Phosphoric acid	7664-38-2
Ammonium hydroxide	1336-21-6
Ammonium sulfate	7783-20-2
2,2'-Iminodiethanol	111-42-2

### California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and Lead, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### California List of Hazardous Substances

Mica	12001-26-2
Hydrocarbons, C9, aromatics	64742-95-6


### California Permissible Exposure Limits for Chemical Contaminants

Mica	12001-26-2
2,2',2''-Nitrilotriethanol	102-71-6
Hydrocarbons, C9, aromatics	64742-95-6
Titanium dioxide	13463-67-7

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA 704:



#### HMIS® IV:

HEALTH	/	2
FLAMMABILITY		2
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version	Revision Date:	SDS Number:	Date of last issue: 01/24/2024
12.0	05/03/2024	1347358-00051	Date of first issue: 02/27/2017

---

For further information contact the local Chemours office or nominated distributors.

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	:	USA. Occupational Exposure Limits (OSHA) - Table Z-2
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 953G-401 TOPCOAT PEWTER

Version	Revision Date:	SDS Number:	Date of last issue: 01/24/2024
12.0	05/03/2024	1347358-00051	Date of first issue: 02/27/2017

---

(United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 05/03/2024

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8