

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347517-00047      Date of last issue: 11/30/2023  
Date of first issue: 02/27/2017

---

### SECTION 1. IDENTIFICATION

Product name : 958G-313 ONE COAT BLACK  
Product code : D14856918  
SDS-Identcode : 130000127977

#### Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC  
Address : 1007 Market Street  
Wilmington, DE 19801 United States of America (USA)  
Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)  
Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

#### Recommended use of the chemical and restrictions on use

Recommended use : Coatings  
Restrictions on use : For industrial use only.  
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Carcinogenicity : Category 2  
Reproductive toxicity : Category 1B  
Specific target organ toxicity : Category 3  
- single exposure

#### GHS label elements

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347517-00047      Date of last issue: 11/30/2023  
Date of first issue: 02/27/2017

---

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H226 Flammable liquid and vapor.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H360D May damage the unborn child.

Precautionary Statements

: **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, sparks, open flame and hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P241 Use explosion-proof electrical, ventilating and lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing mist or vapors.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves, protective clothing, eye protection and face protection.

**Response:**  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical attention.  
P332 + P313 If skin irritation occurs: Get medical attention.  
P337 + P313 If eye irritation persists: Get medical attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

**Disposal:**  
P501 Dispose of contents and container to an approved waste disposal plant.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347517-00047      Date of last issue: 11/30/2023  
Date of first issue: 02/27/2017

### Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.  
Vapors may form explosive mixture with air.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture  
Chemical nature : Paint

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
N-Methyl-2-pyrrolidone	872-50-4	$\geq 30 - < 50$
Isobutyl methyl ketone	108-10-1	$\geq 10 - < 20$
Hydrocarbons, C9, aromatics	64742-95-6	$\geq 5 - < 10$
Carbon black	1333-86-4	$\geq 1 - < 5$

Actual concentration is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.  
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.  
If vomiting occurs have person lean forward.  
Call a physician or poison control center immediately.  
Rinse mouth thoroughly with water.  
Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/30/2023
12.0	05/03/2024	1347517-00047	Date of first issue: 02/27/2017

---

- Suspected of causing cancer.  
May damage the unborn child.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.  
Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Nitrogen oxides (NO<sub>x</sub>)  
Carbon oxides  
Hydrogen fluoride  
carbonyl fluoride  
potentially toxic fluorinated compounds  
aerosolized particulates
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or
-

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/30/2023
12.0	05/03/2024	1347517-00047	Date of first issue: 02/27/2017

---

oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.

Advice on safe handling : Do not get on skin or clothing.  
Avoid breathing mist or vapors.  
Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Non-sparking tools should be used.  
Keep container tightly closed.  
Already sensitized individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitizers.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347517-00047      Date of last issue: 11/30/2023  
Date of first issue: 02/27/2017

Conditions for safe storage : Keep in properly labeled containers.  
Store locked up.  
Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Self-reactive substances and mixtures  
Organic peroxides  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives  
Gases  
Very acutely toxic substances and mixtures

Recommended storage temperature : 41 - 77 °F / 5 - 25 °C

Further information on storage stability : Do not freeze.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
N-Methyl-2-pyrrolidone	872-50-4	TWA	15 ppm 60 mg/m <sup>3</sup>	US WEEL
		STEL	30 ppm 120 mg/m <sup>3</sup>	US WEEL
Isobutyl methyl ketone	108-10-1	TWA	20 ppm	ACGIH
		STEL	75 ppm	ACGIH
		TWA	50 ppm 205 mg/m <sup>3</sup>	NIOSH REL
		ST	75 ppm 300 mg/m <sup>3</sup>	NIOSH REL
		TWA	100 ppm 410 mg/m <sup>3</sup>	OSHA Z-1
Hydrocarbons, C9, aromatics	64742-95-6	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH
		TWA (Mist)	5 mg/m <sup>3</sup>	NIOSH REL

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347517-00047      Date of last issue: 11/30/2023  
Date of first issue: 02/27/2017

		ST (Mist)	10 mg/m <sup>3</sup>	NIOSH REL
Carbon black	1333-86-4	TWA (Inhalable particulate matter)	3 mg/m <sup>3</sup>	ACGIH
		TWA	3.5 mg/m <sup>3</sup>	NIOSH REL
		TWA	3.5 mg/m <sup>3</sup>	OSHA Z-1

### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
		C	6 ppm 5 mg/m <sup>3</sup>	NIOSH REL
		TWA	3 ppm 2.5 mg/m <sup>3</sup>	NIOSH REL
Carbonyl difluoride	353-50-4	TWA	3 ppm	OSHA Z-2
		TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m <sup>3</sup>	NIOSH REL
Carbon dioxide	124-38-9	ST	5 ppm 15 mg/m <sup>3</sup>	NIOSH REL
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	NIOSH REL
Carbon monoxide	630-08-0	ST	30,000 ppm 54,000 mg/m <sup>3</sup>	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	OSHA Z-1
		TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m <sup>3</sup>	NIOSH REL
Formaldehyde	50-00-0	C	200 ppm 229 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm 55 mg/m <sup>3</sup>	OSHA Z-1
		TWA	0.1 ppm	ACGIH
		STEL	0.3 ppm	ACGIH
		TWA	0.016 ppm	NIOSH REL
		C	0.1 ppm	NIOSH REL
		PEL	0.75 ppm	OSHA CARC
		STEL	2 ppm	OSHA CARC

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347517-00047      Date of last issue: 11/30/2023  
Date of first issue: 02/27/2017

		TWA	0.016 ppm (Formaldehyde)	NIOSH REL
		C	0.1 ppm (Formaldehyde)	NIOSH REL
Butan-1-ol	71-36-3	TWA	20 ppm	ACGIH
		C	50 ppm 150 mg/m <sup>3</sup>	NIOSH REL
		TWA	100 ppm 300 mg/m <sup>3</sup>	OSHA Z-1
2-Methyl-1-propanol	78-83-1	TWA	50 ppm	ACGIH
		TWA	50 ppm 150 mg/m <sup>3</sup>	NIOSH REL
		TWA	100 ppm 300 mg/m <sup>3</sup>	OSHA Z-1

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
N-Methyl-2-pyrrolidone	872-50-4	5-Hydroxy-N-methyl-2-pyrrolidone	Urine	End of shift (As soon as possible after exposure ceases)	100 mg/l	ACGIH BEI
Isobutyl methyl ketone	108-10-1	methyl isobutyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	1 mg/l	ACGIH BEI

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.

### Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/30/2023
12.0	05/03/2024	1347517-00047	Date of first issue: 02/27/2017

---

respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

### Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: black
Odor	: No data available
Odor Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/30/2023
12.0	05/03/2024	1347517-00047	Date of first issue: 02/27/2017

---

Initial boiling point and boiling range : > 212 °F / > 100 °C

Flash point : 109 °F / 43 °C  
Method: ISO 2719

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Sustains combustion

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : 1.0890 g/cm<sup>3</sup>

Solubility(ies)  
Water solubility : No data available

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : 94 mPa.s  
Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics  
Particle size : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347517-00047      Date of last issue: 11/30/2023  
Date of first issue: 02/27/2017

---

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Flammable liquid and vapor.  
Vapors may form explosive mixture with air.  
Can react with strong oxidizing agents.  
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

### Hazardous decomposition products

Thermal decomposition : Hydrogen fluoride  
Carbonyl difluoride  
Carbon dioxide  
Carbon monoxide  
Formaldehyde  
Butan-1-ol  
2-Methyl-1-propanol

---

## SECTION 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

### Acute toxicity

Not classified based on available information.

### Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 81.94 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

### Components:

#### **N-Methyl-2-pyrrolidone:**

Acute oral toxicity : LD50 (Rat): 4,150 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.1 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347517-00047      Date of last issue: 11/30/2023  
Date of first issue: 02/27/2017

---

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

### Isobutyl methyl ketone:

Acute oral toxicity : LD50 (Rat): 2,080 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Expert judgment

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

### Hydrocarbons, C9, aromatics:

Acute oral toxicity : LD50 (Rat, female): 3,492 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.193 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

### Carbon black:

Acute oral toxicity : LD50 (Rat): > 10,000 mg/kg

### Skin corrosion/irritation

Causes skin irritation.

### Components:

#### N-Methyl-2-pyrrolidone:

Result : Skin irritation

#### Isobutyl methyl ketone:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

#### Hydrocarbons, C9, aromatics:

Assessment : Repeated exposure may cause skin dryness or cracking.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347517-00047      Date of last issue: 11/30/2023  
Date of first issue: 02/27/2017

---

### Carbon black:

Species : Rabbit  
Result : No skin irritation

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Components:

#### N-Methyl-2-pyrrolidone:

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

#### Isobutyl methyl ketone:

Species : Human  
Result : Irritation to eyes, reversing within 21 days

#### Hydrocarbons, C9, aromatics:

Species : Rabbit  
Result : No eye irritation

### Carbon black:

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

### Components:

#### N-Methyl-2-pyrrolidone:

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : negative  
Remarks : Based on data from similar materials

#### Isobutyl methyl ketone:

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347517-00047      Date of last issue: 11/30/2023  
Date of first issue: 02/27/2017

---

### Hydrocarbons, C9, aromatics:

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

### Carbon black:

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### N-Methyl-2-pyrrolidone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Method: OECD Test Guideline 474  
Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Hamster  
Application Route: Ingestion  
Method: OECD Test Guideline 475  
Result: negative

#### Isobutyl methyl ketone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347517-00047      Date of last issue: 11/30/2023  
Date of first issue: 02/27/2017

Genotoxicity in vivo : Test Type: In vitro mammalian cell gene mutation test  
Result: equivocal

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative

### Hydrocarbons, C9, aromatics:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### Carbon black:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vitro : Test Type: In vitro sister chromatid exchange assay in mammalian cells  
Method: OECD Test Guideline 479  
Result: negative

Genotoxicity in vitro : Test Type: in vitro micronucleus test  
Method: OECD Test Guideline 487  
Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in Drosophila melanogaster (in vivo)  
Species: Drosophila melanogaster (vinegar fly)  
Application Route: Ingestion  
Method: OECD Test Guideline 477  
Result: negative

**Carcinogenicity**  
Suspected of causing cancer.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347517-00047      Date of last issue: 11/30/2023  
Date of first issue: 02/27/2017

---

### Components:

#### **N-Methyl-2-pyrrolidone:**

Species : Rat  
Application Route : Ingestion  
Exposure time : 2 Years  
Result : negative

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Result : negative

#### **Isobutyl methyl ketone:**

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Method : OECD Test Guideline 451  
Result : positive

Species : Mouse  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Method : OECD Test Guideline 451  
Result : positive

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

#### **Carbon black:**

Species : Rat  
Application Route : Inhalation  
Exposure time : 24 Months  
Result : positive

Species : Rat  
Application Route : Ingestion  
Exposure time : 2 Years  
Result : negative

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

**IARC**      Group 2B: Possibly carcinogenic to humans  
Isobutyl methyl ketone      108-10-1

**OSHA**      No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**      No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347517-00047      Date of last issue: 11/30/2023  
Date of first issue: 02/27/2017

---

### Reproductive toxicity

May damage the unborn child.

#### Components:

##### **N-Methyl-2-pyrrolidone:**

Effects on fertility	:	Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: Ingestion Method: OECD Test Guideline 416 Result: negative
Effects on fetal development	:	Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Method: OECD Test Guideline 414 Result: positive
		Test Type: Fertility/early embryonic development Species: Rat Application Route: inhalation (vapor) Result: positive
		Test Type: Embryo-fetal development Species: Rabbit Application Route: Ingestion Result: positive
Reproductive toxicity - Assessment	:	Clear evidence of adverse effects on development, based on animal experiments.

##### **Isobutyl methyl ketone:**

Effects on fertility	:	Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: inhalation (vapor) Result: negative
Effects on fetal development	:	Test Type: Embryo-fetal development Species: Rat Application Route: inhalation (vapor) Result: negative

##### **Hydrocarbons, C9, aromatics:**

Effects on fertility	:	Test Type: Three-generation reproduction toxicity study Species: Rat Application Route: inhalation (vapor) Result: negative
Effects on fetal development	:	Test Type: Embryo-fetal development Species: Mouse Application Route: inhalation (vapor) Result: negative

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347517-00047      Date of last issue: 11/30/2023  
Date of first issue: 02/27/2017

---

### Carbon black:

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

Test Type: Embryo-fetal development  
Species: Mouse  
Application Route: inhalation (dust/mist/fume)  
Result: negative

### STOT-single exposure

May cause respiratory irritation.  
May cause drowsiness or dizziness.

### Components:

#### N-Methyl-2-pyrrolidone:

Assessment : May cause respiratory irritation.

#### Isobutyl methyl ketone:

Assessment : May cause drowsiness or dizziness.

#### Hydrocarbons, C9, aromatics:

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

### STOT-repeated exposure

Not classified based on available information.

### Repeated dose toxicity

### Components:

#### N-Methyl-2-pyrrolidone:

Species : Rat, male  
NOAEL : 169 mg/kg  
LOAEL : 433 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Method : OECD Test Guideline 408

Species : Rat  
NOAEL : 0.5 mg/l  
LOAEL : 1 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 96 Days  
Method : OECD Test Guideline 413

Species : Rabbit

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/30/2023
12.0	05/03/2024	1347517-00047	Date of first issue: 02/27/2017

---

NOAEL	:	826 mg/kg
LOAEL	:	1,653 mg/kg
Application Route	:	Skin contact
Exposure time	:	20 Days

### Isobutyl methyl ketone:

Species	:	Rat
NOAEL	:	250 mg/kg
LOAEL	:	1,000 mg/kg
Application Route	:	Ingestion
Exposure time	:	13 Weeks

Species	:	Rat
NOAEL	:	4.106 mg/l
Application Route	:	inhalation (vapor)
Exposure time	:	14 Weeks

### Hydrocarbons, C9, aromatics:

Species	:	Rat, female
NOAEL	:	900 mg/m <sup>3</sup>
Application Route	:	inhalation (vapor)
Exposure time	:	12 Months
Remarks	:	Based on data from similar materials

### Aspiration toxicity

Not classified based on available information.

### Components:

#### Isobutyl methyl ketone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

#### Hydrocarbons, C9, aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

### Experience with human exposure

### Components:

#### N-Methyl-2-pyrrolidone:

Skin contact : Symptoms: Skin irritation

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347517-00047      Date of last issue: 11/30/2023  
Date of first issue: 02/27/2017

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Components:

##### **N-Methyl-2-pyrrolidone:**

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 500 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 24 h Method: DIN 38412
Toxicity to algae/aquatic plants	:	ErC50 (Desmodesmus subspicatus (green algae)): 600.5 mg/l Exposure time: 72 h  EC10 (Desmodesmus subspicatus (green algae)): 92.6 mg/l Exposure time: 72 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 12.5 mg/l Exposure time: 21 d Method: OECD Test Guideline 211
Toxicity to microorganisms	:	EC50: > 600 mg/l Exposure time: 30 min Method: ISO 8192

##### **Isobutyl methyl ketone:**

Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): > 179 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 200 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 30 mg/l Exposure time: 21 d

##### **Hydrocarbons, C9, aromatics:**

Toxicity to fish	:	LL50 (Oncorhynchus mykiss (rainbow trout)): 9.2 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): 3.2 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347517-00047      Date of last issue: 11/30/2023  
Date of first issue: 02/27/2017

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 7.9 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
  
NOELR (Pseudokirchneriella subcapitata (green algae)): 0.22 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 99 mg/l  
Exposure time: 10 min

### Carbon black:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 5,600 mg/l  
Exposure time: 24 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL10 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
  
EL50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

### Persistence and degradability

#### Components:

#### **N-Methyl-2-pyrrolidone:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 73 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301C

#### **Isobutyl methyl ketone:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347517-00047      Date of last issue: 11/30/2023  
Date of first issue: 02/27/2017

---

||

### Hydrocarbons, C9, aromatics:

|| Biodegradability : Result: Readily biodegradable.  
Biodegradation: 78 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

### Bioaccumulative potential

### Components:

#### N-Methyl-2-pyrrolidone:

|| Partition coefficient: n-octanol/water : log Pow: -0.46  
Method: OECD Test Guideline 107

#### Isobutyl methyl ketone:

|| Partition coefficient: n-octanol/water : log Pow: 1.9

### Hydrocarbons, C9, aromatics:

|| Partition coefficient: n-octanol/water : log Pow: 3.7 - 4.5

### Mobility in soil

No data available

### Other adverse effects

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.  
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number : UN 1263

---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/30/2023
12.0	05/03/2024	1347517-00047	Date of first issue: 02/27/2017

---

Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : 3  
Environmentally hazardous : no

### IATA-DGR

UN/ID No. : UN 1263  
Proper shipping name : Paint  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

### IMDG-Code

UN number : UN 1263  
Proper shipping name : PAINT  
  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

UN/ID/NA number : UN 1263  
Proper shipping name : Paint

Class : CBL  
Packing group : III  
Labels : NONE  
ERG Code : 128  
Marine pollutant : no  
Remarks :

Above applies only to containers over 119 gallons or 450 liters. Not regulated if shipped in packages less than or equal to 119 gallons (450 liters). If transporting by vessel or aircraft, unless other means of transportation is impracticable, then the product must be shipped as a flammable liquid.

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347517-00047      Date of last issue: 11/30/2023  
Date of first issue: 02/27/2017

### SECTION 15. REGULATORY INFORMATION

#### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Isobutyl methyl ketone	108-10-1	5000	37243

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Carcinogenicity  
Reproductive toxicity  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Specific target organ toxicity (single or repeated exposure)

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

N-Methyl-2-pyrrolidone	872-50-4	>= 30 - < 50 %
Isobutyl methyl ketone	108-10-1	>= 10 - < 20 %

#### Volatile organic compounds (VOC) content

VOC content: 752.05 g/l  
Remarks: less exempt

VOC content: 751.93 g/l  
Remarks: as packaged

#### US State Regulations

##### Pennsylvania Right To Know

N-Methyl-2-pyrrolidone	872-50-4
Polyamide-imide	Trade secret
Isobutyl methyl ketone	108-10-1
Fluoropolymer	Trade secret
Hydrocarbons, C9, aromatics	64742-95-6
Carbon black	1333-86-4
Butan-2-ol	78-92-2
Butan-1-ol	71-36-3
2-Methyl-1-propanol	78-83-1
Formaldehyde	50-00-0



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version 12.0      Revision Date: 05/03/2024      SDS Number: 1347517-00047      Date of last issue: 11/30/2023  
Date of first issue: 02/27/2017

### California Prop. 65

WARNING: This product can expose you to chemicals including Isobutyl methyl ketone, which is/are known to the State of California to cause cancer, and N-Methyl-2-pyrrolidone, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### California List of Hazardous Substances

Isobutyl methyl ketone	108-10-1
Hydrocarbons, C9, aromatics	64742-95-6
Carbon black	1333-86-4


### California Permissible Exposure Limits for Chemical Contaminants

N-Methyl-2-pyrrolidone	872-50-4
Isobutyl methyl ketone	108-10-1
Hydrocarbons, C9, aromatics	64742-95-6
Carbon black	1333-86-4

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA 704:



#### HMIS® IV:

HEALTH	*	2
FLAMMABILITY		2
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or nominated distributors.

### Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA CARC	: OSHA Specifically Regulated Chemicals/Carcinogens
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/30/2023
12.0	05/03/2024	1347517-00047	Date of first issue: 02/27/2017

---

OSHA Z-2	:	USA. Occupational Exposure Limits (OSHA) - Table Z-2
US WEEL	:	USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA CARC / PEL	:	Permissible exposure limit (PEL)
OSHA CARC / STEL	:	Excursion limit
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average
US WEEL / TWA	:	8-hr TWA
US WEEL / STEL	:	Short-Term TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <a href="http://echa.europa.eu/">http://echa.europa.eu/</a>
--	---	---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-313 ONE COAT BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 11/30/2023
12.0	05/03/2024	1347517-00047	Date of first issue: 02/27/2017

---

Revision Date : 05/03/2024

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8