

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-1003 FEP POWDER BLACK

Version 9.1 Revision Date: 10/09/2024 SDS Number: 1341917-00047 Date of last issue: 04/30/2024
Date of first issue: 02/27/2017

SECTION 1. IDENTIFICATION

Product name : 532-1003 FEP POWDER BLACK

SDS-Identcode : 130000126446

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Coatings

Restrictions on use : For industrial use only.
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitization : Category 1

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H315 Causes skin irritation.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-1003 FEP POWDER BLACK

Version 9.1 Revision Date: 10/09/2024 SDS Number: 1341917-00047 Date of last issue: 04/30/2024
Date of first issue: 02/27/2017

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary Statements :

Prevention:

P261 Avoid breathing dust, fume, gas, mist, vapors or spray.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves, eye protection and face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P337 + P313 If eye irritation persists: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Paint

Components

Chemical name	CAS-No.	Concentration (% w/w)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)	25068-38-6	\geq 70 - $<$ 90
Carbon black	1333-86-4	\geq 1 - $<$ 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-1003 FEP POWDER BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 04/30/2024
9.1	10/09/2024	1341917-00047	Date of first issue: 02/27/2017

- Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Hydrogen fluoride
carbonyl fluoride
potentially toxic fluorinated compounds
aerosolized particulates
Nitrogen oxides (NO_x)
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-1003 FEP POWDER BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 04/30/2024
9.1	10/09/2024	1341917-00047	Date of first issue: 02/27/2017

Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.
Avoid breathing dust, fume, gas, mist, vapors or spray.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-1003 FEP POWDER BLACK

Version 9.1 Revision Date: 10/09/2024 SDS Number: 1341917-00047 Date of last issue: 04/30/2024
Date of first issue: 02/27/2017

Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Carbon black	1333-86-4	TWA (Inhalable particulate matter)	3 mg/m ³	ACGIH
		TWA	3.5 mg/m ³	NIOSH REL
		TWA	3.5 mg/m ³	OSHA Z-1

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
		TWA	3 ppm	OSHA Z-2
		C	6 ppm 5 mg/m ³	NIOSH REL
		TWA	3 ppm 2.5 mg/m ³	NIOSH REL
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m ³	NIOSH REL
		ST	5 ppm 15 mg/m ³	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m ³	NIOSH REL
		ST	30,000 ppm 54,000 mg/m ³	NIOSH REL
Carbon monoxide	630-08-0	TWA	5,000 ppm 9,000 mg/m ³	OSHA Z-1
		TWA	25 ppm	ACGIH
		TWA	35 ppm	NIOSH REL

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-1003 FEP POWDER BLACK

Version 9.1 Revision Date: 10/09/2024 SDS Number: 1341917-00047 Date of last issue: 04/30/2024
Date of first issue: 02/27/2017

			40 mg/m ³	
		C	200 ppm 229 mg/m ³	NIOSH REL
		TWA	50 ppm 55 mg/m ³	OSHA Z-1
1-Propene, 1,1,3,3,3-pentafluoro-2-(trifluoromethyl)-	382-21-8	C	0.01 ppm	ACGIH

Engineering measures : Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-1003 FEP POWDER BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 04/30/2024
9.1	10/09/2024	1341917-00047	Date of first issue: 02/27/2017

workplace.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	solid
Color	:	black
Odor	:	No data available
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Density	:	1.3470 g/cm ³
Solubility(ies) Water solubility	:	slightly soluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-1003 FEP POWDER BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 04/30/2024
9.1	10/09/2024	1341917-00047	Date of first issue: 02/27/2017

Viscosity
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics
Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products

Thermal decomposition : Hydrogen fluoride
Carbonyl difluoride
Carbon dioxide
Carbon monoxide
1-Propene, 1,1,3,3,3-pentafluoro-2-(trifluoromethyl)-

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700):

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-1003 FEP POWDER BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 04/30/2024
9.1	10/09/2024	1341917-00047	Date of first issue: 02/27/2017

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Carbon black:

Acute oral toxicity : LD50 (Rat): > 10,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700):

Result : Skin irritation
Remarks : Based on national or regional regulation.

Carbon black:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700):

Result : Irritation to eyes, reversing within 21 days
Remarks : Based on national or regional regulation.

Carbon black:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700):

Test Type : Maximization Test

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-1003 FEP POWDER BLACK

Version 9.1 Revision Date: 10/09/2024 SDS Number: 1341917-00047 Date of last issue: 04/30/2024
Date of first issue: 02/27/2017

Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : positive

Assessment : Probability or evidence of skin sensitization in humans

Carbon black:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: equivocal

Test Type: Chromosome aberration test in vitro
Result: positive

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Carbon black:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Method: OECD Test Guideline 479
Result: negative

Test Type: in vitro micronucleus test

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-1003 FEP POWDER BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 04/30/2024
9.1	10/09/2024	1341917-00047	Date of first issue: 02/27/2017

Method: OECD Test Guideline 487
Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in *Drosophila melanogaster* (in vivo)
Species: *Drosophila melanogaster* (vinegar fly)
Application Route: Ingestion
Method: OECD Test Guideline 477
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Species : Rat
Application Route : Ingestion
Exposure time : 24 Months
Method : OECD Test Guideline 453
Result : negative

Species : Mouse
Application Route : Skin contact
Exposure time : 24 Months
Method : OECD Test Guideline 453
Result : negative

Carbon black:

Species : Rat
Application Route : Inhalation
Exposure time : 24 Months
Result : positive

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-1003 FEP POWDER BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 04/30/2024
9.1	10/09/2024	1341917-00047	Date of first issue: 02/27/2017

Reproductive toxicity

Not classified based on available information.

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Skin contact
Result: negative

Carbon black:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Test Type: Embryo-fetal development
Species: Mouse
Application Route: inhalation (dust/mist/fume)
Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Assessment : No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

Repeated dose toxicity

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Species : Rat
NOAEL : 50 mg/kg
LOAEL : 250 mg/kg
Application Route : Ingestion

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-1003 FEP POWDER BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 04/30/2024
9.1	10/09/2024	1341917-00047	Date of first issue: 02/27/2017

Exposure time	:	90 Days
Method	:	OECD Test Guideline 408
Species	:	Mouse
NOAEL	:	>= 100 mg/kg
Application Route	:	Skin contact
Exposure time	:	13 Weeks
Method	:	OECD Test Guideline 411

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Toxicity to fish	:	LL50 (Oncorhynchus mykiss (rainbow trout)): > 1 - 10 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): > 1 - 10 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	:	EL50 (Scenedesmus capricornutum (fresh water algae)): > 10 - 100 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials NOELR (Scenedesmus capricornutum (fresh water algae)): > 1 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): > 0.1 - 1 mg/l Exposure time: 21 d Remarks: Based on data from similar materials
Toxicity to microorganisms	:	IC50: > 100 mg/l Exposure time: 3 h Remarks: Based on data from similar materials

Carbon black:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-1003 FEP POWDER BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 04/30/2024
9.1	10/09/2024	1341917-00047	Date of first issue: 02/27/2017

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 1,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 5,600 mg/l
Exposure time: 24 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL10 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

EL50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Persistence and degradability

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Bioaccumulative potential

Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700):

Partition coefficient: n-octanol/water : log Pow: 3.5

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-1003 FEP POWDER BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 04/30/2024
9.1	10/09/2024	1341917-00047	Date of first issue: 02/27/2017

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700))
Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
(Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700))
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 956
Packing instruction (passenger aircraft) : 956
Environmentally hazardous : yes

IMDG-Code

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700))
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
(Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-1003 FEP POWDER BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 04/30/2024
9.1	10/09/2024	1341917-00047	Date of first issue: 02/27/2017

(number average molecular weight \leq 700))

Class	: 9
Packing group	: III
Labels	: CLASS 9
ERG Code	: 171
Marine pollutant	: yes(Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700))
Remarks	: Above applies only to containers over 119 gallons or 450 liters. Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)	25068-38-6
Fluoropolymer	Trade secret
Cyanoguanidine	461-58-5
Carbon black	1333-86-4
Aluminum oxide	1344-28-1

California Prop. 65

WARNING: This product can expose you to chemicals including Pentadecafluorooctanoic acid, which is/are known to the State of California to cause cancer, and Carbon monoxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. Note to User: This product is not made with PFOA nor

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-1003 FEP POWDER BLACK

Version 9.1 Revision Date: 10/09/2024 SDS Number: 1341917-00047 Date of last issue: 04/30/2024
Date of first issue: 02/27/2017

is PFOA intentionally present in the product; however, it is possible that PFOA may be present as an impurity at background (environmental) levels.

California List of Hazardous Substances

Carbon black 1333-86-4


California Permissible Exposure Limits for Chemical Contaminants

Carbon black 1333-86-4

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	/	2
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or nominated distributors.

Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-2 : USA. Occupational Exposure Limits (OSHA) - Table Z-2
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit
- ACGIH / C : Ceiling limit
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
- NIOSH REL / C : Ceiling value not be exceeded at any time.
- OSHA Z-1 / TWA : 8-hour time weighted average
- OSHA Z-2 / TWA : 8-hour time weighted average

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-1003 FEP POWDER BLACK

Version	Revision Date:	SDS Number:	Date of last issue: 04/30/2024
9.1	10/09/2024	1341917-00047	Date of first issue: 02/27/2017

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/09/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8