according to the OSHA Hazard Communication Standard



532G-13032 PFA POWDER GRAY

Version 8.3	Revision Date: 09/24/2024		S Number: 6182-00049	Date of last issue: 12/14/2023 Date of first issue: 02/27/2017
SECTION	1. IDENTIFICATION			
Prod	uct name	:	532G-13032 PFA	POWDER GRAY
SDS	Identcode	:	130000127745	
Man	ufacturer or supplier's	detai	ls	
Com	pany name of supplier	:	The Chemours Co	ompany FC, LLC
Addr	ess		1007 Market Stree Wilmington, DE 1	et 9801 United States of America (USA)
Telep	bhone	:	1-844-773-CHEM	(outside the U.S. 1-302-773-1000)
Eme	gency telephone			cy: 1-866-595-1473 (outside the U.S. 1-302- sport emergency: +1-800-424-9300 (outside 27-3887)
Reco	ommended use of the o	chemi	ical and restriction	ons on use
Reco	mmended use	:	Coatings	
Rest	rictions on use		tions involving imp internal body fluid written agreemen	only. ell Chemours™ materials in medical applica- plantation in the human body or contact with s or tissues unless agreed to by Seller in a t covering such use. For further information, ur Chemours representative.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flulike symptoms in humans, especially when smoking contaminated tobacco.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Paint

according to the OSHA Hazard Communication Standard



532G-13032 PFA POWDER GRAY

Version	Revision Date:	SDS Number:	Date of last issue: 12/14/2023
8.3	09/24/2024	1346182-00049	Date of first issue: 02/27/2017

Components

Chemical name	CAS-No.	Concentration (% w/w)
Silicon carbide	409-21-2	>= 10 - < 20
Actual concentration is withheld	as a trade secret	

SECTION 4. FIRST AID MEASURES

If inhaled	:	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	:	Wash with water and soap as a precaution. Get medical attention if symptoms occur.
In case of eye contact	:	Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
If swallowed	:	If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	:	None known.
Protection of first-aiders	:	No special precautions are necessary for first aid responders.
Notes to physician	:	Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	None known.
Specific hazards during fire fighting	:	Exposure to combustion products may be a hazard to health.
Hazardous combustion prod- ucts	:	Hydrogen fluoride carbonyl fluoride potentially toxic fluorinated compounds aerosolized particulates Carbon oxides
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.

according to the OSHA Hazard Communication Standard



532G-13032 PFA POWDER GRAY

Versio 8.3	on Revision Date: 09/24/2024		S Number: 46182-00049	Date of last issue: 12/14/2023 Date of first issue: 02/27/2017
				o cool unopened containers. ged containers from fire area if it is safe to do
	Special protective equipment or fire-fighters	:	necessary.	ed breathing apparatus for firefighting if rective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Follow safe handling advice (see section 7) and personal pro- tective equipment recommendations (see section 8).
Environmental precautions	:	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Sweep up or vacuum up spillage and collect in suitable con- tainer for disposal. Local or national regulations may apply to releases and dispo- sal of this material, as well as those materials and items em- ployed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures	:	See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation	:	Use only with adequate ventilation.
Advice on safe handling	:	Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as- sessment Take care to prevent spills, waste and minimize release to the environment.
		Do not breathe decomposition products.
Conditions for safe storage	:	Keep in properly labeled containers. Store in accordance with the particular national regulations.
Materials to avoid	:	Do not store with the following product types:

according to the OSHA Hazard Communication Standard



532G-13032 PFA POWDER GRAY

Version	Revision Date:	SDS Number:	Date of last issue: 12/14/2023
8.3	09/24/2024	1346182-00049	Date of first issue: 02/27/2017

Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Silicon carbide	409-21-2	TWA (Res- pirable)	5 mg/m³	NIOSH REL
		TWA (total)	10 mg/m³	NIOSH REL
		TWA (total dust)	15 mg/m³	OSHA Z-1
		TWA (respir- able fraction)	5 mg/m³	OSHA Z-1
		TWA (Inhal- able particu- late matter)	10 mg/m³	ACGIH
		TWA (Res- pirable par- ticulate mat- ter)	3 mg/m³	ACGIH

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
		TWA	3 ppm	OSHA Z-2
		C	6 ppm 5 mg/m³	NIOSH REL
		TWA	3 ppm 2.5 mg/m ³	NIOSH REL
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m ³	NIOSH REL
		ST	5 ppm 15 mg/m³	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m ³	NIOSH REL
		ST	30,000 ppm 54,000 mg/m ³	NIOSH REL

according to the OSHA Hazard Communication Standard



532G-13032 PFA POWDER GRAY

sion	Revision Date: 09/24/2024		lumber: 82-00049		of last issue: 12/14/20 of first issue: 02/27/20	
				TWA	5,000 ppm 9,000 mg/m³	OSHA Z-
Carbo	on monoxide	630	-08-0	TWA	25 ppm	ACGIH
				TWA	35 ppm 40 mg/m ³	NIOSH RI
				С	200 ppm 229 mg/m ³	NIOSH R
				TWA	50 ppm 55 mg/m³	OSHA Z-1
-	neering measures	10 En Mi). sure adeq	uate ventila	zardous compounds tion, especially in cor osure concentrations.	fined areas.
	onal protective equip iratory protection				st ventilation is recon	
		un Fo us by do res ex wh	known, ap llow OSH/ e NIOSH/I air purifyir us chemic spirator if t posure lev	Propriate rea A respirator i MSHA appro ng respirator al is limited. here is any p vels are unkr	e recommended limits spiratory protection s regulations (29 CFR oved respirators. Prot 's against exposure to Use a positive press potential for uncontro nown, or any other cir rators may not provid	hould be worn. 1910.134) and ection provided o any hazar- ure air supplied lled release, roumstance
Hand	protection					
Re	emarks	: W	ash hands	before brea	ks and at the end of	workday.
Eye p	protection		ear the foll fety glasse		nal protective equipn	nent:
Skin	and body protection	: Sk	in should l	be washed a	after contact.	
مايين	ene measures		exposure to e flushing	o chemical i	- Black also de la tempio de la combio de la	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	solid
Color	:	gray

according to the OSHA Hazard Communication Standard



532G-13032 PFA POWDER GRAY

Vers 8.3		Revision Date: 09/24/2024		S Number: 6182-00049	Date of last issue: 12/14/2023 Date of first issue: 02/27/2017
	_				
	Odor		:	No data available)
	Odor Th	reshold	:	No data available)
	pН		:	No data available)
	Melting	point/freezing point	:	No data available	9
	Initial bo range	iling point and boiling	:	No data available	
	Flash po	pint	:	Not applicable	
	Evapora	tion rate	:	Not applicable	
	Flamma	bility (solid, gas)	:	Not classified as	a flammability hazard
		xplosion limit / Upper pility limit	:	No data available	3
		xplosion limit / Lower pility limit	:	No data available	
	Vapor p	ressure	:	Not applicable	
	Relative	vapor density	:	Not applicable	
	Density		:	2.2310 g/cm ³	
	Solubilit Wate	y(ies) er solubility	:	insoluble	
	Partition octanol/	coefficient: n- water	:	Not applicable	
	Autoigni	tion temperature	:	No data available	9
	Decomp	oosition temperature	:	No data available	9
	Viscosity Visco	y osity, kinematic	:	Not applicable	
	Explosiv	ve properties	:	Not explosive	
	Oxidizin	g properties	:	The substance of	r mixture is not classified as oxidizing.
	Particle Particle	characteristics size	:	No data available	

according to the OSHA Hazard Communication Standard



532G-13032 PFA POWDER GRAY

Versior 8.3	Revision Date: 09/24/2024		S Number: 46182-00049	Date of last issue: 12/14/2023 Date of first issue: 02/27/2017	
SECTIO	ON 10. STABILITY AND RE	EAC	ΤΙVITY		
Re	eactivity	:	Not classified as	a reactivity hazard.	
Ch	nemical stability	:	Stable under normal conditions.		
Pc tio	essibility of hazardous reac- ns	:	 Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevatemperatures. 		
Co	onditions to avoid	:	: None known.		
Inc	compatible materials	:	Oxidizing agents		
На	zardous decomposition p	orod	ucts		
Th	ermal decomposition	:	Hydrogen fluorid Carbonyl difluorid Carbon dioxide		

Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure Skin contact Ingestion Eye contact						
Acute toxicity Not classified based on ava	lable information.					
Components:						
Silicon carbide: Acute oral toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 423					
Acute dermal toxicity	 LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity 					
Skin corrosion/irritation Not classified based on ava Components:	lable information.					

Silicon carbide:

Species	:	Rat
Result	:	No skin irritation

according to the OSHA Hazard Communication Standard



532G-13032 PFA POWDER GRAY

Version 8.3	Revision Date: 09/24/2024	SDS Number: 1346182-00049	Date of last issue: 12/14/2023 Date of first issue: 02/27/2017					
	Serious eye damage/eye irritation Not classified based on available information.							
Resp	piratory or skin sensit	tization						
	sensitization	ilable information.						
-	biratory sensitization classified based on ava	ilable information.						
	n cell mutagenicity classified based on ava	ilable information.						
Com	ponents:							
	on carbide: otoxicity in vitro		acterial reverse mutation assay (AMES) D Test Guideline 471 ve					
Not o	inogenicity classified based on ava ponents:	ilable information.						
Silic	on carbide:							
	cation Route sure time	: Rat : Intraperitonea : 40 weeks : negative	I injection					
IARC	0	• •	sent at levels greater than or equal to 0.1% is or confirmed human carcinogen by IARC.	3				
OSH		No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.						
NTP		No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.						
Repr	oductive toxicity							
Not c	Not classified based on available information.							
	STOT-single exposure Not classified based on available information.							
STO	STOT-repeated exposure							

Not classified based on available information.

Components:

Silicon carbide:

Assessment

: No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

according to the OSHA Hazard Communication Standard



532G-13032 PFA POWDER GRAY

Version	Revision Date:	SDS Number:	Date of last issue: 12/14/2023
8.3	09/24/2024	1346182-00049	Date of first issue: 02/27/2017

Repeated dose toxicity

Components:

Silicon carbide:

Species	:	Rat
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	50 hrs

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Silicon carbide:

Toxicity to daphnia and other	:	NOEC (Daphnia magna (Water flea)): >= 100 mg/l
aquatic invertebrates (Chron-		Exposure time: 22 d
ic toxicity)		Method: OECD Test Guideline 211

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Waste from residues	:	Dispose of in accordance with local regulations. Do not dispose of waste into sewer.
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

according to the OSHA Hazard Communication Standard



532G-13032 PFA POWDER GRAY

Version	Revision Date:	SDS Number:	Date of last issue: 12/14/2023
8.3	09/24/2024	1346182-00049	Date of first issue: 02/27/2017

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	No SARA Hazards
----------------------	---	-----------------

SARA 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Fluoropolymer Silicon carbide Trade secret 409-21-2

California Prop. 65

WARNING: This product can expose you to chemicals including Pentadecafluorooctanoic acid, which is/are known to the State of California to cause cancer, and Carbon monoxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. Note to User: This product is not made with PFOA nor is PFOA intentionally present in the product; however, it is possible that PFOA may be present as an impurity at background (environmental) levels.

California Permissible Exposure Limits for Chemical Contaminants

Silicon carbide

409-21-2

according to the OSHA Hazard Communication Standard



532G-13032 PFA POWDER GRAY


Version	Revision Date:	SDS Number:	Date of last issue: 12/14/2023
8.3	09/24/2024	1346182-00049	Date of first issue: 02/27/2017

SECTION 16. OTHER INFORMATION

Further information



HMIS® IV:



Chemours [™] and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

Full text of other abbreviations

ACGIH NIOSH REL OSHA Z-1	:	USA. ACGIH Threshold Limit Values (TLV) USA. NIOSH Recommended Exposure Limits USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
OSHA Z-2	:	USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA		8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C OSHA Z-1 / TWA OSHA Z-2 / TWA	:	Ceiling value not be exceeded at any time. 8-hour time weighted average 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% response; EMS - Extremely Hazardous Substance; ERG - Emergency Response Guide; GHS - Globally Harmonized Sys-

according to the OSHA Hazard Communication Standard



532G-13032 PFA POWDER GRAY

Version	Revision Date:	SDS Number:	Date of last issue: 12/14/2023
8.3	09/24/2024	1346182-00049	Date of first issue: 02/27/2017

tem; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen- cy, http://echa.europa.eu/
--	---	--

Revision Date : 09/24/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8