

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version 13.2      Revision Date: 10/10/2024      SDS Number: 1347699-00047      Date of last issue: 05/03/2024  
Date of first issue: 02/27/2017

---

### SECTION 1. IDENTIFICATION

Product name : 959G-204 ONE COAT GREEN  
Product code : D14566539  
SDS-Identcode : 130000127986

#### Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC  
Address : 1007 Market Street  
Wilmington, DE 19801 United States of America (USA)  
Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)  
Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

#### Recommended use of the chemical and restrictions on use

Recommended use : Coatings  
Restrictions on use : For industrial use only.  
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Carcinogenicity : Category 2  
Reproductive toxicity : Category 1B  
Specific target organ toxicity : Category 3  
- single exposure

#### GHS label elements

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version 13.2      Revision Date: 10/10/2024      SDS Number: 1347699-00047      Date of last issue: 05/03/2024  
Date of first issue: 02/27/2017

---

Hazard pictograms :   

Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H360D May damage the unborn child.

Precautionary Statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, sparks, open flame and hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P241 Use explosion-proof electrical, ventilating and lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing mist or vapors.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves, protective clothing, eye protection and face protection.

**Response:**  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical attention.  
P332 + P313 If skin irritation occurs: Get medical attention.  
P337 + P313 If eye irritation persists: Get medical attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

**Disposal:**  
P501 Dispose of contents and container to an approved waste disposal plant.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version 13.2      Revision Date: 10/10/2024      SDS Number: 1347699-00047      Date of last issue: 05/03/2024  
Date of first issue: 02/27/2017

### Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.  
Vapors may form explosive mixture with air.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture  
Chemical nature : Paint

### Components

Chemical name	CAS-No.	Concentration (% w/w)
N-Methyl-2-pyrrolidone	872-50-4	$\geq 30 - < 50$
Isobutyl methyl ketone	108-10-1	$\geq 20 - < 30$
Hydrocarbons, C9, aromatics	64742-95-6	$\geq 5 - < 10$
Chromium oxide	1308-38-9	$\geq 1 - < 5$
2-(2-Butoxyethoxy)ethanol	112-34-5	$\geq 1 - < 5$

Actual concentration is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.  
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.  
If vomiting occurs have person lean forward.  
Call a physician or poison control center immediately.  
Rinse mouth thoroughly with water.  
Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 05/03/2024
13.2	10/10/2024	1347699-00047	Date of first issue: 02/27/2017

---

May cause drowsiness or dizziness.  
Suspected of causing cancer.  
May damage the unborn child.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

---

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.  
Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Nitrogen oxides (NO<sub>x</sub>)  
Carbon oxides  
Hydrogen fluoride  
carbonyl fluoride  
potentially toxic fluorinated compounds  
aerosolized particulates  
Chromium compounds

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency measures : Remove all sources of ignition.  
Use personal protective equipment.

---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 05/03/2024
13.2	10/10/2024	1347699-00047	Date of first issue: 02/27/2017

---

- gency procedures : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.
- Advice on safe handling : Do not get on skin or clothing.  
Avoid breathing mist or vapors.  
Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Non-sparking tools should be used.  
Keep container tightly closed.  
Already sensitized individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitizers.  
Keep away from heat, hot surfaces, sparks, open flames and

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version 13.2      Revision Date: 10/10/2024      SDS Number: 1347699-00047      Date of last issue: 05/03/2024  
Date of first issue: 02/27/2017

other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labeled containers.  
Store locked up.  
Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Self-reactive substances and mixtures  
Organic peroxides  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives  
Gases  
Very acutely toxic substances and mixtures

Recommended storage temperature : 41 - 77 °F / 5 - 25 °C

Further information on storage stability : Do not freeze.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
N-Methyl-2-pyrrolidone	872-50-4	TWA	15 ppm 60 mg/m <sup>3</sup>	US WEEL
		STEL	30 ppm 120 mg/m <sup>3</sup>	US WEEL
Isobutyl methyl ketone	108-10-1	TWA	20 ppm	ACGIH
		STEL	75 ppm	ACGIH
		TWA	50 ppm 205 mg/m <sup>3</sup>	NIOSH REL
		ST	75 ppm 300 mg/m <sup>3</sup>	NIOSH REL
		TWA	100 ppm 410 mg/m <sup>3</sup>	OSHA Z-1

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version 13.2      Revision Date: 10/10/2024      SDS Number: 1347699-00047      Date of last issue: 05/03/2024  
Date of first issue: 02/27/2017

Hydrocarbons, C9, aromatics	64742-95-6	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH
		TWA (Mist)	5 mg/m <sup>3</sup>	NIOSH REL
		ST (Mist)	10 mg/m <sup>3</sup>	NIOSH REL
Chromium oxide	1308-38-9	TWA	0.5 mg/m <sup>3</sup> (chromium)	OSHA Z-1
		TWA	0.5 mg/m <sup>3</sup> (chromium)	NIOSH REL
2-(2-Butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH

### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
		TWA	3 ppm	OSHA Z-2
		C	6 ppm 5 mg/m <sup>3</sup>	NIOSH REL
Carbonyl difluoride	353-50-4	TWA	3 ppm 2.5 mg/m <sup>3</sup>	NIOSH REL
		TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m <sup>3</sup>	NIOSH REL
Carbon dioxide	124-38-9	ST	5 ppm 15 mg/m <sup>3</sup>	NIOSH REL
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	NIOSH REL
Carbon monoxide	630-08-0	ST	30,000 ppm 54,000 mg/m <sup>3</sup>	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	OSHA Z-1
		TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m <sup>3</sup>	NIOSH REL
		C	200 ppm 229 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm 55 mg/m <sup>3</sup>	OSHA Z-1

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version 13.2      Revision Date: 10/10/2024      SDS Number: 1347699-00047      Date of last issue: 05/03/2024  
Date of first issue: 02/27/2017

1-Propene, 1,1,3,3,3-pentafluoro-2-(trifluoromethyl)-	382-21-8	C	0.01 ppm	ACGIH
Formaldehyde	50-00-0	TWA	0.1 ppm	ACGIH
		STEL	0.3 ppm	ACGIH
		TWA	0.016 ppm	NIOSH REL
		C	0.1 ppm	NIOSH REL
		PEL	0.75 ppm	OSHA CARC
		STEL	2 ppm	OSHA CARC
		TWA	0.016 ppm (Formaldehyde)	NIOSH REL
		C	0.1 ppm (Formaldehyde)	NIOSH REL
Butan-1-ol	71-36-3	TWA	20 ppm	ACGIH
		C	50 ppm 150 mg/m <sup>3</sup>	NIOSH REL
		TWA	100 ppm 300 mg/m <sup>3</sup>	OSHA Z-1
2-Methyl-1-propanol	78-83-1	TWA	50 ppm	ACGIH
		TWA	50 ppm 150 mg/m <sup>3</sup>	NIOSH REL
		TWA	100 ppm 300 mg/m <sup>3</sup>	OSHA Z-1

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
N-Methyl-2-pyrrolidone	872-50-4	5-Hydroxy-N-methyl-2-pyrrolidone	Urine	End of shift (As soon as possible after exposure ceases)	100 mg/l	ACGIH BEI
Isobutyl methyl ketone	108-10-1	methyl isobutyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	1 mg/l	ACGIH BEI

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 05/03/2024
13.2	10/10/2024	1347699-00047	Date of first issue: 02/27/2017

---

### Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

### Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : green

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 05/03/2024
13.2	10/10/2024	1347699-00047	Date of first issue: 02/27/2017

---

Odor : No data available

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : > 212 °F / > 100 °C

Flash point : 96.01 °F / 35.56 °C  
Method: ISO 2719

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Sustains combustion

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : 1.0590 g/cm<sup>3</sup>

Solubility(ies)  
Water solubility : No data available

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version 13.2      Revision Date: 10/10/2024      SDS Number: 1347699-00047      Date of last issue: 05/03/2024  
Date of first issue: 02/27/2017

---

Particle characteristics  
Particle size : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Flammable liquid and vapor.  
Vapors may form explosive mixture with air.  
Can react with strong oxidizing agents.  
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

#### Hazardous decomposition products

Thermal decomposition : Hydrogen fluoride  
Carbonyl difluoride  
Carbon dioxide  
Carbon monoxide  
1-Propene, 1,1,3,3,3-pentafluoro-2-(trifluoromethyl)-  
Formaldehyde  
Butan-1-ol  
2-Methyl-1-propanol

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: 4,415 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 46.62 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version 13.2      Revision Date: 10/10/2024      SDS Number: 1347699-00047      Date of last issue: 05/03/2024  
Date of first issue: 02/27/2017

---

Method: Calculation method

### Components:

#### **N-Methyl-2-pyrrolidone:**

Acute oral toxicity : LD50 (Rat): 4,150 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.1 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

#### **Isobutyl methyl ketone:**

Acute oral toxicity : LD50 (Rat): 2,080 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Expert judgment

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

#### **Hydrocarbons, C9, aromatics:**

Acute oral toxicity : LD50 (Rat, female): 3,492 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.193 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

#### **Chromium oxide:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.41 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

#### **2-(2-Butoxyethoxy)ethanol:**

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version 13.2      Revision Date: 10/10/2024      SDS Number: 1347699-00047      Date of last issue: 05/03/2024  
Date of first issue: 02/27/2017

---

Acute oral toxicity : LD50 (Mouse): 2,410 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 2,764 mg/kg

### **Skin corrosion/irritation**

Causes skin irritation.

#### **Components:**

##### **N-Methyl-2-pyrrolidone:**

Result : Skin irritation

##### **Isobutyl methyl ketone:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

##### **Hydrocarbons, C9, aromatics:**

Assessment : Repeated exposure may cause skin dryness or cracking.

##### **Chromium oxide:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

##### **2-(2-Butoxyethoxy)ethanol:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Mild skin irritation

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Components:**

##### **N-Methyl-2-pyrrolidone:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

##### **Isobutyl methyl ketone:**

Species : Human  
Result : Irritation to eyes, reversing within 21 days

##### **Hydrocarbons, C9, aromatics:**

Species : Rabbit  
Result : No eye irritation

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version 13.2      Revision Date: 10/10/2024      SDS Number: 1347699-00047      Date of last issue: 05/03/2024  
Date of first issue: 02/27/2017

---

### Chromium oxide:

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

### 2-(2-Butoxyethoxy)ethanol:

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

### Components:

#### N-Methyl-2-pyrrolidone:

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : negative  
Remarks : Based on data from similar materials

#### Isobutyl methyl ketone:

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

#### Hydrocarbons, C9, aromatics:

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

#### Chromium oxide:

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative  
Remarks : Based on data from similar materials

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version 13.2      Revision Date: 10/10/2024      SDS Number: 1347699-00047      Date of last issue: 05/03/2024  
Date of first issue: 02/27/2017

---

### **2-(2-Butoxyethoxy)ethanol:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

### **Germ cell mutagenicity**

Not classified based on available information.

### **Components:**

#### **N-Methyl-2-pyrrolidone:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Method: OECD Test Guideline 474  
Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Hamster  
Application Route: Ingestion  
Method: OECD Test Guideline 475  
Result: negative

#### **Isobutyl methyl ketone:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: equivocal

Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version 13.2      Revision Date: 10/10/2024      SDS Number: 1347699-00047      Date of last issue: 05/03/2024  
Date of first issue: 02/27/2017

---

Result: negative

### Hydrocarbons, C9, aromatics:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### Chromium oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative

### 2-(2-Butoxyethoxy)ethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

### Carcinogenicity

Suspected of causing cancer.

### Components:

#### N-Methyl-2-pyrrolidone:

Species : Rat  
Application Route : Ingestion  
Exposure time : 2 Years  
Result : negative

Species : Rat





# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version 13.2      Revision Date: 10/10/2024      SDS Number: 1347699-00047      Date of last issue: 05/03/2024  
Date of first issue: 02/27/2017

---

Test Type: Fertility/early embryonic development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: positive

Test Type: Embryo-fetal development  
Species: Rabbit  
Application Route: Ingestion  
Result: positive

Reproductive toxicity - Assessment : Clear evidence of adverse effects on development, based on animal experiments.

### **Isobutyl methyl ketone:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### **Hydrocarbons, C9, aromatics:**

Effects on fertility : Test Type: Three-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Mouse  
Application Route: inhalation (vapor)  
Result: negative

### **Chromium oxide:**

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

### **2-(2-Butoxyethoxy)ethanol:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 415  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version 13.2      Revision Date: 10/10/2024      SDS Number: 1347699-00047      Date of last issue: 05/03/2024  
Date of first issue: 02/27/2017

---

Species: Rat  
Application Route: Ingestion  
Result: negative

### STOT-single exposure

May cause respiratory irritation.  
May cause drowsiness or dizziness.

#### Components:

##### **N-Methyl-2-pyrrolidone:**

Assessment : May cause respiratory irritation.

##### **Isobutyl methyl ketone:**

Assessment : May cause drowsiness or dizziness.

##### **Hydrocarbons, C9, aromatics:**

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

### STOT-repeated exposure

Not classified based on available information.

### Repeated dose toxicity

#### Components:

##### **N-Methyl-2-pyrrolidone:**

Species : Rat, male  
NOAEL : 169 mg/kg  
LOAEL : 433 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Method : OECD Test Guideline 408

Species : Rat  
NOAEL : 0.5 mg/l  
LOAEL : 1 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 96 Days  
Method : OECD Test Guideline 413

Species : Rabbit  
NOAEL : 826 mg/kg  
LOAEL : 1,653 mg/kg  
Application Route : Skin contact  
Exposure time : 20 Days

##### **Isobutyl methyl ketone:**

Species : Rat

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version 13.2      Revision Date: 10/10/2024      SDS Number: 1347699-00047      Date of last issue: 05/03/2024  
Date of first issue: 02/27/2017

---

NOAEL : 250 mg/kg  
LOAEL : 1,000 mg/kg  
Application Route : Ingestion  
Exposure time : 13 Weeks

Species : Rat  
NOAEL : 4.106 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 14 Weeks

### Hydrocarbons, C9, aromatics:

Species : Rat, female  
NOAEL : 900 mg/m<sup>3</sup>  
Application Route : inhalation (vapor)  
Exposure time : 12 Months  
Remarks : Based on data from similar materials

### Chromium oxide:

Species : Rat  
NOAEL : 2,000 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

### 2-(2-Butoxyethoxy)ethanol:

Species : Rat  
NOAEL : 250 mg/kg  
LOAEL : 1,000 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Method : OECD Test Guideline 408

Species : Rat  
NOAEL :  $\geq 0.094$  mg/l  
Application Route : inhalation (vapor)  
Exposure time : 90 Days  
Method : OECD Test Guideline 413

Species : Rat  
NOAEL :  $\geq 2,000$  mg/kg  
Application Route : Skin contact  
Exposure time : 90 Days

### Aspiration toxicity

Not classified based on available information.

### Components:

#### Isobutyl methyl ketone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 05/03/2024
13.2	10/10/2024	1347699-00047	Date of first issue: 02/27/2017

---

### Hydrocarbons, C9, aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

### Experience with human exposure

#### Components:

#### **N-Methyl-2-pyrrolidone:**

Skin contact : Symptoms: Skin irritation

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

#### **N-Methyl-2-pyrrolidone:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 500 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l  
Exposure time: 24 h  
Method: DIN 38412

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 600.5 mg/l  
Exposure time: 72 h

EC10 (Desmodesmus subspicatus (green algae)): 92.6 mg/l  
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 12.5 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: > 600 mg/l  
Exposure time: 30 min  
Method: ISO 8192

#### **Isobutyl methyl ketone:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 179 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 200 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 30 mg/l  
Exposure time: 21 d

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 05/03/2024
13.2	10/10/2024	1347699-00047	Date of first issue: 02/27/2017

---

### Hydrocarbons, C9, aromatics:

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 9.2 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3.2 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 7.9 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201
- NOELR (Pseudokirchneriella subcapitata (green algae)): 0.22 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC50: > 99 mg/l  
Exposure time: 10 min

### Chromium oxide:

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 10,000 mg/l  
Exposure time: 96 h
- Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 848.6 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): 1,000 mg/l  
Exposure time: 30 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): > 0.02 mg/l  
Exposure time: 21 d  
Remarks: No toxicity at the limit of solubility.
- Toxicity to microorganisms : EC50: > 10,000 mg/l  
Exposure time: 3 h

### 2-(2-Butoxyethoxy)ethanol:

- Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 1,300 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version 13.2      Revision Date: 10/10/2024      SDS Number: 1347699-00047      Date of last issue: 05/03/2024  
Date of first issue: 02/27/2017

---

Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): >= 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10: > 1,995 mg/l  
Exposure time: 30 min

### Persistence and degradability

#### Components:

##### **N-Methyl-2-pyrrolidone:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 73 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301C

##### **Isobutyl methyl ketone:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

##### **Hydrocarbons, C9, aromatics:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 78 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

##### **2-(2-Butoxyethoxy)ethanol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 85 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301C

### Bioaccumulative potential

#### Components:

##### **N-Methyl-2-pyrrolidone:**

Partition coefficient: n-octanol/water : log Pow: -0.46  
Method: OECD Test Guideline 107

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 05/03/2024
13.2	10/10/2024	1347699-00047	Date of first issue: 02/27/2017

---

### Isobutyl methyl ketone:

Partition coefficient: n-octanol/water : log Pow: 1.9

### Hydrocarbons, C9, aromatics:

Partition coefficient: n-octanol/water : log Pow: 3.7 - 4.5

### Chromium oxide:

Bioaccumulation : Species: Fish  
Bioconcentration factor (BCF): 260 - 800

### 2-(2-Butoxyethoxy)ethanol:

Partition coefficient: n-octanol/water : log Pow: 1

### Mobility in soil

No data available

### Other adverse effects

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.  
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : 3  
Environmentally hazardous : no

#### IATA-DGR



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version 13.2      Revision Date: 10/10/2024      SDS Number: 1347699-00047      Date of last issue: 05/03/2024  
Date of first issue: 02/27/2017

UN/ID No. : UN 1263  
Proper shipping name : Paint  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

### IMDG-Code

UN number : UN 1263  
Proper shipping name : PAINT  
  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

UN/ID/NA number : UN 1263  
Proper shipping name : Paint  
  
Class : 3  
Packing group : III  
Labels : FLAMMABLE LIQUID  
ERG Code : 128  
Marine pollutant : no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Isobutyl methyl ketone	108-10-1	5000	21191

### SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version 13.2      Revision Date: 10/10/2024      SDS Number: 1347699-00047      Date of last issue: 05/03/2024  
Date of first issue: 02/27/2017

Carcinogenicity  
Reproductive toxicity  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Specific target organ toxicity (single or repeated exposure)

### SARA 313

: The following components are subject to reporting levels established by SARA Title III, Section 313:

N-Methyl-2-pyrrolidone	872-50-4	>= 30 - < 50 %
Isobutyl methyl ketone	108-10-1	>= 20 - < 30 %
Chromium oxide	1308-38-9	>= 1 - < 5 %
2-(2-Butoxyethoxy)ethanol	112-34-5	>= 1 - < 5 %
2-Butoxyethanol	111-76-2	< 0.1 %

### Volatile organic compounds (VOC) content

VOC content: 727.01 g/l  
Remarks: less exempt

VOC content: 726.89 g/l  
Remarks: as packaged

### US State Regulations

#### Pennsylvania Right To Know

N-Methyl-2-pyrrolidone	872-50-4
Isobutyl methyl ketone	108-10-1
Polyamide-imide	Trade secret
Fluoropolymer	Trade secret
Hydrocarbons, C9, aromatics	64742-95-6
Chromium oxide	1308-38-9
2-(2-Butoxyethoxy)ethanol	112-34-5
Butan-1-ol	71-36-3
Butan-2-ol	78-92-2
2-Methyl-1-propanol	78-83-1
Formaldehyde	50-00-0

#### California Prop. 65

WARNING: This product can expose you to chemicals including Isobutyl methyl ketone, which is/are known to the State of California to cause cancer, and N-Methyl-2-pyrrolidone, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version 13.2      Revision Date: 10/10/2024      SDS Number: 1347699-00047      Date of last issue: 05/03/2024  
Date of first issue: 02/27/2017

### California List of Hazardous Substances

Isobutyl methyl ketone      108-10-1  
Hydrocarbons, C9, aromatics      64742-95-6  
Chromium oxide      1308-38-9


### California Permissible Exposure Limits for Chemical Contaminants

N-Methyl-2-pyrrolidone      872-50-4  
Isobutyl methyl ketone      108-10-1  
Hydrocarbons, C9, aromatics      64742-95-6  
Chromium oxide      1308-38-9

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA 704:



#### HMIS® IV:

HEALTH	*	2
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or nominated distributors.

### Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-2 : USA. Occupational Exposure Limits (OSHA) - Table Z-2
- US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit
- ACGIH / C : Ceiling limit
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 05/03/2024
13.2	10/10/2024	1347699-00047	Date of first issue: 02/27/2017

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday

NIOSH REL / C : Ceiling value not be exceeded at any time.

OSHA CARC / PEL : Permissible exposure limit (PEL)

OSHA CARC / STEL : Excursion limit

OSHA Z-1 / TWA : 8-hour time weighted average

OSHA Z-2 / TWA : 8-hour time weighted average

US WEEL / TWA : 8-hr TWA

US WEEL / STEL : Short-Term TWA

AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/10/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 959G-204 ONE COAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 05/03/2024
13.2	10/10/2024	1347699-00047	Date of first issue: 02/27/2017

---

safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8