according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Resin 350 X

Versio 4.3	on	Revision Date: 10/17/2024		0S Number: 55016-00016	Date of last issue: 09/15/2023 Date of first issue: 08/12/2017				
SECT	FION 1	. IDENTIFICATION							
F	Product name		:	: PFA Fluoroplastic Resin 350 X					
S	SDS-Id	entcode	:	130000143691					
Ν	Manufa	acturer or supplier's o	deta	iils					
C	Compa	ny name of supplier	:						
Δ	Address		:	1007 Market Street Wilmington, DE 19801 United States of America (USA)					
Т	Telephone		:	1-844-773-CHEM (outside the U.S. 1-302-773-1000)					
E	Emergency telephone		:	Medical emergency: 1-866-595-1473 (outside the U.S. 1-302- 773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)					
F	Recom	mended use of the c	hen	nical and restriction	ons on use				
F	Recom	mended use	:	Resin for moulding and/or extrusion					
F	Restrict	tions on use	:	Do not use or res tions involving im internal body fluid written agreemen	only. ell Chemours™ materials in medical applica- plantation in the human body or contact with s or tissues unless agreed to by Seller in a t covering such use. For further information, ur Chemours representative.				

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flulike symptoms in humans, especially when smoking contaminated tobacco.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Substance
Substance name	:	Poly(Heptafluoropropyl Trifluorovinyl Ether/Tetrafluoroethylene)

according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Resin 350 X

Version 4.3	Revision Date: 10/17/2024	-	DS Number: 355016-00016	Date of last issue: 09/15/2023 Date of first issue: 08/12/2017		
CAS	-No.	:	26655-00-5			
	n ponents nazardous ingredients					
SECTION	1 4. FIRST AID MEASUF	RES				
lf inh	If inhaled		If inhaled, remove to fresh air. Get medical attention if symptoms occur.			
In ca	ase of skin contact	:	Wash with water and soap as a precaution. Get medical attention if symptoms occur.			
In ca	In case of eye contact		Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.			
lf sw	allowed	:	Get medical atter	NOT induce vomiting. ntion if symptoms occur. oughly with water.		
	t important symptoms effects, both acute and yed	:	: Polymer fume fever			
Prote	ection of first-aiders	:	No special preca	utions are necessary for first aid responders.		
Note	es to physician	:	Treat symptomatically and supportively.			

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	None known.
Specific hazards during fire fighting	:	Exposure to combustion products may be a hazard to health.
Hazardous combustion prod- ucts	:	Hydrogen fluoride carbonyl fluoride potentially toxic fluorinated compounds aerosolized particulates Carbon oxides
Specific extinguishing meth-	:	Use extinguishing measures that are appropriate to local cir-

according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Resin 350 X

Version 4.3	Revision Date: 10/17/2024		DS Number: 355016-00016	Date of last issue: 09/15/2023 Date of first issue: 08/12/2017
ods			Use water spray	the surrounding environment. to cool unopened containers. Iged containers from fire area if it is safe to do
	ial protective equipment e-fighters	:	necessary.	ned breathing apparatus for firefighting if tective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Follow safe handling advice (see section 7) and personal pro- tective equipment recommendations (see section 8).
Environmental precautions	:	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Sweep up or vacuum up spillage and collect in suitable con- tainer for disposal. Local or national regulations may apply to releases and dispo- sal of this material, as well as those materials and items em- ployed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures	:	See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.	
Local/Total ventilation	:	Use only with adequate ventilation.	
Advice on safe handling	:	Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as- sessment Take care to prevent spills, waste and minimize release to the environment.	
		Do not breathe decomposition products.	
Conditions for safe storage	:	Keep in properly labeled containers. Store in accordance with the particular national regulations.	

according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Resin 350 X

Version 4.3	Revision Date: 10/17/2024	-	DS Number: 355016-00016	Date of last issue: 09/15/2023 Date of first issue: 08/12/2017
Mate	rials to avoid	:	Do not store with Strong oxidizing a	the following product types: agents
	er information on stor- tability	:	Stable under reco	ommended storage conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		С	2 ppm (Fluorine)	ACGIH
		TWA	3 ppm	OSHA Z-2
		С	6 ppm 5 mg/m³	NIOSH REL
		TWA	3 ppm 2.5 mg/m ³	NIOSH REL
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m ³	NIOSH REL
		ST	5 ppm 15 mg/m³	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m³	NIOSH REL
		ST	30,000 ppm 54,000 mg/m ³	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m ³	OSHA Z-1
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m ³	NIOSH REL
		С	200 ppm 229 mg/m ³	NIOSH REL
		TWA	50 ppm 55 mg/m³	OSHA Z-1

Engineering measures

Processing may form hazardous compounds (see section 10).

:

according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Resin 350 X

Versio 4.3	on	Revision Date: 10/17/2024		S Number: 55016-00016	Date of last issue: 09/15/2023 Date of first issue: 08/12/2017
					ventilation, especially in confined areas. ce exposure concentrations.
F	Person	al protective equip	ment		
F	Respira	atory protection	:	maintain vapor ex concentrations ar unknown, approp Follow OSHA res use NIOSH/MSH/ by air purifying re dous chemical is respirator if there exposure levels a	exhaust ventilation is recommended to sposures below recommended limits. Where e above recommended limits or are riate respiratory protection should be worn. pirator regulations (29 CFR 1910.134) and A approved respirators. Protection provided spirators against exposure to any hazar- limited. Use a positive pressure air supplied is any potential for uncontrolled release, re unknown, or any other circumstance g respirators may not provide adequate
H	Hand p Mate	rotection erial	:	Heat resistant glo	ves
	Rem	narks	:	on the concentrat applications, we r micals of the afore manufacturer. Wa	protect hands against chemicals depending ion specific to place of work. For special ecommend clarifying the resistance to che- ementioned protective gloves with the glove ash hands before breaks and at the end of rough time is not determined for the pro- ves often!
E	Eye pro	otection	:	Wear the following Safety glasses	g personal protective equipment:
5	Skin an	d body protection	:	Skin should be wa	ashed after contact.
ŀ	Hygien	e measures	:	 If exposure to chemical is likely during typical use, providely eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use. 	
SECT	FION 9	. PHYSICAL AND C	HEMI		S
ŀ	Appear	ance	:	pellets, granules	
C	Color		:	translucent	
(Odor		:	odorless	
(Odor TI	hreshold	:	No data available	2

according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Resin 350 X

Vers 4.3	ion	Revision Date: 10/17/2024		S Number: 5016-00016	Date of last issue: 09/15/2023 Date of first issue: 08/12/2017
	pН		:	No data available	
	Melting	point/freezing point	:	> 572 °F / > 300	°C
	Initial boiling point and boiling range		:	No data available)
	Flash p	oint	:	Not applicable	
	Evapora	ation rate	:	Not applicable	
	Flamma	ability (solid, gas)	:	Not classified as explosive dust-ai	a flammability hazard, Not expected to form r mixtures.
		explosion limit / Upper bility limit	:	No data available	9
		explosion limit / Lower bility limit	:	No data available	
	Vapor pressure		:	Not applicable	
	Relative	e vapor density	:	Not applicable	
	Density		:	2.1 - 2.2 g/cm ³	
	Solubili Wat	ty(ies) er solubility	:	insoluble	
	Partition octanol	n coefficient: n- /water	:	No data available	
	Autoign	ition temperature	:	No data available)
	Decom	position temperature	:	No data available)
	Viscosi Visc	ty osity, kinematic	:	Not applicable	
	Explosi	ve properties	:	Not explosive	
	Oxidizir	ng properties	:	The substance of	r mixture is not classified as oxidizing.
	Particle Particle	characteristics size	:	No data available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity

: Not classified as a reactivity hazard.

according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Resin 350 X

Vers 4.3	sion	Revision Date: 10/17/2024		S Number: 5016-00016	Date of last issue: 09/15/2023 Date of first issue: 08/12/2017	
		cal stability ility of hazardous reac-	:		mal conditions. rong oxidizing agents. mposition products will be formed at elevated	
	Conditi	ons to avoid	:	None known.		
	Incompatible materials		:	Oxidizing agents		
	Hazardous decomposition pro Thermal decomposition		orodi :		de	

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

- **IARC** No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- **OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
- **NTP** No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Resin 350 X

Version	Revision Date:	SDS Number:	Date of last issue: 09/15/2023
4.3	10/17/2024	1855016-00016	Date of first issue: 08/12/2017

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods		
Waste from residues	:	Dispose of in accordance with local regulations. Do not dispose of waste into sewer.
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Resin 350 X

Version	Revision Date:	SDS Number:	Date of last issue: 09/15/2023
4.3	10/17/2024	1855016-00016	Date of first issue: 08/12/2017

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable for product as supplied.

Domestic regulation

49 CFR Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	: No SARA Hazards	
SARA 313	: This material does not contain any chemical components w known CAS numbers that exceed the threshold (De Minimis reporting levels established by SARA Title III, Section 313.	

US State Regulations

Pennsylvania Right To Know

Poly(Heptafluoropropyl Trifluorovinyl Ether/Tetrafluoroethylene)

26655-00-5

California Prop. 65

WARNING: This product can expose you to chemicals including Pentadecafluorooctanoic acid, which is/are known to the State of California to cause cancer, and Carbon monoxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. Note to User: This product is not made with PFOA nor is PFOA intentionally present in the product; however, it is possible that PFOA may be present as an impurity at background (environmental) levels.


SECTION 16. OTHER INFORMATION

Further information

according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Resin 350 X



Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
OSHA Z-2		USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	÷	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organiza-

according to the OSHA Hazard Communication Standard



PFA Fluoroplastic Resin 350 X

Version	Revision Date:	SDS Number:	Date of last issue: 09/15/2023
4.3	10/17/2024	1855016-00016	Date of first issue: 08/12/2017

tion; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to	:	Internal technical data, data from raw material SDSs, OECD
compile the Material Safety		eChem Portal search results and European Chemicals Agen-
Data Sheet		cy, http://echa.europa.eu/

Revision Date

: 10/17/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8