according to the OSHA Hazard Communication Standard



PTFE Fine Powder Fluoroplastic Resin 602 X

Version 5.2	Revision Date: 10/15/2024		SDS Number:Date of last issue: 11/02/20231729164-00013Date of first issue: 08/12/2017				
SECTIO	N 1. IDENTIFICATION						
Pro	duct name	:	PTFE Fine Powde	er Fluoroplastic Resin 602 X			
SD	SDS-Identcode		130000109859				
Ma	nufacturer or supplier's	deta	ails				
Cor	npany name of supplier	:	The Chemours Co	ompany FC, LLC			
Ado	Address		1007 Market Street Wilmington, DE 19801 United States of America (USA)				
Tel	Telephone		1-844-773-CHEM (outside the U.S. 1-302-773-1000)				
Em	Emergency telephone		Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)				
Red	commended use of the c	hen	nical and restriction	ons on use			
Red	commended use	:	Resin for mouldin	g and/or extrusion			
Res	strictions on use	:	Do not use or rest tions involving imp internal body fluid written agreemen	only. ell Chemours™ materials in medical applica- blantation in the human body or contact with s or tissues unless agreed to by Seller in a t covering such use. For further information, ur Chemours representative.			

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flulike symptoms in humans, especially when smoking contaminated tobacco. Dust contact with the eyes can lead to mechanical irritation. Contact with dust can cause mechanical irritation or drying of the skin.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

:

Substance / Mixture : Substance

Substance name

Polytetrafluoroethylene

according to the OSHA Hazard Communication Standard



PTFE Fine Powder Fluoroplastic Resin 602 X

Vers 5.2	sion	Revision Date: 10/15/2024		0S Number: 29164-00013	Date of last issue: 11/02/2023 Date of first issue: 08/12/2017
	CAS-N	0.	:	9002-84-0	
	Compo No haz	onents ardous ingredients			
SEC	TION 4	. FIRST AID MEASUR	ES		
	Genera	al advice	:	vice immediately. When symptoms	ident or if you feel unwell, seek medical ad- persist or in all cases of doubt seek medical
	lf inhale	ed	:	advice. If inhaled, remove Get medical atten	to fresh air. tion if symptoms occur.
	In case	of skin contact	:	Wash with water a Get medical atten	and soap. tion if symptoms occur.
	In case	of eye contact	:	If in eyes, rinse w Get medical atten	ell with water. tion if irritation develops and persists.
	If swall	owed	:		NOT induce vomiting. tion if symptoms occur. oughly with water.
		nportant symptoms ects, both acute and d	:	 Polymer fume fever Contact with dust can cause mechanical irritation or dryin the skin. Dust contact with the eyes can lead to mechanical irritation 	
	Protect	ion of first-aiders	:	No special precau	tions are necessary for first aid responders.
	Notes t	o physician	:	Treat symptomati	cally and supportively.
SEC	TION 5	. FIRE-FIGHTING ME	ASL	JRES	
	Suitabl	e extinguishing media	:	Water spray Alcohol-resistant Carbon dioxide (C Dry chemical	
	Unsuita media	able extinguishing	:	None known.	
	Specific fighting	c hazards during fire	:	Exposure to comb	pustion products may be a hazard to health.
	Hazard	ous combustion prod-	:	Hydrogen fluoride	



PTFE Fine Powder Fluoroplastic Resin 602 X

Versi 5.2	on	Revision Date: 10/15/2024		S Number: 29164-00013	Date of last issue: 11/02/2023 Date of first issue: 08/12/2017
l	ucts			carbonyl fluoride potentially toxic flu aerosolized partic Carbon oxides	uorinated compounds ulates
	Specific ods	extinguishing meth-	:	cumstances and t Use water spray to	measures that are appropriate to local cir- he surrounding environment. o cool unopened containers. ged containers from fire area if it is safe to do
		protective equipment fighters	:	Wear self-contain necessary. Use personal prot	ed breathing apparatus for firefighting if ective equipment.
SEC	TION 6.	ACCIDENTAL RELE	ASE	E MEASURES	
t	tive equ	al precautions, protec- lipment and emer- procedures	:		ing advice (see section 7) and personal pro- recommendations (see section 8).
I	Environ	mental precautions	:	Retain and dispos	akage or spillage if safe to do so. e of contaminated wash water. should be advised if significant spillages
		s and materials for ment and cleaning up	:	tainer for disposal Avoid dispersal of with compressed Local or national r sal of this materia ployed in the clear which regulations Sections 13 and 1	dust in the air (i.e., clearing dust surfaces air). regulations may apply to releases and dispo- I, as well as those materials and items em- nup of releases. You will need to determine

SECTION 7. HANDLING AND STORAGE

Technical measures	:	See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation	:	Use only with adequate ventilation.
Advice on safe handling	:	Do not breathe dust. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

SAFETY DATA SHEET according to the OSHA Hazard Communication Standard



PTFE Fine Powder Fluoroplastic Resin 602 X

Version 5.2	Revision Date: 10/15/2024	SDS Number: 1729164-00013		Date of last issue: 11/02/2023 Date of first issue: 08/12/2017
		Keep Take	ize dust ger container cl	neration and accumulation. osed when not in use. ent spills, waste and minimize release to the
		Do no	t breathe de	ecomposition products.
Cond	itions for safe storage			abeled containers. ce with the particular national regulations.
Mate	rials to avoid	_	t store with g oxidizing a	the following product types: Igents
	er information on stor- tability	: Stable	e under reco	mmended storage conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace co	Ingredients with workplace control parameters				
inert or nuisance dust	50 Million particles per cubic foot Value type (Form of exposure): TWA (total dust) Basis: OSHA Z-3				
	15 mg/m³ Value type (Form of exposure): TWA (total dust) Basis: OSHA Z-3				
	5 mg/m³ Value type (Form of exposure): TWA (respirable fraction) Basis: OSHA Z-3				
	15 Million particles per cubic foot Value type (Form of exposure): TWA (respirable fraction) Basis: OSHA Z-3				
Dust, nuisance dust and par- ticulates	10 mg/m³ Value type (Form of exposure): PEL (Total dust) Basis: CAL PEL				
	5 mg/m³ Value type (Form of exposure): PEL (respirable dust fraction) Basis: CAL PEL				

Contains no substances with occupational exposure limit values.

according to the OSHA Hazard Communication Standard



PTFE Fine Powder Fluoroplastic Resin 602 X

Version	Revision Date:	SDS Number:	Date of last issue: 11/02/2023
5.2	10/15/2024	1729164-00013	Date of first issue: 08/12/2017

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		С	2 ppm (Fluorine)	ACGIH
		TWA	3 ppm	OSHA Z-2
		С	6 ppm 5 mg/m ³	NIOSH REL
		TWA	3 ppm 2.5 mg/m ³	NIOSH REL
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m ³	NIOSH REL
		ST	5 ppm 15 mg/m³	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m ³	NIOSH REL
		ST	30,000 ppm 54,000 mg/m ³	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m ³	OSHA Z-1
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m ³	NIOSH REL
		С	200 ppm 229 mg/m ³	NIOSH REL
		TWA	50 ppm 55 mg/m³	OSHA Z-1

Engineering measures

5

Processing may form hazardous compounds (see section 10).

Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations. Ensure that dust-handling systems (such as exhaust ducts,

dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn.

Chemours⁻

according to the OSHA Hazard Communication Standard

PTFE Fine Powder Fluoroplastic Resin 602 X

Vers 5.2	ion	Revision Date: 10/15/2024	-	9S Number: 29164-00013	Date of last issue: 11/02/2023 Date of first issue: 08/12/2017	
				use NIOSH/MSH/ by air purifying re- dous chemical is respirator if there exposure levels a	pirator regulations (29 CFR 1910.134) and A approved respirators. Protection provided spirators against exposure to any hazar- limited. Use a positive pressure air supplied is any potential for uncontrolled release, re unknown, or any other circumstance g respirators may not provide adequate	
Hand protection Material		:	Heat resistant gloves			
Remarks		:	Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to che- micals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the pro- duct. Change gloves often!			
Eye protection		:	Wear the following personal protective equipment: Safety goggles			
	Skin an	d body protection	:	Skin should be wa	ashed after contact.	
	Hygiene	e measures	:	eye flushing syste king place. When using do no	emical is likely during typical use, provide ems and safety showers close to the wor- ot eat, drink or smoke. ed clothing before re-use.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	powder
Color	:	white
Odor	:	odorless
Odor Threshold	:	No data available
рН	:	No data available
Melting point/freezing point	:	> 608 °F / > 320 °C
Initial boiling point and boiling range	:	No data available

according to the OSHA Hazard Communication Standard



PTFE Fine Powder Fluoroplastic Resin 602 X

Vers 5.2	sion	Revision Date: 10/15/2024	-	S Number: 29164-00013	Date of last issue: 11/02/2023 Date of first issue: 08/12/2017
	Flash p	oint	:	Not applicable	
	Evapora	ation rate	:	Not applicable	
	Flamma	ability (solid, gas)	:	Not classified as explosive dust-ai	a flammability hazard, Not expected to form r mixtures.
	Upper e flamma	explosion limit / Upper bility limit	:	No data available	9
		explosion limit / Lower bility limit	:	No data available	
	Vapor p	pressure	:	Not applicable	
	Relative	e vapor density	:	Not applicable	
	Density	,	:	2.14 - 2.24 g/cm ³	i de la constante de
	Solubili Wat	ty(ies) er solubility	:	insoluble	
	Partition octanol	n coefficient: n- /water	:	No data available	
	Autoign	ition temperature	:	No data available)
	Decom	position temperature	:	No data available)
	Viscosi Visc	ty osity, kinematic	:	Not applicable	
	Explosi	ve properties	:	Not explosive	
	Oxidizir	ng properties	•	The substance of	r mixture is not classified as oxidizing.
	Particle Particle	characteristics size	:	No data available	9

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reac- tions	:	Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid	:	None known.

according to the OSHA Hazard Communication Standard



PTFE Fine Powder Fluoroplastic Resin 602 X

Version 5.2	Revision Date: 10/15/2024	SDS Number: 1729164-00013	Date of last issue: 11/02/2023 Date of first issue: 08/12/2017			
Incon	npatible materials	: Oxidizing age	nts			
Haza	Hazardous decomposition products					
Therr	Thermal decomposition : Hydrogen fluoride Carbonyl difluoride Carbon dioxide Carbon monoxide					
SECTION 11. TOXICOLOGICAL INFORMATION						
Infor	Information on likely routes of exposure					
Inhala						
Inges	contact stion					

Eye contact

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

- **IARC** No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- **OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
- **NTP** No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

according to the OSHA Hazard Communication Standard



PTFE Fine Powder Fluoroplastic Resin 602 X

Version	Revision Date:	SDS Number:	Date of last issue: 11/02/2023
5.2	10/15/2024	1729164-00013	Date of first issue: 08/12/2017

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity
No data available
Persistence and degradability
No data available
Bioaccumulative potential
No data available
Mobility in soil
No data available
Other adverse effects
No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	:	Dispose of in accordance with local regulations. Do not dispose of waste into sewer.
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG Not regulated as a dangerous good

IATA-DGR Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR Not regulated as a dangerous good

according to the OSHA Hazard Communication Standard



PTFE Fine Powder Fluoroplastic Resin 602 X

Version	Revision Date:	SDS Number:	Date of las
5.2	10/15/2024	1729164-00013	Date of fire

Date of last issue: 11/02/2023 Date of first issue: 08/12/2017

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	No SARA Hazards
SARA 313	:	This material does not contain any chem

:	This material does not contain any chemical components with
	known CAS numbers that exceed the threshold (De Minimis)
	reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Polytetrafluoroethylene

9002-84-0

California Prop. 65

WARNING: This product can expose you to chemicals including Pentadecafluorooctanoic acid, which is/are known to the State of California to cause cancer, and Carbon monoxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. Note to User: This product is not made with PFOA nor is PFOA intentionally present in the product; however, it is possible that PFOA may be present as an impurity at background (environmental) levels.


SECTION 16. OTHER INFORMATION

Further information

according to the OSHA Hazard Communication Standard



PTFE Fine Powder Fluoroplastic Resin 602 X



Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

Full text of other abbreviations

	USA. ACGIH Threshold Limit Values (TLV)			
:	California permissible exposure limits for chemical contami- nants (Title 8, Article 107)			
:	USA. NIOSH Recommended Exposure Limits			
:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants			
:	USA. Occupational Exposure Limits (OSHA) - Table Z-2			
:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts			
:	8-hour, time-weighted average			
:	Short-term exposure limit			
:	Ceiling limit			
:	Permissible exposure limit			
:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek			
:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday			
:	Ceiling value not be exceeded at any time.			
:	8-hour time weighted average			
:	8-hour time weighted average			
:	8-hour time weighted average			

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule;

SAFETY DATA SHEET according to the OSHA Hazard Communication Standard



PTFE Fine Powder Fluoroplastic Resin 602 X

Version	Revision Date:	SDS Number:	Date of last issue: 11/02/2023
5.2	10/15/2024	1729164-00013	Date of first issue: 08/12/2017

ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 10/15/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8