

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 12/10/2024
17.0	06/24/2025	1346429-00052	Date of first issue: 02/27/2017

SECTION 1. IDENTIFICATION

Product name : 851G-214 TOPCOAT GREEN

Product code : D14847244

SDS-Identcode : 130000127772

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Coatings

Restrictions on use : For industrial use only.
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 4

Serious eye damage : Category 1

Skin sensitization : Category 1

Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.
Vapors may form explosive mixture with air.

GHS label elements

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version 17.0 Revision Date: 06/24/2025 SDS Number: 1346429-00052 Date of last issue: 12/10/2024
Date of first issue: 02/27/2017

Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	H227 Combustible liquid. H317 May cause an allergic skin reaction. H318 Causes serious eye damage.
Supplemental Hazard Statements	:	Corrosive to the respiratory tract.
Precautionary Statements	:	Prevention: P210 Keep away from heat, sparks, open flame and hot surfaces. No smoking. P261 Avoid breathing mist or vapors. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves, protective clothing, eye protection and face protection. Response: P302 + P352 IF ON SKIN: Wash with plenty of water. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER. P333 + P313 If skin irritation or rash occurs: Get medical attention. Disposal: P501 Dispose of contents and container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Paint

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Chromium oxide	1308-38-9*	>= 5 - <= 10	TSC
Hydrocarbons, C9, aromatics	64742-95-6*	>= 3 - <= 7	TSC
Sodium lauryl sulfate	73296-89-6*	>= 1 - <= 5	TSC

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version 17.0 Revision Date: 06/24/2025 SDS Number: 1346429-00052 Date of last issue: 12/10/2024
Date of first issue: 02/27/2017

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxy-ethanol	60828-78-6*	$\geq 1 - \leq 5$	TSC
Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9*	≤ 0.1	TSC

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

Alternative CAS Numbers for some regions

Chemical name	Alternative CAS Number(s)
Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	2682-20-4, 26172-55-4

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention immediately.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
Causes serious eye damage.
Corrosive to the respiratory tract.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 12/10/2024
17.0	06/24/2025	1346429-00052	Date of first issue: 02/27/2017

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Hydrogen fluoride
carbonyl fluoride
potentially toxic fluorinated compounds
aerosolized particulates
Carbon oxides
Chromium compounds
Metal oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 12/10/2024
17.0	06/24/2025	1346429-00052	Date of first issue: 02/27/2017

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.
Avoid breathing mist or vapors.
Do not swallow.
Do not get in eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labeled containers.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Explosives
Gases

Recommended storage temperature : 41 - 77 °F / 5 - 25 °C

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version 17.0 Revision Date: 06/24/2025 SDS Number: 1346429-00052 Date of last issue: 12/10/2024
Date of first issue: 02/27/2017

perature

Further information on storage stability : Do not freeze.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Chromium oxide	1308-38-9	TWA	0.5 mg/m ³ (chromium)	OSHA Z-1
		TWA	0.5 mg/m ³ (chromium)	NIOSH REL
Hydrocarbons, C9, aromatics	64742-95-6	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
		TWA	3 ppm	OSHA Z-2
		C	6 ppm 5 mg/m ³	NIOSH REL
		TWA	3 ppm 2.5 mg/m ³	NIOSH REL
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m ³	NIOSH REL
		ST	5 ppm 15 mg/m ³	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m ³	NIOSH REL
		ST	30,000 ppm 54,000 mg/m ³	NIOSH REL
		TWA	5,000 ppm	OSHA Z-1

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version 17.0 Revision Date: 06/24/2025 SDS Number: 1346429-00052 Date of last issue: 12/10/2024
Date of first issue: 02/27/2017

			9,000 mg/m ³	
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m ³	NIOSH REL
		C	200 ppm 229 mg/m ³	NIOSH REL
		TWA	50 ppm 55 mg/m ³	OSHA Z-1

Engineering measures : Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
If splashes are likely to occur, wear:
Face-shield

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version 17.0	Revision Date: 06/24/2025	SDS Number: 1346429-00052	Date of last issue: 12/10/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : green

Odor : No data available

Odor Threshold : No data available

pH : 9.5 - 10.5

Melting point/freezing point : No data available

Initial boiling point and boiling range : > 212 °F / > 100 °C

Flash point : 144 °F / 62 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 12/10/2024
17.0	06/24/2025	1346429-00052	Date of first issue: 02/27/2017

Density	:	1.3510 g/cm ³
Solubility(ies)	:	
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, dynamic	:	32 mPa.s
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics	:	
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Combustible liquid. Vapors may form explosive mixture with air. Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents Acids

Hazardous decomposition products

Thermal decomposition	:	Hydrogen fluoride Carbonyl difluoride Carbon dioxide Carbon monoxide
-----------------------	---	---

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 12/10/2024
17.0	06/24/2025	1346429-00052	Date of first issue: 02/27/2017

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

|| Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

Chromium oxide:

|| Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
|| Acute inhalation toxicity : LC50 (Rat): > 5.41 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Hydrocarbons, C9, aromatics:

|| Acute oral toxicity : LD50 (Rat, female): 3,492 mg/kg
|| Acute inhalation toxicity : LC50 (Rat): > 6.193 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity
|| Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Sodium lauryl sulfate:

|| Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
|| Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

|| Acute oral toxicity : LD50 (Rat): 3,300 mg/kg

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 12/10/2024
17.0	06/24/2025	1346429-00052	Date of first issue: 02/27/2017

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Acute oral toxicity : LD50 (Rat): 64 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.171 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 (Rabbit): 87.12 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Chromium oxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Hydrocarbons, C9, aromatics:

Assessment : Repeated exposure may cause skin dryness or cracking.

Sodium lauryl sulfate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation
Remarks : Based on data from similar materials

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Result : Skin irritation

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 1 to 4 hours of exposure

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Chromium oxide:

Species : Rabbit

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 12/10/2024
17.0	06/24/2025	1346429-00052	Date of first issue: 02/27/2017

Result	: No eye irritation
Method	: OECD Test Guideline 405

Hydrocarbons, C9, aromatics:

Species	: Rabbit
Result	: No eye irritation

Sodium lauryl sulfate:

Species	: Rabbit
Result	: Irreversible effects on the eye
Method	: OECD Test Guideline 405
Remarks	: Based on data from similar materials

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Result	: Irreversible effects on the eye
--------	-----------------------------------

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Result	: Irreversible effects on the eye
Remarks	: Based on skin corrosivity.

Respiratory or skin sensitization

Skin sensitization

|| May cause an allergic skin reaction.

Respiratory sensitization

|| Not classified based on available information.

Components:

Chromium oxide:

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative
Remarks	: Based on data from similar materials

Hydrocarbons, C9, aromatics:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

Sodium lauryl sulfate:

Test Type	: Maximization Test
Routes of exposure	: Skin contact

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 12/10/2024
17.0	06/24/2025	1346429-00052	Date of first issue: 02/27/2017

Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative
Remarks	: Based on data from similar materials

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: positive

Assessment	: Probability or evidence of high skin sensitization rate in humans
------------	---

Germ cell mutagenicity

Not classified based on available information.

Components:

Chromium oxide:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: negative

Hydrocarbons, C9, aromatics:

Genotoxicity in vitro	: Test Type: Chromosome aberration test in vitro Result: negative
Genotoxicity in vivo	: Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Rat Application Route: inhalation (vapor) Result: negative

Sodium lauryl sulfate:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Ingestion Method: OECD Test Guideline 474

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version 17.0	Revision Date: 06/24/2025	SDS Number: 1346429-00052	Date of last issue: 12/10/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Chromium oxide:

Species	: Rat
Application Route	: Ingestion
Exposure time	: 2 Years
Result	: negative

Sodium lauryl sulfate:

Species	: Rat
Application Route	: Ingestion
Exposure time	: 2 Years
Result	: negative
Remarks	: Based on data from similar materials

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Chromium oxide:

Effects on fetal development	: Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Result: negative Remarks: Based on data from similar materials
------------------------------	--

Hydrocarbons, C9, aromatics:

Effects on fertility	: Test Type: Three-generation reproduction toxicity study Species: Rat Application Route: inhalation (vapor) Result: negative
Effects on fetal development	: Test Type: Embryo-fetal development Species: Mouse Application Route: inhalation (vapor) Result: negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 12/10/2024
17.0	06/24/2025	1346429-00052	Date of first issue: 02/27/2017

||

Sodium lauryl sulfate:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

|| Corrosive to the respiratory tract.

Components:

Hydrocarbons, C9, aromatics:

|| Assessment : May cause drowsiness or dizziness.

|| Assessment : May cause respiratory irritation.

STOT-repeated exposure

|| Not classified based on available information.

Repeated dose toxicity

Components:

Chromium oxide:

Species : Rat
NOAEL : 2,000 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Hydrocarbons, C9, aromatics:

Species : Rat, female
NOAEL : 900 mg/m³
Application Route : inhalation (vapor)
Exposure time : 12 Months
Remarks : Based on data from similar materials

Sodium lauryl sulfate:

Species : Rat
NOAEL : > 430 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Remarks : Based on data from similar materials

Aspiration toxicity

|| Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 12/10/2024
17.0	06/24/2025	1346429-00052	Date of first issue: 02/27/2017

Components:

Hydrocarbons, C9, aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Chromium oxide:

Toxicity to fish	: LC50 (Danio rerio (zebra fish)): > 10,000 mg/l Exposure time: 96 h
Toxicity to algae/aquatic plants	: EC50 (Desmodesmus subspicatus (green algae)): > 848.6 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOEC (Danio rerio (zebra fish)): 1,000 mg/l Exposure time: 30 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): > 0.02 mg/l Exposure time: 21 d Remarks: No toxicity at the limit of solubility.
Toxicity to microorganisms	: EC50: > 10,000 mg/l Exposure time: 3 h

Hydrocarbons, C9, aromatics:

Toxicity to fish	: LL50 (Oncorhynchus mykiss (rainbow trout)): 9.2 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): 3.2 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: EL50 (Pseudokirchneriella subcapitata (green algae)): 7.9 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 NOELR (Pseudokirchneriella subcapitata (green algae)): 0.22 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 12/10/2024
17.0	06/24/2025	1346429-00052	Date of first issue: 02/27/2017

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 99 mg/l
Exposure time: 10 min

Sodium lauryl sulfate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 3.6 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.7 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 20 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

EC10 (Desmodesmus subspicatus (green algae)): 5.4 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 0.11 mg/l
Exposure time: 34 d
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.14 mg/l
Exposure time: 21 d
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC10 (Pseudomonas putida): 1,083.85 mg/l
Exposure time: 16 h
Method: DIN 38 412 Part 8
Remarks: Based on data from similar materials

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 39 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 81.2 mg/l
Exposure time: 48 h

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.19 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.16 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic : ErC50 (Skeletonema costatum (marine diatom)): 0.0052 mg/l

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 12/10/2024
17.0	06/24/2025	1346429-00052	Date of first issue: 02/27/2017

plants	Exposure time: 48 h
	NOEC (Skeletonema costatum (marine diatom)): 0.00049 mg/l Exposure time: 48 h
Toxicity to fish (Chronic toxicity)	: NOEC (Pimephales promelas (fathead minnow)): 0.02 mg/l Exposure time: 36 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 0.10 mg/l Exposure time: 21 d

Persistence and degradability

Components:

Hydrocarbons, C9, aromatics:

Biodegradability	: Result: Readily biodegradable. Biodegradation: 78 % Exposure time: 28 d Method: OECD Test Guideline 301F
------------------	---

Sodium lauryl sulfate:

Biodegradability	: Result: Readily biodegradable. Biodegradation: 100 % Exposure time: 28 d Method: OECD Test Guideline 301B
------------------	--

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Biodegradability	: Result: Not readily biodegradable.
------------------	--------------------------------------

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 62 % Exposure time: 28 d Method: OECD Test Guideline 301B
------------------	---

Bioaccumulative potential

Components:

Chromium oxide:

Bioaccumulation	: Species: Fish Bioconcentration factor (BCF): 260 - 800
-----------------	---

Hydrocarbons, C9, aromatics:

Partition coefficient: n-octanol/water	: log Pow: 3.7 - 4.5
--	----------------------

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 12/10/2024
17.0	06/24/2025	1346429-00052	Date of first issue: 02/27/2017

Sodium lauryl sulfate:

Partition coefficient: n-octanol/water : log Pow: ≤ -2.1

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Partition coefficient: n-octanol/water : log Pow: < 1

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number	: NA 1993
Proper shipping name	: Combustible liquid, n.o.s. (Hydrocarbons, C9, aromatics)
Class	: CBL

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 12/10/2024
17.0	06/24/2025	1346429-00052	Date of first issue: 02/27/2017

Packing group	:	III
Labels	:	NONE
ERG Code	:	128
Marine pollutant	:	no
Remarks	:	Above applies only to containers over 119 gallons or 450 liters. Not regulated if shipped in packages less than or equal to 119 gallons (450 liters).

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	Flammable (gases, aerosols, liquids, or solids)
		Respiratory or skin sensitization
		Serious eye damage or eye irritation

SARA 313	:	The following components are subject to reporting levels established by SARA Title III, Section 313:
-----------------	---	--

Chromium oxide	1308-38-9	>= 5 - < 10 %
Mercury	7439-97-6	< 0.1 %
Lead	7439-92-1	< 0.1 %

Volatile organic compounds (VOC) content

VOC content: 187.53 g/l
Remarks: less exempt

VOC content: 72.26 g/l
Remarks: as packaged

US State Regulations

Pennsylvania Right To Know

Water	7732-18-5
Fluoropolymer	Trade secret
Chromium oxide	1308-38-9

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 12/10/2024
17.0	06/24/2025	1346429-00052	Date of first issue: 02/27/2017

Hydrocarbons, C9, aromatics	64742-95-6
Sodium lauryl sulfate	73296-89-6
Ammonium hydroxide	1336-21-6

California Prop. 65

WARNING: This product can expose you to chemicals including Cadmium, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Chromium oxide	1308-38-9
Hydrocarbons, C9, aromatics	64742-95-6


California Permissible Exposure Limits for Chemical Contaminants

Chromium oxide	1308-38-9
Hydrocarbons, C9, aromatics	64742-95-6

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	/	3
FLAMMABILITY		2
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.
Before use read Chemours safety information.
For further information contact the local Chemours office or nominated distributors.

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	: USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 12/10/2024
17.0	06/24/2025	1346429-00052	Date of first issue: 02/27/2017

ACGIH / C	: Ceiling limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	: Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-2 / TWA	: 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 06/24/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-214 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 12/10/2024
17.0	06/24/2025	1346429-00052	Date of first issue: 02/27/2017

safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8