

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

SECTION 1. IDENTIFICATION

Product name : 851G-224 TOPCOAT GREEN

Product code : D14808411

SDS-Identcode : 130000127774

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Coatings

Restrictions on use : For industrial use only.
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3

Serious eye damage : Category 1

Skin sensitization : Category 1

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 2 (Central nervous system, Auditory system)
- repeated exposure

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.

GHS label elements

Hazard pictograms

:



Signal Word

:

Danger

Hazard Statements

:

H226 Flammable liquid and vapor.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs (Central nervous system, Auditory system) through prolonged or repeated exposure.

Supplemental Hazard Statements

:

Corrosive to the respiratory tract.

Precautionary Statements

:

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, sparks, open flame and hot surfaces. No smoking.
P233 Keep container tightly closed.
P241 Use explosion-proof electrical, ventilating and lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapors.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER.
P308 + P313 IF exposed or concerned: Get medical attention.
P333 + P313 If skin irritation or rash occurs: Get medical attention.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version 14.0 Revision Date: 06/24/2025 SDS Number: 1346473-00049 Date of last issue: 11/05/2024
Date of first issue: 02/27/2017

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Additional Labeling

The following percentage of the mixture consists of ingredient(s) with unknown acute oral toxicity: 1.6572 %

The following percentage of the mixture consists of ingredient(s) with unknown acute dermal toxicity: 1.6572 %

The following percentage of the mixture consists of ingredient(s) with unknown acute inhalation toxicity: 1.6572 %

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Paint

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Hydrocarbons, C9, aromatics	64742-95-6*	$\geq 3 - \leq 7$	TSC
Chromium oxide	1308-38-9*	$\geq 3 - \leq 7$	TSC
Titanium dioxide	13463-67-7*	$\geq 1 - \leq 5$	TSC
Sodium lauryl sulfate	73296-89-6*	$\geq 1 - \leq 5$	TSC
2,6,8-Trimethyl-4-nonyloxypolyethyleneoxy-ethanol	60828-78-6*	$\geq 1 - \leq 5$	TSC
Toluene	108-88-3*	$\geq 1 - \leq 5$	TSC
Xylene	1330-20-7*	$\geq 0.5 - \leq 1.5$	TSC
Ethylbenzene	100-41-4*	$\geq 0.1 - \leq 1$	TSC
Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9*	≤ 0.1	TSC

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

Alternative CAS Numbers for some regions

Chemical name	Alternative CAS Number(s)
Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-	2682-20-4, 26172-55-4

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

isothiazol-3-one [EC no. 220-239-6] (3:1)

SECTION 4. FIRST AID MEASURES

- | | |
|---|--|
| General advice | : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice. |
| If inhaled | : If inhaled, remove to fresh air.
Get medical attention. |
| In case of skin contact | : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse. |
| In case of eye contact | : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention immediately. |
| If swallowed | : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water. |
| Most important symptoms and effects, both acute and delayed | : May cause an allergic skin reaction.
Causes serious eye damage.
Suspected of damaging the unborn child.
May cause damage to organs through prolonged or repeated exposure.
Corrosive to the respiratory tract. |
| Protection of first-aiders | : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8). |
| Notes to physician | : Treat symptomatically and supportively. |

SECTION 5. FIRE-FIGHTING MEASURES

- | | |
|--------------------------------|--|
| Suitable extinguishing media | : Water spray
Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : None known. |
| Specific hazards during fire | : Vapors may form explosive mixtures with air. |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version 14.0	Revision Date: 06/24/2025	SDS Number: 1346473-00049	Date of last issue: 11/05/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

- | | |
|--|---|
| fighting | Exposure to combustion products may be a hazard to health. |
| Hazardous combustion products | : Hydrogen fluoride
carbonyl fluoride
potentially toxic fluorinated compounds
aerosolized particulates
Carbon oxides
Chromium compounds
Metal oxides
Silicon oxides
Chlorine compounds |
| Specific extinguishing methods | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area. |
| Special protective equipment for fire-fighters | : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8). |
| Environmental precautions | : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained. |
| Methods and materials for containment and cleaning up | : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version 14.0 Revision Date: 06/24/2025 SDS Number: 1346473-00049 Date of last issue: 11/05/2024
Date of first issue: 02/27/2017

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.
- Advice on safe handling : Do not get on skin or clothing.
Do not breathe mist or vapors.
Do not swallow.
Do not get in eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products.
- Conditions for safe storage : Keep in properly labeled containers.
Keep tightly closed.
Store in accordance with the particular national regulations.
- Materials to avoid : No special restrictions on storage with other products.
- Recommended storage temperature : 41 - 77 °F / 5 - 25 °C
- Further information on storage stability : Do not freeze.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrocarbons, C9, aromatics	64742-95-6	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Chromium oxide	1308-38-9	TWA	0.5 mg/m ³ (chromium)	OSHA Z-1

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version
14.0

Revision Date:
06/24/2025

SDS Number:
1346473-00049

Date of last issue: 11/05/2024
Date of first issue: 02/27/2017

		TWA	0.5 mg/m ³ (chromium)	NIOSH REL
Titanium dioxide	13463-67-7	TWA (Respirable particulate matter)	2.5 mg/m ³ (Titanium dioxide)	ACGIH
		TWA (total dust)	15 mg/m ³	OSHA Z-1
Toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m ³	NIOSH REL
		ST	150 ppm 560 mg/m ³	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm (10 minutes)	OSHA Z-2
Xylene	1330-20-7	TWA	100 ppm 435 mg/m ³	OSHA Z-1
		TWA	20 ppm	ACGIH
Ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m ³	NIOSH REL
		ST	125 ppm 545 mg/m ³	NIOSH REL
		TWA	100 ppm 435 mg/m ³	OSHA Z-1

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
		TWA	3 ppm	OSHA Z-2
		C	6 ppm 5 mg/m ³	NIOSH REL
		TWA	3 ppm 2.5 mg/m ³	NIOSH REL
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m ³	NIOSH REL
		ST	5 ppm 15 mg/m ³	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version 14.0 Revision Date: 06/24/2025 SDS Number: 1346473-00049 Date of last issue: 11/05/2024
Date of first issue: 02/27/2017

		TWA	5,000 ppm 9,000 mg/m ³	NIOSH REL
		ST	30,000 ppm 54,000 mg/m ³	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m ³	OSHA Z-1
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m ³	NIOSH REL
		C	200 ppm 229 mg/m ³	NIOSH REL
		TWA	50 ppm 55 mg/m ³	OSHA Z-1

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g creatinine	ACGIH BEI
Xylene	1330-20-7	Methyl-hippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	0.3 g/g cre-atinine	ACGIH BEI
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl gly-oxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	150 mg/g creatinine	ACGIH BEI

Engineering measures : Processing may form hazardous compounds (see section 10).

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version 14.0	Revision Date: 06/24/2025	SDS Number: 1346473-00049	Date of last issue: 11/05/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.
Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
If splashes are likely to occur, wear:
Face-shield

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version 14.0	Revision Date: 06/24/2025	SDS Number: 1346473-00049	Date of last issue: 11/05/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

Appearance	: liquid
Color	: green
Odor	: No data available
Odor Threshold	: No data available
pH	: 8.5 - 11
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: > 212 °F / > 100 °C
Flash point	: 118 °F / 48 °C Method: ISO 2719
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Flammability (liquids)	: Does not sustain combustion.
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: No data available
Relative vapor density	: No data available
Density	: 1.3310 g/cm ³
Solubility(ies) Water solubility	: soluble
Partition coefficient: n-octanol/water	: Not applicable
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity Viscosity, dynamic	: 32 mPa.s

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics	:	
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Vapors may form explosive mixture with air. Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid	:	None known.
Incompatible materials	:	None.

Hazardous decomposition products

Thermal decomposition	:	Hydrogen fluoride Carbonyl difluoride Carbon dioxide Carbon monoxide
-----------------------	---	---

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

|| Not classified based on available information.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 200 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

Hydrocarbons, C9, aromatics:

Acute oral toxicity	: LD50 (Rat, female): 3,492 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 6.193 mg/l Exposure time: 4 h Test atmosphere: vapor Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	: LD50 (Rabbit): > 3,160 mg/kg Assessment: The substance or mixture has no acute dermal toxicity

Chromium oxide:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 5.41 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity

Titanium dioxide:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 425
Acute inhalation toxicity	: LC50 (Rat): > 6.82 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	: Acute toxicity estimate (Rat): > 2,000 mg/kg Method: Expert judgment Assessment: The substance or mixture has no acute dermal toxicity

Sodium lauryl sulfate:

Acute oral toxicity	: LD50 (Rat): > 2,000 mg/kg
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

II

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Acute oral toxicity	: LD50 (Rat): 3,300 mg/kg
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg

Toluene:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 28.1 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg

Xylene:

Acute oral toxicity	: LD50 (Rat): 3,523 mg/kg Method: Directive 67/548/EEC, Annex V, B.1.
Acute inhalation toxicity	: LC50 (Rat): 27.571 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	: LD50 (Rabbit): > 4,200 mg/kg

Ethylbenzene:

Acute oral toxicity	: LD50 (Rat): 3,500 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 17.8 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Acute oral toxicity	: LD50 (Rat): 64 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 0.171 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: Corrosive to the respiratory tract.
Acute dermal toxicity	: LD50 (Rabbit): 87.12 mg/kg

Skin corrosion/irritation

II Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

Components:

Hydrocarbons, C9, aromatics:

|| Assessment : Repeated exposure may cause skin dryness or cracking.

Chromium oxide:

|| Species : Rabbit
|| Method : OECD Test Guideline 404
|| Result : No skin irritation

Titanium dioxide:

|| Species : Rabbit
|| Method : OECD Test Guideline 404
|| Result : No skin irritation

Sodium lauryl sulfate:

|| Species : Rabbit
|| Method : OECD Test Guideline 404
|| Result : Skin irritation
|| Remarks : Based on data from similar materials

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

|| Result : Skin irritation

Toluene:

|| Species : Rabbit
|| Method : Directive 67/548/EEC, Annex V, B.4.
|| Result : Skin irritation

Xylene:

|| Species : Rabbit
|| Result : Skin irritation

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

|| Species : Rabbit
|| Method : OECD Test Guideline 404
|| Result : Corrosive after 1 to 4 hours of exposure

Serious eye damage/eye irritation

|| Causes serious eye damage.

Components:

Hydrocarbons, C9, aromatics:

|| Species : Rabbit
|| Result : No eye irritation

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

Chromium oxide:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405

Titanium dioxide:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405

Sodium lauryl sulfate:

Species	: Rabbit
Result	: Irreversible effects on the eye
Method	: OECD Test Guideline 405
Remarks	: Based on data from similar materials

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Result	: Irreversible effects on the eye
--------	-----------------------------------

Toluene:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405

Xylene:

Species	: Rabbit
Result	: Irritation to eyes, reversing within 21 days

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Result	: Irreversible effects on the eye
Remarks	: Based on skin corrosivity.

Respiratory or skin sensitization

Skin sensitization

|| May cause an allergic skin reaction.

Respiratory sensitization

|| Not classified based on available information.

Components:

Hydrocarbons, C9, aromatics:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

Chromium oxide:

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative
Remarks	: Based on data from similar materials

Titanium dioxide:

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative

Routes of exposure	: Inhalation
Species	: Mouse
Result	: negative

Routes of exposure	: Inhalation
Species	: Humans
Result	: negative

Sodium lauryl sulfate:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative
Remarks	: Based on data from similar materials

Toluene:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: Directive 67/548/EEC, Annex V, B.6.
Result	: negative

Xylene:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Result	: negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: positive

Assessment	: Probability or evidence of high skin sensitization rate in humans
------------	---

Germ cell mutagenicity

Not classified based on available information.

Components:

Hydrocarbons, C9, aromatics:

Genotoxicity in vitro	: Test Type: Chromosome aberration test in vitro Result: negative
Genotoxicity in vivo	: Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Rat Application Route: inhalation (vapor) Result: negative

Chromium oxide:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: negative

Titanium dioxide:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative Test Type: comet assay
-----------------------	--

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

	Method: OPPTS 870.5140 Result: positive
Genotoxicity in vivo	: Test Type: In vivo mammalian alkaline comet assay Species: Rat Application Route: intratracheal Method: OECD Test Guideline 489 Result: negative Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: Ingestion Method: OECD Test Guideline 474 Result: negative Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 475 Result: negative Test Type: Transgenic rodent germ cell gene mutation assay Species: Mouse Application Route: Intravenous injection Method: OECD Test Guideline 488 Result: negative
Germ cell mutagenicity - Assessment	: Weight of evidence does not support classification as a germ cell mutagen.

Sodium lauryl sulfate:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Ingestion Method: OECD Test Guideline 474 Result: negative Remarks: Based on data from similar materials

Toluene:

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Result: negative Test Type: Bacterial reverse mutation assay (AMES) Result: negative
-----------------------	---

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Intraperitoneal injection
Result: negative

Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: inhalation (vapor)
Method: OECD Test Guideline 478
Result: negative

Xylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Skin contact
Result: negative

Ethylbenzene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with mammalian liver cells in vivo
Species: Mouse
Application Route: Inhalation
Method: OECD Test Guideline 486
Result: negative

Carcinogenicity

Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

Components:

Chromium oxide:

Species	: Rat
Application Route	: Ingestion
Exposure time	: 2 Years
Result	: negative

Titanium dioxide:

Species	: Rat
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 2 Years
Result	: negative

Species	: Rat
Application Route	: Ingestion
Exposure time	: 105 weeks
Result	: negative

Species	: Mouse
Application Route	: Ingestion
Exposure time	: 103 weeks
Result	: negative

Carcinogenicity - Assessment	: Weight of evidence does not support classification as a carcinogen
------------------------------	--

Sodium lauryl sulfate:

Species	: Rat
Application Route	: Ingestion
Exposure time	: 2 Years
Result	: negative
Remarks	: Based on data from similar materials

Toluene:

Species	: Rat
Application Route	: inhalation (vapor)
Exposure time	: 103 weeks
Result	: negative

Species	: Mouse
Application Route	: Skin contact
Exposure time	: 24 Months
Result	: negative

Xylene:

Species	: Rat
Application Route	: Ingestion
Exposure time	: 103 weeks
Result	: negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

Ethylbenzene:

Species	:	Rat
Application Route	:	inhalation (vapor)
Exposure time	:	104 weeks
Result	:	positive
Remarks	:	The mechanism or mode of action may not be relevant in humans.

IARC

Group 2B: Possibly carcinogenic to humans	
Titanium dioxide	13463-67-7
Group 2B: Possibly carcinogenic to humans	
Ethylbenzene	100-41-4

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

Hydrocarbons, C9, aromatics:

Effects on fertility	:	Test Type: Three-generation reproduction toxicity study Species: Rat Application Route: inhalation (vapor) Result: negative
Effects on fetal development	:	Test Type: Embryo-fetal development Species: Mouse Application Route: inhalation (vapor) Result: negative

Chromium oxide:

Effects on fetal development	:	Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Result: negative Remarks: Based on data from similar materials
------------------------------	---	--

Titanium dioxide:

Effects on fertility	:	Test Type: One-generation reproduction toxicity study Species: Rat Application Route: Ingestion Method: OECD Test Guideline 443 Result: negative
Effects on fetal development	:	Test Type: Prenatal development toxicity study (teratogenicity) Species: Rat Application Route: Ingestion

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

	Method: OECD Test Guideline 414 Result: negative
Reproductive toxicity - Assessment	: Weight of evidence does not support classification for reproductive toxicity

Sodium lauryl sulfate:

Effects on fetal development	: Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Result: negative Remarks: Based on data from similar materials
------------------------------	--

Toluene:

Effects on fertility	: Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: inhalation (vapor) Method: OECD Test Guideline 416 Result: negative
Effects on fetal development	: Test Type: Embryo-fetal development Species: Rat Application Route: inhalation (vapor) Result: positive
Reproductive toxicity - Assessment	: Some evidence of adverse effects on development, based on animal experiments.

Xylene:

Effects on fertility	: Test Type: One-generation reproduction toxicity study Species: Rat Application Route: inhalation (vapor) Result: negative
Effects on fetal development	: Test Type: Embryo-fetal development Species: Rat Application Route: inhalation (vapor) Result: negative

Ethylbenzene:

Effects on fertility	: Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: inhalation (vapor) Method: OECD Test Guideline 416 Result: negative
Effects on fetal development	: Test Type: Embryo-fetal development Species: Rat Application Route: Inhalation Method: OECD Test Guideline 414 Result: negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

||

STOT-single exposure

|| Corrosive to the respiratory tract.

Components:

Hydrocarbons, C9, aromatics:

|| Assessment : May cause drowsiness or dizziness.

|| Assessment : May cause respiratory irritation.

Titanium dioxide:

|| Routes of exposure : Skin contact
|| Assessment : No significant health effects observed in animals at concentrations of 2000 mg/kg bw or less

|| Routes of exposure : Ingestion
|| Assessment : No significant health effects observed in animals at concentrations of 2000 mg/kg bw or less

|| Routes of exposure : inhalation (dust/mist/fume)
|| Assessment : No significant health effects observed in animals at concentrations of 5.0 mg/l/4h or less

Toluene:

|| Assessment : May cause drowsiness or dizziness.

Xylene:

|| Assessment : May cause respiratory irritation.

STOT-repeated exposure

|| May cause damage to organs (Central nervous system, Auditory system) through prolonged or repeated exposure.

Components:

Titanium dioxide:

|| Routes of exposure : Ingestion
|| Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

|| Routes of exposure : inhalation (dust/mist/fume)
|| Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

|| Routes of exposure : Ingestion
|| Assessment : No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

Toluene:

Routes of exposure	: Inhalation
Target Organs	: Central nervous system
Assessment	: May cause damage to organs through prolonged or repeated exposure.

Xylene:

Routes of exposure	: inhalation (vapor)
Target Organs	: Auditory system
Assessment	: Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Ethylbenzene:

Routes of exposure	: inhalation (vapor)
Target Organs	: Auditory system
Assessment	: Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Repeated dose toxicity

Components:

Hydrocarbons, C9, aromatics:

Species	: Rat, female
NOAEL	: 900 mg/m ³
Application Route	: inhalation (vapor)
Exposure time	: 12 Months
Remarks	: Based on data from similar materials

Chromium oxide:

Species	: Rat
NOAEL	: 2,000 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days

Titanium dioxide:

Species	: Rat, male and female
NOAEL	: 24,000 mg/kg
LOAEL	: > 24,000 mg/kg
Application Route	: Ingestion
Exposure time	: 28 Days
Method	: OECD Test Guideline 407
Remarks	: No significant adverse effects were reported

Species	: Rat, male and female
NOAEL	: 0.01 mg/l
LOAEL	: 0.5 mg/l
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 24 Months
Method	: OECD Test Guideline 453

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

Remarks : No significant adverse effects were reported

Species : Rat, male and female
NOAEL : 962 mg/kg
LOAEL : > 962 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408
Remarks : No significant adverse effects were reported

Sodium lauryl sulfate:

Species : Rat
NOAEL : > 430 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Remarks : Based on data from similar materials

Toluene:

Species : Rat
LOAEL : 1.875 mg/l
Application Route : inhalation (vapor)
Exposure time : 6 Months

Species : Rat
NOAEL : 625 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

Xylene:

Species : Rat
LOAEL : > 0.2 - 1 mg/l
Application Route : inhalation (vapor)
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

Species : Rat
LOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Ethylbenzene:

Species : Rat
LOAEL : 0.868 mg/l
Application Route : inhalation (vapor)
Exposure time : 13 Weeks

Species : Rat
NOAEL : 75 mg/kg
LOAEL : 250 mg/kg
Application Route : Ingestion
Method : OECD Test Guideline 408

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

Aspiration toxicity

|| Not classified based on available information.

Components:

Hydrocarbons, C9, aromatics:

|| The substance or mixture is known to cause human aspiration toxicity hazards or has to be re-garded as if it causes a human aspiration toxicity hazard.

Titanium dioxide:

|| No aspiration toxicity classification

Toluene:

|| The substance or mixture is known to cause human aspiration toxicity hazards or has to be re-garded as if it causes a human aspiration toxicity hazard.

Xylene:

|| The substance or mixture is known to cause human aspiration toxicity hazards or has to be re-garded as if it causes a human aspiration toxicity hazard.

Ethylbenzene:

|| The substance or mixture is known to cause human aspiration toxicity hazards or has to be re-garded as if it causes a human aspiration toxicity hazard.

Experience with human exposure

Components:

Toluene:

|| Inhalation : Target Organs: Central nervous system
Symptoms: Neurological disorders

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Hydrocarbons, C9, aromatics:

Toxicity to fish	:	LL50 (Oncorhynchus mykiss (rainbow trout)): 9.2 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): 3.2 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

Toxicity to algae/aquatic plants	: EL50 (Pseudokirchneriella subcapitata (green algae)): 7.9 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 NOELR (Pseudokirchneriella subcapitata (green algae)): 0.22 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201
Toxicity to microorganisms	: EC50: > 99 mg/l Exposure time: 10 min

Chromium oxide:

Toxicity to fish	: LC50 (Danio rerio (zebra fish)): > 10,000 mg/l Exposure time: 96 h
Toxicity to algae/aquatic plants	: EC50 (Desmodesmus subspicatus (green algae)): > 848.6 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOEC (Danio rerio (zebra fish)): 1,000 mg/l Exposure time: 30 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): > 0.02 mg/l Exposure time: 21 d Remarks: No toxicity at the limit of solubility.
Toxicity to microorganisms	: EC50: > 10,000 mg/l Exposure time: 3 h

Titanium dioxide:

Toxicity to fish	: LC50 (Fish): > 1,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 LC50 (Marine species): > 10,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia sp. (Water flea)): > 1,000 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 EC50 (No species specified): > 1,000 mg/l Exposure time: 48 h Method: OECD Test Guideline 202

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l Exposure time: 72 h Method: ISO 10253 NOEC (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 3 d Method: OECD Test Guideline 201 NOEC (Skeletonema costatum (marine diatom)): 5,600 mg/l Exposure time: 3 d Method: ISO 10253
----------------------------------	---	--

Sodium lauryl sulfate:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 3.6 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 4.7 mg/l Exposure time: 48 h Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): > 20 mg/l Exposure time: 72 h Remarks: Based on data from similar materials EC10 (Desmodesmus subspicatus (green algae)): 5.4 mg/l Exposure time: 72 h Remarks: Based on data from similar materials
Toxicity to fish (Chronic toxicity)	:	NOEC (Pimephales promelas (fathead minnow)): 0.11 mg/l Exposure time: 34 d Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 0.14 mg/l Exposure time: 21 d Remarks: Based on data from similar materials
Toxicity to microorganisms	:	EC10 (Pseudomonas putida): 1,083.85 mg/l Exposure time: 16 h Method: DIN 38 412 Part 8 Remarks: Based on data from similar materials

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 39 mg/l Exposure time: 96 h
------------------	---	---

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 81.2 mg/l
Exposure time: 48 h

Toluene:

Toxicity to fish : LC50 (Oncorhynchus kisutch (coho salmon)): 5.5 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 3.78 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Skeletonema costatum (marine diatom)): 10 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus kisutch (coho salmon)): 1.39 mg/l
Exposure time: 40 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): 0.74 mg/l
Exposure time: 7 d

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 84 mg/l
Exposure time: 24 h

Xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13.5 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): 10 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): > 0.1 - < 1 mg/l
Exposure time: 35 d
Method: OECD Test Guideline 210
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Ethylbenzene:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 4.2 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 1.8 - 2.4 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	: EC50 (Pseudokirchneriella subcapitata (green algae)): 3.6 mg/l Exposure time: 96 h NOEC (Pseudokirchneriella subcapitata (green algae)): 3.4 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Ceriodaphnia dubia (water flea)): 0.96 mg/l Exposure time: 7 d
Toxicity to microorganisms	: EC50 (Nitrosomonas sp.): 96 mg/l Exposure time: 24 h

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 0.19 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 0.16 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	: ErC50 (Skeletonema costatum (marine diatom)): 0.0052 mg/l Exposure time: 48 h NOEC (Skeletonema costatum (marine diatom)): 0.00049 mg/l Exposure time: 48 h
Toxicity to fish (Chronic toxicity)	: NOEC (Pimephales promelas (fathead minnow)): 0.02 mg/l Exposure time: 36 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 0.10 mg/l Exposure time: 21 d

Persistence and degradability

Components:

Hydrocarbons, C9, aromatics:

Biodegradability	: Result: Readily biodegradable. Biodegradation: 78 % Exposure time: 28 d Method: OECD Test Guideline 301F
------------------	---

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

Sodium lauryl sulfate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Biodegradability : Result: Not readily biodegradable.

Toluene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 20 d

Xylene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Ethylbenzene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 - 80 %
Exposure time: 28 d

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 62 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Bioaccumulative potential

Components:

Hydrocarbons, C9, aromatics:

Partition coefficient: n-octanol/water : log Pow: 3.7 - 4.5

Chromium oxide:

Bioaccumulation : Species: Fish
Bioconcentration factor (BCF): 260 - 800

Titanium dioxide:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 352

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version 14.0	Revision Date: 06/24/2025	SDS Number: 1346473-00049	Date of last issue: 11/05/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

||

Sodium lauryl sulfate:

|| Partition coefficient: n-octanol/water : log Pow: <= -2.1

Toluene:

|| Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 90

|| Partition coefficient: n-octanol/water : log Pow: 2.73

Xylene:

|| Partition coefficient: n-octanol/water : log Pow: 3.16
Remarks: Calculation

Ethylbenzene:

|| Partition coefficient: n-octanol/water : log Pow: 3.6

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

|| Partition coefficient: n-octanol/water : log Pow: < 1

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number	:	UN 3082
Proper shipping name	:	Environmentally hazardous substance, liquid, n.o.s. (Xylene)
Class	:	9
Packing group	:	III
Labels	:	CLASS 9
ERG Code	:	171
Marine pollutant	:	no
Remarks	:	THE ABOVE INFORMATION ONLY APPLIES TO PACKAGE SIZES WHERE THE HAZARDOUS SUBSTANCE MEETS THE REPORTABLE QUANTITY.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	8325
Toluene	108-88-3	1000	58129

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Respiratory or skin sensitization
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)
Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version 14.0	Revision Date: 06/24/2025	SDS Number: 1346473-00049	Date of last issue: 11/05/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

Chromium oxide	1308-38-9	>= 1 - < 5 %
Toluene	108-88-3	>= 1 - < 5 %
Xylene	1330-20-7	>= 1 - < 5 %
Ethylbenzene	100-41-4	>= 0.1 - < 1 %
Lead	7439-92-1	< 0.1 %
Mercury	7439-97-6	< 0.1 %

Volatile organic compounds (VOC) content

VOC content: 262.91 g/l
Remarks: less exempt

VOC content: 118.03 g/l
Remarks: as packaged

US State Regulations

Pennsylvania Right To Know

Water	7732-18-5
Fluoropolymer	Trade secret
Hydrocarbons, C9, aromatics	64742-95-6
Chromium oxide	1308-38-9
Titanium dioxide	13463-67-7
Toluene	108-88-3
Xylene	1330-20-7
Ethylbenzene	100-41-4
Butan-1-ol	71-36-3
Aluminum oxide	1344-28-1
Ammonium hydroxide	1336-21-6

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Hydrocarbons, C9, aromatics	64742-95-6
Chromium oxide	1308-38-9
Toluene	108-88-3
Xylene	1330-20-7

California Permissible Exposure Limits for Chemical Contaminants

Hydrocarbons, C9, aromatics	64742-95-6
Chromium oxide	1308-38-9
Titanium dioxide	13463-67-7
Toluene	108-88-3
Xylene	1330-20-7

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard




851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	*	3
FLAMMABILITY		2
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	: USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
ACGIH / C	: Ceiling limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	: Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-2 / TWA	: 8-hour time weighted average
OSHA Z-2 / CEIL	: Acceptable ceiling concentration
OSHA Z-2 / Peak	: Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Sub-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



851G-224 TOPCOAT GREEN

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/24/2025	1346473-00049	Date of first issue: 02/27/2017

stances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 06/24/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8