

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

### SECTION 1. IDENTIFICATION

Product name : 857G-018 ONE COAT BLUE

Product code : D15091177

SDS-Identcode : 130000127885

#### Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street  
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

#### Recommended use of the chemical and restrictions on use

Recommended use : Coatings

Restrictions on use : For industrial use only.  
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin irritation : Category 2

Serious eye damage : Category 1

Skin sensitization : Category 1

#### Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.

#### GHS label elements


# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version 14.0      Revision Date: 06/13/2025      SDS Number: 1347000-00050      Date of last issue: 11/05/2024  
Date of first issue: 02/27/2017

Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage.
Supplemental Hazard Statements	:	Corrosive to the respiratory tract.
Precautionary Statements	:	<b>Prevention:</b> P261 Avoid breathing mist or vapors. P264 Wash skin thoroughly after handling. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves, eye protection and face protection. <b>Response:</b> P302 + P352 IF ON SKIN: Wash with plenty of water. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER. P333 + P313 If skin irritation or rash occurs: Get medical attention. P362 + P364 Take off contaminated clothing and wash it before reuse. <b>Disposal:</b> P501 Dispose of contents and container to an approved waste disposal plant.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture  
Chemical nature : Paint

#### Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 -	25068-38-6*	>= 10 - <= 30	TSC

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version 14.0      Revision Date: 06/13/2025      SDS Number: 1347000-00050      Date of last issue: 11/05/2024  
Date of first issue: 02/27/2017

1200)			
2-Butoxyethanol	111-76-2*	$\geq 3 - \leq 7$	TSC
2-(2-Butoxyethoxy)ethanol	112-34-5*	$\geq 1 - \leq 5$	TSC
2-Dimethylaminoethanol	108-01-0*	$\geq 1 - \leq 5$	TSC
Titanium dioxide	13463-67-7*	$\geq 1 - \leq 5$	TSC

\* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention immediately.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye damage.  
Corrosive to the respiratory tract.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version 14.0	Revision Date: 06/13/2025	SDS Number: 1347000-00050	Date of last issue: 11/05/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Chlorine compounds  
Carbon oxides  
Hydrogen fluoride  
carbonyl fluoride  
potentially toxic fluorinated compounds  
aerosolized particulates  
Nitrogen oxides (NO<sub>x</sub>)  
Metal oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absor-

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not breathe decomposition products.

Do not get on skin or clothing.

Avoid breathing mist or vapors.

Do not swallow.

Do not get in eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment

Keep container tightly closed.

Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.  
Keep tightly closed.  
Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

Recommended storage temperature : 41 - 77 °F / 5 - 25 °C

Further information on storage stability : Do not freeze.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-Butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm	OSHA Z-1

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version 14.0      Revision Date: 06/13/2025      SDS Number: 1347000-00050      Date of last issue: 11/05/2024  
Date of first issue: 02/27/2017

			240 mg/m <sup>3</sup>	
2-(2-Butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH
Titanium dioxide	13463-67-7	TWA (Respirable particulate matter)	2.5 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH
		TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1

### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
		TWA	3 ppm	OSHA Z-2
		C	6 ppm 5 mg/m <sup>3</sup>	NIOSH REL
		TWA	3 ppm 2.5 mg/m <sup>3</sup>	NIOSH REL
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m <sup>3</sup>	NIOSH REL
		ST	5 ppm 15 mg/m <sup>3</sup>	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	NIOSH REL
		ST	30,000 ppm 54,000 mg/m <sup>3</sup>	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	OSHA Z-1
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m <sup>3</sup>	NIOSH REL
		C	200 ppm 229 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm 55 mg/m <sup>3</sup>	OSHA Z-1
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version 14.0      Revision Date: 06/13/2025      SDS Number: 1347000-00050      Date of last issue: 11/05/2024  
Date of first issue: 02/27/2017

		ST	250 ppm 325 mg/m <sup>3</sup>	NIOSH REL
		TWA	200 ppm 260 mg/m <sup>3</sup>	NIOSH REL
		TWA	200 ppm 260 mg/m <sup>3</sup>	OSHA Z-1
Formaldehyde	50-00-0	TWA	0.1 ppm	ACGIH
		STEL	0.3 ppm	ACGIH
		TWA	0.016 ppm	NIOSH REL
		C	0.1 ppm	NIOSH REL
		PEL	0.75 ppm	OSHA CARC
		STEL	2 ppm	OSHA CARC
		TWA	0.016 ppm (Formaldehyde)	NIOSH REL

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
2-Butoxyethanol	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g creatinine	ACGIH BEI

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

### Personal protective equipment

**Respiratory protection** : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

**Hand protection**

**Material** : Chemical-resistant gloves

**Remarks** : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

time is not determined for the product. Change gloves often!  
For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

- Eye protection : Wear the following personal protective equipment:  
Chemical resistant goggles must be worn.  
If splashes are likely to occur, wear:  
Face-shield
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Contaminated work clothing should not be allowed out of the workplace.  
Wash contaminated clothing before re-use.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : blue
- Odor : No data available
- Odor Threshold : No data available
- pH : 7 - 10
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : 212 °F / 100 °C
- Flash point : does not flash
- Evaporation rate : No data available
- Flammability (solid, gas) : Not applicable



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

Flammability (liquids)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Density	:	1.1530 g/cm <sup>3</sup>
Solubility(ies)	:	
Water solubility	:	soluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics	:	
Particle size	:	Not applicable

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid	:	None known.
Incompatible materials	:	None.

#### Hazardous decomposition products

Thermal decomposition	:	Hydrogen fluoride Carbonyl difluoride Carbon dioxide
-----------------------	---	--

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

Carbon monoxide  
Methanol  
Formaldehyde

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

|| Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

|| Acute inhalation toxicity : Acute toxicity estimate: 38.96 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

#### Components:

**Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):**

|| Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 420  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: Based on data from similar materials

|| Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

#### **2-Butoxyethanol:**

|| Acute oral toxicity : LD50 (Guinea pig): 1,200 mg/kg

|| Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Expert judgment

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

Acute dermal toxicity : LD50 (Guinea pig): > 2,000 mg/kg

### 2-(2-Butoxyethoxy)ethanol:

Acute oral toxicity : LD50 (Mouse): 2,410 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 2,764 mg/kg

### 2-Dimethylaminoethanol:

Acute oral toxicity : LD50 (Rat): 1,182 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 5.97 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403

Assessment: Not corrosive to the respiratory tract.

Acute dermal toxicity : LD50 (Rabbit): 1,214 mg/kg

### Titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 425

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : Acute toxicity estimate (Rat): > 2,000 mg/kg  
Method: Expert judgment  
Assessment: The substance or mixture has no acute dermal toxicity

### Skin corrosion/irritation

Causes skin irritation.

### Product:

Result : Skin irritation

### Components:

**Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):**

Result : Skin irritation

### 2-Butoxyethanol:

Species : Rabbit  
Method : Directive 67/548/EEC, Annex V, B.4.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

|| Result : Skin irritation

### 2-(2-Butoxyethoxy)ethanol:

|| Species : Rabbit  
|| Method : OECD Test Guideline 404  
|| Result : Mild skin irritation

### 2-Dimethylaminoethanol:

|| Species : Rabbit  
|| Method : OECD Test Guideline 404  
|| Result : Corrosive after 3 minutes to 1 hour of exposure

### Titanium dioxide:

|| Species : Rabbit  
|| Method : OECD Test Guideline 404  
|| Result : No skin irritation

### Serious eye damage/eye irritation

|| Causes serious eye damage.

### Components:

**Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):**

|| Result : Irritation to eyes, reversing within 21 days

### 2-Butoxyethanol:

|| Species : Rabbit  
|| Result : Irritation to eyes, reversing within 21 days  
|| Method : OECD Test Guideline 405

### 2-(2-Butoxyethoxy)ethanol:

|| Species : Rabbit  
|| Result : Irritation to eyes, reversing within 21 days

### 2-Dimethylaminoethanol:

|| Species : Rabbit  
|| Result : Irreversible effects on the eye

### Titanium dioxide:

|| Species : Rabbit  
|| Result : No eye irritation  
|| Method : OECD Test Guideline 405

### Respiratory or skin sensitization

#### Skin sensitization

|| May cause an allergic skin reaction.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

### Respiratory sensitization

|| Not classified based on available information.

### Components:

**Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):**

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: positive
Remarks	: Based on data from similar materials

|| Assessment : Probability or evidence of skin sensitization in humans

### 2-Butoxyethanol:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

### 2-(2-Butoxyethoxy)ethanol:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: negative

### 2-Dimethylaminoethanol:

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: negative

### Titanium dioxide:

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative

Routes of exposure	: Inhalation
Species	: Mouse
Result	: negative

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

Routes of exposure	: Inhalation
Species	: Humans
Result	: negative

### Germ cell mutagenicity

Not classified based on available information.

### Components:

**Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):**

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative Remarks: Based on data from similar materials
Genotoxicity in vivo	: Test Type: Rodent dominant lethal test (germ cell) (in vivo) Species: Mouse Application Route: Ingestion Result: negative Remarks: Based on data from similar materials

### 2-Butoxyethanol:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative  Test Type: Chromosome aberration test in vitro Result: negative  Test Type: In vitro mammalian cell gene mutation test Result: negative  Test Type: In vitro sister chromatid exchange assay in mammalian cells Result: equivocal
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: Intraperitoneal injection Result: negative  Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative

### 2-(2-Butoxyethoxy)ethanol:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
-----------------------	--

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

Genotoxicity in vivo	:	Test Type: In vitro mammalian cell gene mutation test Result: negative
	:	Test Type: Chromosome aberration test in vitro Result: negative
	:	Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Mouse Application Route: Ingestion Result: negative
	:	

### 2-Dimethylaminoethanol:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
	:	Test Type: In vitro mammalian cell gene mutation test Result: negative
	:	Test Type: In vitro sister chromatid exchange assay in mammalian cells Result: negative
Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative
	:	

### Titanium dioxide:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
	:	Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
	:	Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
	:	Test Type: comet assay Method: OPPTS 870.5140 Result: positive
Genotoxicity in vivo	:	Test Type: In vivo mammalian alkaline comet assay Species: Rat Application Route: intratracheal Method: OECD Test Guideline 489 Result: negative
	:	

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: Ingestion Method: OECD Test Guideline 474 Result: negative
	Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 475 Result: negative
	Test Type: Transgenic rodent germ cell gene mutation assay Species: Mouse Application Route: Intravenous injection Method: OECD Test Guideline 488 Result: negative
Germ cell mutagenicity - Assessment	: Weight of evidence does not support classification as a germ cell mutagen.

### Carcinogenicity

Not classified based on available information.

### Components:

**Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):**

Species	: Rat
Application Route	: Ingestion
Exposure time	: 24 month(s)
Method	: OECD Test Guideline 453
Result	: negative
Remarks	: Based on data from similar materials

### 2-Butoxyethanol:

Species	: Rat
Application Route	: inhalation (vapor)
Exposure time	: 2 Years
Result	: negative

### 2-Dimethylaminoethanol:

Species	: Mouse
Application Route	: Ingestion
Exposure time	: 105 weeks
Result	: negative

### Titanium dioxide:

Species	: Rat
---------	-------



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

Application Route	: inhalation (dust/mist/fume)
Exposure time	: 2 Years
Result	: negative

Species	: Rat
Application Route	: Ingestion
Exposure time	: 105 weeks
Result	: negative

Species	: Mouse
Application Route	: Ingestion
Exposure time	: 103 weeks
Result	: negative

Carcinogenicity - Assessment	: Weight of evidence does not support classification as a carcinogen
------------------------------	--

IARC	Group 2B: Possibly carcinogenic to humans	13463-67-7
	Titanium dioxide	

OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
------	--

NTP	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
-----	--

### Reproductive toxicity

Not classified based on available information.

#### Components:

**Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):**

Effects on fertility	: Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: Ingestion Method: OECD Test Guideline 416 Result: negative Remarks: Based on data from similar materials
----------------------	---

Effects on fetal development	: Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Method: OECD Test Guideline 414 Result: negative Remarks: Based on data from similar materials
------------------------------	---

#### **2-Butoxyethanol:**

Effects on fertility	: Test Type: Two-generation reproduction toxicity study Species: Mouse Application Route: Ingestion Result: negative
----------------------	---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### 2-(2-Butoxyethoxy)ethanol:

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 415  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

### 2-Dimethylaminoethanol:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 421  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 414  
Result: negative

Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Method: OPPTS 870.3700  
Result: negative

### Titanium dioxide:

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 443  
Result: negative

Effects on fetal development : Test Type: Prenatal development toxicity study (teratogenicity)  
Species: Rat  
Application Route: Ingestion

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version 14.0	Revision Date: 06/13/2025	SDS Number: 1347000-00050	Date of last issue: 11/05/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

Reproductive toxicity - Assessment	:	Method: OECD Test Guideline 414 Result: negative Weight of evidence does not support classification for reproductive toxicity
------------------------------------	---	---

### STOT-single exposure

Corrosive to the respiratory tract.

#### Components:

##### 2-Dimethylaminoethanol:

Assessment : May cause respiratory irritation.

##### Titanium dioxide:

Routes of exposure	:	Skin contact
Assessment	:	No significant health effects observed in animals at concentrations of 2000 mg/kg bw or less
Routes of exposure	:	Ingestion
Assessment	:	No significant health effects observed in animals at concentrations of 2000 mg/kg bw or less
Routes of exposure	:	inhalation (dust/mist/fume)
Assessment	:	No significant health effects observed in animals at concentrations of 5.0 mg/l/4h or less

### STOT-repeated exposure

Not classified based on available information.

#### Components:

##### Titanium dioxide:

Routes of exposure	:	Ingestion
Assessment	:	No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.
Routes of exposure	:	inhalation (dust/mist/fume)
Assessment	:	No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.
Routes of exposure	:	Ingestion
Assessment	:	No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

### Repeated dose toxicity

#### Components:

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):

Species : Rat

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

NOAEL	: 50 mg/kg
LOAEL	: 250 mg/kg
Application Route	: Ingestion
Exposure time	: 14 Weeks
Method	: OECD Test Guideline 408
Remarks	: Based on data from similar materials

### 2-(2-Butoxyethoxy)ethanol:

Species	: Rat
NOAEL	: 250 mg/kg
LOAEL	: 1,000 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days
Method	: OECD Test Guideline 408

Species	: Rat
NOAEL	: $\geq 0.094$ mg/l
Application Route	: inhalation (vapor)
Exposure time	: 90 Days
Method	: OECD Test Guideline 413

Species	: Rat
NOAEL	: $\geq 2,000$ mg/kg
Application Route	: Skin contact
Exposure time	: 90 Days

### Titanium dioxide:

Species	: Rat, male and female
NOAEL	: 24,000 mg/kg
LOAEL	: $> 24,000$ mg/kg
Application Route	: Ingestion
Exposure time	: 28 Days
Method	: OECD Test Guideline 407
Remarks	: No significant adverse effects were reported

Species	: Rat, male and female
NOAEL	: 0.01 mg/l
LOAEL	: 0.5 mg/l
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 24 Months
Method	: OECD Test Guideline 453
Remarks	: No significant adverse effects were reported

Species	: Rat, male and female
NOAEL	: 962 mg/kg
LOAEL	: $> 962$ mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days
Method	: OECD Test Guideline 408
Remarks	: No significant adverse effects were reported

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

### Aspiration toxicity

|| Not classified based on available information.

### Components:

#### Titanium dioxide:

|| No aspiration toxicity classification

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### 2-Butoxyethanol:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 1,464 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,800 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): 1,840 mg/l Exposure time: 72 h Method: OECD Test Guideline 201  EC10 (Pseudokirchneriella subcapitata (green algae)): 679 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	:	NOEC (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 21 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	EC10 (Daphnia magna (Water flea)): 134 mg/l Exposure time: 21 d Method: OECD Test Guideline 211

##### 2-(2-Butoxyethoxy)ethanol:

Toxicity to fish	:	LC50 (Lepomis macrochirus (Bluegill sunfish)): 1,300 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 201

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

NOEC (Desmodesmus subspicatus (green algae)):  $\geq 100$  mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10:  $> 1,995$  mg/l  
Exposure time: 30 min

### 2-Dimethylaminoethanol:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 146.63 mg/l  
Exposure time: 96 h  
Test substance: Neutralized product  
Method: DIN 38412

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 98.37 mg/l  
Exposure time: 48 h  
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 66.08 mg/l  
Exposure time: 72 h  
  
EC10 (Desmodesmus subspicatus (green algae)): 24.49 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : EC10 (Pseudomonas putida): 273.8 mg/l  
Exposure time: 17 h  
Method: DIN 38 412 Part 8

### Titanium dioxide:

Toxicity to fish : LC50 (Fish):  $> 1,000$  mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

LC50 (Marine species):  $> 10,000$  mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia sp. (Water flea)):  $> 1,000$  mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

EC50 (No species specified):  $> 1,000$  mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)):  $> 100$  mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

EC50 (Skeletonema costatum (marine diatom)):  $> 10,000$  mg/l  
Exposure time: 72 h

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version 14.0	Revision Date: 06/13/2025	SDS Number: 1347000-00050	Date of last issue: 11/05/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

Method: ISO 10253

NOEC (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l

Exposure time: 3 d

Method: OECD Test Guideline 201

NOEC (Skeletonema costatum (marine diatom)): 5,600 mg/l

Exposure time: 3 d

Method: ISO 10253

### Persistence and degradability

#### Components:

**Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200):**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

#### **2-Butoxyethanol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 90.4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

#### **2-(2-Butoxyethoxy)ethanol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 85 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301C

#### **2-Dimethylaminoethanol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 60.5 %  
Exposure time: 14 d  
Method: OECD Test Guideline 301C

### Bioaccumulative potential

#### Components:

#### **2-Butoxyethanol:**

Partition coefficient: n-octanol/water : log Pow: 0.81

#### **2-(2-Butoxyethoxy)ethanol:**

Partition coefficient: n-octanol/water : log Pow: 1

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

|| octanol/water

### 2-Dimethylaminoethanol:

|| Partition coefficient: n- : log Pow: -0.55  
|| octanol/water

### Titanium dioxide:

|| Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)  
|| Bioconcentration factor (BCF): 352

### Mobility in soil

No data available

### Other adverse effects

No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.  
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste  
handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to IMO instruments

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

Not regulated as a dangerous good

### Special precautions for user

Not applicable



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

### SECTION 15. REGULATORY INFORMATION

#### CERCLA Reportable Quantity

|| Listed substances in the product are at low enough levels to not be expected to exceed the RQ

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

|| **SARA 311/312 Hazards** : Respiratory or skin sensitization  
Skin corrosion or irritation  
Serious eye damage or eye irritation

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

2-Butoxyethanol	111-76-2	>= 5 - < 10 %
2-(2-Butoxyethoxy)ethanol	112-34-5	>= 1 - < 5 %
Lead	7439-92-1	< 0.1 %

#### Volatile organic compounds (VOC) content

VOC content: 303.77 g/l  
Remarks: less exempt

VOC content: 125.7 g/l  
Remarks: as packaged

#### US State Regulations

##### Pennsylvania Right To Know

Water	7732-18-5
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - 1200)	25068-38-6
2-Butoxyethanol	111-76-2
Fluoropolymer	Trade secret
2-(2-Butoxyethoxy)ethanol	112-34-5
2-Dimethylaminoethanol	108-01-0
Titanium dioxide	13463-67-7
Resin acids and Rosin acids, zinc salts	9010-69-9
Aluminum oxide	1344-28-1
Formaldehyde	50-00-0

##### California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

Lead, which is/are known to the State of California to cause birth defects or other reproductive harm.  
For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### California List of Hazardous Substances

2-Butoxyethanol	111-76-2
-----------------	----------


### California Permissible Exposure Limits for Chemical Contaminants

2-Butoxyethanol	111-76-2
Titanium dioxide	13463-67-7

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA 704:



#### HMIS® IV:

HEALTH	/	3
FLAMMABILITY		0
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

### Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA CARC	: OSHA Specifically Regulated Chemicals/Carcinogens
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	: USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
ACGIH / C	: Ceiling limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

NIOSH REL / C	: Ceiling value not be exceeded at any time.
OSHA CARC / PEL	: Permissible exposure limit (PEL)
OSHA CARC / STEL	: Excursion limit
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-2 / TWA	: 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 06/13/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS mate-

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-018 ONE COAT BLUE

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
14.0	06/13/2025	1347000-00050	Date of first issue: 02/27/2017

---

Material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8