

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 11/06/2024  |
| 16.0    | 05/26/2025     | 1347488-00051 | Date of first issue: 02/27/2017 |

### SECTION 1. IDENTIFICATION

Product name : 958G-303 ONE COAT BLACK

Product code : D15445480

SDS-Identcode : 130000127975

#### Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street  
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

#### Recommended use of the chemical and restrictions on use

Recommended use : Coatings

Restrictions on use : For industrial use only.  
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

|                                                     |               |
|-----------------------------------------------------|---------------|
| Flammable liquids                                   | : Category 3  |
| Skin irritation                                     | : Category 2  |
| Eye irritation                                      | : Category 2A |
| Carcinogenicity                                     | : Category 2  |
| Reproductive toxicity                               | : Category 1B |
| Specific target organ toxicity<br>- single exposure | : Category 3  |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 11/06/2024  |
| 16.0    | 05/26/2025     | 1347488-00051 | Date of first issue: 02/27/2017 |

### Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.  
Vapors may form explosive mixture with air.

### GHS label elements

|                          |   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|--------------------------|---|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hazard pictograms        | : |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Signal Word              | : | Danger                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Hazard Statements        | : | H226 Flammable liquid and vapor.<br>H315 Causes skin irritation.<br>H319 Causes serious eye irritation.<br>H335 May cause respiratory irritation.<br>H336 May cause drowsiness or dizziness.<br>H351 Suspected of causing cancer.<br>H360D May damage the unborn child.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Precautionary Statements | : | <b>Prevention:</b><br>P201 Obtain special instructions before use.<br>P202 Do not handle until all safety precautions have been read and understood.<br>P210 Keep away from heat, sparks, open flame and hot surfaces. No smoking.<br>P233 Keep container tightly closed.<br>P241 Use explosion-proof electrical, ventilating and lighting equipment.<br>P242 Use non-sparking tools.<br>P243 Take action to prevent static discharges.<br>P261 Avoid breathing mist or vapors.<br>P264 Wash skin thoroughly after handling.<br>P271 Use only outdoors or in a well-ventilated area.<br>P280 Wear protective gloves, protective clothing, eye protection and face protection.<br><br><b>Response:</b><br>P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.<br>P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.<br>P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.<br>P308 + P313 IF exposed or concerned: Get medical attention.<br>P332 + P313 If skin irritation occurs: Get medical attention.<br>P337 + P313 If eye irritation persists: Get medical attention.<br><br><b>Storage:</b><br>P403 + P235 Store in a well-ventilated place. Keep cool. |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

Version 16.0      Revision Date: 05/26/2025      SDS Number: 1347488-00051      Date of last issue: 11/06/2024  
Date of first issue: 02/27/2017

P405 Store locked up.

### Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Paint

#### Components

| Chemical name               | CAS No./Unique ID | Concentration (% w/w) | Trade secret |
|-----------------------------|-------------------|-----------------------|--------------|
| N-Methyl-2-pyrrolidone      | 872-50-4*         | $\geq 30 - \leq 60$   | TSC          |
| Isobutyl methyl ketone      | 108-10-1*         | $\geq 10 - \leq 30$   | TSC          |
| Hydrocarbons, C9, aromatics | 64742-95-6*       | $\geq 7 - \leq 13$    | TSC          |
| Carbon black                | 1333-86-4*        | $\geq 1 - \leq 5$     | TSC          |

\* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.  
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.  
If vomiting occurs have person lean forward.  
Call a physician or poison control center immediately.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|                 |                              |                              |                                                                   |
|-----------------|------------------------------|------------------------------|-------------------------------------------------------------------|
| Version<br>16.0 | Revision Date:<br>05/26/2025 | SDS Number:<br>1347488-00051 | Date of last issue: 11/06/2024<br>Date of first issue: 02/27/2017 |
|-----------------|------------------------------|------------------------------|-------------------------------------------------------------------|

Rinse mouth thoroughly with water.  
Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
Suspected of causing cancer.  
May damage the unborn child.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.  
Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Nitrogen oxides (NO<sub>x</sub>)  
Carbon oxides  
Hydrogen fluoride  
carbonyl fluoride  
potentially toxic fluorinated compounds  
aerosolized particulates

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 11/06/2024  |
| 16.0    | 05/26/2025     | 1347488-00051 | Date of first issue: 02/27/2017 |

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.
- Advice on safe handling : Do not get on skin or clothing.  
Avoid breathing mist or vapors.  
Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment.  
Non-sparking tools should be used.  
Keep container tightly closed.  
Already sensitized individuals, and those susceptible

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

Version 16.0      Revision Date: 05/26/2025      SDS Number: 1347488-00051      Date of last issue: 11/06/2024  
Date of first issue: 02/27/2017

to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitizers.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labeled containers.  
Store locked up.  
Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Self-reactive substances and mixtures  
Organic peroxides  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives  
Gases  
Very acutely toxic substances and mixtures

Recommended storage temperature : 41 - 77 °F / 5 - 25 °C

Further information on storage stability : Do not freeze.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

| Components             | CAS-No.  | Value type<br>(Form of exposure) | Control parameters / Permissible concentration | Basis     |
|------------------------|----------|----------------------------------|------------------------------------------------|-----------|
| N-Methyl-2-pyrrolidone | 872-50-4 | TWA                              | 15 ppm<br>60 mg/m <sup>3</sup>                 | US WEEL   |
|                        |          | STEL                             | 30 ppm<br>120 mg/m <sup>3</sup>                | US WEEL   |
| Isobutyl methyl ketone | 108-10-1 | TWA                              | 20 ppm                                         | ACGIH     |
|                        |          | STEL                             | 75 ppm                                         | ACGIH     |
|                        |          | TWA                              | 50 ppm<br>205 mg/m <sup>3</sup>                | NIOSH REL |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

Version 16.0      Revision Date: 05/26/2025      SDS Number: 1347488-00051      Date of last issue: 11/06/2024  
Date of first issue: 02/27/2017

|                             |            |                                    |                                  |           |
|-----------------------------|------------|------------------------------------|----------------------------------|-----------|
|                             |            | ST                                 | 75 ppm<br>300 mg/m <sup>3</sup>  | NIOSH REL |
|                             |            | TWA                                | 100 ppm<br>410 mg/m <sup>3</sup> | OSHA Z-1  |
| Hydrocarbons, C9, aromatics | 64742-95-6 | TWA (Mist)                         | 5 mg/m <sup>3</sup>              | OSHA Z-1  |
|                             |            | TWA (Inhalable particulate matter) | 5 mg/m <sup>3</sup>              | ACGIH     |
|                             |            | TWA (Mist)                         | 5 mg/m <sup>3</sup>              | NIOSH REL |
|                             |            | ST (Mist)                          | 10 mg/m <sup>3</sup>             | NIOSH REL |
| Carbon black                | 1333-86-4  | TWA (Inhalable particulate matter) | 3 mg/m <sup>3</sup>              | ACGIH     |
|                             |            | TWA                                | 3.5 mg/m <sup>3</sup>            | NIOSH REL |
|                             |            | TWA                                | 3.5 mg/m <sup>3</sup>            | OSHA Z-1  |

### Occupational exposure limits of decomposition products

| Components          | CAS-No.   | Value type<br>(Form of exposure) | Control parameters / Permissible concentration | Basis     |
|---------------------|-----------|----------------------------------|------------------------------------------------|-----------|
| Hydrogen fluoride   | 7664-39-3 | TWA                              | 0.5 ppm<br>(Fluorine)                          | ACGIH     |
|                     |           | C                                | 2 ppm<br>(Fluorine)                            | ACGIH     |
|                     |           | TWA                              | 3 ppm                                          | OSHA Z-2  |
|                     |           | C                                | 6 ppm<br>5 mg/m <sup>3</sup>                   | NIOSH REL |
|                     |           | TWA                              | 3 ppm<br>2.5 mg/m <sup>3</sup>                 | NIOSH REL |
| Carbonyl difluoride | 353-50-4  | TWA                              | 2 ppm                                          | ACGIH     |
|                     |           | STEL                             | 5 ppm                                          | ACGIH     |
|                     |           | TWA                              | 2 ppm<br>5 mg/m <sup>3</sup>                   | NIOSH REL |
|                     |           | ST                               | 5 ppm<br>15 mg/m <sup>3</sup>                  | NIOSH REL |
| Carbon dioxide      | 124-38-9  | TWA                              | 5,000 ppm                                      | ACGIH     |
|                     |           | STEL                             | 30,000 ppm                                     | ACGIH     |
|                     |           | TWA                              | 5,000 ppm<br>9,000 mg/m <sup>3</sup>           | NIOSH REL |
|                     |           | ST                               | 30,000 ppm<br>54,000 mg/m <sup>3</sup>         | NIOSH REL |
|                     |           | TWA                              | 5,000 ppm<br>9,000 mg/m <sup>3</sup>           | OSHA Z-1  |
| Carbon monoxide     | 630-08-0  | TWA                              | 25 ppm                                         | ACGIH     |
|                     |           | TWA                              | 35 ppm<br>40 mg/m <sup>3</sup>                 | NIOSH REL |
|                     |           | C                                | 200 ppm<br>229 mg/m <sup>3</sup>               | NIOSH REL |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

Version 16.0      Revision Date: 05/26/2025      SDS Number: 1347488-00051      Date of last issue: 11/06/2024  
Date of first issue: 02/27/2017

|                     |         |      |                                  |           |
|---------------------|---------|------|----------------------------------|-----------|
|                     |         | TWA  | 50 ppm<br>55 mg/m <sup>3</sup>   | OSHA Z-1  |
| Formaldehyde        | 50-00-0 | TWA  | 0.1 ppm                          | ACGIH     |
|                     |         | STEL | 0.3 ppm                          | ACGIH     |
|                     |         | TWA  | 0.016 ppm                        | NIOSH REL |
|                     |         | C    | 0.1 ppm                          | NIOSH REL |
|                     |         | PEL  | 0.75 ppm                         | OSHA CARC |
|                     |         | STEL | 2 ppm                            | OSHA CARC |
|                     |         | TWA  | 0.016 ppm<br>(Formaldehyde)      | NIOSH REL |
|                     |         | C    | 0.1 ppm<br>(Formaldehyde)        | NIOSH REL |
| Butan-1-ol          | 71-36-3 | TWA  | 20 ppm                           | ACGIH     |
|                     |         | C    | 50 ppm<br>150 mg/m <sup>3</sup>  | NIOSH REL |
|                     |         | TWA  | 100 ppm<br>300 mg/m <sup>3</sup> | OSHA Z-1  |
| 2-Methyl-1-propanol | 78-83-1 | TWA  | 50 ppm                           | ACGIH     |
|                     |         | TWA  | 50 ppm<br>150 mg/m <sup>3</sup>  | NIOSH REL |
|                     |         | TWA  | 100 ppm<br>300 mg/m <sup>3</sup> | OSHA Z-1  |

### Biological occupational exposure limits

| Components             | CAS-No.  | Control parameters               | Biological specimen | Sam-pling time                                           | Permissible concentra-tion | Basis     |
|------------------------|----------|----------------------------------|---------------------|----------------------------------------------------------|----------------------------|-----------|
| N-Methyl-2-pyrrolidone | 872-50-4 | 5-Hydroxy-N-methyl-2-pyrrolidone | Urine               | End of shift (As soon as possible after exposure ceases) | 100 mg/l                   | ACGIH BEI |
| Isobutyl methyl ketone | 108-10-1 | methyl isobutyl ketone           | Urine               | End of shift (As soon as possible after exposure ceases) | 1 mg/l                     | ACGIH BEI |

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 11/06/2024  |
| 16.0    | 05/26/2025     | 1347488-00051 | Date of first issue: 02/27/2017 |

### Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

### Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : black

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 11/06/2024  |
| 16.0    | 05/26/2025     | 1347488-00051 | Date of first issue: 02/27/2017 |

---

Odor : No data available

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : > 212 °F / > 100 °C

Flash point : 109 °F / 43 °C  
Method: ISO 2719

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Sustains combustion

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : 1.0660 g/cm<sup>3</sup>

Solubility(ies)  
Water solubility : No data available

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : 98 mPa.s

Viscosity, kinematic : No data available

Explosive properties : Not explosive

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 11/06/2024  |
| 16.0    | 05/26/2025     | 1347488-00051 | Date of first issue: 02/27/2017 |

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics  
Particle size : Not applicable

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Flammable liquid and vapor.  
Vapors may form explosive mixture with air.  
Can react with strong oxidizing agents.  
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

#### Hazardous decomposition products

Thermal decomposition : Hydrogen fluoride  
Carbonyl difluoride  
Carbon dioxide  
Carbon monoxide  
Formaldehyde  
Butan-1-ol  
2-Methyl-1-propanol

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: 4,672 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 65.96 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 11/06/2024  |
| 16.0    | 05/26/2025     | 1347488-00051 | Date of first issue: 02/27/2017 |

II

### Components:

#### **N-Methyl-2-pyrrolidone:**

|                           |                                                                                                                                                                           |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Acute oral toxicity       | : LD50 (Rat): 4,150 mg/kg<br>Method: OECD Test Guideline 401<br>Remarks: The test was conducted equivalent or similar to guideline                                        |
| Acute inhalation toxicity | : LC50 (Rat): > 5.1 mg/l<br>Exposure time: 4 h<br>Test atmosphere: dust/mist<br>Method: OECD Test Guideline 403<br>Remarks: The test was conducted according to guideline |
| Acute dermal toxicity     | : LD50 (Rat): > 5,000 mg/kg<br>Method: OECD Test Guideline 402<br>Remarks: The test was conducted equivalent or similar to guideline                                      |

#### **Isobutyl methyl ketone:**

|                           |                                                                                                                                     |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Acute oral toxicity       | : LD50 (Rat): 2,080 mg/kg                                                                                                           |
| Acute inhalation toxicity | : Acute toxicity estimate: 11 mg/l<br>Exposure time: 4 h<br>Test atmosphere: vapor<br>Method: Expert judgment                       |
| Acute dermal toxicity     | : LD50 (Rat): > 2,000 mg/kg<br>Method: OECD Test Guideline 402<br>Assessment: The substance or mixture has no acute dermal toxicity |

#### **Hydrocarbons, C9, aromatics:**

|                           |                                                                                                                                                     |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Acute oral toxicity       | : LD50 (Rat, female): 3,492 mg/kg                                                                                                                   |
| Acute inhalation toxicity | : LC50 (Rat): > 6.193 mg/l<br>Exposure time: 4 h<br>Test atmosphere: vapor<br>Assessment: The substance or mixture has no acute inhalation toxicity |
| Acute dermal toxicity     | : LD50 (Rabbit): > 3,160 mg/kg<br>Assessment: The substance or mixture has no acute dermal toxicity                                                 |

#### **Carbon black:**

|                     |                              |
|---------------------|------------------------------|
| Acute oral toxicity | : LD50 (Rat): > 10,000 mg/kg |
|---------------------|------------------------------|

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 11/06/2024  |
| 16.0    | 05/26/2025     | 1347488-00051 | Date of first issue: 02/27/2017 |

---

### Skin corrosion/irritation

Causes skin irritation.

#### Components:

##### N-Methyl-2-pyrrolidone:

|         |                                                             |
|---------|-------------------------------------------------------------|
| Species | : Rabbit                                                    |
| Method  | : OECD Test Guideline 404                                   |
| Result  | : Skin irritation                                           |
| Remarks | : The test was conducted equivalent or similar to guideline |

##### Isobutyl methyl ketone:

|         |                           |
|---------|---------------------------|
| Species | : Rabbit                  |
| Method  | : OECD Test Guideline 404 |
| Result  | : No skin irritation      |

|            |                                                         |
|------------|---------------------------------------------------------|
| Assessment | : Repeated exposure may cause skin dryness or cracking. |
|------------|---------------------------------------------------------|

##### Hydrocarbons, C9, aromatics:

|            |                                                         |
|------------|---------------------------------------------------------|
| Assessment | : Repeated exposure may cause skin dryness or cracking. |
|------------|---------------------------------------------------------|

##### Carbon black:

|         |                      |
|---------|----------------------|
| Species | : Rabbit             |
| Result  | : No skin irritation |

### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Components:

##### N-Methyl-2-pyrrolidone:

|         |                                                             |
|---------|-------------------------------------------------------------|
| Species | : Rabbit                                                    |
| Result  | : Irritation to eyes, reversing within 21 days              |
| Method  | : OECD Test Guideline 405                                   |
| Remarks | : The test was conducted equivalent or similar to guideline |

##### Isobutyl methyl ketone:

|         |                                                |
|---------|------------------------------------------------|
| Species | : Human                                        |
| Result  | : Irritation to eyes, reversing within 21 days |

##### Hydrocarbons, C9, aromatics:

|         |                     |
|---------|---------------------|
| Species | : Rabbit            |
| Result  | : No eye irritation |

##### Carbon black:

|         |                           |
|---------|---------------------------|
| Species | : Rabbit                  |
| Result  | : No eye irritation       |
| Method  | : OECD Test Guideline 405 |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 11/06/2024  |
| 16.0    | 05/26/2025     | 1347488-00051 | Date of first issue: 02/27/2017 |

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

#### Components:

##### N-Methyl-2-pyrrolidone:

|                    |                                        |
|--------------------|----------------------------------------|
| Test Type          | : Local lymph node assay (LLNA)        |
| Routes of exposure | : Skin contact                         |
| Species            | : Mouse                                |
| Method             | : OECD Test Guideline 429              |
| Result             | : negative                             |
| Remarks            | : Based on data from similar materials |

##### Isobutyl methyl ketone:

|                    |                           |
|--------------------|---------------------------|
| Test Type          | : Maximization Test       |
| Routes of exposure | : Skin contact            |
| Species            | : Guinea pig              |
| Method             | : OECD Test Guideline 406 |
| Result             | : negative                |

##### Hydrocarbons, C9, aromatics:

|                    |                           |
|--------------------|---------------------------|
| Test Type          | : Maximization Test       |
| Routes of exposure | : Skin contact            |
| Species            | : Guinea pig              |
| Method             | : OECD Test Guideline 406 |
| Result             | : negative                |

##### Carbon black:

|                    |                           |
|--------------------|---------------------------|
| Test Type          | : Buehler Test            |
| Routes of exposure | : Skin contact            |
| Species            | : Guinea pig              |
| Method             | : OECD Test Guideline 406 |
| Result             | : negative                |

### Germ cell mutagenicity

Not classified based on available information.

#### Components:

##### N-Methyl-2-pyrrolidone:

|                       |                                                                                                                                                                       |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Genotoxicity in vitro | : Test Type: Bacterial reverse mutation assay (AMES)<br>Method: OECD Test Guideline 471<br>Result: negative<br>Remarks: The test was conducted according to guideline |
|                       | Test Type: In vitro mammalian cell gene mutation test<br>Method: OECD Test Guideline 476                                                                              |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|                 |                              |                              |                                                                   |
|-----------------|------------------------------|------------------------------|-------------------------------------------------------------------|
| Version<br>16.0 | Revision Date:<br>05/26/2025 | SDS Number:<br>1347488-00051 | Date of last issue: 11/06/2024<br>Date of first issue: 02/27/2017 |
|-----------------|------------------------------|------------------------------|-------------------------------------------------------------------|

|                      |   |                                                                                                                                                                                                                                                   |
|----------------------|---|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                      |   | Result: negative<br>Remarks: The test was conducted according to guideline                                                                                                                                                                        |
|                      |   | Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)<br>Method: OECD Test Guideline 482<br>Result: negative<br>Remarks: The test was conducted equivalent or similar to guideline                            |
| Genotoxicity in vivo | : | Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)<br>Species: Mouse<br>Application Route: Ingestion<br>Method: OECD Test Guideline 474<br>Result: negative<br>Remarks: The test was conducted according to guideline |

### Isobutyl methyl ketone:

|                       |   |                                                                                                                                                                                                         |
|-----------------------|---|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Genotoxicity in vitro | : | Test Type: Bacterial reverse mutation assay (AMES)<br>Result: negative                                                                                                                                  |
|                       |   | Test Type: In vitro mammalian cell gene mutation test<br>Result: equivocal                                                                                                                              |
|                       |   | Test Type: Chromosome aberration test in vitro<br>Result: negative                                                                                                                                      |
| Genotoxicity in vivo  | : | Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)<br>Species: Mouse<br>Application Route: Intraperitoneal injection<br>Method: OECD Test Guideline 474<br>Result: negative |

### Hydrocarbons, C9, aromatics:

|                       |   |                                                                                                                                                                             |
|-----------------------|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Genotoxicity in vitro | : | Test Type: Chromosome aberration test in vitro<br>Result: negative                                                                                                          |
| Genotoxicity in vivo  | : | Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)<br>Species: Rat<br>Application Route: inhalation (vapor)<br>Result: negative |

### Carbon black:

|                       |   |                                                                                                           |
|-----------------------|---|-----------------------------------------------------------------------------------------------------------|
| Genotoxicity in vitro | : | Test Type: Bacterial reverse mutation assay (AMES)<br>Method: OECD Test Guideline 471<br>Result: negative |
|                       |   | Test Type: In vitro mammalian cell gene mutation test<br>Method: OECD Test Guideline 476                  |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 11/06/2024  |
| 16.0    | 05/26/2025     | 1347488-00051 | Date of first issue: 02/27/2017 |

|                      |                                                                                    |
|----------------------|------------------------------------------------------------------------------------|
|                      | Result: negative                                                                   |
|                      | Test Type: In vitro sister chromatid exchange assay in mammalian cells             |
|                      | Method: OECD Test Guideline 479                                                    |
|                      | Result: negative                                                                   |
|                      | Test Type: in vitro micronucleus test                                              |
|                      | Method: OECD Test Guideline 487                                                    |
|                      | Result: negative                                                                   |
| Genotoxicity in vivo | : Test Type: Sex-linked recessive lethal test in Drosophila melanogaster (in vivo) |
|                      | Species: Drosophila melanogaster (vinegar fly)                                     |
|                      | Application Route: Ingestion                                                       |
|                      | Method: OECD Test Guideline 477                                                    |
|                      | Result: negative                                                                   |

### Carcinogenicity

Suspected of causing cancer.

### Components:

#### N-Methyl-2-pyrrolidone:

|                   |                                                 |
|-------------------|-------------------------------------------------|
| Species           | : Rat                                           |
| Application Route | : Ingestion                                     |
| Exposure time     | : 2 Years                                       |
| Method            | : OECD Test Guideline 451                       |
| Result            | : negative                                      |
| Remarks           | : The test was conducted according to guideline |

|                   |                                                             |
|-------------------|-------------------------------------------------------------|
| Species           | : Rat                                                       |
| Application Route | : Inhalation                                                |
| Exposure time     | : 2 Years                                                   |
| Method            | : OECD Test Guideline 453                                   |
| Result            | : negative                                                  |
| Remarks           | : The test was conducted equivalent or similar to guideline |

#### Isobutyl methyl ketone:

|                   |                           |
|-------------------|---------------------------|
| Species           | : Rat                     |
| Application Route | : inhalation (vapor)      |
| Exposure time     | : 2 Years                 |
| Method            | : OECD Test Guideline 451 |
| Result            | : positive                |

|                   |                           |
|-------------------|---------------------------|
| Species           | : Mouse                   |
| Application Route | : inhalation (vapor)      |
| Exposure time     | : 2 Years                 |
| Method            | : OECD Test Guideline 451 |
| Result            | : positive                |

|                              |                                                         |
|------------------------------|---------------------------------------------------------|
| Carcinogenicity - Assessment | : Limited evidence of carcinogenicity in animal studies |
|------------------------------|---------------------------------------------------------|

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 11/06/2024  |
| 16.0    | 05/26/2025     | 1347488-00051 | Date of first issue: 02/27/2017 |

II

### Carbon black:

|                   |              |
|-------------------|--------------|
| Species           | : Rat        |
| Application Route | : Inhalation |
| Exposure time     | : 24 Months  |
| Result            | : positive   |

|                   |             |
|-------------------|-------------|
| Species           | : Rat       |
| Application Route | : Ingestion |
| Exposure time     | : 2 Years   |
| Result            | : negative  |

|                              |                                                                      |
|------------------------------|----------------------------------------------------------------------|
| Carcinogenicity - Assessment | : Weight of evidence does not support classification as a carcinogen |
|------------------------------|----------------------------------------------------------------------|

|      |                                           |          |
|------|-------------------------------------------|----------|
| IARC | Group 2B: Possibly carcinogenic to humans |          |
|      | Isobutyl methyl ketone                    | 108-10-1 |

|      |                                                                                                                          |
|------|--------------------------------------------------------------------------------------------------------------------------|
| OSHA | No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens. |
|------|--------------------------------------------------------------------------------------------------------------------------|

|     |                                                                                                                                          |
|-----|------------------------------------------------------------------------------------------------------------------------------------------|
| NTP | No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. |
|-----|------------------------------------------------------------------------------------------------------------------------------------------|

### Reproductive toxicity

May damage the unborn child.

### Components:

#### N-Methyl-2-pyrrolidone:

|                      |                                                                                                                                                                                                                          |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Effects on fertility | : Test Type: Two-generation reproduction toxicity study<br>Species: Rat<br>Application Route: Ingestion<br>Method: OECD Test Guideline 416<br>Result: negative<br>Remarks: The test was conducted according to guideline |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                              |                                                                                                                                                                                                        |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Effects on fetal development | : Test Type: Embryo-fetal development<br>Species: Rat<br>Application Route: Ingestion<br>Method: OECD Test Guideline 414<br>Result: positive<br>Remarks: The test was conducted according to guideline |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|  |                                                                                                                                                                                                                                        |
|--|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | Test Type: Fertility/early embryonic development<br>Species: Rat<br>Application Route: inhalation (vapor)<br>Method: OECD Test Guideline 414<br>Result: positive<br>Remarks: The test was conducted equivalent or similar to guideline |
|--|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|  |                                     |
|--|-------------------------------------|
|  | Test Type: Embryo-fetal development |
|--|-------------------------------------|

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|                 |                              |                              |                                                                   |
|-----------------|------------------------------|------------------------------|-------------------------------------------------------------------|
| Version<br>16.0 | Revision Date:<br>05/26/2025 | SDS Number:<br>1347488-00051 | Date of last issue: 11/06/2024<br>Date of first issue: 02/27/2017 |
|-----------------|------------------------------|------------------------------|-------------------------------------------------------------------|

|                                    |   |                                                                                                                                                                              |
|------------------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                    |   | Species: Rabbit<br>Application Route: Ingestion<br>Method: OECD Test Guideline 414<br>Result: positive<br>Remarks: The test was conducted equivalent or similar to guideline |
| Reproductive toxicity - Assessment | : | Clear evidence of adverse effects on development, based on animal experiments.                                                                                               |

### Isobutyl methyl ketone:

|                              |   |                                                                                                                                    |
|------------------------------|---|------------------------------------------------------------------------------------------------------------------------------------|
| Effects on fertility         | : | Test Type: Two-generation reproduction toxicity study<br>Species: Rat<br>Application Route: inhalation (vapor)<br>Result: negative |
| Effects on fetal development | : | Test Type: Embryo-fetal development<br>Species: Rat<br>Application Route: inhalation (vapor)<br>Result: negative                   |

### Hydrocarbons, C9, aromatics:

|                              |   |                                                                                                                                      |
|------------------------------|---|--------------------------------------------------------------------------------------------------------------------------------------|
| Effects on fertility         | : | Test Type: Three-generation reproduction toxicity study<br>Species: Rat<br>Application Route: inhalation (vapor)<br>Result: negative |
| Effects on fetal development | : | Test Type: Embryo-fetal development<br>Species: Mouse<br>Application Route: inhalation (vapor)<br>Result: negative                   |

### Carbon black:

|                              |   |                                                                                                                                                                                                                                                                               |
|------------------------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Effects on fetal development | : | Test Type: Embryo-fetal development<br>Species: Rat<br>Application Route: Ingestion<br>Method: OECD Test Guideline 414<br>Result: negative<br><br>Test Type: Embryo-fetal development<br>Species: Mouse<br>Application Route: inhalation (dust/mist/fume)<br>Result: negative |
|------------------------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### STOT-single exposure

May cause respiratory irritation.  
May cause drowsiness or dizziness.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 11/06/2024  |
| 16.0    | 05/26/2025     | 1347488-00051 | Date of first issue: 02/27/2017 |

### Components:

#### **N-Methyl-2-pyrrolidone:**

|| Assessment : May cause respiratory irritation.

#### **Isobutyl methyl ketone:**

|| Assessment : May cause drowsiness or dizziness.

#### **Hydrocarbons, C9, aromatics:**

|| Assessment : May cause drowsiness or dizziness.

|| Assessment : May cause respiratory irritation.

### **STOT-repeated exposure**

Not classified based on available information.

### **Repeated dose toxicity**

### Components:

#### **N-Methyl-2-pyrrolidone:**

|| Species : Rat, male  
|| NOAEL : 169 mg/kg  
|| LOAEL : 433 mg/kg  
|| Application Route : Ingestion  
|| Exposure time : 90 Days  
|| Method : OECD Test Guideline 408  
|| Remarks : The test was conducted according to guideline

|| Species : Rat  
|| NOAEL : 0.5 mg/l  
|| LOAEL : 1 mg/l  
|| Application Route : inhalation (dust/mist/fume)  
|| Exposure time : 96 Days  
|| Method : OECD Test Guideline 413  
|| Remarks : The test was conducted according to guideline

|| Species : Rabbit, male  
|| NOAEL : 826 mg/kg  
|| LOAEL : 1,653 mg/kg  
|| Application Route : Skin contact  
|| Exposure time : 20 Days  
|| Method : OECD Test Guideline 410  
|| Remarks : The test was conducted equivalent or similar to guideline

#### **Isobutyl methyl ketone:**

|| Species : Rat  
|| NOAEL : 250 mg/kg  
|| LOAEL : 1,000 mg/kg  
|| Application Route : Ingestion  
|| Exposure time : 13 Weeks

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 11/06/2024  |
| 16.0    | 05/26/2025     | 1347488-00051 | Date of first issue: 02/27/2017 |

|                   |                      |
|-------------------|----------------------|
| Species           | : Rat                |
| NOAEL             | : 4.106 mg/l         |
| Application Route | : inhalation (vapor) |
| Exposure time     | : 14 Weeks           |

### Hydrocarbons, C9, aromatics:

|                   |                                        |
|-------------------|----------------------------------------|
| Species           | : Rat, female                          |
| NOAEL             | : 900 mg/m <sup>3</sup>                |
| Application Route | : inhalation (vapor)                   |
| Exposure time     | : 12 Months                            |
| Remarks           | : Based on data from similar materials |

### Aspiration toxicity

Not classified based on available information.

### Components:

#### Isobutyl methyl ketone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

### Hydrocarbons, C9, aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

### Experience with human exposure

### Components:

#### N-Methyl-2-pyrrolidone:

|              |                             |
|--------------|-----------------------------|
| Skin contact | : Symptoms: Skin irritation |
|--------------|-----------------------------|

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

### Components:

#### N-Methyl-2-pyrrolidone:

|                                                     |                                                                                                                                                         |
|-----------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Toxicity to fish                                    | : LC50 (Oncorhynchus mykiss (rainbow trout)): > 500 mg/l<br>Exposure time: 96 h                                                                         |
| Toxicity to daphnia and other aquatic invertebrates | : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l<br>Exposure time: 24 h<br>Method: DIN 38412<br>Remarks: The test was conducted according to guideline |
| Toxicity to algae/aquatic plants                    | : ErC50 (Desmodesmus subspicatus (green algae)): 600.5 mg/l<br>Exposure time: 72 h                                                                      |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 11/06/2024  |
| 16.0    | 05/26/2025     | 1347488-00051 | Date of first issue: 02/27/2017 |

|                                                                        |                                                                                                                                                                    |
|------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                        | EC10 (Desmodesmus subspicatus (green algae)): 92.6 mg/l<br>Exposure time: 72 h                                                                                     |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : NOEC (Daphnia magna (Water flea)): 12.5 mg/l<br>Exposure time: 21 d<br>Method: OECD Test Guideline 211<br>Remarks: The test was conducted according to guideline |
| Toxicity to microorganisms                                             | : EC50 (activated sludge): > 600 mg/l<br>Exposure time: 30 min<br>Method: ISO 8192<br>Remarks: The test was conducted according to guideline                       |

### Isobutyl methyl ketone:

|                                                                        |                                                                                                           |
|------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| Toxicity to fish                                                       | : LC50 (Danio rerio (zebra fish)): > 179 mg/l<br>Exposure time: 96 h<br>Method: OECD Test Guideline 203   |
| Toxicity to daphnia and other aquatic invertebrates                    | : EC50 (Daphnia magna (Water flea)): > 200 mg/l<br>Exposure time: 48 h<br>Method: OECD Test Guideline 202 |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : NOEC (Daphnia magna (Water flea)): 30 mg/l<br>Exposure time: 21 d                                       |

### Hydrocarbons, C9, aromatics:

|                                                     |                                                                                                                                                                                                                                                                                                                                                            |
|-----------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Toxicity to fish                                    | : LL50 (Oncorhynchus mykiss (rainbow trout)): 9.2 mg/l<br>Exposure time: 96 h<br>Test substance: Water Accommodated Fraction<br>Method: OECD Test Guideline 203                                                                                                                                                                                            |
| Toxicity to daphnia and other aquatic invertebrates | : EL50 (Daphnia magna (Water flea)): 3.2 mg/l<br>Exposure time: 48 h<br>Test substance: Water Accommodated Fraction<br>Method: OECD Test Guideline 202                                                                                                                                                                                                     |
| Toxicity to algae/aquatic plants                    | : EL50 (Pseudokirchneriella subcapitata (green algae)): 7.9 mg/l<br>Exposure time: 72 h<br>Test substance: Water Accommodated Fraction<br>Method: OECD Test Guideline 201<br><br>NOELR (Pseudokirchneriella subcapitata (green algae)): 0.22 mg/l<br>Exposure time: 72 h<br>Test substance: Water Accommodated Fraction<br>Method: OECD Test Guideline 201 |
| Toxicity to microorganisms                          | : EC50: > 99 mg/l<br>Exposure time: 10 min                                                                                                                                                                                                                                                                                                                 |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 11/06/2024  |
| 16.0    | 05/26/2025     | 1347488-00051 | Date of first issue: 02/27/2017 |

### Carbon black:

|                                                     |                                                                                                                                                                        |
|-----------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Toxicity to fish                                    | : LL50 (Danio rerio (zebra fish)): > 1,000 mg/l<br>Exposure time: 96 h<br>Method: OECD Test Guideline 203                                                              |
| Toxicity to daphnia and other aquatic invertebrates | : EL50 (Daphnia magna (Water flea)): > 5,600 mg/l<br>Exposure time: 24 h<br>Test substance: Water Accommodated Fraction<br>Method: OECD Test Guideline 202             |
| Toxicity to algae/aquatic plants                    | : EL10 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l<br>Exposure time: 72 h<br>Test substance: Water Accommodated Fraction<br>Method: OECD Test Guideline 201 |
|                                                     | : EL50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l<br>Exposure time: 72 h<br>Test substance: Water Accommodated Fraction<br>Method: OECD Test Guideline 201 |

### Persistence and degradability

#### Components:

##### N-Methyl-2-pyrrolidone:

|                  |                                                                                                                                                                               |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Biodegradability | : Result: Readily biodegradable.<br>Biodegradation: 73 %<br>Exposure time: 28 d<br>Method: OECD Test Guideline 301C<br>Remarks: The test was conducted according to guideline |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

##### Isobutyl methyl ketone:

|                  |                                                                                                                     |
|------------------|---------------------------------------------------------------------------------------------------------------------|
| Biodegradability | : Result: Readily biodegradable.<br>Biodegradation: 83 %<br>Exposure time: 28 d<br>Method: OECD Test Guideline 301F |
|------------------|---------------------------------------------------------------------------------------------------------------------|

##### Hydrocarbons, C9, aromatics:

|                  |                                                                                                                     |
|------------------|---------------------------------------------------------------------------------------------------------------------|
| Biodegradability | : Result: Readily biodegradable.<br>Biodegradation: 78 %<br>Exposure time: 28 d<br>Method: OECD Test Guideline 301F |
|------------------|---------------------------------------------------------------------------------------------------------------------|

### Bioaccumulative potential

#### Components:

##### N-Methyl-2-pyrrolidone:

|                           |                  |
|---------------------------|------------------|
| Partition coefficient: n- | : log Pow: -0.46 |
|---------------------------|------------------|

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 11/06/2024  |
| 16.0    | 05/26/2025     | 1347488-00051 | Date of first issue: 02/27/2017 |

|| octanol/water

Method: OECD Test Guideline 107

Remarks: The test was conducted according to guideline

### Isobutyl methyl ketone:

|| Partition coefficient: n- : log Pow: 1.9  
|| octanol/water

### Hydrocarbons, C9, aromatics:

|| Partition coefficient: n- : log Pow: 3.7 - 4.5  
|| octanol/water

### Mobility in soil

No data available

### Other adverse effects

No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.  
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number : UN 1263  
Proper shipping name : PAINT  
|| Class : 3  
|| Packing group : III  
|| Labels : 3  
Environmentally hazardous : no

#### IATA-DGR

UN/ID No. : UN 1263  
Proper shipping name : Paint  
|| Class : 3  
|| Packing group : III  
|| Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 11/06/2024  |
| 16.0    | 05/26/2025     | 1347488-00051 | Date of first issue: 02/27/2017 |

Packing instruction (passenger aircraft) : 355

### IMDG-Code

UN number : UN 1263  
Proper shipping name : PAINT

Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

### Transport in bulk according to IMO instruments

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

UN/ID/NA number : UN 1263  
Proper shipping name : Paint

Class : CBL  
Packing group : III  
Labels : NONE  
ERG Code : 128  
Marine pollutant : no  
Remarks : Above applies only to containers over 119 gallons or 450 liters. Not regulated if shipped in packages less than or equal to 119 gallons (450 liters). If transporting by vessel or aircraft, unless other means of transportation is impracticable, then the product must be shipped as a flammable liquid.

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### CERCLA Reportable Quantity

| Components             | CAS-No.  | Component RQ (lbs) | Calculated product RQ (lbs) |
|------------------------|----------|--------------------|-----------------------------|
| Isobutyl methyl ketone | 108-10-1 | 5000               | 29982                       |

### SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Carcinogenicity

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 11/06/2024  |
| 16.0    | 05/26/2025     | 1347488-00051 | Date of first issue: 02/27/2017 |

Reproductive toxicity  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Specific target organ toxicity (single or repeated exposure)

### SARA 313

: The following components are subject to reporting levels established by SARA Title III, Section 313:

|                        |          |                |
|------------------------|----------|----------------|
| N-Methyl-2-pyrrolidone | 872-50-4 | >= 30 - < 50 % |
|------------------------|----------|----------------|

|                        |          |                |
|------------------------|----------|----------------|
| Isobutyl methyl ketone | 108-10-1 | >= 10 - < 20 % |
|------------------------|----------|----------------|

### Volatile organic compounds (VOC) content

VOC content: 777.1 g/l  
Remarks: less exempt

VOC content: 776.86 g/l  
Remarks: as packaged

### US State Regulations

#### Pennsylvania Right To Know

|                             |              |
|-----------------------------|--------------|
| N-Methyl-2-pyrrolidone      | 872-50-4     |
| Isobutyl methyl ketone      | 108-10-1     |
| Polyamide-imide             | Trade secret |
| Fluoropolymer               | Trade secret |
| Hydrocarbons, C9, aromatics | 64742-95-6   |
| Carbon black                | 1333-86-4    |
| Butan-2-ol                  | 78-92-2      |
| Butan-1-ol                  | 71-36-3      |
| 2-Methyl-1-propanol         | 78-83-1      |
| Formaldehyde                | 50-00-0      |

#### California Prop. 65

WARNING: This product can expose you to chemicals including Isobutyl methyl ketone, which is/are known to the State of California to cause cancer, and N-Methyl-2-pyrrolidone, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### California List of Hazardous Substances

|                             |            |
|-----------------------------|------------|
| Isobutyl methyl ketone      | 108-10-1   |
| Hydrocarbons, C9, aromatics | 64742-95-6 |
| Carbon black                | 1333-86-4  |

#### California Permissible Exposure Limits for Chemical Contaminants

|                             |            |
|-----------------------------|------------|
| N-Methyl-2-pyrrolidone      | 872-50-4   |
| Isobutyl methyl ketone      | 108-10-1   |
| Hydrocarbons, C9, aromatics | 64742-95-6 |
| Carbon black                | 1333-86-4  |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard




## 958G-303 ONE COAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 11/06/2024  |
| 16.0    | 05/26/2025     | 1347488-00051 | Date of first issue: 02/27/2017 |

### SECTION 16. OTHER INFORMATION

#### Further information

##### NFPA 704:



##### HMIS® IV:

|                 |   |   |
|-----------------|---|---|
| HEALTH          | * | 2 |
| FLAMMABILITY    |   | 2 |
| PHYSICAL HAZARD |   | 0 |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

#### Full text of other abbreviations

|                  |                                                                                             |
|------------------|---------------------------------------------------------------------------------------------|
| ACGIH            | : USA. ACGIH Threshold Limit Values (TLV)                                                   |
| ACGIH BEI        | : ACGIH - Biological Exposure Indices (BEI)                                                 |
| NIOSH REL        | : USA. NIOSH Recommended Exposure Limits                                                    |
| OSHA CARC        | : OSHA Specifically Regulated Chemicals/Carcinogens                                         |
| OSHA Z-1         | : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants          |
| OSHA Z-2         | : USA. Occupational Exposure Limits (OSHA) - Table Z-2                                      |
| US WEEL          | : USA. Workplace Environmental Exposure Levels (WEEL)                                       |
| ACGIH / TWA      | : 8-hour, time-weighted average                                                             |
| ACGIH / STEL     | : Short-term exposure limit                                                                 |
| ACGIH / C        | : Ceiling limit                                                                             |
| NIOSH REL / TWA  | : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek |
| NIOSH REL / ST   | : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday    |
| NIOSH REL / C    | : Ceiling value not be exceeded at any time.                                                |
| OSHA CARC / PEL  | : Permissible exposure limit (PEL)                                                          |
| OSHA CARC / STEL | : Excursion limit                                                                           |
| OSHA Z-1 / TWA   | : 8-hour time weighted average                                                              |
| OSHA Z-2 / TWA   | : 8-hour time weighted average                                                              |
| US WEEL / TWA    | : 8-hr TWA                                                                                  |
| US WEEL / STEL   | : Short-Term TWA                                                                            |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 958G-303 ONE COAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 11/06/2024  |
| 16.0    | 05/26/2025     | 1347488-00051 | Date of first issue: 02/27/2017 |

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 05/26/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8