

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
12.0	06/24/2025	1341822-00046	Date of first issue: 02/27/2017

### SECTION 1. IDENTIFICATION

Product name : TN-8748 THINNER

Product code : D11981599

SDS-Identcode : 130000126181

#### Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street  
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

#### Recommended use of the chemical and restrictions on use

Recommended use : Solvents, dispersions, pigments

Restrictions on use : For industrial use only.  
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Carcinogenicity : Category 1B

Reproductive toxicity : Category 2

Specific target organ toxicity  
- single exposure : Category 3

Specific target organ toxicity : Category 2 (Auditory system)

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version 12.0	Revision Date: 06/24/2025	SDS Number: 1341822-00046	Date of last issue: 11/05/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

- repeated exposure

Aspiration hazard : Category 1

### Other hazards

Vapors may form explosive mixture with air.

### GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H350 May cause cancer.  
H361d Suspected of damaging the unborn child.  
H373 May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, sparks, open flame and hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P241 Use explosion-proof electrical, ventilating and lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P260 Do not breathe mist or vapors.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves, protective clothing, eye protection and face protection.  
**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version 12.0      Revision Date: 06/24/2025      SDS Number: 1341822-00046      Date of last issue: 11/05/2024  
Date of first issue: 02/27/2017

P308 + P313 IF exposed or concerned: Get medical attention.  
P331 Do NOT induce vomiting.  
P332 + P313 If skin irritation occurs: Get medical attention.  
P337 + P313 If eye irritation persists: Get medical attention.

### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

### Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture  
Chemical nature : Paint related material

### Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Xylene	1330-20-7*	>= 60 - <= 80	TSC
Diacetone alcohol	123-42-2*	>= 10 - <= 30	TSC
Ethylbenzene	100-41-4*	>= 10 - <= 30	TSC
Cumene	98-82-8*	>= 0.1 - <= 1	TSC

\* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.  
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version 12.0	Revision Date: 06/24/2025	SDS Number: 1341822-00046	Date of last issue: 11/05/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

- If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
If vomiting occurs have person lean forward.  
Call a physician or poison control center immediately.  
Rinse mouth thoroughly with water.  
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause cancer.  
Suspected of damaging the unborn child.  
May cause damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.  
Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version 12.0	Revision Date: 06/24/2025	SDS Number: 1341822-00046	Date of last issue: 11/05/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.

Advice on safe handling : Do not get on skin or clothing.  
Do not breathe mist or vapors.  
Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version 12.0	Revision Date: 06/24/2025	SDS Number: 1341822-00046	Date of last issue: 11/05/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

practice, based on the results of the workplace exposure assessment  
Non-sparking tools should be used.  
Keep container tightly closed.  
Already sensitized individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitizers.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.  
Store locked up.  
Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Self-reactive substances and mixtures  
Organic peroxides  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives  
Gases  
Very acutely toxic substances and mixtures

Recommended storage temperature : 41 - 77 °F / 5 - 25 °C

Further information on storage stability : Do not freeze.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Xylene	1330-20-7	TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA Z-1
		TWA	20 ppm	ACGIH
Diacetone alcohol	123-42-2	TWA	50 ppm	ACGIH
		TWA	50 ppm	NIOSH REL

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version 12.0      Revision Date: 06/24/2025      SDS Number: 1341822-00046      Date of last issue: 11/05/2024  
Date of first issue: 02/27/2017

			240 mg/m <sup>3</sup>	
		TWA	50 ppm 240 mg/m <sup>3</sup>	OSHA Z-1
Ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m <sup>3</sup>	NIOSH REL
		ST	125 ppm 545 mg/m <sup>3</sup>	NIOSH REL
		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA Z-1
Cumene	98-82-8	TWA	5 ppm	ACGIH
		TWA	50 ppm 245 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm 245 mg/m <sup>3</sup>	OSHA Z-1

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Xylene	1330-20-7	Methyl-hippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	0.3 g/g creatinine	ACGIH BEI
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	150 mg/g creatinine	ACGIH BEI

**Engineering measures** : Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.

### Personal protective equipment

**Respiratory protection** : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version 12.0	Revision Date: 06/24/2025	SDS Number: 1341822-00046	Date of last issue: 11/05/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

where air purifying respirators may not provide adequate protection.

### Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : clear

Odor : No data available

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version 12.0	Revision Date: 06/24/2025	SDS Number: 1341822-00046	Date of last issue: 11/05/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

---

Initial boiling point and boiling range : > 275 °F / > 135 °C

Flash point : 79 °F / 26 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Sustains combustion

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : 0.876 g/cm<sup>3</sup>

Solubility(ies)  
Water solubility : No data available

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics  
Particle size : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version 12.0	Revision Date: 06/24/2025	SDS Number: 1341822-00046	Date of last issue: 11/05/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

Possibility of hazardous reactions	: Flammable liquid and vapor. Vapors may form explosive mixture with air. Can react with strong oxidizing agents.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity	: Acute toxicity estimate: 3,440 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate: 29.9 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate: 3,517 mg/kg Method: Calculation method

#### Components:

##### Xylene:

Acute oral toxicity	: LD50 (Rat): 3,523 mg/kg Method: Directive 67/548/EEC, Annex V, B.1.
Acute inhalation toxicity	: LC50 (Rat): 27.571 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	: LD50 (Rabbit): > 4,200 mg/kg

##### Diacetone alcohol:

Acute oral toxicity	: LD50 (Rat): 3,002 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 7.6 mg/l Exposure time: 4 h Test atmosphere: vapor

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
12.0	06/24/2025	1341822-00046	Date of first issue: 02/27/2017

---

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

### Ethylbenzene:

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 17.8 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

### Cumene:

Acute oral toxicity : LD50 (Rat): 2,700 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

### Skin corrosion/irritation

Causes skin irritation.

### Components:

#### Xylene:

Species : Rabbit  
Result : Skin irritation

#### Diacetone alcohol:

Species : Rabbit  
Result : No skin irritation

#### Cumene:

Species : Rabbit  
Result : No skin irritation

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Components:

#### Xylene:

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

#### Diacetone alcohol:

Species : Rabbit  
Result : Irritation to eyes, reversing within 7 days  
Method : OECD Test Guideline 405

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
12.0	06/24/2025	1341822-00046	Date of first issue: 02/27/2017

---

### Cumene:

Species	: Rabbit
Result	: No eye irritation

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

### Components:

#### Xylene:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Result	: negative

#### Diacetone alcohol:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

#### Cumene:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: negative

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### Xylene:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
	Test Type: Chromosome aberration test in vitro Result: negative
	Test Type: In vitro mammalian cell gene mutation test Result: negative
	Test Type: In vitro sister chromatid exchange assay in mam- malian cells Result: negative

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version 12.0	Revision Date: 06/24/2025	SDS Number: 1341822-00046	Date of last issue: 11/05/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: Skin contact  
Result: negative

### Diacetone alcohol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

### Ethylbenzene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with  
mammalian liver cells in vivo  
Species: Mouse  
Application Route: Inhalation  
Method: OECD Test Guideline 486  
Result: negative

### Cumene:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative

### Carcinogenicity

May cause cancer.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
12.0	06/24/2025	1341822-00046	Date of first issue: 02/27/2017

### Components:

#### **Xylene:**

Species	: Rat
Application Route	: Ingestion
Exposure time	: 103 weeks
Result	: negative

#### **Ethylbenzene:**

Species	: Rat
Application Route	: inhalation (vapor)
Exposure time	: 104 weeks
Result	: positive
Remarks	: The mechanism or mode of action may not be relevant in humans.

#### **Cumene:**

Species	: Rat
Application Route	: inhalation (vapor)
Exposure time	: 105 weeks
Method	: OECD Test Guideline 451
Result	: positive

Species	: Mouse
Application Route	: inhalation (vapor)
Exposure time	: 105 weeks
Method	: OECD Test Guideline 451
Result	: positive

Carcinogenicity - Assessment	: Sufficient evidence of carcinogenicity in animal experiments
------------------------------	--

<b>IARC</b>	Group 2B: Possibly carcinogenic to humans	
	Ethylbenzene	100-41-4
	Group 2B: Possibly carcinogenic to humans	
	Cumene	98-82-8

<b>OSHA</b>	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
-------------	--

<b>NTP</b>	Reasonably anticipated to be a human carcinogen	
	Cumene	98-82-8

### **Reproductive toxicity**

Suspected of damaging the unborn child.

### Components:

#### **Xylene:**

Effects on fertility	: Test Type: One-generation reproduction toxicity study
	Species: Rat
	Application Route: inhalation (vapor)

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
12.0	06/24/2025	1341822-00046	Date of first issue: 02/27/2017

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### Diacetone alcohol:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rabbit  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

### Ethylbenzene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 416  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Inhalation  
Method: OECD Test Guideline 414  
Result: negative

### Cumene:

Effects on fertility : Species: Rat, male  
Application Route: inhalation (vapor)  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 414  
Result: negative

### STOT-single exposure

May cause respiratory irritation.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
12.0	06/24/2025	1341822-00046	Date of first issue: 02/27/2017

### Components:

#### **Xylene:**

|| Assessment : May cause respiratory irritation.

#### **Diacetone alcohol:**

|| Assessment : May cause respiratory irritation.

#### **Cumene:**

|| Assessment : May cause respiratory irritation.

### **STOT-repeated exposure**

May cause damage to organs (Auditory system) through prolonged or repeated exposure.

### Components:

#### **Xylene:**

|| Routes of exposure : inhalation (vapor)  
|| Target Organs : Auditory system  
|| Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

#### **Ethylbenzene:**

|| Routes of exposure : inhalation (vapor)  
|| Target Organs : Auditory system  
|| Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

### **Repeated dose toxicity**

### Components:

#### **Xylene:**

|| Species : Rat  
|| LOAEL : > 0.2 - 1 mg/l  
|| Application Route : inhalation (vapor)  
|| Exposure time : 13 Weeks  
|| Remarks : Based on data from similar materials

|| Species : Rat  
|| LOAEL : 150 mg/kg  
|| Application Route : Ingestion  
|| Exposure time : 90 Days

#### **Diacetone alcohol:**

|| Species : Rat  
|| NOAEL : >= 600 mg/kg  
|| Application Route : Ingestion  
|| Exposure time : 13 Weeks  
|| Method : OECD Test Guideline 408



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
12.0	06/24/2025	1341822-00046	Date of first issue: 02/27/2017

---

Species	: Rat
NOAEL	: $\geq 4.685$ mg/l
Application Route	: inhalation (vapor)
Exposure time	: 6 Weeks

### Ethylbenzene:

Species	: Rat
LOAEL	: 0.868 mg/l
Application Route	: inhalation (vapor)
Exposure time	: 13 Weeks

Species	: Rat
NOAEL	: 75 mg/kg
LOAEL	: 250 mg/kg
Application Route	: Ingestion
Method	: OECD Test Guideline 408

### Cumene:

Species	: Rat
NOAEL	: 125 ppm
LOAEL	: 250 ppm
Application Route	: inhalation (vapor)
Exposure time	: 90 Days

### Aspiration toxicity

May be fatal if swallowed and enters airways.

### Components:

#### Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### Ethylbenzene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### Cumene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

### Components:

#### Xylene:

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
12.0	06/24/2025	1341822-00046	Date of first issue: 02/27/2017

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 13.5 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l Exposure time: 24 h Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	: EC50 (Skeletonema costatum (marine diatom)): 10 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: NOEC (Danio rerio (zebra fish)): > 0.1 - < 1 mg/l Exposure time: 35 d Method: OECD Test Guideline 210 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: EL10 (Daphnia magna (Water flea)): > 1 - 10 mg/l Exposure time: 21 d Method: OECD Test Guideline 211 Remarks: Based on data from similar materials
Toxicity to microorganisms	: NOEC: > 100 mg/l Exposure time: 3 h Method: OECD Test Guideline 209 Remarks: Based on data from similar materials

### Diacetone alcohol:

Toxicity to fish	: LC50 (Oryzias latipes (Japanese medaka)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: ErC50 (Raphidocelis subcapitata (freshwater green alga)): > 1,000 mg/l Exposure time: 72 h Method: OECD Test Guideline 201  NOEC (Raphidocelis subcapitata (freshwater green alga)): > 1,000 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 100 mg/l Exposure time: 21 d Method: OECD Test Guideline 211
Toxicity to microorganisms	: EC50 (activated sludge): > 1,000 mg/l Exposure time: 3 h Method: OECD Test Guideline 209

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
12.0	06/24/2025	1341822-00046	Date of first issue: 02/27/2017

### Ethylbenzene:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 4.2 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 1.8 - 2.4 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	: EC50 (Pseudokirchneriella subcapitata (green algae)): 3.6 mg/l Exposure time: 96 h  NOEC (Pseudokirchneriella subcapitata (green algae)): 3.4 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Ceriodaphnia dubia (water flea)): 0.96 mg/l Exposure time: 7 d
Toxicity to microorganisms	: EC50 (Nitrosomonas sp.): 96 mg/l Exposure time: 24 h

### Cumene:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 4.8 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 2.14 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: ErC50 (Desmodesmus subspicatus (green algae)): 2.01 mg/l Exposure time: 72 h Method: OECD Test Guideline 201  EC10 (Desmodesmus subspicatus (green algae)): 1.35 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 0.35 mg/l Exposure time: 21 d

### Persistence and degradability

#### Components:

#### Xylene:

Biodegradability	: Result: Readily biodegradable. Biodegradation: > 70 % Exposure time: 28 d Method: OECD Test Guideline 301F Remarks: Based on data from similar materials
------------------	--

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
12.0	06/24/2025	1341822-00046	Date of first issue: 02/27/2017

II

### Diacetone alcohol:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 98.51 %  
Exposure time: 28 d

### Ethylbenzene:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 70 - 80 %  
Exposure time: 28 d

### Cumene:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 70 %  
Exposure time: 20 d

### Bioaccumulative potential

#### Components:

#### Xylene:

Partition coefficient: n-octanol/water : log Pow: 3.16  
Remarks: Calculation

#### Diacetone alcohol:

Partition coefficient: n-octanol/water : log Pow: -0.09  
Remarks: Calculation

#### Ethylbenzene:

Partition coefficient: n-octanol/water : log Pow: 3.6

#### Cumene:

Partition coefficient: n-octanol/water : log Pow: 3.55

### Mobility in soil

No data available

### Other adverse effects

No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.  
Do not dispose of waste into sewer.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
12.0	06/24/2025	1341822-00046	Date of first issue: 02/27/2017

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

UN number : UN 1263  
Proper shipping name : PAINT RELATED MATERIAL  
Class : 3  
Packing group : III  
Labels : 3  
Environmentally hazardous : no

##### IATA-DGR

UN/ID No. : UN 1263  
Proper shipping name : Paint related material  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

##### IMDG-Code

UN number : UN 1263  
Proper shipping name : PAINT RELATED MATERIAL  
  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

#### Transport in bulk according to IMO instruments

Not applicable for product as supplied.

#### Domestic regulation

##### 49 CFR

UN/ID/NA number : UN 1263  
Proper shipping name : Paint related material  
  
Class : 3  
Packing group : III  
Labels : FLAMMABLE LIQUID  
ERG Code : 128  
Marine pollutant : no

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version 12.0      Revision Date: 06/24/2025      SDS Number: 1341822-00046      Date of last issue: 11/05/2024  
Date of first issue: 02/27/2017

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	140
Ethylbenzene	100-41-4	1000	7330
Naphthalene	91-20-3	100	117647

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Carcinogenicity  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)  
Aspiration hazard  
Skin corrosion or irritation  
Serious eye damage or eye irritation

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Xylene	1330-20-7	>= 70 - < 90 %
Ethylbenzene	100-41-4	>= 10 - < 20 %
Cumene	98-82-8	>= 0.1 - < 1 %

### Volatile organic compounds (VOC) content

VOC content: 874.76 g/l  
Remarks: less exempt

VOC content: 874.76 g/l  
Remarks: as packaged

## US State Regulations

### Pennsylvania Right To Know

Xylene	1330-20-7
Diacetone alcohol	123-42-2
Ethylbenzene	100-41-4
Cumene	98-82-8

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
12.0	06/24/2025	1341822-00046	Date of first issue: 02/27/2017

Naphthalene  
Toluene

91-20-3  
108-88-3

### California Prop. 65

WARNING: This product can expose you to chemicals including Ethylbenzene, which is/are known to the State of California to cause cancer, and Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### California List of Hazardous Substances

Xylene	1330-20-7
Diacetone alcohol	123-42-2
Ethylbenzene	100-41-4


### California Permissible Exposure Limits for Chemical Contaminants

Xylene	1330-20-7
Diacetone alcohol	123-42-2
Ethylbenzene	100-41-4

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA 704:



#### HMIS® IV:

HEALTH	*	3
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.  
Before use read Chemours safety information.  
For further information contact the local Chemours office or nominated distributors.

### Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
12.0	06/24/2025	1341822-00046	Date of first issue: 02/27/2017

ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 06/24/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TN-8748 THINNER

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2024
12.0	06/24/2025	1341822-00046	Date of first issue: 02/27/2017

---

to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8