

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-6210 ETFE POWDER TOPCOAT CLEAR

Version 11.0 Revision Date: 01/13/2026 SDS Number: 1341960-00049 Date of last issue: 10/19/2025
Date of first issue: 02/27/2017

SECTION 1. IDENTIFICATION

Product name : 532-6210 ETFE POWDER TOPCOAT CLEAR
Product code : D15438081
SDS-Identcode : 130000126470

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC
Address : 1007 Market Street
Wilmington, DE 19801 United States of America (USA)
Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)
Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Coatings
Restrictions on use : For industrial use only.
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Combustible dust

Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.
Dust contact with the eyes can lead to mechanical irritation.
Contact with dust can cause mechanical irritation or drying of the skin.

GHS label elements

Signal Word : Warning
Hazard Statements : May form combustible dust concentrations in air.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-6210 ETFE POWDER TOPCOAT CLEAR

Version 11.0 Revision Date: 01/13/2026 SDS Number: 1341960-00049 Date of last issue: 10/19/2025
Date of first issue: 02/27/2017

Hazards resulting from a reaction with other chemicals under normal conditions of use:

Conditions	Chemicals formed	Hazards
Thermal decomposition at elevated temperatures	Vapors of fluorinated plastics	May cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco
Thermal decomposition at elevated temperatures	Refer to Section 10 for list of hazardous decomposition products	Hazardous decomposition products will be formed at elevated temperatures.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance
Chemical nature : Paint
Substance name : Fluoropolymer
CAS-No. : Trade secret

Components

No hazardous ingredients

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap.
Get medical attention if symptoms occur.

In case of eye contact : If in eyes, rinse well with water.
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : Contact with dust can cause mechanical irritation or drying of the skin.
Dust contact with the eyes can lead to mechanical irritation.
No information available.

Protection of first-aiders : No special precautions are necessary for first aid responders.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-6210 ETFE POWDER TOPCOAT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2025
11.0	01/13/2026	1341960-00049	Date of first issue: 02/27/2017

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
Do not use a solid water stream as it may scatter and spread fire.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Hydrogen fluoride
carbonyl fluoride
potentially toxic fluorinated compounds
aerosolized particulates
Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-6210 ETFE POWDER TOPCOAT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2025
11.0	01/13/2026	1341960-00049	Date of first issue: 02/27/2017

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).
Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : Static electricity may accumulate and ignite suspended dust causing an explosion.
Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not breathe dust.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Minimize dust generation and accumulation.
Keep container closed when not in use.
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

inert or nuisance dust	50 Million particles per cubic foot Value type (Form of exposure): TWA (total dust) Basis: OSHA Z-3
------------------------	---

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-6210 ETFE POWDER TOPCOAT CLEAR

Version 11.0 Revision Date: 01/13/2026 SDS Number: 1341960-00049 Date of last issue: 10/19/2025
Date of first issue: 02/27/2017

	15 mg/m ³ Value type (Form of exposure): TWA (total dust) Basis: OSHA Z-3
	5 mg/m ³ Value type (Form of exposure): TWA (respirable fraction) Basis: OSHA Z-3
	15 Million particles per cubic foot Value type (Form of exposure): TWA (respirable fraction) Basis: OSHA Z-3
Dust, nuisance dust and particulates	10 mg/m ³ Value type (Form of exposure): PEL (Total dust) Basis: CAL PEL
	5 mg/m ³ Value type (Form of exposure): PEL (respirable dust fraction) Basis: CAL PEL

Contains no substances with occupational exposure limit values.

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
		TWA	3 ppm	OSHA Z-2
		C	6 ppm 5 mg/m ³	NIOSH REL
		TWA	3 ppm 2.5 mg/m ³	NIOSH REL
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m ³	NIOSH REL
		ST	5 ppm 15 mg/m ³	NIOSH REL
		TWA	2.5 mg/m ³ (Fluorine)	OSHA Z-1
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-6210 ETFE POWDER TOPCOAT CLEAR

Version 11.0 Revision Date: 01/13/2026 SDS Number: 1341960-00049 Date of last issue: 10/19/2025
Date of first issue: 02/27/2017

		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m ³	NIOSH REL
		ST	30,000 ppm 54,000 mg/m ³	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m ³	OSHA Z-1
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m ³	NIOSH REL
		C	200 ppm 229 mg/m ³	NIOSH REL
		TWA	50 ppm 55 mg/m ³	OSHA Z-1

Engineering measures : Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.
Apply measures to prevent dust explosions.
Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : For prolonged or repeated contact use protective gloves.
Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-6210 ETFE POWDER TOPCOAT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2025
11.0	01/13/2026	1341960-00049	Date of first issue: 02/27/2017

eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	powder
Color	:	clear
Odor	:	No data available
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Not classified as a flammability hazard, May form combustible dust concentrations in air.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Density	:	1.7300 g/cm ³
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-6210 ETFE POWDER TOPCOAT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2025
11.0	01/13/2026	1341960-00049	Date of first issue: 02/27/2017

Decomposition temperature : No data available

Viscosity
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics
Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : May form combustible dust concentrations in air.
Can react with strong oxidizing agents.
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Heat, flames and sparks.
Avoid dust formation.

Incompatible materials : Oxidizing agents

Hazardous decomposition products

Thermal decomposition : Hydrogen fluoride
Carbonyl difluoride
Carbon dioxide
Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-6210 ETFE POWDER TOPCOAT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2025
11.0	01/13/2026	1341960-00049	Date of first issue: 02/27/2017

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-6210 ETFE POWDER TOPCOAT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2025
11.0	01/13/2026	1341960-00049	Date of first issue: 02/27/2017

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.
-

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Combustible dust

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-6210 ETFE POWDER TOPCOAT CLEAR

Version 11.0 Revision Date: 01/13/2026 SDS Number: 1341960-00049 Date of last issue: 10/19/2025
Date of first issue: 02/27/2017

US State Regulations

Pennsylvania Right To Know

Fluoropolymer

Trade secret


California Prop. 65

WARNING: This product can expose you to chemicals including Pentadecafluorooctanoic acid, which is/are known to the State of California to cause cancer, and Carbon monoxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. Note to User: This product is not made with PFOA nor is PFOA intentionally present in the product; however, it is possible that PFOA may be present as an impurity at background (environmental) levels.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	/	0
FLAMMABILITY		2
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or nominated distributors.

Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- CAL PEL : California permissible exposure limits for chemical contaminants (Title 8, Article 107)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-2 : USA. Occupational Exposure Limits (OSHA) - Table Z-2
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- ACGIH / TWA : 8-hour, time-weighted average

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-6210 ETFE POWDER TOPCOAT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2025
11.0	01/13/2026	1341960-00049	Date of first issue: 02/27/2017

ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
CAL PEL / PEL	:	Permissible exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 01/13/2026

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



532-6210 ETFE POWDER TOPCOAT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2025
11.0	01/13/2026	1341960-00049	Date of first issue: 02/27/2017

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8