

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 532G-13032 PFA POWDER GRAY

Version 9.2      Revision Date: 03/03/2026      SDS Number: 1346182-00052      Date of last issue: 10/15/2025  
Date of first issue: 02/27/2017

---

### SECTION 1. IDENTIFICATION

Product name : 532G-13032 PFA POWDER GRAY

SDS-Identcode : 130000127745

#### Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street  
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

#### Recommended use of the chemical and restrictions on use

Recommended use : Coatings

Restrictions on use : For industrial use only.  
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

---

### SECTION 2. HAZARDS IDENTIFICATION

**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

#### Hazards for the product as supplied

Not a hazardous substance or mixture.

#### Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.

#### GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

---

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Paint

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 532G-13032 PFA POWDER GRAY

Version 9.2      Revision Date: 03/03/2026      SDS Number: 1346182-00052      Date of last issue: 10/15/2025  
Date of first issue: 02/27/2017

### Components

| Chemical name   | CAS No./Unique ID | Concentration (% w/w) | Trade secret |
|-----------------|-------------------|-----------------------|--------------|
| Silicon carbide | 409-21-2*         | >= 10 - <= 30         | TSC          |

\* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- General advice : No information available.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.  
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : No information available.
- Protection of first-aiders : No special precautions are necessary for first aid responders.
- Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 532G-13032 PFA POWDER GRAY

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 10/15/2025  |
| 9.2     | 03/03/2026     | 1346182-00052 | Date of first issue: 02/27/2017 |

---

- Hazardous combustion products : Hydrogen fluoride  
carbonyl fluoride  
potentially toxic fluorinated compounds  
aerosolized particulates  
Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Use personal protective equipment.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Take care to prevent spills, waste and minimize release to the

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 532G-13032 PFA POWDER GRAY

Version 9.2      Revision Date: 03/03/2026      SDS Number: 1346182-00052      Date of last issue: 10/15/2025  
Date of first issue: 02/27/2017

environment.

Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labeled containers.  
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

| Components      | CAS-No.  | Value type (Form of exposure)       | Control parameters / Permissible concentration | Basis     |
|-----------------|----------|-------------------------------------|--|-----------|
| Silicon carbide | 409-21-2 | TWA (Respirable)                    | 5 mg/m <sup>3</sup>                            | NIOSH REL |
|                 |          | TWA (total)                         | 10 mg/m <sup>3</sup>                           | NIOSH REL |
|                 |          | TWA (total dust)                    | 15 mg/m <sup>3</sup>                           | OSHA Z-1  |
|                 |          | TWA (respirable fraction)           | 5 mg/m <sup>3</sup>                            | OSHA Z-1  |
|                 |          | TWA (Inhalable particulate matter)  | 10 mg/m <sup>3</sup>                           | ACGIH     |
|                 |          | TWA (Respirable particulate matter) | 3 mg/m <sup>3</sup>                            | ACGIH     |

#### Occupational exposure limits of decomposition products

| Components          | CAS-No.   | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis     |
|---------------------|-----------|-------------------------------|--|-----------|
| Hydrogen fluoride   | 7664-39-3 | TWA                           | 0.5 ppm (Fluorine)                             | ACGIH     |
|                     |           | C                             | 2 ppm (Fluorine)                               | ACGIH     |
|                     |           | TWA                           | 3 ppm  | OSHA Z-2  |
|                     |           | C                             | 6 ppm<br>5 mg/m <sup>3</sup>                   | NIOSH REL |
|                     |           | TWA                           | 3 ppm<br>2.5 mg/m <sup>3</sup>                 | NIOSH REL |
| Carbonyl difluoride | 353-50-4  | TWA                           | 2 ppm  | ACGIH     |
|                     |           | STEL                          | 5 ppm  | ACGIH     |
|                     |           | TWA                           | 2 ppm<br>5 mg/m <sup>3</sup>                   | NIOSH REL |
|                     |           | ST                            | 5 ppm  | NIOSH REL |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 532G-13032 PFA POWDER GRAY

Version 9.2      Revision Date: 03/03/2026      SDS Number: 1346182-00052      Date of last issue: 10/15/2025  
Date of first issue: 02/27/2017

|                 |          |      |  |           |
|-----------------|----------|------|--|-----------|
|                 |          |      | 15 mg/m <sup>3</sup>                   |           |
|                 |          | TWA  | 2.5 mg/m <sup>3</sup><br>(Fluorine)    | OSHA Z-1  |
| Carbon dioxide  | 124-38-9 | TWA  | 5,000 ppm                              | ACGIH     |
|                 |          | STEL | 30,000 ppm                             | ACGIH     |
|                 |          | TWA  | 5,000 ppm<br>9,000 mg/m <sup>3</sup>   | NIOSH REL |
|                 |          | ST   | 30,000 ppm<br>54,000 mg/m <sup>3</sup> | NIOSH REL |
|                 |          | TWA  | 5,000 ppm<br>9,000 mg/m <sup>3</sup>   | OSHA Z-1  |
| Carbon monoxide | 630-08-0 | TWA  | 25 ppm                                 | ACGIH     |
|                 |          | TWA  | 35 ppm<br>40 mg/m <sup>3</sup>         | NIOSH REL |
|                 |          | C    | 200 ppm<br>229 mg/m <sup>3</sup>       | NIOSH REL |
|                 |          | TWA  | 50 ppm<br>55 mg/m <sup>3</sup>         | OSHA Z-1  |

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

### Personal protective equipment

**Respiratory protection** : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

**Hand protection**

**Remarks** : Wash hands before breaks and at the end of workday.

**Eye protection** : Wear the following personal protective equipment:  
Safety glasses

**Skin and body protection** : Skin should be washed after contact.

**Hygiene measures** : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 532G-13032 PFA POWDER GRAY

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 10/15/2025  |
| 9.2     | 03/03/2026     | 1346182-00052 | Date of first issue: 02/27/2017 |

---

Wash contaminated clothing before re-use.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

|  |   |   |
|--|---|---|
| Appearance                                       | : | solid                                   |
| Color  | : | gray                                    |
| Odor   | : | No data available                       |
| Odor Threshold                                   | : | No data available                       |
| pH   | : | No data available                       |
| Melting point/freezing point                     | : | No data available                       |
| Initial boiling point and boiling range          | : | No data available                       |
| Flash point                                      | : | Not applicable                          |
| Evaporation rate                                 | : | Not applicable                          |
| Flammability (solid, gas)                        | : | Not classified as a flammability hazard |
| Upper explosion limit / Upper flammability limit | : | No data available                       |
| Lower explosion limit / Lower flammability limit | : | No data available                       |
| Vapor pressure                                   | : | Not applicable                          |
| Relative vapor density                           | : | Not applicable                          |
| Density  | : | 2.2310 g/cm <sup>3</sup>                |
| Solubility(ies)<br>Water solubility              | : | insoluble                               |
| Partition coefficient: n-octanol/water           | : | Not applicable                          |
| Autoignition temperature                         | : | No data available                       |
| Decomposition temperature                        | : | No data available                       |
| Viscosity  | : |   |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 532G-13032 PFA POWDER GRAY

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 10/15/2025  |
| 9.2     | 03/03/2026     | 1346182-00052 | Date of first issue: 02/27/2017 |

---

|                          |   |  |
|--------------------------|---|--|
| Viscosity, kinematic     | : | Not applicable   |
| Explosive properties     | : | Not explosive  |
| Oxidizing properties     | : | The substance or mixture is not classified as oxidizing. |
| Particle characteristics | : |  |
| Particle size            | : | No data available  |

---

### SECTION 10. STABILITY AND REACTIVITY

|                                    |   |   |
|------------------------------------|---|---|
| Reactivity                         | : | Not classified as a reactivity hazard.  |
| Chemical stability                 | : | Stable under normal conditions.   |
| Possibility of hazardous reactions | : | Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevated temperatures. |
| Conditions to avoid                | : | None known.   |
| Incompatible materials             | : | Oxidizing agents  |

#### Hazardous decomposition products

|                       |   |   |
|-----------------------|---|---|
| Thermal decomposition | : | Hydrogen fluoride<br>Carbonyl difluoride<br>Carbon dioxide<br>Carbon monoxide |
|-----------------------|---|---|

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **Silicon carbide:**

|                       |   |   |
|-----------------------|---|---|
| Acute oral toxicity   | : | LD50 (Rat): > 2,000 mg/kg<br>Method: OECD Test Guideline 423  |
| Acute dermal toxicity | : | LD50 (Rat): > 2,000 mg/kg<br>Method: OECD Test Guideline 402<br>Assessment: The substance or mixture has no acute dermal toxicity |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 532G-13032 PFA POWDER GRAY

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 10/15/2025  |
| 9.2     | 03/03/2026     | 1346182-00052 | Date of first issue: 02/27/2017 |

---

### Skin corrosion/irritation

Not classified based on available information.

### Components:

#### Silicon carbide:

|         |   |                    |
|---------|---|--------------------|
| Species | : | Rat                |
| Result  | : | No skin irritation |

### Serious eye damage/eye irritation

Not classified based on available information.

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### Silicon carbide:

|                       |   |   |
|-----------------------|---|---|
| Genotoxicity in vitro | : | Test Type: Bacterial reverse mutation assay (AMES)<br>Method: OECD Test Guideline 471<br>Result: negative |
|-----------------------|---|---|

### Carcinogenicity

Not classified based on available information.

### Components:

#### Silicon carbide:

|                   |   |                           |
|-------------------|---|---------------------------|
| Species           | : | Rat                       |
| Application Route | : | Intraperitoneal injection |
| Exposure time     | : | 40 weeks                  |
| Result            | : | negative                  |

**IARC** No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

Not classified based on available information.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 532G-13032 PFA POWDER GRAY

Version 9.2      Revision Date: 03/03/2026      SDS Number: 1346182-00052      Date of last issue: 10/15/2025  
Date of first issue: 02/27/2017

---

### STOT-single exposure

Not classified based on available information.

### STOT-repeated exposure

Not classified based on available information.

### Components:

#### Silicon carbide:

Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

### Repeated dose toxicity

### Components:

#### Silicon carbide:

Species : Rat  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 50 hrs

### Aspiration toxicity

Not classified based on available information.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

### Components:

#### Silicon carbide:

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)):  $\geq 100$  mg/l  
Exposure time: 22 d  
Method: OECD Test Guideline 211

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.  
Do not dispose of waste into sewer.

---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 532G-13032 PFA POWDER GRAY

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 10/15/2025  |
| 9.2     | 03/03/2026     | 1346182-00052 | Date of first issue: 02/27/2017 |

---

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

##### Transport in bulk according to IMO instruments

Not applicable for product as supplied.

##### Domestic regulation

##### 49 CFR

Not regulated as a dangerous good

##### Special precautions for user

Not applicable

---

### SECTION 15. REGULATORY INFORMATION

#### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### US State Regulations

##### Pennsylvania Right To Know

Fluoropolymer  
Silicon carbide

Trade secret  
409-21-2

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 532G-13032 PFA POWDER GRAY

Version 9.2      Revision Date: 03/03/2026      SDS Number: 1346182-00052      Date of last issue: 10/15/2025  
Date of first issue: 02/27/2017

### California Prop. 65

WARNING: This product can expose you to chemicals including Pentadecafluorooctanoic acid, which is/are known to the State of California to cause cancer, and Carbon monoxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov). Note to User: This product is not made with PFOA nor is PFOA intentionally present in the product; however, it is possible that PFOA may be present as an impurity at background (environmental) levels.


### California Permissible Exposure Limits for Chemical Contaminants

Silicon carbide 409-21-2

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA 704:



#### HMIS® IV:

|                 |   |   |
|-----------------|---|---|
| HEALTH          | / | 0 |
| FLAMMABILITY    |   | 1 |
| PHYSICAL HAZARD |   | 0 |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or nominated distributors.

### Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-2 : USA. Occupational Exposure Limits (OSHA) - Table Z-2
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit
- ACGIH / C : Ceiling limit
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 532G-13032 PFA POWDER GRAY

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 10/15/2025  |
| 9.2     | 03/03/2026     | 1346182-00052 | Date of first issue: 02/27/2017 |

NIOSH REL / C : Ceiling value not be exceeded at any time.  
OSHA Z-1 / TWA : 8-hour time weighted average  
OSHA Z-2 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 03/03/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 532G-13032 PFA POWDER GRAY

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 10/15/2025  |
| 9.2     | 03/03/2026     | 1346182-00052 | Date of first issue: 02/27/2017 |

---

US / Z8