

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 852G-201 TOPCOAT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 01/29/2026
13.0	05/19/2026	1346509-00052	Date of first issue: 02/27/2017

---

### SECTION 1. IDENTIFICATION

Product name : 852G-201 TOPCOAT CLEAR

Product code : D15444894

SDS-Identcode : 130000127786

#### Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street  
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

#### Recommended use of the chemical and restrictions on use

Recommended use : Coatings

Restrictions on use : For industrial use only.  
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

---

### SECTION 2. HAZARDS IDENTIFICATION

**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

#### Hazards for the product as supplied

Flammable liquids : Category 3

Serious eye damage : Category 1

Skin sensitization : Category 1

#### Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.

#### GHS label elements

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 852G-201 TOPCOAT CLEAR

Version 13.0      Revision Date: 05/19/2026      SDS Number: 1346509-00052      Date of last issue: 01/29/2026  
Date of first issue: 02/27/2017

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H226 Flammable liquid and vapor.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.

Supplemental Hazard Statements

: Corrosive to the respiratory tract.

Precautionary Statements

: **Prevention:**

P210 Keep away from heat, sparks, open flame and hot surfaces. No smoking.

P233 Keep container tightly closed.

P241 Use explosion-proof electrical, ventilating and lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing mist or vapors.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves, protective clothing, eye protection and face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER.

P333 + P313 If skin irritation or rash occurs: Get medical attention.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

**Disposal:**

P501 Dispose of contents and container to an approved waste disposal plant.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

Chemical nature

: Paint

#### Components

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 852G-201 TOPCOAT CLEAR

Version 13.0      Revision Date: 05/19/2026      SDS Number: 1346509-00052      Date of last issue: 01/29/2026  
Date of first issue: 02/27/2017

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Hydrocarbons, C9, aromatics	64742-95-6*	$\geq 3 - \leq 7$	TSC
Sodium lauryl sulfate	73296-89-6*	$\geq 1 - \leq 5$	TSC
2,6,8-Trimethyl-4-nonyloxypolyethyleneoxy-ethanol	60828-78-6*	$\geq 1 - \leq 5$	TSC
Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9*	$> 0 - \leq 0.1$	TSC

\* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

### Alternative CAS Numbers for some regions

Chemical name	Alternative CAS Number(s)
Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	2682-20-4, 26172-55-4

## SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention immediately.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.  
Causes serious eye damage.  
Corrosive to the respiratory tract.
- Protection of first-aiders : First Aid responders should pay attention to self-protection,

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 852G-201 TOPCOAT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 01/29/2026
13.0	05/19/2026	1346509-00052	Date of first issue: 02/27/2017

---

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

---

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Hydrogen fluoride  
carbonyl fluoride  
potentially toxic fluorinated compounds  
aerosolized particulates  
Carbon oxides  
Metal oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages
-

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 852G-201 TOPCOAT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 01/29/2026
13.0	05/19/2026	1346509-00052	Date of first issue: 02/27/2017

---

cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.

Advice on safe handling : Do not get on skin or clothing.  
Avoid breathing mist or vapors.  
Do not swallow.  
Do not get in eyes.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Non-sparking tools should be used.  
Keep container tightly closed.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.  
  
Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labeled containers.  
Keep tightly closed.  
Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

Recommended storage temperature : 41 - 77 °F / 5 - 25 °C

Further information on storage stability : Do not freeze.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 852G-201 TOPCOAT CLEAR

Version 13.0      Revision Date: 05/19/2026      SDS Number: 1346509-00052      Date of last issue: 01/29/2026  
Date of first issue: 02/27/2017

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrocarbons, C9, aromatics	64742-95-6	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH
		TWA (Mist)	5 mg/m <sup>3</sup>	NIOSH REL
		ST (Mist)	10 mg/m <sup>3</sup>	NIOSH REL

#### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis		
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH		
		C	2 ppm (Fluorine)	ACGIH		
		TWA	3 ppm 2.5 mg/m <sup>3</sup>	NIOSH REL		
		C	6 ppm 5 mg/m <sup>3</sup>	NIOSH REL		
		TWA	3 ppm	OSHA Z-2		
		TWA	2 ppm	ACGIH		
Carbonyl difluoride	353-50-4	STEL	5 ppm	ACGIH		
		TWA	2 ppm 5 mg/m <sup>3</sup>	NIOSH REL		
		ST	5 ppm 15 mg/m <sup>3</sup>	NIOSH REL		
		TWA	2.5 mg/m <sup>3</sup> (Fluorine)	OSHA Z-1		
		Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
				STEL	30,000 ppm	ACGIH
TWA	5,000 ppm 9,000 mg/m <sup>3</sup>			NIOSH REL		
ST	30,000 ppm 54,000 mg/m <sup>3</sup>			NIOSH REL		
Carbon monoxide	630-08-0	TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	OSHA Z-1		
		TWA	25 ppm	ACGIH		
		TWA	35 ppm 40 mg/m <sup>3</sup>	NIOSH REL		
		C	200 ppm	NIOSH REL		

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 852G-201 TOPCOAT CLEAR

Version 13.0      Revision Date: 05/19/2026      SDS Number: 1346509-00052      Date of last issue: 01/29/2026  
Date of first issue: 02/27/2017

			229 mg/m <sup>3</sup>	
		TWA	50 ppm 55 mg/m <sup>3</sup>	OSHA Z-1

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.  
Use explosion-proof electrical, ventilating and lighting equipment.

### Personal protective equipment

**Respiratory protection** : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

### Hand protection

**Material** : Chemical-resistant gloves

**Remarks** : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

**Eye protection** : Wear the following personal protective equipment:  
Chemical resistant goggles must be worn.  
If splashes are likely to occur, wear:  
Face-shield

**Skin and body protection** : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

**Hygiene measures** : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Contaminated work clothing should not be allowed out of the workplace.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 852G-201 TOPCOAT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 01/29/2026
13.0	05/19/2026	1346509-00052	Date of first issue: 02/27/2017

---

Wash contaminated clothing before re-use.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	clear
Odor	:	No data available
Odor Threshold	:	No data available
pH	:	8.5 - 11
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	> 212 °F / > 100 °C
Flash point	:	130.3 °F / 54.6 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Does not sustain combustion.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Density	:	1.3670 g/cm <sup>3</sup>
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 852G-201 TOPCOAT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 01/29/2026
13.0	05/19/2026	1346509-00052	Date of first issue: 02/27/2017

---

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : 32 mPa.s

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics  
Particle size : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Vapors may form explosive mixture with air.  
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : None known.

Incompatible materials : None.

#### Hazardous decomposition products

Thermal decomposition : Hydrogen fluoride  
Carbonyl difluoride  
Carbon dioxide  
Carbon monoxide

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 852G-201 TOPCOAT CLEAR

Version 13.0      Revision Date: 05/19/2026      SDS Number: 1346509-00052      Date of last issue: 01/29/2026  
Date of first issue: 02/27/2017

---

### Components:

#### **Hydrocarbons, C9, aromatics:**

Acute oral toxicity : LD50 (Rat, female): 3,492 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.193 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

#### **Sodium lauryl sulfate:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

#### **2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:**

Acute oral toxicity : LD50 (Rat): 3,300 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

#### **Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):**

Acute oral toxicity : LD50 (Rat): 64 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.171 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 (Rabbit): 87.12 mg/kg

#### **Skin corrosion/irritation**

Not classified based on available information.

### Components:

#### **Hydrocarbons, C9, aromatics:**

Assessment : Repeated exposure may cause skin dryness or cracking.

#### **Sodium lauryl sulfate:**

Species : Rabbit

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 852G-201 TOPCOAT CLEAR

Version 13.0      Revision Date: 05/19/2026      SDS Number: 1346509-00052      Date of last issue: 01/29/2026  
Date of first issue: 02/27/2017

---

Method : OECD Test Guideline 404  
Result : Skin irritation  
Remarks : Based on data from similar materials

### 2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Result : Skin irritation

### Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Corrosive after 1 to 4 hours of exposure

### Serious eye damage/eye irritation

Causes serious eye damage.

#### Components:

##### Hydrocarbons, C9, aromatics:

Species : Rabbit  
Result : No eye irritation

##### Sodium lauryl sulfate:

Species : Rabbit  
Result : Irreversible effects on the eye  
Method : OECD Test Guideline 405  
Remarks : Based on data from similar materials

### 2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Result : Irreversible effects on the eye

### Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Result : Irreversible effects on the eye  
Remarks : Based on skin corrosivity.

### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### Respiratory sensitization

Not classified based on available information.

#### Components:

##### Hydrocarbons, C9, aromatics:

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 852G-201 TOPCOAT CLEAR

Version 13.0      Revision Date: 05/19/2026      SDS Number: 1346509-00052      Date of last issue: 01/29/2026  
Date of first issue: 02/27/2017

---

Method : OECD Test Guideline 406  
Result : negative

### Sodium lauryl sulfate:

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative  
Remarks : Based on data from similar materials

### Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : positive

Assessment : Probability or evidence of high skin sensitization rate in humans

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### Hydrocarbons, C9, aromatics:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Result: negative  
Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

#### Sodium lauryl sulfate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

### Carcinogenicity

Not classified based on available information.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 852G-201 TOPCOAT CLEAR

Version 13.0      Revision Date: 05/19/2026      SDS Number: 1346509-00052      Date of last issue: 01/29/2026  
Date of first issue: 02/27/2017

---

### Components:

#### **Sodium lauryl sulfate:**

Species : Rat  
Application Route : Ingestion  
Exposure time : 2 Years  
Result : negative  
Remarks : Based on data from similar materials

**IARC**      No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**      No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**      No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### **Reproductive toxicity**

Not classified based on available information.

### Components:

#### **Hydrocarbons, C9, aromatics:**

Effects on fertility : Test Type: Three-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Mouse  
Application Route: inhalation (vapor)  
Result: negative

#### **Sodium lauryl sulfate:**

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

### **STOT-single exposure**

Corrosive to the respiratory tract.

### Components:

#### **Hydrocarbons, C9, aromatics:**

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 852G-201 TOPCOAT CLEAR

Version 13.0      Revision Date: 05/19/2026      SDS Number: 1346509-00052      Date of last issue: 01/29/2026  
Date of first issue: 02/27/2017

---

### STOT-repeated exposure

Not classified based on available information.

### Repeated dose toxicity

#### Components:

#### Hydrocarbons, C9, aromatics:

Species	: Rat, female
NOAEL	: 900 mg/m <sup>3</sup>
Application Route	: inhalation (vapor)
Exposure time	: 12 Months
Remarks	: Based on data from similar materials

#### Sodium lauryl sulfate:

Species	: Rat
NOAEL	: > 430 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days
Remarks	: Based on data from similar materials

### Aspiration toxicity

Not classified based on available information.

#### Components:

#### Hydrocarbons, C9, aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

#### Hydrocarbons, C9, aromatics:

Toxicity to fish	: LL50 (Oncorhynchus mykiss (rainbow trout)): 9.2 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): 3.2 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: EL50 (Pseudokirchneriella subcapitata (green algae)): 7.9 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 852G-201 TOPCOAT CLEAR

Version 13.0      Revision Date: 05/19/2026      SDS Number: 1346509-00052      Date of last issue: 01/29/2026  
Date of first issue: 02/27/2017

NOELR (Pseudokirchneriella subcapitata (green algae)): 0.22 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 99 mg/l  
Exposure time: 10 min

### Sodium lauryl sulfate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 3.6 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.7 mg/l  
Exposure time: 48 h  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 20 mg/l  
Exposure time: 72 h  
Remarks: Based on data from similar materials

EC10 (Desmodesmus subspicatus (green algae)): 5.4 mg/l  
Exposure time: 72 h  
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 0.11 mg/l  
Exposure time: 34 d  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.14 mg/l  
Exposure time: 21 d  
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC10 (Pseudomonas putida): 1,083.85 mg/l  
Exposure time: 16 h  
Method: DIN 38 412 Part 8  
Remarks: Based on data from similar materials

### 2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 39 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 81.2 mg/l  
Exposure time: 48 h

### Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.19 mg/l  
Exposure time: 96 h

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 852G-201 TOPCOAT CLEAR

Version 13.0      Revision Date: 05/19/2026      SDS Number: 1346509-00052      Date of last issue: 01/29/2026  
Date of first issue: 02/27/2017

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.16 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Skeletonema costatum (marine diatom)): 0.0052 mg/l  
Exposure time: 48 h

NOEC (Skeletonema costatum (marine diatom)): 0.00049 mg/l  
Exposure time: 48 h

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 0.02 mg/l  
Exposure time: 36 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.10 mg/l  
Exposure time: 21 d

### Persistence and degradability

#### Components:

##### Hydrocarbons, C9, aromatics:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 78 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

##### Sodium lauryl sulfate:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

##### 2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Biodegradability : Result: Not readily biodegradable.

##### Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 62 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

### Bioaccumulative potential

#### Components:

##### Hydrocarbons, C9, aromatics:

Partition coefficient: n-octanol/water : log Pow: 3.7 - 4.5

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 852G-201 TOPCOAT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 01/29/2026
13.0	05/19/2026	1346509-00052	Date of first issue: 02/27/2017

---

### Sodium lauryl sulfate:

Partition coefficient: n-octanol/water : log Pow: <= -2.1

### Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Partition coefficient: n-octanol/water : log Pow: < 1

### Mobility in soil

No data available

### Other adverse effects

No data available

### Endocrine disrupting properties

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.  
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to IMO instruments

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

Not regulated as a dangerous good

### Special precautions for user

Not applicable

---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 852G-201 TOPCOAT CLEAR

Version 13.0      Revision Date: 05/19/2026      SDS Number: 1346509-00052      Date of last issue: 01/29/2026  
Date of first issue: 02/27/2017

---

### SECTION 15. REGULATORY INFORMATION

#### CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Respiratory or skin sensitization  
Serious eye damage or eye irritation

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Mercury	7439-97-6	< 0.1 %
Lead	7439-92-1	< 0.1 %

#### Volatile organic compounds (VOC) content

VOC content: 169.32 g/l  
Remarks: less exempt

VOC content: 71.18 g/l  
Remarks: as packaged

#### US State Regulations

##### Pennsylvania Right To Know

Fluoropolymer	Trade secret
Water	7732-18-5
Hydrocarbons, C9, aromatics	64742-95-6
Ammonium hydroxide	1336-21-6

##### California Prop. 65

WARNING: This product can expose you to chemicals including Cadmium, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

##### California List of Hazardous Substances

Hydrocarbons, C9, aromatics	64742-95-6
-----------------------------	------------

##### California Permissible Exposure Limits for Chemical Contaminants

Hydrocarbons, C9, aromatics	64742-95-6
-----------------------------	------------

---

### SECTION 16. OTHER INFORMATION

#### Further information

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 852G-201 TOPCOAT CLEAR


Version  
13.0

Revision Date:  
05/19/2026

SDS Number:  
1346509-00052

Date of last issue: 01/29/2026  
Date of first issue: 02/27/2017

### NFPA 704:



### HMIS® IV / CED:

HEALTH	/	3
FLAMMABILITY		2
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or nominated distributors.

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	:	USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organiza-

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 852G-201 TOPCOAT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 01/29/2026
13.0	05/19/2026	1346509-00052	Date of first issue: 02/27/2017

---

tion; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 05/19/2026

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8