

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 09/11/2025  |
| 12.2    | 10/29/2025     | 1347029-00050 | Date of first issue: 02/27/2017 |

---

### SECTION 1. IDENTIFICATION

Product name : 857G-135 MIDCOAT BLACK

Product code : D15444802

SDS-Identcode : 130000127894

#### Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street  
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

#### Recommended use of the chemical and restrictions on use

Recommended use : Coatings

Restrictions on use : For industrial use only.  
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

---

### SECTION 2. HAZARDS IDENTIFICATION

**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

#### Hazards for the product as supplied

Serious eye damage : Category 1

Reproductive toxicity : Category 1B

#### Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.

#### GHS label elements

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

Version 12.2      Revision Date: 10/29/2025      SDS Number: 1347029-00050      Date of last issue: 09/11/2025  
Date of first issue: 02/27/2017

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H318 Causes serious eye damage.  
H360D May damage the unborn child.

Supplemental Hazard Statements : Corrosive to the respiratory tract.

Precautionary Statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P280 Wear protective gloves, protective clothing, eye protection and face protection.  
**Response:**  
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER.  
P308 + P313 IF exposed or concerned: Get medical attention.  
**Storage:**  
P405 Store locked up.  
**Disposal:**  
P501 Dispose of contents and container to an approved waste disposal plant.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Paint

#### Components

| Chemical name                                     | CAS No./Unique ID | Concentration (% w/w) | Trade secret |
|---|-------------------|-----------------------|--------------|
| 2,2',2''-Nitrilotriethanol                        | 102-71-6*         | >= 3 - <= 7           | TSC          |
| 2,6,8-Trimethyl-4-nonyloxypolyethyleneoxy-ethanol | 60828-78-6*       | >= 3 - <= 7           | TSC          |
| 2-(2-Butoxyethoxy)ethanol                         | 112-34-5*         | >= 0.5 - <= 1.5       | TSC          |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

Version 12.2      Revision Date: 10/29/2025      SDS Number: 1347029-00050      Date of last issue: 09/11/2025  
Date of first issue: 02/27/2017

|                            |             |                       |     |
|----------------------------|-------------|-----------------------|-----|
| Carbon black               | 1333-86-4*  | $\geq 0.5 - \leq 1.5$ | TSC |
| Cerium 2-ethylhexanoate    | 56797-01-4* | $\geq 0.1 - \leq 1$   | TSC |
| Rutile (TiO <sub>2</sub> ) | 1317-80-2*  | $\geq 0.1 - \leq 1$   | TSC |

\* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention immediately.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes serious eye damage.  
May damage the unborn child.  
Corrosive to the respiratory tract.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing : None known.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 09/11/2025  |
| 12.2    | 10/29/2025     | 1347029-00050 | Date of first issue: 02/27/2017 |

---

media

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Hydrogen fluoride  
carbonyl fluoride  
potentially toxic fluorinated compounds  
aerosolized particulates  
Carbon oxides  
Nitrogen oxides (NO<sub>x</sub>)

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

Version 12.2      Revision Date: 10/29/2025      SDS Number: 1347029-00050      Date of last issue: 09/11/2025  
Date of first issue: 02/27/2017

### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
Do not breathe vapors or spray mist.  
Do not swallow.  
Do not get in eyes.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep container tightly closed.  
Take care to prevent spills, waste and minimize release to the environment.  
  
Do not breathe decomposition products.
- Conditions for safe storage : Keep in properly labeled containers.  
Store locked up.  
Keep tightly closed.  
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Explosives  
Gases
- Recommended storage temperature : 41 - 77 °F / 5 - 25 °C
- Further information on storage stability : Do not freeze.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

| Components                 | CAS-No.   | Value type (Form of exposure)      | Control parameters / Permissible concentration | Basis |
|----------------------------|-----------|------------------------------------|--|-------|
| 2,2',2''-Nitrilotriethanol | 102-71-6  | TWA                                | 5 mg/m <sup>3</sup>                            | ACGIH |
| 2-(2-Butoxyethoxy)ethanol  | 112-34-5  | TWA (Inhalable fraction and vapor) | 10 ppm   | ACGIH |
| Carbon black               | 1333-86-4 | TWA (Inhalable particu-            | 3 mg/m <sup>3</sup>                            | ACGIH |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

Version 12.2      Revision Date: 10/29/2025      SDS Number: 1347029-00050      Date of last issue: 09/11/2025  
 Date of first issue: 02/27/2017

|                            |           |                                     |   |           |
|----------------------------|-----------|-------------------------------------|---|-----------|
|                            |           | late matter)                        |   |           |
|                            |           | TWA                                 | 3.5 mg/m <sup>3</sup>                       | NIOSH REL |
|                            |           | TWA                                 | 3.5 mg/m <sup>3</sup>                       | OSHA Z-1  |
| Rutile (TiO <sub>2</sub> ) | 1317-80-2 | TWA (Respirable particulate matter) | 2.5 mg/m <sup>3</sup><br>(Titanium dioxide) | ACGIH     |

**This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.**

Carbon black

### Occupational exposure limits of decomposition products

| Components          | CAS-No.   | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis     |
|---------------------|-----------|-------------------------------|--|-----------|
| Hydrogen fluoride   | 7664-39-3 | TWA                           | 0.5 ppm<br>(Fluorine)                          | ACGIH     |
|                     |           | C                             | 2 ppm<br>(Fluorine)                            | ACGIH     |
|                     |           | TWA                           | 3 ppm  | OSHA Z-2  |
|                     |           | C                             | 6 ppm<br>5 mg/m <sup>3</sup>                   | NIOSH REL |
|                     |           | TWA                           | 3 ppm<br>2.5 mg/m <sup>3</sup>                 | NIOSH REL |
| Carbonyl difluoride | 353-50-4  | TWA                           | 2 ppm  | ACGIH     |
|                     |           | STEL                          | 5 ppm  | ACGIH     |
|                     |           | TWA                           | 2 ppm<br>5 mg/m <sup>3</sup>                   | NIOSH REL |
|                     |           | ST                            | 5 ppm<br>15 mg/m <sup>3</sup>                  | NIOSH REL |
|                     |           | TWA                           | 2.5 mg/m <sup>3</sup><br>(Fluorine)            | OSHA Z-1  |
| Carbon dioxide      | 124-38-9  | TWA                           | 5,000 ppm                                      | ACGIH     |
|                     |           | STEL                          | 30,000 ppm                                     | ACGIH     |
|                     |           | TWA                           | 5,000 ppm<br>9,000 mg/m <sup>3</sup>           | NIOSH REL |
|                     |           | ST                            | 30,000 ppm<br>54,000 mg/m <sup>3</sup>         | NIOSH REL |
|                     |           | TWA                           | 5,000 ppm<br>9,000 mg/m <sup>3</sup>           | OSHA Z-1  |
| Carbon monoxide     | 630-08-0  | TWA                           | 25 ppm   | ACGIH     |
|                     |           | TWA                           | 35 ppm<br>40 mg/m <sup>3</sup>                 | NIOSH REL |
|                     |           | C                             | 200 ppm<br>229 mg/m <sup>3</sup>               | NIOSH REL |
|                     |           | TWA                           | 50 ppm<br>55 mg/m <sup>3</sup>                 | OSHA Z-1  |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 09/11/2025  |
| 12.2    | 10/29/2025     | 1347029-00050 | Date of first issue: 02/27/2017 |

---

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.

### Personal protective equipment

**Respiratory protection** : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

### Hand protection

**Material** : Chemical-resistant gloves

**Remarks** : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

**Eye protection** : Wear the following personal protective equipment:  
Chemical resistant goggles must be worn.  
If splashes are likely to occur, wear:  
Face-shield

**Skin and body protection** : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

**Hygiene measures** : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : liquid

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 09/11/2025  |
| 12.2    | 10/29/2025     | 1347029-00050 | Date of first issue: 02/27/2017 |

---

|  |   |                          |
|--|---|--------------------------|
| Color  | : | black                    |
| Odor   | : | No data available        |
| Odor Threshold                                   | : | No data available        |
| pH   | : | 8.5 - 11                 |
| Melting point/freezing point                     | : | No data available        |
| Initial boiling point and boiling range          | : | > 212 °F / > 100 °C      |
| Flash point                                      | : | does not flash           |
| Evaporation rate                                 | : | No data available        |
| Flammability (solid, gas)                        | : | Not applicable           |
| Flammability (liquids)                           | : | Not applicable           |
| Upper explosion limit / Upper flammability limit | : | No data available        |
| Lower explosion limit / Lower flammability limit | : | No data available        |
| Vapor pressure                                   | : | No data available        |
| Relative vapor density                           | : | No data available        |
| Density  | : | 1.3170 g/cm <sup>3</sup> |
| Solubility(ies)                                  |   |                          |
| Water solubility                                 | : | soluble                  |
| Partition coefficient: n-octanol/water           | : | Not applicable           |
| Autoignition temperature                         | : | No data available        |
| Decomposition temperature                        | : | No data available        |
| Viscosity  |   |                          |
| Viscosity, dynamic                               | : | 682 mPa.s                |
| Viscosity, kinematic                             | : | No data available        |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 09/11/2025  |
| 12.2    | 10/29/2025     | 1347029-00050 | Date of first issue: 02/27/2017 |

---

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics  
Particle size : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : None known.

Incompatible materials : None.

#### Hazardous decomposition products

Thermal decomposition : Hydrogen fluoride  
Carbonyl difluoride  
Carbon dioxide  
Carbon monoxide

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

#### Components:

##### **2,2',2''-Nitrilotriethanol:**

Acute oral toxicity : LD50 (Rat): 6,400 mg/kg

---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 09/11/2025  |
| 12.2    | 10/29/2025     | 1347029-00050 | Date of first issue: 02/27/2017 |

---

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

### **2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:**

Acute oral toxicity : LD50 (Rat): 3,300 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

### **2-(2-Butoxyethoxy)ethanol:**

Acute oral toxicity : LD50 (Mouse): 2,410 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 2,764 mg/kg

### **Carbon black:**

Acute oral toxicity : LD50 (Rat): > 10,000 mg/kg

### **Cerium 2-ethylhexanoate:**

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg  
Remarks: Based on data from similar materials

### **Rutile (TiO<sub>2</sub>):**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

### **Skin corrosion/irritation**

Not classified based on available information.

### **Components:**

#### **2,2',2''-Nitrilotriethanol:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

#### **2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:**

Result : Skin irritation

#### **2-(2-Butoxyethoxy)ethanol:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Mild skin irritation

### **Carbon black:**

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

Version 12.2      Revision Date: 10/29/2025      SDS Number: 1347029-00050      Date of last issue: 09/11/2025  
Date of first issue: 02/27/2017

---

Species : Rabbit  
Result : No skin irritation

### **Cerium 2-ethylhexanoate:**

Species : reconstructed human epidermis (RhE)  
Method : OECD Test Guideline 439

Result : No skin irritation

### **Rutile (TiO<sub>2</sub>):**

Species : Rabbit  
Result : No skin irritation

### **Serious eye damage/eye irritation**

Causes serious eye damage.

### **Components:**

#### **2,2',2''-Nitrilotriethanol:**

Species : Rabbit  
Result : No eye irritation

#### **2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:**

Result : Irreversible effects on the eye

#### **2-(2-Butoxyethoxy)ethanol:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

### **Carbon black:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

### **Cerium 2-ethylhexanoate:**

Species : Bovine cornea  
Method : OECD Test Guideline 437

Result : No eye irritation

### **Rutile (TiO<sub>2</sub>):**

Species : Rabbit  
Result : No eye irritation

### **Respiratory or skin sensitization**

#### **Skin sensitization**

Not classified based on available information.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

Version 12.2      Revision Date: 10/29/2025      SDS Number: 1347029-00050      Date of last issue: 09/11/2025  
Date of first issue: 02/27/2017

---

### Respiratory sensitization

Not classified based on available information.

### Components:

#### **2,2',2''-Nitrilotriethanol:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

#### **2-(2-Butoxyethoxy)ethanol:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

#### **Carbon black:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

#### **Cerium 2-ethylhexanoate:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative  
Remarks : Based on data from similar materials

#### **Rutile (TiO<sub>2</sub>):**

Test Type : Local lymph node assay (LLNA)  
Species : Mouse  
Result : negative

Test Type : Buehler Test  
Species : Guinea pig  
Result : negative

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### **2,2',2''-Nitrilotriethanol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

Version 12.2      Revision Date: 10/29/2025      SDS Number: 1347029-00050      Date of last issue: 09/11/2025  
Date of first issue: 02/27/2017

---

### 2-(2-Butoxyethoxy)ethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow  
cytogenetic test, chromosomal analysis)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

### Carbon black:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-  
malian cells  
Method: OECD Test Guideline 479  
Result: negative

Test Type: in vitro micronucleus test  
Method: OECD Test Guideline 487  
Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in Drosophila mel-  
anogaster (in vivo)  
Species: Drosophila melanogaster (vinegar fly)  
Application Route: Ingestion  
Method: OECD Test Guideline 477  
Result: negative

### Cerium 2-ethylhexanoate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Remarks: Based on data from similar materials

### Rutile (TiO<sub>2</sub>):

Germ cell mutagenicity -  
Assessment : Weight of evidence does not support classification as a germ  
cell mutagen.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

Version 12.2      Revision Date: 10/29/2025      SDS Number: 1347029-00050      Date of last issue: 09/11/2025  
Date of first issue: 02/27/2017

---

### **Carcinogenicity**

Not classified based on available information.

### **Components:**

#### **2,2',2''-Nitrilotriethanol:**

Species : Rat  
Application Route : Skin contact  
Exposure time : 103 weeks  
Result : negative

#### **Carbon black:**

Species : Rat  
Application Route : Inhalation  
Exposure time : 24 Months  
Result : positive  
Remarks : IARC: (International Agency for Research on Cancer)  
This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Species : Rat  
Application Route : Ingestion  
Exposure time : 2 Years  
Result : negative

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

#### **Rutile (TiO<sub>2</sub>):**

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

**IARC**      Group 2B: Possibly carcinogenic to humans  
Carbon black      1333-86-4  
Group 2B: Possibly carcinogenic to humans  
Rutile (TiO<sub>2</sub>)      1317-80-2

**OSHA**      No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**      No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### **Reproductive toxicity**

May damage the unborn child.

### **Components:**

#### **2,2',2''-Nitrilotriethanol:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

Version 12.2      Revision Date: 10/29/2025      SDS Number: 1347029-00050      Date of last issue: 09/11/2025  
Date of first issue: 02/27/2017

---

Method: OECD Test Guideline 416  
Result: negative

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 421  
Result: negative

### **2-(2-Butoxyethoxy)ethanol:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 415  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

### **Carbon black:**

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

Test Type: Embryo-fetal development  
Species: Mouse  
Application Route: inhalation (dust/mist/fume)  
Result: negative

### **Cerium 2-ethylhexanoate:**

Effects on fertility : Test Type: Fertility/early embryonic development  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 443  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: positive  
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Clear evidence of adverse effects on development, based on animal experiments.  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

Version 12.2      Revision Date: 10/29/2025      SDS Number: 1347029-00050      Date of last issue: 09/11/2025  
Date of first issue: 02/27/2017

---

### STOT-single exposure

Corrosive to the respiratory tract.

### STOT-repeated exposure

Not classified based on available information.

### Components:

#### 2,2',2''-Nitrilotriethanol:

Assessment : No significant health effects observed in animals at concentrations of 200 mg/kg bw or less., No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

#### Rutile (TiO<sub>2</sub>):

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

### Repeated dose toxicity

### Components:

#### 2,2',2''-Nitrilotriethanol:

Species : Rat  
NOAEL :  $\geq 1,000$  mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

Species : Rat  
NOAEL :  $\geq 0.5$  mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 28 Days  
Method : OECD Test Guideline 412

Species : Rat  
NOAEL : 125 mg/kg  
Application Route : Skin contact  
Exposure time : 90 Days

#### 2-(2-Butoxyethoxy)ethanol:

Species : Rat  
NOAEL : 250 mg/kg  
LOAEL : 1,000 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Method : OECD Test Guideline 408

Species : Rat  
NOAEL :  $\geq 0.094$  mg/l  
Application Route : inhalation (vapor)  
Exposure time : 90 Days  
Method : OECD Test Guideline 413

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

Version 12.2      Revision Date: 10/29/2025      SDS Number: 1347029-00050      Date of last issue: 09/11/2025  
Date of first issue: 02/27/2017

---

Species : Rat  
NOAEL :  $\geq 2,000$  mg/kg  
Application Route : Skin contact  
Exposure time : 90 Days

### Carbon black:

Species : Rat  
NOAEL : 1 mg/kg  
LOAEL : 7 mg/kg  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 90 Days  
Remarks : This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

### Cerium 2-ethylhexanoate:

Species : Rat  
NOAEL :  $> 215$  mg/kg  
Application Route : Ingestion  
Exposure time : 42 - 47 Days  
Method : OECD Test Guideline 422  
Remarks : Based on data from similar materials

### Rutile (TiO<sub>2</sub>):

Species : Rat  
NOAEL : 24,000 mg/kg  
LOAEL :  $> 24,000$  mg/kg  
Application Route : Ingestion  
Exposure time : 28 d  
Remarks : No significant adverse effects were reported  
Based on data from similar materials

### Aspiration toxicity

Not classified based on available information.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

#### **2,2',2''-Nitrilotriethanol:**

Toxicity to fish : LC<sub>50</sub> (Pimephales promelas (fathead minnow)): 11,800 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC<sub>50</sub> (Ceriodaphnia dubia (water flea)): 609.88 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC<sub>50</sub> (Desmodesmus subspicatus (green algae)): 512 mg/l  
Exposure time: 72 h  
Test substance: Neutralized product

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

Version 12.2      Revision Date: 10/29/2025      SDS Number: 1347029-00050      Date of last issue: 09/11/2025  
Date of first issue: 02/27/2017

---

EC10 (Desmodesmus subspicatus (green algae)): 26 mg/l  
Exposure time: 72 h  
Test substance: Neutralized product

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 16 mg/l  
Exposure time: 21 d

Toxicity to microorganisms : IC50: > 1,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

### **2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 39 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 81.2 mg/l  
Exposure time: 48 h

### **2-(2-Butoxyethoxy)ethanol:**

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 1,300 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): >= 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10: > 1,995 mg/l  
Exposure time: 30 min

### **Carbon black:**

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 5,600 mg/l  
Exposure time: 24 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL10 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l  
Exposure time: 72 h

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

Version 12.2      Revision Date: 10/29/2025      SDS Number: 1347029-00050      Date of last issue: 09/11/2025  
Date of first issue: 02/27/2017

---

Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

EL50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

### **Cerium 2-ethylhexanoate:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.1 - 1 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 1 - 10 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

### **Rutile (TiO<sub>2</sub>):**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Remarks: Based on data from similar materials

NOEC (algae): 5,600 mg/l  
Exposure time: 72 h

### **Persistence and degradability**

#### **Components:**

#### **2,2',2''-Nitrilotriethanol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 96 %  
Exposure time: 19 d

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 09/11/2025  |
| 12.2    | 10/29/2025     | 1347029-00050 | Date of first issue: 02/27/2017 |

---

### 2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Biodegradability : Result: Not readily biodegradable.

### 2-(2-Butoxyethoxy)ethanol:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 85 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301C  
Remarks: The test was conducted according to guideline

### Bioaccumulative potential

#### Components:

#### 2,2',2"-Nitrilotriethanol:

Bioaccumulation : Species: Cyprinus carpio (Carp)  
Bioconcentration factor (BCF): < 3.9

Partition coefficient: n-octanol/water : log Pow: -1.9

#### 2-(2-Butoxyethoxy)ethanol:

Partition coefficient: n-octanol/water : log Pow: 1

### Mobility in soil

No data available

### Other adverse effects

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.  
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

Version 12.2      Revision Date: 10/29/2025      SDS Number: 1347029-00050      Date of last issue: 09/11/2025  
Date of first issue: 02/27/2017

### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to IMO instruments

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

Not regulated as a dangerous good

### Special precautions for user

Not applicable

## SECTION 15. REGULATORY INFORMATION

### CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Reproductive toxicity  
Serious eye damage or eye irritation

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

|                           |           |              |
|---------------------------|-----------|--------------|
| 2-(2-Butoxyethoxy)ethanol | 112-34-5  | >= 1 - < 5 % |
| 2-Butoxyethanol           | 111-76-2  | < 0.1 %      |
| Lead                      | 7439-92-1 | < 0.1 %      |

### Volatile organic compounds (VOC) content

VOC content: 201.43 g/l  
Remarks: less exempt

VOC content: 96.7 g/l  
Remarks: as packaged

## US State Regulations

### Pennsylvania Right To Know

|                            |              |
|----------------------------|--------------|
| Water                      | 7732-18-5    |
| Fluoropolymer              | Trade secret |
| Fluoropolymer              | Trade secret |
| 2,2',2''-Nitrilotriethanol | 102-71-6     |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

Version 12.2      Revision Date: 10/29/2025      SDS Number: 1347029-00050      Date of last issue: 09/11/2025  
Date of first issue: 02/27/2017

Acrylic Copolymer      Trade secret  
2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol      60828-78-6  
2-(2-Butoxyethoxy)ethanol      112-34-5  
Ammonium hydroxide      1336-21-6

### California Prop. 65

WARNING: This product can expose you to chemicals including Carbon black, which is/are known to the State of California to cause cancer, and Lead, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).


### California Permissible Exposure Limits for Chemical Contaminants

2,2',2''-Nitrilotriethanol      102-71-6

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA 704:



#### HMIS® IV:

|                 |   |   |
|-----------------|---|---|
| HEALTH          | * | 3 |
| FLAMMABILITY    |   | 0 |
| PHYSICAL HAZARD |   | 0 |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or nominated distributors.

### Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-2 : USA. Occupational Exposure Limits (OSHA) - Table Z-2
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit
- ACGIH / C : Ceiling limit
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 09/11/2025  |
| 12.2    | 10/29/2025     | 1347029-00050 | Date of first issue: 02/27/2017 |

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday  
NIOSH REL / C : Ceiling value not be exceeded at any time.  
OSHA Z-1 / TWA : 8-hour time weighted average  
OSHA Z-2 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/29/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## 857G-135 MIDCOAT BLACK

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 09/11/2025  |
| 12.2    | 10/29/2025     | 1347029-00050 | Date of first issue: 02/27/2017 |

---

intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8